

Package ‘photobiology’

June 7, 2020

Type Package

Title Photobiological Calculations

Version 0.10.4

Date 2020-06-06

Description Definitions of classes, methods, operators and functions for use in photobiology and radiation meteorology and climatology. Calculation of effective (weighted) and not-weighted irradiances/doses, fluence rates, transmittance, reflectance, absorptance, absorbance and diverse ratios and other derived quantities from spectral data. Local maxima and minima: peaks, valleys and spikes. Conversion between energy-and photon-based units. Wavelength interpolation. Astronomical calculations related solar angles and day length. Colours and vision. This package is part of the 'r4photobiology' suite, Aphalo, P. J. (2015) <doi:10.19232/uv4pb.2015.1.14>.

License GPL (>= 2)

Depends R (>= 3.6.0)

Imports stats, polynom (>= 1.4-0), tibble (>= 3.0.1), stringr (>= 1.4.0), lubridate (>= 1.7.8), plyr (>= 1.8.4), dplyr (>= 1.0.0), splus2R (>= 1.2-2), zoo (>= 1.8-7), rlang (>= 0.4.6)

Suggests knitr (>= 1.28), rmarkdown (>= 2.2), testthat (>= 2.3.2), roxygen2 (>= 7.1.0)

LazyLoad yes

LazyData yes

ByteCompile true

URL <https://docs.r4photobiology.info/photobiology>,
<https://bitbucket.org/aphalo/photobiology>

BugReports <https://bitbucket.org/aphalo/photobiology/issues>

Encoding UTF-8

RoxygenNote 7.1.0

VignetteBuilder knitr

NeedsCompilation no

Author Pedro J. Aphalo [aut, cre] (<<https://orcid.org/0000-0003-3385-972X>>),
 Titta K. Kotilainen [ctb] (<<https://orcid.org/0000-0002-2822-9734>>),
 Glenn Davis [ctb],
 Agnese Fazio [ctb]

Maintainer Pedro J. Aphalo <pedro.aphalo@helsinki.fi>

Repository CRAN

Date/Publication 2020-06-07 05:40:05 UTC

R topics documented:

photobiology-package	8
A.illuminant.spct	10
A2T	11
absorbance	12
absorptance	15
add_atr2tb	18
Afr2T	19
any2T	21
as.calibration_mspct	22
as.calibration_spct	24
as.chroma_mspct	25
as.chroma_spct	26
as.cps_mspct	27
as.cps_spct	28
as.filter_mspct	29
as.filter_spct	31
as.generic_mspct	32
as.generic_spct	34
as.matrix_mspct	34
as.object_mspct	35
as.object_spct	37
as.raw_mspct	38
as.raw_spct	39
as.reflector_mspct	40
as.reflector_spct	42
as.response_mspct	43
as.response_spct	44
as.solar_date	45
as.source_mspct	46
as.source_spct	48
as_energy	49
as_quantum	49
as_quantum_mol	50
as_tod	51
average_spct	52
beesxyzCMF.spct	52
black_body.spct	53

c	54
calc_multipliers	54
calc_source_output	55
ccd.spct	56
checkTimeUnit	57
check_spct	58
check_spectrum	61
check_w.length	62
ciev10.spct	62
ciev2.spct	63
cixyzCC10.spct	64
cixyzCC2.spct	65
cixyzCMF10.spct	66
cixyzCMF2.spct	67
class_spct	68
clean	68
clear.spct	73
clear_body.spct	74
clip_wl	74
color_of	76
compare_spct	78
cone_fundamentals10.spct	79
convertTfrType	80
convertThickness	81
convertTimeUnit	82
convolve_each	83
copy_attributes	84
cps2irrad	85
D2.UV586	86
D2.UV653	86
D2.UV654	87
D2_spectrum	87
D65.illuminant.spct	88
day_night	89
defunct	92
despike	93
diffraction_single_slit	99
dim.generic_mspct	100
div-.generic_spct	101
div_spectra	101
e2q	103
e2qmol_multipliers	104
e2quantum_multipliers	104
enable_check_spct	105
energy_as_default	106
energy_irradiance	106
energy_ratio	107
eq_ratio	109

Extract	111
Extract_mspct	113
e_fluence	114
e_irrad	117
e_ratio	120
e_response	123
FEL.BN.9101.165	126
FEL_spectrum	126
findMultipleWl	127
find_peaks	127
find_spikes	128
find_wls	130
fit_peaks	131
fluence	133
format.solar_time	136
format.tod_time	136
formatted_range	137
fscale	137
fshift	142
generic_mspct	146
getBSWFUsed	148
getFilterProperties	148
getHowMeasured	150
getIdFactor	151
getInstrDesc	152
getInstrSettings	153
getMspctVersion	153
getMultipleWl	154
getNormalized	155
getRfrType	155
getScaled	156
getSpctVersion	157
getTfrType	157
getTimeUnit	158
getWhatMeasured	159
getWhenMeasured	160
getWhereMeasured	161
get_attributes	163
get_peaks	164
green_leaf.spct	166
head_tail	167
insert_hinges	168
insert_spct_hinges	169
integrate_spct	170
integrate_xy	171
interpolate_spct	171
interpolate_spectrum	173
interpolate_wl	174

irrad	175
irradiance	179
is.generic_mspct	180
is.generic_spct	181
is.old_spct	182
is.solar_time	183
is.summary_generic_spct	183
is.waveband	184
isValidInstrDesc	185
isValidInstrSettings	186
is_absorbance_based	186
is_effective	187
is_normalized	188
is_photon_based	189
is_scaled	190
is_tagged	191
join_mspct	191
labels	193
Ler_leaf.spct	194
Ler_leaf_rflt.spct	195
Ler_leaf_trns.spct	196
Ler_leaf_trns_i.spct	197
log	198
MathFun	199
merge2object_spct	199
merge_attributes	200
minus-.generic_spct	201
mod-.generic_spct	202
msmsply	202
mspct_classes	203
na.omit	204
normalization	206
normalize	207
normalized_diff_ind	211
normalize_range_arg	213
opaque.spct	214
oper_spectra	214
peaks	216
photodiode.spct	222
photons_energy_ratio	223
photon_irradiance	224
photon_ratio	226
plus-.generic_spct	227
polyester.spct	228
print	228
print.solar_time	229
print.summary_generic_spct	230
print.tod_time	231

print.waveband	231
prod_spectra	232
q2e	233
qe_ratio	234
q_fluence	237
q_irrad	239
q_ratio	242
q_response	245
rbindspct	248
reflectance	250
relative_AM	252
replace_bad_pixs	253
response	255
Rfr_from_n	257
rgb_spct	258
rmDerivedMspct	259
rmDerivedSpct	260
round	261
select_spct_attributes	262
setBSWFUsed	263
setFilterProperties	263
setGenericSpct	265
setHowMeasured	268
setIdFactor	269
setInstrDesc	269
setInstrSettings	270
setMultipleWl	271
setNormalized	271
setRfrType	272
setScaled	273
setTfrType	274
setTimeUnit	275
setWhatMeasured	276
setWhenMeasured	277
setWhereMeasured	278
shared_member_class	280
sign	280
slash-generic_spct	281
smooth_spct	281
solar_time	283
source_spct	284
spct_attr2tb	288
spct_classes	289
spikes	289
split2mspct	294
split_bands	297
split_energy_irradiance	298
split_irradiance	299

split_photon_irradiance	301
spread	302
Subset	304
subset2mspct	305
subt_spectra	306
summary	307
summary_spct_classes	308
sum_spectra	308
sun.daily.data	310
sun.daily.spct	311
sun.data	312
sun.spct	313
sun_angles	314
s_e_irrad2rgb	316
s_mean	317
s_mean_se	319
s_median	320
s_prod	321
s_range	323
s_sd	324
s_se	325
s_sum	327
s_var	328
T2A	330
T2Afr	331
tag	333
thin_wl	335
times-generic_spct	338
transmittance	338
Trig	341
trimInstrDesc	342
trimInstrSettings	343
trim_spct	343
trim_tails	346
trim_waveband	347
trim_wl	349
tz_time_diff	351
uncollect	351
untag	353
upgrade_spct	354
upgrade_spectra	354
using_Tfr	355
validate_geocode	356
valleys	357
verbose_as_default	363
v_insert_hinges	363
v_replace_hinges	364
water_vp_sat	365

waveband	368
waveband_ratio	370
wb2rect_spct	371
wb2spct	372
wb2tagged_spct	373
wb_trim_as_default	374
white_body.spct	374
white_led.cps_spct	375
white_led.raw_spct	375
white_led.source_spct	376
wls_at_target	377
wl_colors.spct	381
wl_max	382
wl_midpoint	383
wl_min	384
wl_range	385
wl_stepsize	386
w_length2rgb	387
w_length_range2rgb	388
yellow_gel.spct	389
^.generic_spct	389

Index**391**

photobiology-package *photobiology: Photobiological Calculations*

Description

Definitions of classes, methods, operators and functions for use in photobiology and radiation meteorology and climatology. Calculation of effective (weighted) and not-weighted irradiances/doses, fluence rates, transmittance, reflectance, absorptance, absorbance and diverse ratios and other derived quantities from spectral data. Local maxima and minima: peaks, valleys and spikes. Conversion between energy- and photon-based units. Wavelength interpolation. Astronomical calculations related solar angles and day length. Colours and vision. This package is part of the 'r4photobiology' suite, Aphalo, P. J. (2015) <doi:10.19232/uv4pb.2015.1.14>.

Details

Package 'photobiology' is at the core of a suite of packages for analysis and plotting of data relevant to photobiology (described at <https://www.r4photobiology.info/>). The accompanying packages (under development) provide data and definitions that are to a large extent application-area specific while the functions in the present package are widely useful in photobiology and radiation quantification in geophysics and meteorology. Package 'photobiology' has its main focus in the characterization of the light environment in a biologically relevant manner and in the manipulation of spectral data to simulate photo-physical, photo-chemical and photo-biological interactions and responses. The focus of package 'pavo' (Maia et al., 2003) is in colour perception by animals and assessment of animal coloration. In spite of the different focus, there is some degree of overlap.

Acknowledgements

This work was funded by the Academy of Finland (decision 252548). COST Action FA9604 'UV4Growth' facilitated discussions and exchanges of ideas that lead to the development of this package. The contributions of Andy McLeod, Lars Olof Björn, Nigel Paul, Lasse Ylianttila, T. Matthew Robson and Titta Kotilainen were specially significant. Tutorials by Hadley Wickham and comments on my presentation at UseR!2015 allowed me to significantly improve the coding and functionality.

Note

Code for some of the astronomical calculations has been adapted from that in package 'pavo'.

Author(s)

Maintainer: Pedro J. Aphalo <pedro.aphalo@helsinki.fi> ([ORCID](#))

Other contributors:

- Titta K. Kotilainen ([ORCID](#)) [contributor]
- Glenn Davis <gdavis@gluonics.com> [contributor]
- Agnese Fazio <agnese.fazio@uni-jena.de> [contributor]

References

Aphalo, P. J., Albert, A., Björn, L. O., McLeod, A. R., Robson, T. M., Rosenqvist, E. (Eds.). (2012). Beyond the Visible: A handbook of best practice in plant UV photobiology (1st ed., p. xx + 174). Helsinki: University of Helsinki, Department of Biosciences, Division of Plant Biology. ISBN 978-952-10-8363-1 (PDF), 978-952-10-8362-4 (paperback). Open access PDF download available at <https://hdl.handle.net/10138/37558>

Aphalo, Pedro J. (2015) The r4photobiology suite. UV4Plants Bulletin, 2015:1, 21-29. <https://doi.org/10.19232/uv4pb.2015.1.14>.

Maia, R., Eliason, C. M., Bitton, P. P., Doucet, S. M., Shawkey, M. D. (2013) pavo: an R package for the analysis, visualization and organization of spectral data. Methods in Ecology and Evolution, 4(10):906-913. <https://doi.org/10.1111/2041-210X.12069>.

See Also

Useful links:

- <https://docs.r4photobiology.info/photobiology>
- <https://bitbucket.org/aphalo/photobiology>
- Report bugs at <https://bitbucket.org/aphalo/photobiology/issues>

Examples

```
# irradiance of the whole spectrum
irrad(sun.spct)
# photon irradiance 400 nm to 700 nm
q_irrad(sun.spct, waveband(c(400,700)))
```

```
# energy irradiance 400 nm to 700 nm
e_irrad(sun.spct, waveband(c(400,700)))
# simulating the effect of a filter on solar irradiance
e_irrad(sun.spct * yellow_gel.spct, waveband(c(400,500)))
e_irrad(sun.spct * yellow_gel.spct, waveband(c(500,700)))
# daylength
sunrise_time(lubridate::today(tzone = "EET"), tz = "EET",
             geocode = data.frame(lat = 60, lon = 25), unit.out = "hour")
day_length(lubridate::today(tzone = "EET"), tz = "EET",
           geocode = data.frame(lat = 60, lon = 25), unit.out = "hour")
# colour as seen by humans
color_of(sun.spct)
color_of(sun.spct * yellow_gel.spct)
# filter transmittance
transmittance(yellow_gel.spct)
transmittance(yellow_gel.spct, waveband(c(400,500)))
transmittance(yellow_gel.spct, waveband(c(500,700)))
```

A.illuminant.spct *CIE A illuminant data*

Description

A dataset containing wavelengths at a 5 nm interval (300 nm to 830 nm) and the corresponding spectral energy irradiance normalized to 1 at 560 nm. Spectrum approximates typical, domestic, tungsten-filament lighting and 'corresponds' to a black body a 2856 K. CIE standard illuminant A is intended to represent typical, domestic, tungsten-filament lighting. Original data from <http://files.cie.co.at/204.xls> downloaded on 2014-07-25 The variables are as follows:

Usage

A.illuminant.spct

Format

A source spectrum with 96 rows and 2 variables

Details

- w.length (nm)
- s.e.irrad (rel. units)

Author(s)

CIE

See Also

Other Spectral data examples: [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps.spct](#), [white_led.raw.spct](#), [white_led.source.spct](#), [yellow_gel.spct](#)

Examples

```
A.illuminant.spct
```

A2T

Convert absorbance into transmittance

Description

Function that converts absorbance (a.u.) into transmittance (fraction).

Usage

```
A2T(x, action, byref, ...)

## Default S3 method:
A2T(x, action = NULL, byref = FALSE, ...)

## S3 method for class 'numeric'
A2T(x, action = NULL, byref = FALSE, ...)

## S3 method for class 'filter_spct'
A2T(x, action = "add", byref = FALSE, ...)

## S3 method for class 'filter_mspct'
A2T(x, action = "add", byref = FALSE, ..., .parallel = FALSE, .paropts = NULL)
```

Arguments

x	an R object
action	a character string
byref	logical indicating if new object will be created by reference or by copy of x
...	not used in current version
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of `x` with a column `Tfr` added and `A` and `Afr` possibly deleted except for `w.length`. If `action = "replace"`, in all cases, the additional columns are removed, even if no column needs to be added.

Methods (by class)

- `default`: Default method for generic function
- `numeric`: method for numeric vectors
- `filter_spct`: Method for filter spectra
- `filter_mspct`: Method for collections of filter spectra

See Also

Other quantity conversion functions: [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

 absorbance

Absorbance

Description

Function to calculate the mean, total, or other summary of absorbance for spectral data stored in a `filter_spct` or in an `object_spct`.

Usage

```
absorbance(spct, w.band, quantity, wb.trim, use.hinges, ...)
```

```
## Default S3 method:
```

```
absorbance(spct, w.band, quantity, wb.trim, use.hinges, ...)
```

```
## S3 method for class 'filter_spct'
```

```
absorbance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)
```

```
## S3 method for class 'object_spct'
```

```
absorbance(
  spct,
```

```

    w.band = NULL,
    quantity = "average",
    wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
    use.hinges = NULL,
    naming = "default",
    ...
)

## S3 method for class 'filter_mspct'
absorbance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'object_mspct'
absorbance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
<code>quantity</code>	character string One of "average" or "mean", "total", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>wb.trim</code>	logical Flag indicating if wavebands crossing spectral data boundaries are trimmed or ignored.

<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- `default`: Default for generic function
- `filter_spct`: Specialization for filter spectra
- `object_spct`: Specialization for object spectra
- `filter_mspct`: Calculates absorbance from a `filter_mspct`
- `object_mspct`: Calculates absorbance from a `object_mspct`

Note

The `use.hinges` parameter controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

Examples

```
absorbance(polyester.spct, new_waveband(400,700))
absorbance(yellow_gel.spct, new_waveband(400,700))
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3))
```

```

absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "average")
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "total")
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "relative")
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "relative.pc")
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "contribution")
absorbance(yellow_gel.spct, split_bands(c(400,700), length.out = 3),
           quantity = "contribution.pc")

```

absorptance

Absorptance

Description

Function to calculate the mean, total, or other summary of absorptance for spectral data stored in a `filter_spct` or in an `object_spct`. Absorptance is a different quantity than absorbance.

Usage

```

absorptance(spct, w.band, quantity, wb.trim, use.hinges, ...)

## Default S3 method:
absorptance(spct, w.band, quantity, wb.trim, use.hinges, ...)

## S3 method for class 'filter_spct'
absorptance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)

## S3 method for class 'object_spct'
absorptance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",

```

```

    ...
)

## S3 method for class 'filter_mspct'
absorptance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx"
)

## S3 method for class 'object_mspct'
absorptance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
<code>quantity</code>	character string One of "average" or "mean", "total", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>wb.trim</code>	logical Flag if wavebands crossing spectral data boundaries are trimmed or ignored.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.

<code>attr2tb</code>	character vector, see <code>add_attr2tb</code> for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- `default`: Default for generic function
- `filter_spct`: Specialization for filter spectra
- `object_spct`: Specialization for object spectra
- `filter_mspct`: Calculates absorptance from a `filter_mspct`
- `object_mspct`: Calculates absorptance from a `object_mspct`

Note

The `use.hinges` parameter controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

Examples

```
absorptance(black_body.spct, new_waveband(400,500))
absorptance(white_body.spct, new_waveband(300,400))
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3))
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "average")
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "total")
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "relative")
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "relative.pc")
```

```
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "contribution")
absorptance(black_body.spct, split_bands(c(400,700), length.out = 3),
  quantity = "contribution.pc")
```

 add_attr2tb

Copy attributes from members of a generic_mspct

Description

Copy the when.measured, where.measured or what.measured attribute from members of a generic_mspct object into a tibble or data.frame.

Usage

```
add_attr2tb(tb, mspct, col.names = NULL, idx = "spct.idx")
```

```
when_measured2tb(
  mspct,
  tb = NULL,
  col.names = "when.measured",
  idx = "spct.idx"
)
```

```
lonlat2tb(mspct, tb = NULL, col.names = c("lon", "lat"), idx = "spct.idx")
```

```
lon2tb(mspct, tb = NULL, col.names = "lon", idx = "spct.idx")
```

```
lat2tb(mspct, tb = NULL, col.names = "lat", idx = "spct.idx")
```

```
geocode2tb(mspct, tb = NULL, col.names = "geocode", idx = "spct.idx")
```

```
what_measured2tb(
  mspct,
  tb = NULL,
  col.names = "what.measured",
  idx = "spct.idx"
)
```

Arguments

tb	tibble or data.frame to which to add the data (optional).
mspct	generic_mspct Any collection of spectra.
col.names	named character vector Name(s) of column(s) to create. Values are the names of the attributes to copy, while if named, the names provide the name for the column.

idx character Name of the column with the names of the members of the collection of spectra.

Details

The attributes are copied to a column in a tibble or data frame. If the `tb` formal parameter receives `NULL` as argument, a new tibble will be created. If an existing `data.frame` or `tibble` is passed as argument, new columns are added to it. However, the number of rows in the argument passed to `tb` must match the number of spectra in the argument passed to `mspct`. If the argument to `col.names` is a named vector, with the names of members matching the names of attributes, then the values are used as names for the columns created. This permits setting any valid name for the new columns. If the vector passed to `col.names` has no names, then the values are interpreted as the names of the attributes to add, and also used as names for the new columns.

Value

A tibble With the metadata attributes in separate new variables.

Note

Currently supported attributes are `"when.measured"`, `"what.measured"` and `"where.measured"`. In the case of `"where.measured"`, which has different components the name `"where.measured"` is ignored, but instead the following names are recognized: `"lon"` and `"lat"` for creating numeric columns of longitudes and latitudes respectively, and `"geocode"` for creating a column of data frames, in which case, if `tb` is not already a tibble it is converted into one before adding the new column. The order of the first two arguments is reversed in `add_attr2tb()` compared to the other functions. This is to allow its use in 'pipes', while the functions for single attributes are expected to be used mostly to create new tibbles.

Examples

```
library(dplyr)

my.mspct <- source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2))
q_irrad(my.mspct) %>%
  add_attr2tb(my.mspct, c(lat = "latitude",
                        lon = "longitude",
                        when.measured = "time"))

when_measured2tb(my.mspct)
```

Description

Function that converts transmittance (fraction) into absorptance (fraction). If reflectance (fraction) is available, it allows conversions between internal and total absorptance.

Usage

```
Afr2T(x, action, byref, clean, ...)

## Default S3 method:
Afr2T(x, action = NULL, byref = FALSE, clean = FALSE, ...)

## S3 method for class 'numeric'
Afr2T(x, action = NULL, byref = FALSE, clean = FALSE, Rfr = NA_real_, ...)

## S3 method for class 'filter_spct'
Afr2T(x, action = "add", byref = FALSE, clean = FALSE, ...)

## S3 method for class 'object_spct'
Afr2T(x, action = "add", byref = FALSE, clean = FALSE, ...)

## S3 method for class 'filter_mspct'
Afr2T(
  x,
  action = "add",
  byref = FALSE,
  clean = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'object_mspct'
Afr2T(
  x,
  action = "add",
  byref = FALSE,
  clean = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

x	an R object
action	character Allowed values "replace" and "add"
byref	logical indicating if new object will be created by reference or by copy of x
clean	logical replace off-boundary values before conversion

...	not used in current version
Rfr	numeric vector. Spectral reflectance or reflectance factor. Set to zero if x is internal reflectance,
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of x with a column Tfr added and other columns possibly deleted except for w.length. If action = "replace", in all cases, the additional columns are removed, even if no column needs to be added.

Methods (by class)

- default: Default method for generic function
- numeric: Default method for generic function
- filter_spct: Method for filter spectra
- object_spct: Method for object spectra
- filter_mspct: Method for collections of filter spectra
- object_mspct: Method for collections of object spectra

See Also

Other quantity conversion functions: [A2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
T2Afr(Ler_leaf.spct)
```

any2T

Convert filter quantities.

Description

Functions that convert or add related physical quantities to filter_spct or object_spct objects. transmittance (fraction) into absorptance (fraction).

Usage

```
any2T(x, action = "add", clean = FALSE)
any2A(x, action = "add", clean = FALSE)
any2Afr(x, action = "add", clean = FALSE)
```

Arguments

x	an filter_spct or a filter_mspct object.
action	character Allowed values "replace" and "add".
clean	logical replace off-boundary values before conversion

Details

These functions are dispatchers for [A2T](#), [Afr2T](#), [T2A](#), and [T2Afr](#). The dispatch is based on the names of the variables stored in x. They do not support in-place modification of x.

Value

A copy of x with the columns for the different quantities added or replaced. If action = "replace", in all cases, the additional columns are removed, even if no column needs to be added.

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
any2Afr(Ler_leaf.spct)
any2T(Ler_leaf.spct)
any2T(polyester.spct)
```

as.calibration_mspct *Coerce to a collection-of-spectra*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```

as.calibration_mspct(x, ...)

## Default S3 method:
as.calibration_mspct(x, ...)

## S3 method for class 'data.frame'
as.calibration_mspct(x, ...)

## S3 method for class 'calibration_spct'
as.calibration_mspct(x, ...)

## S3 method for class 'list'
as.calibration_mspct(x, ..., ncol = 1, byrow = FALSE)

## S3 method for class 'matrix'
as.calibration_mspct(
  x,
  w.length,
  spct.data.var = "irrad.mult",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)

```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelengthvalues sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a calibration_mspctt object.

Methods (by class)

- default:
- data.frame:
- calibration_spct:
- list:
- matrix:

Note

When `x` is a square matrix an explicit argument is needed for `byrow` to indicate how data in `x` should be read. In every case the length of the `w.length` vector must match one of the dimensions of `x`.

See Also

Other Coercion methods for collections of spectra: [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.calibration_spct *Coerce to a spectrum*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.calibration_spct(x, ...)
```

```
## Default S3 method:
as.calibration_spct(x, ...)
```

Arguments

<code>x</code>	an R object
<code>...</code>	other arguments passed to "set" functions

Value

A copy of `x` converted into a `calibration_spct` object.

Methods (by class)

- default:

See Also[setGenericSpct](#)

Other constructors of spectral objects: [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.chroma_mspct	<i>Coerce to a collection-of-spectra</i>
-----------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.chroma_mspct(x, ...)

## Default S3 method:
as.chroma_mspct(x, ...)

## S3 method for class 'data.frame'
as.chroma_mspct(x, ...)

## S3 method for class 'chroma_spct'
as.chroma_mspct(x, ...)

## S3 method for class 'list'
as.chroma_mspct(x, ..., ncol = 1, byrow = FALSE)
```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data

Value

A copy of x converted into a chroma_mspct object.

Methods (by class)

- default:
- data.frame:
- chroma_spct:
- list:

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.chroma_spct	<i>Coerce to a spectrum</i>
----------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.chroma_spct(x, ...)

## Default S3 method:
as.chroma_spct(x, ...)
```

Arguments

x	an R object
...	other arguments passed to "set" functions

Value

A copy of x converted into a chroma_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.cps_mspct	<i>Coerce to a collection-of-spectra</i>
--------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.cps_mspct(x, ...)
```

```
## Default S3 method:
as.cps_mspct(x, ...)
```

```
## S3 method for class 'data.frame'
as.cps_mspct(x, ...)
```

```
## S3 method for class 'cps_spct'
as.cps_mspct(x, ...)
```

```
## S3 method for class 'list'
as.cps_mspct(x, ..., ncol = 1, byrow = FALSE)
```

```
## S3 method for class 'matrix'
as.cps_mspct(
  x,
  w.length,
  spct.data.var = "cps",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)
```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelengthvalues sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.

multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a cps_mspct object.

Methods (by class)

- default:
- data.frame:
- cps_spct:
- list:
- matrix:

Note

When x is a square matrix an explicit argument is needed for byrow to indicate how data in x should be read. In every case the length of the w.length vector must match one of the dimensions of x.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.cps_spct	<i>Coerce to a spectrum</i>
-------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.cps_spct(x, ...)
```

```
## Default S3 method:
as.cps_spct(x, ...)
```

Arguments

x	an R object
...	other arguments passed to "set" functions

Value

A copy of `x` converted into a `cps_spct` object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

<code>as.filter_mspct</code>	<i>Coerce to a collection-of-spectra</i>
------------------------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.filter_mspct(x, ...)

## Default S3 method:
as.filter_mspct(x, ...)

## S3 method for class 'data.frame'
as.filter_mspct(x, Tfr.type = c("total", "internal"), strict.range = TRUE, ...)

## S3 method for class 'filter_spct'
as.filter_mspct(x, ...)

## S3 method for class 'list'
as.filter_mspct(
  x,
  Tfr.type = c("total", "internal"),
  strict.range = TRUE,
  ...,
  ncol = 1,
  byrow = FALSE
)

## S3 method for class 'matrix'
as.filter_mspct(
```

```

x,
w.length,
spct.data.var = "Tfr",
multiplier = 1,
byrow = NULL,
spct.names = "spct_",
...
)

```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
Tfr.type	a character string, either "total" or "internal"
strict.range	logical Flag indicating how off-range values are handled
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelength values sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a filter_mspct object.

Methods (by class)

- default:
- data.frame:
- filter_spct:
- list:
- matrix:

Note

When x is a square matrix an explicit argument is needed for byrow to indicate how data in x should be read. In every case the length of the w.length vector must match one of the dimensions of x.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.filter_spct	<i>Coerce to a spectrum</i>
----------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.filter_spct(x, ...)

## Default S3 method:
as.filter_spct(
  x,
  Tfr.type = c("total", "internal"),
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  ...
)
```

Arguments

x	an R object
...	other arguments passed to "set" functions
Tfr.type	a character string, either "total" or "internal"
strict.range	logical Flag indicating whether off-range values result in an error instead of a warning

Value

A copy of x converted into a filter_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.generic_mspct *Coerce to a collection-of-spectra*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.generic_mspct(x, ...)  
  
## Default S3 method:  
as.generic_mspct(x, ...)  
  
## S3 method for class 'data.frame'  
as.generic_mspct(x, force.spct.class = FALSE, ...)  
  
## S3 method for class 'generic_spct'  
as.generic_mspct(x, force.spct.class = FALSE, ...)  
  
## S3 method for class 'list'  
as.generic_mspct(x, force.spct.class = FALSE, ..., ncol = 1, byrow = FALSE)  
  
## S3 method for class 'matrix'  
as.generic_mspct(  
  x,  
  w.length,  
  member.class,  
  spct.data.var,  
  multiplier = 1,  
  byrow = NULL,  
  spct.names = "spct_",  
  ...  
)  
  
mat2mspct(  
  x,  
  w.length,  
  member.class,  
  spct.data.var,  
  multiplier = 1,  
  byrow = NULL,  
  spct.names = "spct_",  
  ...  
)
```


Arguments

<code>x</code>	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
<code>...</code>	passed to individual spectrum object constructor
<code>force.spct.class</code>	logical indicating whether to change the class of members to <code>generic_spct</code> or retain the existing class.
<code>ncol</code>	integer Number of 'virtual' columns in data
<code>byrow</code>	logical If <code>ncol > 1</code> how to read in the data
<code>w.length</code>	numeric A vector of wavelength values sorted in strictly ascending order (nm).
<code>member.class</code>	character The name of the class of the individual spectra to be constructed.
<code>spct.data.var</code>	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
<code>multiplier</code>	numeric A multiplier to be applied to the values in <code>x</code> to do unit or scale conversion.
<code>spct.names</code>	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of `x` converted into a `generic_mspct` object.

Methods (by class)

- default:
- data.frame:
- generic_spct:
- list:
- matrix:

Note

Members of `generic_mspct` objects can be heterogeneous: they can belong to any class derived from `generic_spct` and class is not enforced. When `x` is a list of data frames `force.spct.class = TRUE` needs to be supplied. When `x` is a square matrix an explicit argument is needed for `byrow` to indicate how data in `x` should be read. In every case the length of the `w.length` vector must match one of the dimensions of `x`.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.generic_spct *Coerce to a spectrum*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.generic_spct(x, ...)

## Default S3 method:
as.generic_spct(x, ...)
```

Arguments

x an R object
 ... other arguments passed to "set" functions

Value

A copy of x converted into a generic_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.matrix-mpsct *Coerce a collection of spectra into a matrix*

Description

Convert an object of class generic_mpsct or a derived class into an R matrix with wavelengths saved as an attribute and spectral data in rows or columns.

Usage

```
## S3 method for class 'generic_mspct'
as.matrix(x, spct.data.var, byrow = attr(x, "mspct.byrow"), ...)

mspct2mat(x, spct.data.var, byrow = attr(x, "mspct.byrow"), ...)
```

Arguments

x	generic_mspct object.
spct.data.var	character The name of the variable containing the spectral data.
byrow	logical. If FALSE (the default) the matrix is filled with the spectra stored by columns, otherwise the matrix is filled by rows.
...	currently ignored.

Warning!

This conversion preserves the spectral data but discards almost all the metadata contained in the spectral objects. In other words a matrix created with this function cannot be used to recreate the original object unless the same metadata is explicitly supplied when converting the matrix into new collection of spectra.

Note

Only collections of spectra containing spectra with exactly the same w. length values can by converted. If needed, the spectra can be re-expressed before attempting the conversion to a matrix.

as.object_mspct	<i>Coerce to a collection-of-spectra</i>
-----------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.object_mspct(x, ...)

## Default S3 method:
as.object_mspct(x, ...)

## S3 method for class 'data.frame'
as.object_mspct(
  x,
  Tfr.type = c("total", "internal"),
  Rfr.type = c("total", "specular"),
  strict.range = TRUE,
```

```

    ...
  )

  ## S3 method for class 'object_spct'
  as.object_mspct(x, ...)

  ## S3 method for class 'list'
  as.object_mspct(
    x,
    Tfr.type = c("total", "internal"),
    Rfr.type = c("total", "specular"),
    strict.range = TRUE,
    ...,
    ncol = 1,
    byrow = FALSE
  )

```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
Tfr.type	a character string, either "total" or "internal"
Rfr.type	a character string, either "total" or "specular"
strict.range	logical Flag indicating how off-range values are handled
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data

Value

A copy of x converted into a object_mspct object.

Methods (by class)

- default:
- data.frame:
- object_spct:
- list:

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.object_spct	<i>Coerce to a spectrum</i>
----------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.object_spct(x, ...)  
  
## Default S3 method:  
as.object_spct(  
  x,  
  Tfr.type = c("total", "internal"),  
  Rfr.type = c("total", "specular"),  
  strict.range = getOption("photobiology.strict.range", default = FALSE),  
  ...  
)
```

Arguments

x	an R object
...	other arguments passed to "set" functions
Tfr.type	a character string, either "total" or "internal"
Rfr.type	a character string, either "total" or "specular"
strict.range	logical Flag indicating whether off-range values result in an error instead of a warning

Value

A copy of x converted into a object_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.raw_mspct	<i>Coerce to a collection-of-spectra</i>
--------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.raw_mspct(x, ...)

## Default S3 method:
as.raw_mspct(x, ...)

## S3 method for class 'data.frame'
as.raw_mspct(x, ...)

## S3 method for class 'raw_spct'
as.raw_mspct(x, ...)

## S3 method for class 'list'
as.raw_mspct(x, ..., ncol = 1, byrow = FALSE)

## S3 method for class 'matrix'
as.raw_mspct(
  x,
  w.length,
  spct.data.var = "counts",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)
```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelengthvalues sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.

multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a raw_mspct object.

Methods (by class)

- default:
- data.frame:
- raw_spct:
- list:
- matrix:

Note

When x is a square matrix an explicit argument is needed for byrow to indicate how data in x should be read. In every case the length of the w.length vector must match one of the dimensions of x.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.raw_spct	<i>Coerce to a spectrum</i>
-------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.raw_spct(x, ...)
```

```
## Default S3 method:
as.raw_spct(x, ...)
```

Arguments

x	an R object
...	other arguments passed to "set" functions

Value

A copy of `x` converted into a `raw_spct` object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.reflector_mspct *Coerce to a collection-of-spectra*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.reflector_mspct(x, ...)

## Default S3 method:
as.reflector_mspct(x, ...)

## S3 method for class 'data.frame'
as.reflector_mspct(
  x,
  Rfr.type = c("total", "specular"),
  strict.range = TRUE,
  ...
)

## S3 method for class 'reflector_spct'
as.reflector_mspct(x, ...)

## S3 method for class 'list'
as.reflector_mspct(
  x,
  Rfr.type = c("total", "specular"),
  strict.range = TRUE,
  ...,
  ncol = 1,
```



```

    byrow = FALSE
  )

## S3 method for class 'matrix'
as.reflector_mspct(
  x,
  w.length,
  spct.data.var = "Rfr",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)

```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
Rfr.type	a character string, either "total" or "specular"
strict.range	logical Flag indicating how off-range values are handled
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelength values sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a reflector_mspct object.

Methods (by class)

- default:
- data.frame:
- reflector_spct:
- list:
- matrix:

Note

When `x` is a square matrix an explicit argument is needed for `byrow` to indicate how data in `x` should be read. In every case the length of the `w`. length vector must match one of the dimensions of `x`.

See Also

Other Coercion methods for collections of spectra: `as.calibration_mspct()`, `as.chroma_mspct()`, `as.cps_mspct()`, `as.filter_mspct()`, `as.generic_mspct()`, `as.object_mspct()`, `as.raw_mspct()`, `as.response_mspct()`, `as.source_mspct()`, `split2mspct()`, `subset2mspct()`

as.reflector_spct *Coerce to a spectrum*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.reflector_spct(x, ...)

## Default S3 method:
as.reflector_spct(
  x,
  Rfr.type = c("total", "specular"),
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  ...
)
```

Arguments

<code>x</code>	an R object
<code>...</code>	other arguments passed to "set" functions
<code>Rfr.type</code>	a character string, either "total" or "specular"
<code>strict.range</code>	logical Flag indicating whether off-range values result in an error instead of a warning

Value

A copy of `x` converted into a `reflector_spct` object.

Methods (by class)

- default:

See Also[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.response_mspct	<i>Coerce to a collection-of-spectra</i>
-------------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.response_mspct(x, ...)

## Default S3 method:
as.response_mspct(x, ...)

## S3 method for class 'data.frame'
as.response_mspct(x, time.unit = "second", ...)

## S3 method for class 'response_spct'
as.response_mspct(x, ...)

## S3 method for class 'list'
as.response_mspct(x, time.unit = "second", ..., ncol = 1, byrow = FALSE)

## S3 method for class 'matrix'
as.response_mspct(
  x,
  w.length,
  spct.data.var = "s.e.response",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)
```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
time.unit	character A string, "second", "day" or "exposure"

ncol	integer	Number of 'virtual' columns in data
byrow	logical	If ncol > 1 how to read in the data
w.length	numeric	A vector of wavelength values sorted in strictly ascending order (nm).
spct.data.var	character	The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
multiplier	numeric	A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character	Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a response_mspct object.

Methods (by class)

- default:
- data.frame:
- response_spct:
- list:
- matrix:

Note

When x is a square matrix an explicit argument is needed for byrow to indicate how data in x should be read. In every case the length of the w.length vector must match one of the dimensions of x.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.response_spct *Coerce to a spectrum*

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.response_spct(x, ...)
```

Default S3 method:

```
as.response_spct(x, time.unit = "second", ...)
```

Arguments

x	an R object
...	other arguments passed to "set" functions
time.unit	character A string, "second", "day" or "exposure"

Value

A copy of x converted into a response_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.source_spct\(\)](#), [source_spct\(\)](#)

as.solar_date	<i>Convert a solar_time object into solar_date object</i>
---------------	---

Description

Convert a solar_time object into solar_date object

Usage

```
as.solar_date(x, time)
```

Arguments

x	solar_time object.
time	an R date time object

Value

For method `as.solar_date()` a date-time object with the class attr set to "solar.time". This is needed only for unambiguous formatting and printing.

as.source_mspct	<i>Coerce to a collection-of-spectra</i>
-----------------	--

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.source_mspct(x, ...)

## Default S3 method:
as.source_mspct(x, ...)

## S3 method for class 'data.frame'
as.source_mspct(
  x,
  time.unit = c("second", "day", "exposure"),
  bswf.used = c("none", "unknown"),
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  ...
)

## S3 method for class 'source_spct'
as.source_mspct(x, ...)

## S3 method for class 'list'
as.source_mspct(
  x,
  time.unit = c("second", "day", "exposure"),
  bswf.used = c("none", "unknown"),
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  ...,
  ncol = 1,
  byrow = FALSE
)

## S3 method for class 'matrix'
as.source_mspct(
  x,
  w.length,
  spct.data.var = "s.e.irrad",
  multiplier = 1,
  byrow = NULL,
  spct.names = "spct_",
  ...
)
```

Arguments

x	a list of spectral objects or a list of objects such as data frames that can be converted into spectral objects.
...	passed to individual spectrum object constructor
time.unit	character A string, "second", "day" or "exposure"
bswf.used	character
strict.range	logical Flag indicating how off-range values are handled
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
w.length	numeric A vector of wavelength values sorted in strictly ascending order (nm).
spct.data.var	character The name of the variable that will contain the spectral data. This indicates what physical quantity is stored in the matrix and the units of expression used.
multiplier	numeric A multiplier to be applied to the values in x to do unit or scale conversion.
spct.names	character Vector of names to be assigned to collection members, either of length 1, or with length equal to the number of spectra.

Value

A copy of x converted into a source_mspct object.

Methods (by class)

- default:
- data.frame:
- source_spct:
- list:
- matrix:

Note

When x is a square matrix an explicit argument is needed for byrow to indicate how data in x should be read. In every case the length of the w.length vector must match one of the dimensions of x.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [split2mspct\(\)](#), [subset2mspct\(\)](#)

as.source_spct	<i>Coerce to a spectrum</i>
----------------	-----------------------------

Description

Return a copy of an R object with its class set to a given type of spectrum.

Usage

```
as.source_spct(x, ...)  
  
## Default S3 method:  
as.source_spct(  
  x,  
  time.unit = c("second", "day", "exposure"),  
  bswf.used = c("none", "unknown"),  
  strict.range = getOption("photobiology.strict.range", default = FALSE),  
  ...  
)
```

Arguments

x	an R object
...	other arguments passed to "set" functions
time.unit	character A string, "second", "day" or "exposure"
bswf.used	character
strict.range	logical Flag indicating whether off-range values result in an error instead of a warning

Value

A copy of x converted into a source_spct object.

Methods (by class)

- default:

See Also

[setGenericSpct](#)

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [source_spct\(\)](#)

as_energy	<i>Convert spectral photon irradiance into spectral energy irradiance</i>
-----------	---

Description

Convert a spectral photon irradiance [mol s⁻¹ m⁻² nm⁻¹] into a spectral energy irradiance [W m⁻² nm⁻¹].

Usage

```
as_energy(w.length, s.qmol.irrad)
```

Arguments

w.length numeric vector of wavelengths (nm).
s.qmol.irrad numeric vector of spectral photon irradiance values.

Value

A numeric vector of spectral (energy) irradiances.

See Also

Other low-level functions operating on numeric vectors.: [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.spct, as_energy(w.length, s.q.irrad))
```

as_quantum	<i>Convert spectral energy irradiance into spectral photon irradiance</i>
------------	---

Description

Convert spectral energy irradiance [W m⁻² nm⁻¹] into spectral photon irradiance expressed as number of photons [s⁻¹ m⁻² nm⁻¹]

Usage

```
as_quantum(w.length, s.e.irrad)
```

Arguments

w.length numeric vector of wavelengths (nm).
s.e.irrad numeric vector of spectral (energy) irradiance values.

Value

A numeric vector of spectral photon irradiances.

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [e2qmол_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
with(sun.data, as_quantum(w.length, s.e.irrad))
```

<code>as_quantum_mol</code>	<i>Convert spectral energy irradiance into spectral photon irradiance</i>
-----------------------------	---

Description

Convert spectral energy irradiance [$\text{W m}^{-2} \text{ nm}^{-1}$] into a spectral photon irradiance expressed in number of molds of photons [$\text{mol s}^{-1} \text{ m}^{-2} \text{ nm}^{-1}$].

Usage

```
as_quantum_mol(w.length, s.e.irrad)
```

Arguments

w.length numeric vector of wavelengths (nm).
s.e.irrad numeric vector of spectral (energy) irradiance values.

Value

a numeric vector of spectral photon irradiances.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data, as_quantum_mol(w.length, s.e.irrad))
```

as_tod	<i>Convert datetime to time-of-day</i>
--------	--

Description

Convert a datetime into a time of day expressed in hours, minutes or seconds from midnight in local time for a time zone. This conversion is useful when time-series data for different days needs to be compared or plotted based on the local time-of-day.

Usage

```
as_tod(x, unit.out = "hours", tz = NULL)
```

Arguments

x	a datetime object accepted by lubridate functions
unit.out	character string, One of "tod_time", "hours", "minutes", or "seconds".
tz	character string indicating time zone to be used in output.

Value

A numeric vector of the same length as x. If unit.out = "tod_time" an object of class "tod_time" which the same as for unit.out = "hours" but with the class attribute set, which dispatches to special format() and print() methods.

Examples

```
library(lubridate)
my_instants <- ymd_hms("2020-05-17 12:05:03") + days(c(0, 30))
my_instants
as_tod(my_instants)
as_tod(my_instants, unit.out = "tod_time")
```

average_spct	<i>Average spectral data.</i>
--------------	-------------------------------

Description

This function gives the result of integrating spectral data over wavelengths and dividing the result by the spread or span of the wavelengths.

Usage

```
average_spct(spct)
```

Arguments

spct	generic_spct
------	--------------

Value

One or more numeric values with no change in scale factor: e.g. [W m⁻² nm⁻¹] -> [W m⁻² nm⁻¹]. Each value in the returned vector corresponds to a variable in the spectral object, except for wavelength.

Examples

```
average_spct(sun.spct)
```

beesxyzCMF.spct	<i>Honeybee xyz chromaticity colour matching function data</i>
-----------------	--

Description

A dataset containing wavelengths at a 5 nm interval (300 nm to 700 nm) and the corresponding x, y, and z chromaticity coordinates. Original data from XXX.

A chroma_spct object with variables as follows:

Usage

```
beesxyzCMF.spct
```

Format

A data frame with 81 rows and 4 variables

Details

- w.length (nm)
- x
- y
- z

See Also

Other Visual response data examples: [ciev10.spct](#), [ciev2.spct](#), [ciexyzCC10.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

black_body.spct	<i>Theoretical black body</i>
-----------------	-------------------------------

Description

A dataset for a hypothetical object with transmittance 0/1 (0%), reflectance 0/1 (0%)

Format

A object_spct object with 4 rows and 3 variables

Details

- w.length (nm)
- Tfr (0..1)
- Rfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

c	<i>Combine collections of spectra</i>
---	---------------------------------------

Description

Combine two or more generic_mspct objects into a single object.

Usage

```
## S3 method for class 'generic_mspct'
c(..., recursive = FALSE, ncol = 1, byrow = FALSE)
```

Arguments

...	one or more generic_mspct objects to combine.
recursive	logical ignored as nesting of collections of spectra is not supported.
ncol	numeric Virtual number of columns
byrow	logical When object has two dimensions, how to map member objects to columns and rows.

Value

A collection of spectra object belonging to the most derived class shared among the combined objects.

calc_multipliers	<i>Spectral weights</i>
------------------	-------------------------

Description

Calculate multipliers for selecting a range of wavelengths and optionally applying a biological spectral weighting function (BSWF) and wavelength normalization. This function returns numeric multipliers that can be used to select a waveband and apply a weight.

Usage

```
calc_multipliers(
  w.length,
  w.band,
  unit.out = "energy",
  unit.in = "energy",
  use.cached.mult = FALSE,
  fill = 0
)
```

Arguments

w.length	numeric vector of wavelengths (nm).
w.band	waveband object.
unit.out	character A string: "photon" or "energy", default is "energy".
unit.in	character A string: "photon" or "energy", default is "energy".
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
fill	numeric If fill = NA then values returned for wavelengths outside the range of the waveband are set to NA.

Value

a numeric vector of multipliers of the same length as w.length.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data, calc_multipliers(w.length, new_waveband(400,700),"photon"))
with(sun.data, calc_multipliers(w.length, new_waveband(400,700),"photon"), use.cached.mult = TRUE)
```

calc_source_output *Scaled and/or interpolated light-source spectral output*

Description

Values calculated by interpolation from user-supplied spectral emission data or by name for light source data included in the packages photobiologySun, photobiologyLamps, or photobiologyLEDs, optionally re-scaling the spectral data values.

Usage

```
calc_source_output(
  w.length.out,
  w.length.in,
  s.irrad.in,
  unit.in = "energy",
```

```

    scaled = NULL,
    fill = NA,
    ...
  )

```

Arguments

w.length.out	numeric vector of wavelengths (nm) for output.
w.length.in	numeric vector of wavelengths (nm) for input.
s.irrad.in	numeric vector of spectral transmittance value (fractions or percent).
unit.in	a character string "energy" or "photon".
scaled	NULL, "peak", "area"; div ignored if !is.null(scaled).
fill	if NA, no extrapolation is done, and NA is returned for wavelengths outside the range of the input. If NULL then the tails are deleted. If 0 then the tails are set to zero.
...	Additional arguments passed to spline if called.

Value

a source_spct with three numeric vectors with wavelength values (w.length), scaled and interpolated spectral energy irradiance (s.e.irrad), scaled and interpolated spectral photon irradiance values (s.q.irrad).

Note

This is a convenience function that adds no new functionality but makes it a little easier to plot lamp spectral emission data consistently. It automates interpolation, extrapolation/trimming and scaling.

Examples

```

with(sun.data,
  calc_source_output(290:1100,
    w.length.in = w.length,
    s.irrad.in = s.e.irrad)
)

```

 ccd.spct

Spectral response of a back-thinned CCD image sensor.

Description

A dataset containing wavelengths at a 1 nm interval and spectral response as quantum efficiency for CCD sensor type S11071/S10420 from Hamamatsu (measured without a quartz window). These vectors are frequently used as sensors in high-UV-sensitivity vector spectrometers. Data digitized from manufacturer's data sheet. The original data is expressed as percent quantum efficiency with a value of 77% at the peak. The data have been re-expressed as fractions of one.

Usage

ccd.spct

Format

A response_spct object with 186 rows and 2 variables

Details

- w.length (nm).
- s.q.response (fractional quantum efficiency)

References

Hamamatsu (2014) Datasheet: CCD Image Sensors S11071/S10420-01 Series. Hamamatsu Photonics KK, Hamamatsu, City. <http://www.hamamatsu.com/jp/en/S11071-1004.html>. Visited 2017-12-15.

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspect](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

ccd.spct

checkTimeUnit

Check the "time.unit" attribute of an existing source_spct object

Description

Function to read the "time.unit" attribute

Usage

checkTimeUnit(x)

Arguments

x a source_spct object

Value

x possibly with the `time.unit` attribute modified

Note

if x is not a `source_spct` or a `response_spct` object, NA is returned

See Also

Other time attribute functions: [convertTfrType\(\)](#), [convertThickness\(\)](#), [convertTimeUnit\(\)](#), [getTimeUnit\(\)](#), [setTimeUnit\(\)](#)

check_spct	<i>Check validity of spectral objects</i>
------------	---

Description

Check that an R object contains the expected data members.

Usage

```
check_spct(x, byref, strict.range, force = FALSE, ...)

## Default S3 method:
check_spct(x, byref = FALSE, strict.range = NA, force = FALSE, ...)

## S3 method for class 'generic_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = NA,
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'calibration_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'raw_spct'
```

```
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'cps_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'filter_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'reflector_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'object_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)
```

```

## S3 method for class 'response_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = NA,
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'source_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

## S3 method for class 'chroma_spct'
check_spct(
  x,
  byref = TRUE,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  force = FALSE,
  multiple.wl = getMultipleWl(x),
  ...
)

```

Arguments

<code>x</code>	An R object
<code>byref</code>	logical indicating if new object will be created by reference or by copy of <code>x</code>
<code>strict.range</code>	logical indicating whether off-range values result in an error instead of a warning, NA disables the test.
<code>force</code>	logical If TRUE check is done even if checks are disabled.
<code>...</code>	additional param possible in derived methods
<code>multiple.wl</code>	numeric Maximum number of repeated w.length entries with same value.

Methods (by class)

- `default`: Default for generic function.
- `generic_spct`: Specialization for `generic_spct`.
- `calibration_spct`: Specialization for `calibration_spct`.
- `raw_spct`: Specialization for `raw_spct`.

- `cps_spct`: Specialization for `cps_spct`.
- `filter_spct`: Specialization for `filter_spct`.
- `reflector_spct`: Specialization for `reflector_spct`.
- `object_spct`: Specialization for `object_spct`.
- `response_spct`: Specialization for `response_spct`.
- `source_spct`: Specialization for `source_spct`.
- `chroma_spct`: Specialization for `chroma_spct`.

See Also

Other data validity check functions: [check_spectrum\(\)](#), [check_w.length\(\)](#), [enable_check_spct\(\)](#)

Examples

```
check_spct(sun.spct)

check_spct(sun.spct)
# try(check_spct(-sun.spct))
# try(check_spct((sun.spct[1, "w.length"] <- 1000)))
```

check_spectrum	<i>Sanity check a spectrum</i>
----------------	--------------------------------

Description

Checks spectral irradiance data in numeric vectors for compliance with assumptions used in calculations.

Usage

```
check_spectrum(w.length, s.irrad)
```

Arguments

<code>w.length</code>	numeric vector of wavelengths (nm).
<code>s.irrad</code>	numeric Corresponding vector of spectral (energy) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$).

Value

A single logical value indicating whether test was passed or not

See Also

Other data validity check functions: [check_spct\(\)](#), [check_w.length\(\)](#), [enable_check_spct\(\)](#)

Examples

```
with(sun.data, check_spectrum(w.length, s.e.irrad))
```

check_w.length	<i>Sanity check of wavelengths (internal function).</i>
----------------	---

Description

This function checks a w.length vector for compliance with assumptions used in calculations.

Usage

```
check_w.length(w.length)
```

Arguments

w.length numeric array of wavelength (nm)

Value

a single logical value indicating whether test was passed or not

See Also

Other data validity check functions: [check_spct\(\)](#), [check_spectrum\(\)](#), [enable_check_spct\(\)](#)

Examples

```
with(sun.data, photobiology:::check_w.length(w.length))
```

ciev10.spct	<i>Linear energy CIE 2008 luminous efficiency function 10 deg data</i>
-------------	--

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding response values for a 10 degrees target. Original data from <http://www.cvrl.org/> downloaded on 2014-04-29 The variables are as follows:

- w.length (nm)
- x
- y
- z

Usage

ciev10.spct

Format

A chroma_spct object with 441 rows and 4 variables

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev2.spct](#), [ciexyzCC10.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

Examples

ciev10.spct

ciev2.spct

Linear energy CIE 2008 luminous efficiency function 2 deg data

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding response values for a 2 degrees target. Original data from <http://www.cvrl.org/> downloaded on 2014-04-29 The variables are as follows:

Usage

ciev2.spct

Format

A chroma_spct object with 441 rows and 4 variables

Details

- w.length (nm)
- x
- y
- z

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciexyzCC10.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

Examples

`ciev2.spct`

<code>ciexyzCC10.spct</code>	<i>CIE xyz chromaticity coordinates (CC) 10 deg data</i>
------------------------------	--

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding x, y, and z chromaticity coordinates. Derived from proposed CIE 2006 standard. Original data from <http://www.cvr1.org/> downloaded on 2014-04-29 The variables are as follows:

- w.length (nm)
- x
- y
- z

Usage

`ciexyzCC10.spct`

Format

A `chroma_spct` object with 441 rows and 4 variables

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciev2.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

Examples

`ciexyzCC10.spct`

ciexyzCC2.spct	<i>CIE xyz chromaticity coordinates 2 deg data</i>
----------------	--

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding x, y, and z chromaticity coordinates. According to proposed CIE 2006 standard. Original data from <http://www.cvr1.org/> downloaded on 2014-04-28 The variables are as follows:

- w.length (nm)
- x
- y
- z

Usage

```
ciexyzCC2.spct
```

Format

A chroma_spct object with 441 rows and 4 variables

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciev2.spct](#), [ciexyzCC10.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

Examples

```
ciexyzCC2.spct
```

ciexyzCMF10.spct	<i>Linear energy CIE xyz colour matching function (CMF) 10 deg data</i>
------------------	---

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding x, y, and z 10 degrees CMF values. Derived from proposed CIE 2006 standard. Original data from <http://www.cvr1.org/> downloaded on 2014-04-29 The variables are as follows:

- w.length (nm)
- x
- y
- z

Usage

ciexyzCMF10.spct

Format

A chroma_spct object with 441 rows and 4 variables

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciev2.spct](#), [ciexyzCC10.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF2.spct](#), [cone_fundamentals10.spct](#)

Examples

ciexyzCMF10.spct

cixyzCMF2.spct	<i>Linear energy CIE xyz colour matching function (CMF) 2 deg data</i>
----------------	--

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding x, y, and z 2 degrees CMF values. Derived from proposed CIE 2006 standard. Original data from <http://www.cvr1.org/> downloaded on 2014-04-29 The variables are as follows:

- w.length (nm)
- x
- y
- z

Usage

```
cixyzCMF2.spct
```

Format

A chroma_spct object with 441 rows and 4 variables

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciev2.spct](#), [cixyzCC10.spct](#), [cixyzCC2.spct](#), [cixyzCMF10.spct](#), [cone_fundamentals10.spct](#)

Examples

```
cixyzCMF2.spct
```

class_spct	<i>Query which is the class of a spectrum</i>
------------	---

Description

Functions to check if an object is a generic spectrum, or coerce it if possible.

Usage

```
class_spct(x)
```

Arguments

x any R object

Value

class_spct returns a vector containing all matching xxxx.spct classes.

Examples

```
class_spct(sun.spct)
class(sun.spct)
```

clean	<i>Clean (=replace) off-range values in a spectrum</i>
-------	--

Description

These functions implement the equivalent of replace() but for spectral objects instead of vectors.

Usage

```
clean(x, range, range.s.data, fill, ...)
```

```
## Default S3 method:
```

```
clean(x, range, range.s.data, fill, ...)
```

```
## S3 method for class 'source_spct'
```

```
clean(
```

```
  x,
```

```
  range = x,
```

```
  range.s.data = c(0, NA),
```

```
  fill = range.s.data,
```

```
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
```

```
    ...
  )

## S3 method for class 'filter_spct'
clean(
  x,
  range = x,
  range.s.data = NULL,
  fill = range.s.data,
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
  ...
)

## S3 method for class 'reflector_spct'
clean(x, range = x, range.s.data = c(0, 1), fill = range.s.data, ...)

## S3 method for class 'object_spct'
clean(
  x,
  range = x,
  range.s.data = c(0, 1),
  fill = range.s.data,
  min.Afr = NULL,
  ...
)

## S3 method for class 'response_spct'
clean(
  x,
  range = x,
  range.s.data = c(0, NA),
  fill = range.s.data,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'cps_spct'
clean(x, range = x, range.s.data = c(0, NA), fill = range.s.data, ...)

## S3 method for class 'raw_spct'
clean(
  x,
  range = x,
  range.s.data = c(NA_real_, NA_real_),
  fill = range.s.data,
  ...
)
```

```
## S3 method for class 'generic_spct'
clean(
  x,
  range = x,
  range.s.data = c(NA_real_, NA_real_),
  fill = range.s.data,
  col.names,
  ...
)

## S3 method for class 'source_mspct'
clean(
  x,
  range = NULL,
  range.s.data = c(0, NA),
  fill = range.s.data,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'filter_mspct'
clean(
  x,
  range = NULL,
  range.s.data = NULL,
  fill = range.s.data,
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'reflector_mspct'
clean(
  x,
  range = NULL,
  range.s.data = c(0, 1),
  fill = range.s.data,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'object_mspct'
clean(
  x,
```

```
    range = NULL,
    range.s.data = c(0, 1),
    fill = range.s.data,
    min.Afr = NULL,
    ...,
    .parallel = FALSE,
    .paropts = NULL
)

## S3 method for class 'response_mspct'
clean(
  x,
  range = NULL,
  range.s.data = c(0, NA),
  fill = range.s.data,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'cps_mspct'
clean(
  x,
  range = NULL,
  range.s.data = c(0, NA),
  fill = range.s.data,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
clean(
  x,
  range = NULL,
  range.s.data = c(0, NA),
  fill = range.s.data,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'generic_mspct'
clean(
  x,
  range = x,
  range.s.data = c(NA_real_, NA_real_),
```

```

    fill = range.s.data,
    col.names,
    ...,
    .parallel = FALSE,
    .paropts = NULL
  )

```

Arguments

<code>x</code>	an R object
<code>range</code>	numeric vector of wavelengths
<code>range.s.data</code>	numeric vector of length two giving the allowable range for the spectral data.
<code>fill</code>	numeric vector of length 1 or 2, giving the replacement values to use at each extreme of the range.
<code>...</code>	currently ignored
<code>unit.out</code>	character string with allowed values "energy", and "photon", or its alias "quantum"
<code>qty.out</code>	character string with allowed values "energy", and "photon", or its alias "quantum"
<code>min.Afr</code>	numeric Gives the minimum value accepted for the computed absorptance. The default NULL sets a valid value ($Afr \geq 0$) with a warning. If an integer value is passed to <code>digits</code> values are adjusted silently.
<code>col.names</code>	character The name of the variable to clean
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of `x`, possibly with some of the spectral data values replaced by the value passed to `fill`.

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Replace off-range values in a source spectrum
- `filter_spct`: Replace off-range values in a filter spectrum
- `reflector_spct`: Replace off-range values in a reflector spectrum
- `object_spct`: Replace off-range values in an object spectrum
- `response_spct`: Replace off-range values in a response spectrum
- `cps_spct`: Replace off-range values in a counts per second spectrum
- `raw_spct`: Replace off-range values in a raw counts spectrum
- `generic_spct`: Replace off-range values in a generic spectrum

- source_mspct:
- filter_mspct:
- reflector_mspct:
- object_mspct:
- response_mspct:
- cps_mspct:
- raw_mspct:
- generic_mspct:

Note

In the case of object_spct objects, cleaning is done first on the Rfr and Tfr columns and subsequently Afr estimated and if needed half of deviation of Afr from the expected minimum value subtracted from each of Rfr and Tfr.

clear.spct

Theoretical spectrum of a clear material

Description

A dataset for a hypothetical object with transmittance 1/1 (100%)

Usage

clear.spct

Format

A filter_spct object with 4 rows and 2 variables

Details

- w.length (nm).
- Tfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

clear.spct

clear_body.spct	<i>Theoretical clear body</i>
-----------------	-------------------------------

Description

A dataset for a hypothetical object with transmittance 1/1 (100%), reflectance 0/1 (0%)

Format

A object_spct object with 4 rows and 3 variables

Details

- w.length (nm)
- Tfr (0..1)
- Rfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

clip_wl	<i>Clip head and/or tail of a spectrum</i>
---------	--

Description

Clip head and tail of a spectrum based on wavelength limits, no interpolation used at range boundaries.

Usage

```
clip_wl(x, range, ...)

## Default S3 method:
clip_wl(x, range, ...)

## S3 method for class 'generic_spct'
clip_wl(x, range = NULL, ...)

## S3 method for class 'generic_mspct'
clip_wl(x, range = NULL, ...)
```

```
## S3 method for class 'waveband'  
clip_wl(x, range = NULL, ...)  
  
## S3 method for class 'list'  
clip_wl(x, range = NULL, ...)
```

Arguments

x	an R object.
range	a numeric vector of length two, or any other object for which function <code>range()</code> will return range of wavelengths expressed in nanometres.
...	ignored (possibly used by derived methods).

Value

A copy of x, most frequently of a shorter length, and never longer.

Methods (by class)

- default: Default for generic function
- generic_spct: Clip an object of class "generic_spct" or derived.
- generic_mspct: Clip an object of class "generic_mspct" or derived.
- waveband: Clip an object of class "waveband".
- list: Clip a list (of objects of class "waveband").

Note

The condition tested is $wl \geq range[1] \ \& \ wl < (range[2] + 1e-13)$.

See Also

Other trim functions: [trim_spct\(\)](#), [trim_waveband\(\)](#), [trim_wl\(\)](#)

Examples

```
clip_wl(sun.spct, range = c(400, 500))  
clip_wl(sun.spct, range = c(NA, 500))  
clip_wl(sun.spct, range = c(400, NA))
```

color_of	<i>Color of an object</i>
----------	---------------------------

Description

Equivalent RGB color of an object such as a spectrum, wavelength or waveband.

Usage

```

color_of(x, ...)

## Default S3 method:
color_of(x, ...)

## S3 method for class 'numeric'
color_of(x, type = "CMF", chroma.type = type, ...)

## S3 method for class 'list'
color_of(x, short.names = TRUE, type = "CMF", chroma.type = type, ...)

## S3 method for class 'waveband'
color_of(x, short.names = TRUE, type = "CMF", chroma.type = type, ...)

## S3 method for class 'source_spct'
color_of(x, type = "CMF", chroma.type = type, ...)

## S3 method for class 'source_mspct'
color_of(x, ..., idx = "spct.idx")

colour_of(x, ...)

color(x, ...)

fast_color_of_wl(x, type = "CMF", ...)

fast_color_of_wb(x, type = "CMF", ...)

```

Arguments

x	an R object.
...	ignored (possibly used by derived methods).
type, chroma.type	character telling whether "CMF", "CC", or "both" should be returned for human vision, or an object of class chroma_spct for any other trichromatic visual system.
short.names	logical indicating whether to use short or long names for wavebands
idx	character Name of the column with the names of the members of the collection of spectra.

Value

A color definition in hexadecimal format as a character string of 7 characters, "#" followed by the red, blue, and green values in hexadecimal (scaled to 0 ... 255). In the case of the specialization for `list`, a list of such definitions is returned. In the case of a collection of spectra, a `data.frame` with one column with such definitions and by default an additional column with names of the spectra as index. In case of missing input the returned value is NA.

Methods (by class)

- `default`: Default method (returns always "black").
- `numeric`: Method that returns Color definitions corresponding to numeric values representing a wavelengths in nm.
- `list`: Method that returns Color of elements in a list.
- `waveband`: Color at midpoint of a `waveband` object.
- `source_spct`:
- `source_mspct`:

Deprecated

Use of `color()` is deprecated as this wrapper function may be removed in future versions of the package because of name clashes. Use `color_of()` instead.

Note

When `x` is a list but not a `waveband`, if a method `color_of` is not available for the class of each element of the list, then `color_of.default` will be called.

Function `fast_color_of_wl()` should be used only when high performance is needed. It speeds up performance by rounding the wavelength values in the numeric vector passed as argument to `x` and then retrieves the corresponding pre-computed color definitions if `type` is either "CMF" or "CC". In other cases it falls-back to calling `color_of.numeric()`. Returned color definitions always have default names irrespective of names of `x`, which is different from the behavior of `color_of()` methods.

Function `fast_color_of_wb()` accepts `waveband` objects and lists of `waveband` objects. If all `wavebands` are narrow, it issues a vectotized call to `fast_color_of_wl()` with a vector of `waveband` midpoint wavelengths.

Examples

```
wavelengths <- c(300, 420, 500, 600, NA) # nanometres
color_of(wavelengths)
color_of(waveband(c(300,400)))
color_of(list(blue = waveband(c(400,480)), red = waveband(c(600,700))))
color_of(numeric())
color_of(NA_real_)

color_of(sun.spct)
```

 compare_spct

Coarse-grained comparison of two spectra

Description

Compare two spectra using a specified summary function pre-applied to wavelength intervals.

Usage

```
compare_spct(
  x,
  w.band = 10,
  .summary.fun = NULL,
  ...,
  .comparison.fun = `/\`,
  returned.value = "spectrum",
  use.hinges = FALSE,
  short.names = TRUE
)
```

Arguments

<code>x</code>	A collection of two spectral objects of the same type.
<code>w.band</code>	waveband object or a numeric stepsize in nanometres.
<code>.summary.fun</code>	function. The summary function to use. It must be a method accepting object <code>x</code> as first argument.
<code>...</code>	additional named arguments passed down to <code>.summary.fun</code> .
<code>.comparison.fun</code>	function. The comparison function to use.
<code>returned.value</code>	character One of "data.frame", "spectrum", "tagged.spectrum".
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the returned spectrum when tagging it.
<code>short.names</code>	logical Flag indicating whether to use short or long names for wavebands when tagging.

Details

Summaries are computed for each of the wavebands in `w.band` by applying function `.summary.fun` separately to each spectrum, after trimming them to the overlapping wavelength region. Next the matching summaries are compared by means of `.comparison.fun`. Both the summaries and the result of the comparison are returned. Columns containing summary values are named by concatenating the name each member spectrum with the name of the argument passed to `.summary.fun`.

Tagging is useful for plotting using wavelength based colours, or when names for wavebands are used as annotations. When tagging is requested, the spectrum is passed to method `tag` with `use.hinges` and `short.names` as additional arguments.

Value

A `generic_spct`, tagged or not with the wavebands, or a `data.frame` object containing the summary values per waveband for each spectrum and the result of applying the comparison function to these summaries.

Examples

```
compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)))
compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)),
              w.band = NULL)
compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)),
              w.band = list(waveband(c(640, 650)), waveband(c(720, 740))))

compare_spct(filter_mspct(list(pet = polyester.spct,
                               yllw = yellow_gel.spct)),
              w.band = 50,
              .comparison.fun = `<`))

head(
  compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)),
              returned.value = "data.frame")
)
compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)),
              returned.value = "tagged.spectrum")
compare_spct(source_mspct(list(sun1 = sun.spct, sun2 = sun.spct * 2)),
              returned.value = "tagged.spectrum",
              use.hinges = TRUE)
```

cone_fundamentals10.spct

Ten-degree cone fundamentals

Description

A dataset containing wavelengths at a 1 nm interval (390 nm to 830 nm) and the corresponding response values for a 2 degrees target. Original data from <http://www.cvrl.org/> downloaded on 2014-04-29 The variables are as follows:

Usage

cone_fundamentals10.spct

cone_fundamentals10.mspct

Format

A `chroma_spct` object with 440 rows and 4 variables

An object of class `response_mspct` (inherits from `generic_mspct`, `list`) with 3 rows and 1 columns.

Details

- `w.length` (nm)
- `x`
- `y`
- `z`

Value

A `chroma_spct` object.

A `response_mspct` object containing the same data in three `response_spct` objects.

Author(s)

CIE

See Also

Other Visual response data examples: [beesxyzCMF.spct](#), [ciev10.spct](#), [ciev2.spct](#), [ciexyzCC10.spct](#), [ciexyzCC2.spct](#), [ciexyzCMF10.spct](#), [ciexyzCMF2.spct](#)

Examples

```
cone_fundamentals10.spct
```

convertTfrType

Convert the "Tfr.type" attribute

Description

Function to set the "Tfr.type" attribute and simultaneously converting the spectral data to correspond to the new type.

Usage

```
convertTfrType(x, Tfr.type = NULL)
```

Arguments

`x` a `filter_spct`, `object_spct`, `filter_mspct` or `object_mspct` object.
`Tfr.type` character One of `#internal` or `"total"`.

Details

Internal transmittance uses as reference the light entering the object while total transmittance takes the incident light as reference. The conversion is possible only if reflectance is known. Either as spectral data in an `object_spct` object, or a `filter_spct` object that is under the hood an `object_spct`, or if a fixed reflectance factor applicable to all wavelengths is known.

Value

`x` possibly with the "thickness" field of the "filter.properties" attribute modified

Note

if `x` is not a `filter_spct` object, `x` is returned unchanged. If or `x` does not have the "filter.properties" attribute set and with no missing data, `x` is returned with `Tfr` set to NA values.

See Also

Other time attribute functions: [checkTimeUnit\(\)](#), [convertThickness\(\)](#), [convertTimeUnit\(\)](#), [getTimeUnit\(\)](#), [setTimeUnit\(\)](#)

Examples

```
my.spct <- polyester.spct
filter_properties(my.spct) <- list(Rfr.constant = 0.07,
                                  thickness = 125e-6,
                                  attenuation.mode = "absorption")
convertTfrType(my.spct, Tfr.type = "internal")
```

<code>convertThickness</code>	<i>Convert the "thickness" attribute of an existing filter_spct object.</i>
-------------------------------	---

Description

Function to set the "thickness" attribute and simultaneously converting the spectral data to correspond to the new thickness.

Usage

```
convertThickness(x, thickness = NULL)
```

Arguments

<code>x</code>	a <code>filter_spct</code> , <code>object_spct</code> , <code>filter_mspct</code> or <code>object_mspct</code> object.
<code>thickness</code>	numeric (m)

Details

For spectral transmittance at a different thickness to be exactly computed, it needs to be based on internal transmittance. This function will apply `convertTfrType()` to `x` if needed, but to succeed metadata should be available. Please, see [convertTfrType](#).

Value

`x` possibly with the "thickness" field of the "filter.properties" attribute modified

Note

if `x` is not a `filter_spct` object, `x` is returned unchanged. If or `x` does not have the "filter.properties" attribute set and with no missing data, `x` is returned with `Tfr` set to NA values.

See Also

Other time attribute functions: [checkTimeUnit\(\)](#), [convertTfrType\(\)](#), [convertTimeUnit\(\)](#), [getTimeUnit\(\)](#), [setTimeUnit\(\)](#)

Examples

```
my.spct <- polyester.spct
filter_properties(my.spct)
convertThickness(my.spct, thickness = 250e-6)
```

convertTimeUnit

Convert the "time.unit" attribute of an existing source_spct object

Description

Function to set the "time.unit" attribute and simultaneously rescaling the spectral data to be expressed using the new time unit as basis of expression. The change is done by reference ('in place').

Usage

```
convertTimeUnit(x, time.unit = NULL, ...)
```

Arguments

<code>x</code>	source_spct or response_spct object
<code>time.unit</code>	a character string, either "second", "hour", "day", "exposure" or "none", or a <code>lubridate::duration</code>
<code>...</code>	(currently ignored)

Value

x possibly with the `time.unit` attribute modified

Note

if x is not a `source_spct` or a `response_spct` object, or `time.unit` is `NULL` x is returned unchanged, if the existing or new `time.unit` cannot be converted to a duration, then the returned spectrum will contain NAs.

See Also

Other time attribute functions: [checkTimeUnit\(\)](#), [convertTfrType\(\)](#), [convertThickness\(\)](#), [getTimeUnit\(\)](#), [setTimeUnit\(\)](#)

Examples

```
my.spct <- sun.spct
my.spct
convertTimeUnit(my.spct, "day")
my.spct
```

convolve_each

Convolve function for collections of spectra

Description

Convolve function for collections of spectra which applies an operation on all the individual members of the collection(s) of spectra.

Usage

```
convolve_each(e1, e2, oper = `*`, sep = "_", ...)
```

Arguments

e1	an object of class <code>generic_mspct</code> or <code>generic_scpt</code> or <code>numeric</code>
e2	an object of class <code>generic_mspct</code> or <code>generic_scpt</code> or <code>numeric</code>
oper	function, usually but not necessarily an operator with two arguments.
sep	character Used when pasting the names of members of e1 and e2 to form the names of members of the returned collection of spectra.
...	additional arguments passed to oper if present.

Note

At least one of e1 and e2 must be a `generic_mspct` object or derived.

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

copy_attributes	<i>Copy attributes</i>
-----------------	------------------------

Description

Copy attributes from *x* to *y*. Methods defined for spectral and waveband objects of classes from package 'photobiology'.

Usage

```
copy_attributes(x, y, which, ...)

## Default S3 method:
copy_attributes(x, y, which = NULL, ...)

## S3 method for class 'generic_spct'
copy_attributes(x, y, which = NULL, which.not = NULL, copy.class = FALSE, ...)

## S3 method for class 'generic_mspct'
copy_attributes(x, y, which = NULL, which.not = NULL, copy.class = FALSE, ...)

## S3 method for class 'waveband'
copy_attributes(x, y, which = NULL, ...)
```

Arguments

<i>x</i> , <i>y</i>	R objects
<i>which</i>	character Names of attributes to copy, if NULL all those relevant according to the class of <i>x</i> is used as default,
...	not used
<i>which.not</i>	character Names of attributes not to be copied. The names passed here are removed from the list for <i>which</i> , which is most useful when we want to modify the default.
<i>copy.class</i>	logical If TRUE class attributes are also copied.

Value

A copy of *y* with additional attributes set.

Methods (by class)

- default: Default for generic function
- generic_spct:
- generic_mspct:
- waveband:

cps2irrad

Conversion from counts per second to physical quantities

Description

Conversion of spectral data expressed as cps into irradiance, transmittance or reflectance.

Usage

```
cps2irrad(x.sample, pre.fun = NULL, ...)
```

```
cps2Rfr(x.sample, x.white, x.black = NULL, dyn.range = NULL)
```

```
cps2Tfr(x.sample, x.clear, x.opaque = NULL, dyn.range = NULL)
```

Arguments

x.sample, x.clear, x.opaque, x.white, x.black	cps_spct objects.
pre.fun	function A function applied to x.sample before conversion.
...	Additional arguments passed to pre.fun.
dyn.range	numeric The effective dynamic range of the instrument, if NULL it is automatically set based on integration time bracketing.

Value

A source_spct, filter_spct or reflector_spct object containing the spectral values expressed in physical units.

Note

In contrast to other classes defined in package 'photobiology', class "cps_spct" can have more than one column of cps counts in cases where the intention is to merge these values as part of the processing at the time the calibration is applied. However, being these functions the final step in the conversion to physical units, they accept as input only objects with a single "cps" column, as merging is expected to have been already done.

D2.UV586

Data for typical calibration lamps

Description

A dataset containing fitted constants to be used as input for function `D2_spectrum`.

Format

A `polynom::polynomial` object with 6 constants.

Details

An object of class `polynom::polynomial`.

Author(s)

Lasse Ylianttila (data)

D2.UV653

Data for typical calibration lamps

Description

A dataset containing fitted constants to be used as input for function `D2_spectrum`.

Format

A `polynom::polynomial` object with 6 constants.

Details

An object of class `polynom::polynomial`.

Author(s)

Lasse Ylianttila (data)

D2.UV654

*Data for typical calibration lamps***Description**

A dataset containing fitted constants to be used as input for function `D2_spectrum`.

Format

A `polynom::polynomial` object with 6 constants.

Details

An object of class `polynom::polynomial`.

Author(s)

Lasse Ylianttila (data)

D2_spectrum

*Calculate deuterium lamp output spectrum from fitted constants***Description**

Calculate values by means of a n th degree polynomial from user-supplied constants (for example from a lamp calibration certificate).

Usage

```
D2_spectrum(w.length, k = photobiology::D2.UV653, fill = NA_real_)
```

Arguments

<code>w.length</code>	numeric vector of wavelengths (nm) for output
<code>k</code>	a <code>polynom::polynomial</code> object with n constants for the polynomial
<code>fill</code>	if NA, no extrapolation is done, and NA is returned for wavelengths outside the range 190 nm to 450 nm. If NULL then the tails are deleted. If 0 then the tails are set to zero, etc. NA is default.

Value

a dataframe with four numeric vectors with wavelength values (`w.length`), energy and photon irradiance (`s.e.irrad`, `s.q.irrad`) depending on the argument passed to `unit.out` (`s.irrad`).

Note

This function is valid for wavelengths in the range 180 nm to 495 nm, for wavelengths outside this range NAs are returned.

Examples

```
D2_spectrum(200)
D2_spectrum(170:220)
```

D65.illuminant.spct *CIE D65 illuminant data*

Description

A dataset containing wavelengths at a 5 nm interval (300 nm to 830 nm) and the corresponding spectral energy irradiance normalized to 1 at 560 nm. Spectrum approximates the midday solar spectrum at middle latitude as 'corresponds' to the white point of a black body a 6504 K. Original data from <http://files.cie.co.at/204.xls> downloaded on 2014-07-25 The variables are as follows:

Usage

```
D65.illuminant.spct
```

Format

A source spectrum with 107 rows and 2 variables

Details

- w.length (nm)
- s.e.irrad (rel. units)

Author(s)

CIE

See Also

Other Spectral data examples: [A.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
D65.illuminant.spct
```

day_night	<i>Times for sun positions</i>
-----------	--------------------------------

Description

Functions for calculating the timing of solar positions, given geographical coordinates and dates. They can be also used to find the time for an arbitrary solar elevation between 90 and -90 degrees by supplying "twilight" angle(s) as argument.

Usage

```
day_night(
  date = lubridate::now(tzone = "UTC"),
  tz = lubridate::tz(date),
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "none",
  unit.out = "hours"
)
```

```
day_night_fast(date, tz, geocode, twilight, unit.out)
```

```
noon_time(
  date = lubridate::today(),
  tz = lubridate::tz(date),
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "none",
  unit.out = "datetime"
)
```

```
sunrise_time(
  date = lubridate::today(),
  tz = lubridate::tz(date),
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "sunlight",
  unit.out = "datetime"
)
```

```
sunset_time(
  date = lubridate::today(),
  tz = lubridate::tz(date),
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "sunlight",
  unit.out = "datetime"
)
```

```

)

day_length(
  date = lubridate::now(),
  tz = "UTC",
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "sunlight",
  unit.out = "hours"
)

night_length(
  date = lubridate::now(),
  tz = "UTC",
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),
  twilight = "sunlight",
  unit.out = "hours"
)

```

Arguments

<code>date</code>	"vector" of POSIXct times or Date objects, any valid TZ is allowed, default is current date at Greenwich.
<code>tz</code>	character vector indicating time zone to be used in output.
<code>geocode</code>	data frame with one or more rows and variables lon and lat as numeric values (degrees). If present, address will be copied to the output.
<code>twilight</code>	character string, one of "none", "rim", "refraction", "sunlight", "civil", "nautical", "astronomical", or a numeric vector of length one, or two, giving solar elevation angle(s) in degrees (negative if below the horizon).
<code>unit.out</code>	character string, One of "datetime", "day", "hour", "minute", or "second".

Details

Twilight names are interpreted as follows. "none": solar elevation = 0 degrees. "rim": upper rim of solar disk at the horizon or solar elevation = $-0.53 / 2$. "refraction": solar elevation = 0 degrees + refraction correction. "sunlight": upper rim of solar disk corrected for refraction, which is close to the value used by the online NOAA Solar Calculator. "civil": -6 degrees, "naval": -12 degrees, and "astronomical": -18 degrees. Unit names for output are as follows: "day", "hours", "minutes" and "seconds" times for sunrise and sunset are returned as times-of-day since midnight expressed in the chosen unit. "date" or "datetime" return the same times as datetime objects with TZ set (this is much slower than "hours"). Day length and night length are returned as numeric values expressed in hours when "datetime" is passed as argument to `unit.out`. If twilight is a numeric vector of length two, the element with index 1 is used for sunrise and that with index 2 for sunset.

Value

A tibble with variables `day`, `tz`, `twilight.rise`, `twilight.set`, `longitude`, `latitude`, `address`, `sunrise`, `noon`, `sunset`, `daylength`, `nightlength` or the corresponding individual vectors.

`noon_time`, `sunrise_time` and `sunset_time` return a vector of POSIXct times

day_length and night_length return numeric a vector giving the length in hours

Warning

Be aware that R's Date class does not save time zone metadata. This can lead to ambiguities in the current implementation based on time instants. The argument passed to date should be of class POSIXct, in other words an instant in time, from which the correct date will be computed based on the tz argument.

Note

This function is an implementation of Meeus equations as used in NOAAs on-line web calculator, which are very precise and valid for a very broad range of dates. For sunrise and sunset the times are affected by refraction in the atmosphere, which does in turn depend on weather conditions. The effect of refraction on the apparent position of the sun is only an estimate based on "typical" conditions. The more tangential to the horizon is the path of the sun, the larger the effect of refraction is on the times of visual occlusion of the sun behind the horizon—i.e. the largest timing errors occur at high latitudes. The computation is not defined for latitudes 90 and -90 degrees, i.e. at the poles.

There exists a different R implementation of the same algorithms called "AstroCalcPureR" available as function astrocalc4r in package 'fishmethods'. Although the equations used are almost all the same, the function signatures and which values are returned differ. In particular, the present implementation splits the calculation into two separate functions, one returning angles at given instants in time, and a separate one returning the timing of events for given dates.

In the current implementation functions sunrise_time, noon_time, sunset_time and day_length are wrappers on day_night, so if more than one quantity is needed it is preferable to directly call day_night as it will be faster.

night_length returns the length of night-time conditions in one day (00:00:00 to 23:59:59), rather than the length of the night between two consecutive days.

References

The primary source for the algorithm used is the book: Meeus, J. (1998) *Astronomical Algorithms*, 2 ed., Willmann-Bell, Richmond, VA, USA. ISBN 978-0943396613.

A different implementation is available at <https://www.nefsc.noaa.gov/AstroCalc4R/> and in R package `astrocalc4r`. In 'fishmethods' (= 1.11-0) there is a bug in function `astrocalc4r()` that affects sunrise and sunset times.

An interactive web page using the same algorithms is available at <https://www.esrl.noaa.gov/gmd/grad/solcalc/>. There are small differences in the returned times compared to our function that seem to be related to the estimation of atmospheric refraction (about 0.1 degrees).

See Also

[sun_angles](#).

Other astronomy related functions: `format.solar_time()`, `format.tod_time()`, `is.solar_time()`, `print.solar_time()`, `print.tod_time()`, `solar_time()`, `sun_angles()`

Examples

```
library(lubridate)
my.geocode <- data.frame(lat = 60, lon = 25)
day_night(ymd("2015-05-30"), geocode = my.geocode)
day_night(ymd("2015-05-30") + days(1:10), geocode = my.geocode, twilight = "civil")
sunrise_time(ymd("2015-05-30"), geocode = my.geocode)
noon_time(ymd("2015-05-30"), geocode = my.geocode)
sunset_time(ymd("2015-05-30"), geocode = my.geocode)
day_length(ymd("2015-05-30"), geocode = my.geocode)
day_length(ymd("2015-05-30"), geocode = my.geocode, unit.out = "day")
```

defunct

Defunct functions and methods

Description

Functions listed here have been removed or deleted, and temporarily replaced by stubs that report this when they are called.

Usage

```
f_mspct(...)
mutate_mspct(...)
calc_filter_multipliers(...)
T2T(...)
getAfrType(...)
setAfrType(...)
```

Arguments

```
...          ignored
```

Note

Function `f_mspct()` has been renamed `msdply()`.
Function `mutate_mspct()` has been renamed `msmsply()`.
Function `calc_filter_multipliers()` has been removed.
Function `calc_filter_multipliers()` has been removed.
Method `getAfrType()` has been removed.
Method `setAfrType()` has been removed.

despike	<i>Remove spikes from spectrum</i>
---------	------------------------------------

Description

Function that returns an R object with observations corresponding to spikes replaced by values computed from neighboring pixels. Spikes are values in spectra that are unusually high compared to neighbors. They are usually individual values or very short runs of similar "unusual" values. Spikes caused by cosmic radiation are a frequent problem in Raman spectra. Another source of spikes are "hot pixels" in CCD and diode array detectors.

Usage

```
despike(x, z.threshold, max.spike.width, window.width, method, na.rm, ...)
```

```
## Default S3 method:
```

```
despike(  
  x,  
  z.threshold = NA,  
  max.spike.width = NA,  
  window.width = NA,  
  method = "run.mean",  
  na.rm = FALSE,  
  ...  
)
```

```
## S3 method for class 'numeric'
```

```
despike(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  window.width = 11,  
  method = "run.mean",  
  na.rm = FALSE,  
  ...  
)
```

```
## S3 method for class 'data.frame'
```

```
despike(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  window.width = 11,  
  method = "run.mean",  
  na.rm = FALSE,  
  ...,  
  y.var.name = NULL,
```

```
    var.name = y.var.name
  )

## S3 method for class 'generic_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...,
  y.var.name = NULL,
  var.name = y.var.name
)

## S3 method for class 'source_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'response_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'filter_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
```

```
    filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
    ...
)

## S3 method for class 'reflector_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...
)

## S3 method for class 'cps_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...
)

## S3 method for class 'raw_spct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...
)

## S3 method for class 'generic_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...,
  y.var.name = NULL,
  var.name = y.var.name,
```

```
.parallel = FALSE,
.paropts = NULL
)

## S3 method for class 'source_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'response_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'filter_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'reflector_mspct'
despike(
```



```

    x,
    z.threshold = 9,
    max.spike.width = 8,
    window.width = 11,
    method = "run.mean",
    na.rm = FALSE,
    ...,
    .parallel = FALSE,
    .paropts = NULL
)

## S3 method for class 'cps_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
despike(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  window.width = 11,
  method = "run.mean",
  na.rm = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>x</code>	an R object
<code>z.threshold</code>	numeric Modified Z values larger than <code>z.threshold</code> are considered to correspond to spikes.
<code>max.spike.width</code>	integer Wider regions with high Z values are not detected as spikes.
<code>window.width</code>	integer. The full width of the window used for the running mean used as replacement.
<code>method</code>	character The name of the method: "run.mean" is running mean as described

	in Whitaker and Hayes (2018); "adj.mean" is mean of adjacent neighbors (isolated bad pixels only).
na.rm	logical indicating whether NA values should be treated as spikes and replaced.
...	Arguments passed by name to find_spikes().
var.name, y.var.name	character Names of columns where to look for spikes to remove.
unit.out	character One of "energy" or "photon"
filter.qty	character One of "transmittance" or "absorbance"
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

x with rows corresponding to spikes replaced by a local average of adjacent neighbors outside the spike.

Methods (by class)

- default: Default returning always NA.
- numeric: Default function usable on numeric vectors.
- data.frame: Method for "data.frame" objects.
- generic_spct: Method for "generic_spct" objects.
- source_spct: Method for "source_spct" objects.
- response_spct: Method for "response_spct" objects.
- filter_spct: Method for "filter_spct" objects.
- reflector_spct: Method for "reflector_spct" objects.
- cps_spct: Method for "cps_spct" objects.
- raw_spct: Method for "raw_spct" objects.
- generic_mspct: Method for "generic_mspct" objects.
- source_mspct: Method for "source_mspct" objects.
- response_mspct: Method for "cps_mspct" objects.
- filter_mspct: Method for "filter_mspct" objects.
- reflector_mspct: Method for "reflector_mspct" objects.
- cps_mspct: Method for "cps_mspct" objects.
- raw_mspct: Method for "raw_mspct" objects.

Note

Current algorithm misidentifies steep smooth slopes as spikes, so manual inspection is needed together with adjustment by trial and error of a suitable argument value for z.threshold.

See Also

See the documentation for [find_spikes](#) and [replace_bad_pixs](#) for details of the algorithm and implementation.

Examples

```
white_led.raw_spct[120:125, ]  
  
# find and replace spike at 245.93 nm  
despike(white_led.raw_spct,  
        z.threshold = 10,  
        window.width = 25)[120:125, ]
```

diffraction_single_slit

Diffraction

Description

Diffraction of optical radiation passing through a single slit can be computed with function `diffraction_single_slit()`, which implements Fraunhofer's equation. Diffraction plus interference for a pair of slits can be computed with `diffraction_double_slit()`.

Usage

```
diffraction_single_slit(w.length, slit.width, angle)
```

```
diffraction_double_slit(w.length, slit.width, slit.distance, angle)
```

Arguments

<code>w.length</code>	numeric Wavelength (nm).
<code>slit.width</code>	numeric Width of the slit (m).
<code>angle</code>	numeric vector Angle (radians).
<code>slit.distance</code>	numeric Distance between the centres of the two slits (m).

Value

A numeric vector of the same length as `angle`, containing relative intensities.

Examples

```

diffraction_single_slit(w.length = 550,
                       slit.width = 1e-5,
                       angle = 0)

# use odd number for length.out so that 0 is in the sequence
angles <- pi * seq(from = -1/2, to = 1/2, length.out = 501)

plot(angles,
     diffraction_single_slit(w.length = 550, # 550 nm
                             slit.width = 6e-6, # 6 um
                             angle = angles),
     type = "l",
     ylab = "Relative irradiance (/1)",
     xlab = "Angle (radian)")

plot(angles,
     diffraction_double_slit(w.length = 550, # 550 nm
                             slit.width = 6e-6, # 6 um
                             slit.distance = 18e-6, # 18 um
                             angle = angles),
     type = "l",
     ylab = "Relative irradiance (/1)",
     xlab = "Angle (radian)")

```

dim.generic_mspct *Dimensions of an Object*

Description

Retrieve or set the dimension of an object.

Usage

```

## S3 method for class 'generic_mspct'
dim(x)

## S3 replacement method for class 'generic_mspct'
dim(x) <- value

```

Arguments

x A generic_mspct object or of a derived class.
value Either NULL or a numeric vector, which is coerced to integer (by truncation).

Value

Either NULL or a numeric vector, which is coerced to integer (by truncation).

div-.generic_spct
Arithmetic Operators

Description

Integer-division operator for generic spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 %/% e2
```

Arguments

e1 an object of class "generic_spct"
e2 an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

div_spectra
Divide two spectra, even if the wavelengths values differ

Description

The wavelength vectors of the two spectra are merged, and the missing spectral values are calculated by interpolation. After this, the two spectral values at each wavelength are operated upon.

Usage

```
div_spectra(
  w.length1,
  w.length2 = NULL,
  s.irrad1,
  s.irrad2,
  trim = "union",
  na.rm = FALSE
)
```

Arguments

w.length1	numeric vector of wavelength (nm) of denominator.
w.length2	numeric vector of wavelength (nm) of divisor.
s.irrad1	a numeric vector of spectral values of denominator.
s.irrad2	a numeric vector of spectral values of divisor.
trim	a character string with value "union" or "intersection".
na.rm	a logical value, if TRUE, not the default, NAs in the input are replaced with zeros.

Details

If trim=="union" spectral values are calculated for the whole range of wavelengths covered by at least one of the input spectra, and missing values are set in each input spectrum to zero before addition. If trim=="intersection" then the range of wavelengths covered by both input spectra is returned, and the non-overlapping regions discarded. If w.length2==NULL, it is assumed that both spectra are measured at the same wavelengths, and a simple addition is used, ensuring fast calculation.

Value

a dataframe with two numeric variables.

- w.lengthA numeric vector with the wavelengths (nm) obtained by "fusing" w.length1 and w.length2. w.length contains all the unique vales, sorted in ascending order.
- s.irradA numeric vector with the sum of the two spectral values at each wavelength.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
head(sun.data)
one.data <- with(sun.data, div_spectra(w.length, w.length, s.e.irrad, s.e.irrad))
head(one.data)
tail(one.data)
```

e2q *Convert energy-based quantities into photon-based quantities.*

Description

Function that converts spectral energy irradiance into spectral photon irradiance (molar).

Usage

```
e2q(x, action, byref, ...)

## Default S3 method:
e2q(x, action = "add", byref = FALSE, ...)

## S3 method for class 'source_spct'
e2q(x, action = "add", byref = FALSE, ...)

## S3 method for class 'response_spct'
e2q(x, action = "add", byref = FALSE, ...)

## S3 method for class 'source_mspct'
e2q(x, action = "add", byref = FALSE, ..., .parallel = FALSE, .paropts = NULL)

## S3 method for class 'response_mspct'
e2q(x, action = "add", byref = FALSE, ..., .parallel = FALSE, .paropts = NULL)
```

Arguments

x	an R object
action	a character string
byref	logical indicating if new object will be created by reference or by copy of x
...	not used in current version
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Methods (by class)

- default: Default method
- source_spct: Method for spectral irradiance
- response_spct: Method for spectral responsiveness
- source_mspct: Method for collections of (light) source spectra
- response_mspct: Method for collections of response spectra

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [q2e\(\)](#)

e2qmol_multipliers *Calculate energy to quantum (mol) multipliers*

Description

Multipliers as a function of wavelength, for converting from energy to photon (quantum) molar units.

Usage

```
e2qmol_multipliers(w.length)
```

Arguments

w.length numeric Vector of wavelengths (nm)

Value

A numeric vector of multipliers

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
with(sun.data, e2qmol_multipliers(w.length))
```

e2quantum_multipliers *Calculate energy to quantum multipliers*

Description

Gives multipliers as a function of wavelength, for converting from energy to photon (quantum) units (number of photons as default, or moles of photons).

Usage

```
e2quantum_multipliers(w.length, molar = FALSE)
```


Arguments

w.length numeric Vector of wavelengths (nm)
molar logical Flag indicating whether output should be in moles or numbers

Value

A numeric vector of multipliers

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmole_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
with(sun.data, e2quantum_multipliers(w.length))  
with(sun.data, e2quantum_multipliers(w.length, molar = TRUE))
```

enable_check_spct *Enable or disable checks*

Description

Choose between protection against errors or faster performance by enabling (the default) or disabling data-consistency and sanity checks.

Usage

```
enable_check_spct()  
  
disable_check_spct()  
  
set_check_spct(x)
```

Arguments

x logical Flag to enable (TRUE), disable (FALSE) or unset (NULL) option.

Value

The previous value of the option, which can be passed as argument to function `set_check_spct()` to restore the previous state of the option.

See Also

Other data validity check functions: [check_spct\(\)](#), [check_spectrum\(\)](#), [check_w.length\(\)](#)

energy_as_default *Set spectral-data options*

Description

Set spectral-data related options easily.

Usage

```
energy_as_default()
photon_as_default()
quantum_as_default()
Tfr_as_default()
Afr_as_default()
A_as_default()
unset_radiation_unit_default()
unset_filter_qty_default()
unset_user_defaults()
```

Value

Previous value of the modified option.

energy_irradiance *Calculate (energy) irradiance from spectral irradiance*

Description

Energy irradiance for a waveband from a radiation spectrum, optionally applying a "biological spectral weighting function" or BSWF.

Usage

```
energy_irradiance(
  w.length,
  s.irrad,
  w.band = NULL,
```

```

    unit.in = "energy",
    check.spectrum = TRUE,
    use.cached.mult = FALSE,
    use.hinges = getOption("photobiology.use.hinges", default = NULL)
  )

```

Arguments

w.length	numeric vector of wavelength (nm).
s.irrad	numeric vector of spectral irradiances, by default as energy (W m ⁻² nm ⁻¹).
w.band	waveband.
unit.in	a character Allowed values "photon" or "energy", default is "energy".
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

A single numeric value with no change in scale factor: [W m⁻² nm⁻¹] -> [W m⁻²].

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```

with(sun.data, energy_irradiance(w.length, s.e.irrad))
with(sun.data, energy_irradiance(w.length, s.e.irrad, new_waveband(400,700)))

```

energy_ratio

Energy:energy ratio

Description

Energy irradiance ratio between two wavebands for a radiation spectrum.

Usage

```
energy_ratio(
  w.length,
  s.irrad,
  w.band.num = NULL,
  w.band.denom = NULL,
  unit.in = "energy",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = NULL
)
```

Arguments

w.length	numeric vector of wavelengths (nm).
s.irrad	numeric vector of spectral (energy) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$).
w.band.num	waveband object used to compute the numerator of the ratio.
w.band.denom	waveband object used to compute the denominator of the ratio.
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

a single numeric value giving the unitless ratio.

Note

The default for both w.band parameters is a waveband covering the whole range of w.length.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data,
     energy_ratio(w.length, s.e.irrad, new_waveband(400,500), new_waveband(400,700)))
```

eq_ratio

Energy:photon ratio

Description

This function returns the energy to mole of photons ratio for each waveband and a light source spectrum.

Usage

```
eq_ratio(spct, w.band, scale.factor, wb.trim, use.cached.mult, use.hinges, ...)
```

```
## Default S3 method:
```

```
eq_ratio(spct, w.band, scale.factor, wb.trim, use.cached.mult, use.hinges, ...)
```

```
## S3 method for class 'source_spct'
```

```
eq_ratio(
  spct,
  w.band = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = FALSE,
  use.hinges = NULL,
  naming = "short",
  name.tag = ifelse(naming != "none", "[e:q]", ""),
  ...
)
```

```
## S3 method for class 'source_mspct'
```

```
eq_ratio(
  spct,
  w.band = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = FALSE,
  use.hinges = NULL,
  naming = "short",
  name.tag = ifelse(naming != "none", "[e:q]", ""),
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
)
```

```

    .paropts = NULL
  )

```

Arguments

<code>spct</code>	source_spect.
<code>w.band</code>	waveband or list of waveband objects.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
<code>use.cached.mult</code>	logical Flag telling whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>name.tag</code>	character Used to tag the name of the returned values.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

Computed values are ratios between energy irradiance and photon irradiance for a given waveband. A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used, with "e:q" prepended. Units [J mol⁻¹].

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Method for `source_spct` objects
- `source_mspct`: Calculates energy:photon from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use_cached_mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other photon and energy ratio functions: [e_ratio\(\)](#), [q_ratio\(\)](#), [qe_ratio\(\)](#)

Examples

```
eq_ratio(sun.spct, new_waveband(400,700))
```

 Extract

Extract or replace parts of a spectrum

Description

Just like extraction and replacement with indexes in base R, but preserving the special attributes used in spectral classes and checking for validity of remaining spectral data.

Usage

```
## S3 method for class 'generic_spct'
x[i, j, drop = NULL]

## S3 method for class 'raw_spct'
x[i, j, drop = NULL]

## S3 method for class 'cps_spct'
x[i, j, drop = NULL]

## S3 method for class 'source_spct'
x[i, j, drop = NULL]

## S3 method for class 'response_spct'
x[i, j, drop = NULL]
```

```
## S3 method for class 'filter_spct'
x[i, j, drop = NULL]

## S3 method for class 'reflector_spct'
x[i, j, drop = NULL]

## S3 method for class 'object_spct'
x[i, j, drop = NULL]

## S3 method for class 'chroma_spct'
x[i, j, drop = NULL]

## S3 replacement method for class 'generic_spct'
x[i, j] <- value

## S3 replacement method for class 'generic_spct'
x$name <- value
```

Arguments

x	spectral object from which to extract element(s) or in which to replace element(s)
i	index for rows,
j	index for columns, specifying elements to extract or replace. Indices are numeric or character vectors or empty (missing) or NULL. Please, see Extract for more details.
drop	logical. If TRUE the result is coerced to the lowest possible dimension. The default is FALSE unless the result is a single column.
value	A suitable replacement value: it will be repeated a whole number of times if necessary and it may be coerced: see the Coercion section. If NULL, deletes the column if a single column is selected.
name	A literal character string or a name (possibly backtick quoted). For extraction, this is normally (see under 'Environments') partially matched to the names of the object.

Details

These methods are just wrappers on the method for data.frame objects which copy the additional attributes used by these classes, and validate the extracted object as a spectral object. When drop is TRUE and the returned object has only one column, then a vector is returned. If the extracted columns are more than one but do not include w.length, a data frame is returned instead of a spectral object.

Value

An object of the same class as x but containing only the subset of rows and columns that are selected. See details for special cases.

Note

If any argument is passed to `j`, even `TRUE`, some metadata attributes are removed from the returned object. This is how the extraction operator works with `data.frames` in R. For the time being we retain this behaviour for spectra, but it may change in the future.

See Also

[subset](#) and [trim_spct](#)

Examples

```
sun.spct[sun.spct$w.length > 400, ]
subset(sun.spct, w.length > 400)

tmp.spct <- sun.spct
tmp.spct[tmp.spct$s.e.irrad < 1e-5 , "s.e.irrad"] <- 0
e2q(tmp.spct[ , c("w.length", "s.e.irrad")]) # restore data consistency!
```

 Extract_mspct

Extract or replace members of a collection of spectra

Description

Just like extraction and replacement with indexes for base R lists, but preserving the special attributes used in spectral classes.

Usage

```
## S3 method for class 'generic_mspct'
x[i, drop = NULL]

## S3 replacement method for class 'generic_mspct'
x[i] <- value

## S3 replacement method for class 'generic_mspct'
x$name <- value

## S3 replacement method for class 'generic_mspct'
x[[name]] <- value
```

Arguments

`x` Collection of spectra object from which to extract member(s) or in which to replace member(s)

`i` Index specifying elements to extract or replace. Indices are numeric or character vectors. Please, see [Extract](#) for more details.

drop	If TRUE the result is coerced to the lowest possible dimension (see the examples). This only works for extracting elements, not for the replacement.
value	A suitable replacement value: it will be repeated a whole number of times if necessary and it may be coerced: see the Coercion section. If NULL, deletes the column if a single column is selected.
name	A literal character string or a name (possibly backtick quoted). For extraction, this is normally (see under 'Environments') partially matched to the names of the object.

Details

This method is a wrapper on base R's extract method for lists that sets additional attributes used by these classes.

Value

An object of the same class as `x` but containing only the subset of members that are selected.

e_fluence	<i>Energy fluence</i>
-----------	-----------------------

Description

Energy fluence for one or more wavebands of a light source spectrum and a duration of the exposure.

Usage

```
e_fluence(
  spct,
  w.band,
  exposure.time,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  allow.scaled,
  ...
)

## Default S3 method:
e_fluence(
  spct,
  w.band,
  exposure.time,
  scale.factor,
  wb.trim,
  use.cached.mult,
```

```

    use.hinges,
    allow.scaled,
    ...
)

## S3 method for class 'source_spct'
e_fluence(
  spct,
  w.band = NULL,
  exposure.time,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = NULL,
  allow.scaled = FALSE,
  naming = "default",
  ...
)

## S3 method for class 'source_mspct'
e_fluence(
  spct,
  w.band = NULL,
  exposure.time,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = NULL,
  allow.scaled = FALSE,
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

spct	an R object
w.band	a list of waveband objects or a waveband object
exposure.time	lubridate::duration object.
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded
use.cached.mult	logical indicating whether multiplier values should be cached between calls

use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
allow.scaled	logical indicating whether scaled or normalized spectra as argument to spct are flagged as an error
...	other arguments (possibly ignored)
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

One numeric value for each waveband with no change in scale factor, with name attribute set to the name of each waveband unless a named list is supplied in which case the names of the list elements are used. The exposure.time is copied to the output as an attribute. Units are as follows: (J) joules per exposure.

Methods (by class)

- default: Default for generic function
- source_spct: Calculate energy fluence from a source_spct object and the duration of the exposure.
- source_mspct: Calculates energy fluence from a source_mspct object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting use.cached.mul t=TRUE. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the w.length vector.

See Also

Other irradiance functions: [e_irrad\(\)](#), [fluence\(\)](#), [irrad\(\)](#), [q_fluence\(\)](#), [q_irrad\(\)](#)

Examples

```
library(lubridate)
e_fluence(sun.spct, w.band = waveband(c(400,700)),
          exposure.time = lubridate::duration(3, "minutes") )
```

e_irrad	<i>Energy irradiance</i>
---------	--------------------------

Description

Energy irradiance for one or more wavebands of a light source spectrum.

Usage

```
e_irrad(
  spct,
  w.band,
  quantity,
  time.unit,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  allow.scaled,
  ...
)

## Default S3 method:
e_irrad(
  spct,
  w.band,
  quantity,
  time.unit,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  allow.scaled,
  ...
)

## S3 method for class 'source_spct'
e_irrad(
  spct,
  w.band = NULL,
  quantity = "total",
```

```

time.unit = NULL,
scale.factor = 1,
wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
use.hinges = NULL,
allow.scaled = !quantity %in% c("average", "mean", "total"),
naming = "default",
...
)

## S3 method for class 'source_mspct'
e_irrad(
  spct,
  w.band = NULL,
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = NULL,
  allow.scaled = !quantity %in% c("average", "mean", "total"),
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	a list of waveband objects or a waveband object.
<code>quantity</code>	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>time.unit</code>	character or lubridate::duration object.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
<code>use.cached.mult</code>	logical indicating whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>allow.scaled</code>	logical indicating whether scaled or normalized spectra as argument to <code>spct</code> are flagged as an error.

...	other arguments (possibly used by derived methods).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter <code>col.names</code> .
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used. The `time.unit` attribute is copied from the spectrum object to the output. Units are as follows: If units are absolute and `time.unit` is second, $[W\ m^{-2}\ nm^{-1}] \rightarrow [W\ m^{-2}]$ If `time.unit` is day, $[J\ d^{-1}\ m^{-2}\ nm^{-1}] \rightarrow [J\ m^{-2}]$; if units are relative, fraction of one or percent.

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Calculates energy irradiance from a `source_spct` object.
- `source_mspct`: Calculates energy irradiance from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other irradiance functions: [e_fluence\(\)](#), [fluence\(\)](#), [irrad\(\)](#), [q_fluence\(\)](#), [q_irrad\(\)](#)

Examples

```

e_irrad(sun.spct, waveband(c(400,700)))
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3))
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "total")
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "average")
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "relative")
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "relative.pc")
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "contribution")
e_irrad(sun.spct, split_bands(c(400,700), length.out = 3),
        quantity = "contribution.pc")

```

e_ratio

Energy:energy ratio

Description

This function returns the photon ratio for a given pair of wavebands of a light source spectrum.

Usage

```

e_ratio(
  spct,
  w.band.num,
  w.band.denom,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  ...
)

## Default S3 method:
e_ratio(
  spct,
  w.band.num,
  w.band.denom,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  ...
)

```



```

## S3 method for class 'source_spct'
e_ratio(
  spct,
  w.band.num = NULL,
  w.band.denom = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = FALSE,
  use.hinges = NULL,
  naming = "short",
  name.tag = ifelse(naming != "none", "[e:e]", ""),
  ...
)

## S3 method for class 'source_mspct'
e_ratio(
  spct,
  w.band.num = NULL,
  w.band.denom = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = FALSE,
  use.hinges = NULL,
  naming = "short",
  name.tag = ifelse(naming != "none", "[e:e]", ""),
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

spct	source_spct
w.band.num	waveband object or a list of waveband objects used to compute the numerator(s) of the ratio(s).
w.band.denom	waveband object or a list of waveband objects used to compute the denominator(s) of the ratio(s).
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded
use.cached.mult	logical Flag telling whether multiplier values should be cached between calls.

use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
...	other arguments (possibly used by derived methods).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
name.tag	character Used to tag the name of the returned values.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach.
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

In the case of methods for individual spectra, a numeric vector of adimensional values giving an energy ratio between integrated energy irradiances for pairs of wavebands, with name attribute set to the name of the wavebands unless a named list of wavebands is supplied in which case the names of the list elements are used, with "(e:e)" appended. A data.frame in the case of collections of spectra, containing one column for each ratio definition, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

Ratio definitions are "assembled" from the arguments passed to w.band.num and w.band.denom. If both arguments are of equal length, then the wavebands are paired to obtain as many ratios as the number of wavebands in each list. Recycling for wavebands takes place when the number of denominator and numerator wavebands differ.

Methods (by class)

- default: Default for generic function
- source_spct: Method for source_spct objects
- source_mspct: Calculates energy:energy ratio from a source_mspct object.

Note

Recycling for wavebands takes place when the number of denominator and denominator wavebands differ. The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting use.cached.mult=TRUE. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the w.length vector.

See Also

Other photon and energy ratio functions: [eq_ratio\(\)](#), [q_ratio\(\)](#), [qe_ratio\(\)](#)

Examples

```
e_ratio(sun.spct, new_waveband(400,500), new_waveband(400,700))
```

e_response	<i>Energy-based photo-response</i>
------------	------------------------------------

Description

This function returns the mean, total, or contribution of response for each waveband and a response spectrum.

Usage

```
e_response(  
  spct,  
  w.band,  
  quantity,  
  time.unit,  
  scale.factor,  
  wb.trim,  
  use.hinges,  
  ...  
)  
  
## Default S3 method:  
e_response(  
  spct,  
  w.band,  
  quantity,  
  time.unit,  
  scale.factor,  
  wb.trim,  
  use.hinges,  
  ...  
)  
  
## S3 method for class 'response_spct'  
e_response(  
  spct,  
  w.band = NULL,  
  quantity = "total",  
  time.unit = NULL,
```

```

    scale.factor = 1,
    wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
    use.hinges = getOption("photobiology.use.hinges", default = NULL),
    naming = "default",
    ...
)

## S3 method for class 'response_mspct'
e_response(
  spct,
  w.band = NULL,
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

spct	an R object.
w.band	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
quantity	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
time.unit	character or lubridate::duration object.
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
...	other arguments (possibly used by derived methods).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.

idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- `default`: Default method for generic function
- `response_spct`: Method for response spectra.
- `response_mspct`: Calculates energy response from a `response_mspct`

Note

The parameter `use.hinges` controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

See Also

Other response functions: [q_response\(\)](#), [response\(\)](#)

Examples

```
e_response(ccd.spct, new_waveband(200,300))
e_response(photodiode.spct)
```

FEL.BN.9101.165 *Data for typical calibration lamps*

Description

A dataset containing fitted constants to be used as input for function FEL_spectrum.

Format

A numeric vector.

Author(s)

Lasse Ylianttila (data)

FEL_spectrum *Incandescent "FEL" lamp emission spectrum*

Description

Calculate values by means of a nth degree polynomial from user-supplied constants (for example from a lamp calibration certificate).

Usage

```
FEL_spectrum(w.length, k = photobiology::FEL.BN.9101.165, fill = NA_real_)
```

Arguments

w.length	numeric vector of wavelengths (nm) for output
k	a numeric vector with n constants for the function
fill	if NA, no extrapolation is done, and NA is returned for wavelengths outside the range 250 nm to 900 nm. If NULL then the tails are deleted. If 0 then the tails are set to zero, etc. NA is default.

Value

a dataframe with four numeric vectors with wavelength values (w.length), energy and photon irradiance (s.e.irrad, s.q.irrad) depending on the argument passed to unit.out (s.irrad).

Note

This is function is valid for wavelengths in the range 250 nm to 900 nm, for wavelengths outside this range NAs are returned.

Examples

```
FEL_spectrum(400)
FEL_spectrum(250:900)
```

findMultipleWl	<i>Find repeated w.length values</i>
----------------	--------------------------------------

Description

Find repeated w.length values

Usage

```
findMultipleWl(x, same.wls = TRUE)
```

Arguments

x	a generic_spect object
same.wls	logical If TRUE all spectra spected to share same w.length values.

Value

integer Number of spectra, guessed from the number of copies of each individual w.length value.

find_peaks	<i>Find peaks in a spectrum</i>
------------	---------------------------------

Description

This function finds all peaks (local maxima) in a spectrum, using a user provided size threshold relative to the tallest peak (global maximum) below which found peaks are ignored—i.e., not included in the returned value. This is a wrapper built on top of function peaks() from package 'splus2R'.

Usage

```
find_peaks(x, ignore_threshold = 0, span = 3, strict = TRUE, na.rm = FALSE)
```

Arguments

x	numeric vector
ignore_threshold	numeric Value between 0.0 and 1.0 indicating the relative size compared to tallest peak threshold below which peaks will be ignored. Negative values set a threshold so that the tallest peaks are ignored, instead of the shortest.
span	integer A peak is defined as an element in a sequence which is greater than all other elements within a window of width span centered at that element. Use NULL for the global peak.
strict	logical If TRUE, an element must be strictly greater than all other values in its window to be considered a peak.
na.rm	logical indicating whether NA values should be stripped before searching for peaks.

Value

A logical vector of the same length as x. Values that are TRUE correspond to local peaks in the data.

Note

This function is a wrapper built on function [peaks](#) from **splus2R** and handles non-finite (including NA) values differently than `splus2R::peaks`, instead of giving an error they are replaced with the smallest finite value in x.

See Also

[peaks](#)

Other peaks and valleys functions: [find_spikes\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```
with(sun.data, w.length[find_peaks(s.e.irrad)])
```

find_spikes

Find spikes

Description

This function finds spikes in a numeric vector using the algorithm of Whitaker and Hayes (2018). Spikes are values in spectra that are unusually high or low compared to neighbors. They are usually individual values or very short runs of similar "unusual" values. Spikes caused by cosmic radiation are a frequent problem in Raman spectra. Another source of spikes are "hot pixels" in CCD and diode arrays. Other kinds of accidental "outliers" will be also detected.

Usage

```
find_spikes(  
  x,  
  x.is.delta = FALSE,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE  
)
```

Arguments

x	numeric vector containing spectral data.
x.is.delta	logical Flag indicating if x contains already differences.
z.threshold	numeric Modified Z values larger than z.threshold are considered to be spikes.
max.spike.width	integer Wider regions with high Z values are not detected as spikes.
na.rm	logical indicating whether NA values should be stripped before searching for spikes.

Details

Spikes are detected based on a modified Z score calculated from the differenced spectrum. The Z threshold used should be adjusted to the characteristics of the input and desired sensitivity. The lower the threshold the more stringent the test becomes, resulting in most cases in more spikes being detected. A modified version of the algorithm is used if a value different from NULL is passed as argument to max.spike.width. In such a case, an additional step filters out broader spikes (or falsely detected steep slopes) from the returned values.

Value

A logical vector of the same length as x. Values that are TRUE correspond to local spikes in the data.

References

Whitaker, D. A.; Hayes, K. (2018) A simple algorithm for despiking Raman spectra. *Chemometrics and Intelligent Laboratory Systems*, 179, 82-84.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```
with(white_led.raw_spct,  
     which(find_spikes(counts_3, z.threshold = 30)))
```

find_wls	<i>Find wavelength values in a spectrum</i>
----------	---

Description

Find wavelength values corresponding to a target y value in any spectrum. The name of the column of the spectral data to be used to match the target needs to be passed as argument unless the spectrum contains a single numerical variable in addition to "w.length".

Usage

```
find_wls(
  x,
  target = NULL,
  col.name.x = NULL,
  col.name = NULL,
  .fun = `<=` ,
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE
)
```

Arguments

x	an R object
target	numeric value indicating the spectral quantity value for which wavelengths are to be searched and interpolated if need. The character strings "half.maximum" and "half.range" are also accepted as arguments.
col.name.x	character The name of the column in which to the independent variable is stored. Defaults to "w.length" for objects of class "generic_spct" or derived.
col.name	character The name of the column in which to search for the target value.
.fun	function A binary comparison function or operator.
interpolate	logical Indicating whether the nearest wavelength value in x should be returned or a value calculated by linear interpolation between wavelength values straddling the target.
idfactor	logical or character Generates an index column of factor type. If idfactor = TRUE then the column is auto named spct.idx. Alternatively the column name can be directly passed as argument to idfactor as a character string.
na.rm	logical indicating whether NA values should be stripped before searching for the target.

Value

A spectrum object of the same class as x with fewer rows, possibly even no rows. If FALSE is passed to interpolate a subset of x is returned, otherwise a new object of the same class containing interpolated wavelenths for the target value is returned.

Note

This function is used internally by method `wls_at_target()`, and these methods should be preferred in user code and scripts.

Examples

```
find_wls(white_led.source_spct)
find_wls(white_led.source_spct, target = "half.maximum")
find_wls(white_led.source_spct, target = 0.4)
find_wls(white_led.source_spct, target = 0.4, interpolate = TRUE)
find_wls(white_led.source_spct, target = c(0.3, 0.4))
find_wls(white_led.source_spct, target = c(0.3, 0.4), idfactor = "target")
find_wls(white_led.source_spct, target = c(0.3, 0.4), idfactor = TRUE)
find_wls(white_led.source_spct, target = c("HM", "HR"))
find_wls(white_led.source_spct, target = c("HM", "HR"), interpolate = TRUE)

led.df <- as.data.frame(white_led.source_spct)
find_wls(led.df, col.name = "s.e.irrad", col.name.x = "w.length")
find_wls(led.df, col.name = "s.e.irrad", col.name.x = "w.length",
         target = 0.4)
find_wls(led.df, col.name = "s.e.irrad", col.name.x = "w.length",
         target = c(0.3, 0.4))
find_wls(led.df, col.name = "s.e.irrad", col.name.x = "w.length",
         target = 0.4, idfactor = "target")
```

fit_peaks

Refine position and value of extremes by fitting

Description

Functions implementing fitting of peaks in a class-agnostic way. The fitting refines the location of peaks and value of peaks based on the location of maxima and minima supplied. This function is to be used together with `find_peaks()` or `find_valleys()`.

Usage

```
fit_peaks(
  x,
  peaks.idx,
  span,
  x.col.name = NULL,
  y.col.name,
  method,
  max.span = 5L,
  maximum = TRUE,
  keep.cols = NULL
)
```

```

fit_valleys(
  x,
  valleys.idx,
  span,
  x.col.name = NULL,
  y.col.name,
  method,
  max.span = 5L,
  maximum = FALSE,
  keep.cols = NULL
)

```

Arguments

x	generic_spct or data.frame object.
peaks.idx, valleys.idx	logical or integer Indexes into x selecting global or local extremes.
span	odd integer The span used when refining the location of maxima or minima of x.
x.col.name, y.col.name	character Name of the column of x on which to operate.
method	character The method to use for the fit.
max.span	odd integer The maximum number of data points used when when refining the location of maxima and minima.
maximum	logical A flag indicating whether to search for maxima or minima.
keep.cols	logical Keep unrecognized columns in data frames

Value

An R object of the same class as x containing the fitted values for the peaks, and optionally the values for at peaks.idx or valleys.idx for other retained columns.

Note

These functions are not meant for everyday use. Use option refine.wl = TRUE of methods peaks() and valleys() instead.

Examples

```

peaks <- find_peaks(sun.spct$s.e.irrad, span = 31)
fit_peaks(sun.spct, peaks, span = 31,
          y.col.name = "s.e.irrad", method = "spline")

```

fluence

Fluence

Description

Energy or photon fluence for one or more wavebands of a light source spectrum and a duration of exposure.

Usage

```
fluence(  
  spct,  
  w.band,  
  unit.out,  
  exposure.time,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  allow.scaled,  
  ...  
)  
  
## Default S3 method:  
fluence(  
  spct,  
  w.band,  
  unit.out,  
  exposure.time,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  allow.scaled,  
  ...  
)  
  
## S3 method for class 'source_spct'  
fluence(  
  spct,  
  w.band = NULL,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  exposure.time,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),  
  use.hinges = NULL,  
  ...  
)
```

```

    allow.scaled = FALSE,
    naming = "default",
    ...
)

## S3 method for class 'source_mspct'
fluence(
  spct,
  w.band = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  exposure.time,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = NULL,
  allow.scaled = FALSE,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	a list of waveband objects or a waveband object.
<code>unit.out</code>	character string with allowed values "energy", and "photon", or its alias "quantum".
<code>exposure.time</code>	lubridate::duration object.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
<code>use.cached.mult</code>	logical indicating whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>allow.scaled</code>	logical indicating whether scaled or normalized spectra as argument to <code>spct</code> are flagged as an error.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.

<code>attr2tb</code>	character vector, see <code>add_attr2tb</code> for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

One numeric value for each waveband with no change in scale factor, with name attribute set to the name of each waveband unless a named list is supplied in which case the names of the list elements are used. The `time.unit` attribute is copied from the spectrum object to the output. Units are as follows: If `time.unit` is second, $[W\ m^{-2}\ nm^{-1}] \rightarrow [mol\ s^{-1}\ m^{-2}]$ If `time.unit` is day, $[J\ d^{-1}\ m^{-2}\ nm^{-1}] \rightarrow [mol\ d^{-1}\ m^{-2}]$

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Calculate photon fluence from a `source_spct` object and the duration of the exposure
- `source_mspct`: Calculates fluence from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use_cached_mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other irradiance functions: `e_fluence()`, `e_irrad()`, `irrad()`, `q_fluence()`, `q_irrad()`

Examples

```
library(lubridate)
fluence(sun.spct,
        w.band = waveband(c(400,700)),
        exposure.time = lubridate::duration(3, "minutes") )
```

format.solar_time *Encode in a Common Format*

Description

Format a solar_time object for pretty printing

Usage

```
## S3 method for class 'solar_time'  
format(x, ..., sep = ":")
```

Arguments

x	an R object
...	ignored
sep	character used as separator

See Also

Other astronomy related functions: [day_night\(\)](#), [format.tod_time\(\)](#), [is.solar_time\(\)](#), [print.solar_time\(\)](#), [print.tod_time\(\)](#), [solar_time\(\)](#), [sun_angles\(\)](#)

format.tod_time *Encode in a Common Format*

Description

Format a tod_time object for pretty printing

Usage

```
## S3 method for class 'tod_time'  
format(x, ..., sep = ":")
```

Arguments

x	an R object
...	ignored
sep	character used as separator

See Also

Other astronomy related functions: [day_night\(\)](#), [format.solar_time\(\)](#), [is.solar_time\(\)](#), [print.solar_time\(\)](#), [print.tod_time\(\)](#), [solar_time\(\)](#), [sun_angles\(\)](#)

formatted_range	<i>Compute range and format it</i>
-----------------	------------------------------------

Description

Compute the range of an R object, and format it as string suitable for printing.

Usage

```
formatted_range(x, na.rm = TRUE, digits = 3, nsmall = 2, collapse = "..")
```

Arguments

x	an R object
na.rm	logical, indicating if NA's should be omitted.
digits, nsmall	numeric, passed to same name parameters of format().
collapse	character, passed to same name parameter of paste().

See Also

[range](#), [format](#) and [paste](#).

Examples

```
formatted_range(c(1, 3.5, -0.01))
```

fscale	<i>Rescale a spectrum using a summary function</i>
--------	--

Description

These functions return a spectral object of the same class as the one supplied as argument but with the spectral data rescaled based on summary function *f* applied over a specific range or wavelengths and a target value for the summary value.

Usage

```
fscale(x, ...)  
  
## Default S3 method:  
fscale(x, ...)  
  
## S3 method for class 'source_spct'  
fscale(
```

```
x,  
range = NULL,  
f = "mean",  
target = 1,  
unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
set.scaled = target == 1,  
...  
)  
  
## S3 method for class 'response_spct'  
fscale(  
  x,  
  range = NULL,  
  f = "mean",  
  target = 1,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  set.scaled = target == 1,  
  ...  
)  
  
## S3 method for class 'filter_spct'  
fscale(  
  x,  
  range = NULL,  
  f = "mean",  
  target = 1,  
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),  
  set.scaled = target == 1,  
  ...  
)  
  
## S3 method for class 'reflector_spct'  
fscale(  
  x,  
  range = NULL,  
  f = "mean",  
  target = 1,  
  qty.out = NULL,  
  set.scaled = target == 1,  
  ...  
)  
  
## S3 method for class 'raw_spct'  
fscale(x, range = NULL, f = "mean", target = 1, set.scaled = target == 1, ...)  
  
## S3 method for class 'cps_spct'  
fscale(x, range = NULL, f = "mean", target = 1, set.scaled = target == 1, ...)
```

```
## S3 method for class 'generic_spct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  set.scaled = target == 1,
  col.names,
  ...
)

## S3 method for class 'source_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'response_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'filter_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)
```

```
)

## S3 method for class 'reflector_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  qty.out = NULL,
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'cps_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  set.scaled = target == 1,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'generic_mspct'
fscale(
  x,
  range = NULL,
  f = "mean",
  target = 1,
  set.scaled = target == 1,
  col.names,
  ...,
```

```

    .parallel = FALSE,
    .paropts = NULL
  )

```

Arguments

x	An R object
...	additional named arguments passed down to f.
range	numeric. An R object on which range() returns a numeric vector of length 2 with the limits of a range of wavelengths in nm, with min and max wavelengths (nm)
f	character string. "mean" or "total" for scaling so that this summary value becomes 1 for the returned object, or the name of a function taking x as first argument and returning a numeric value.
target	numeric A constant used as target value for scaling.
unit.out	character. Allowed values "energy", and "photon", or its alias "quantum".
set.scaled	logical or NULL Flag indicating if the data is to be marked as "scaled" or not.
qty.out	character. Allowed values "transmittance", and "absorbance".
col.names	character vector containing the names of columns or variables to which to apply the scaling.
.parallel	logical if TRUE, apply function in parallel, using parallel backend provided by foreach.
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of x with the original spectral data values replaced with rescaled values, and the "scaled" attribute set to a list describing the scaling applied.

a new object of the same class as x.

Methods (by class)

- default: Default for generic function
- source_spct:
- response_spct:
- filter_spct:
- reflector_spct:
- raw_spct:
- cps_spct:
- generic_spct:

- source_mspct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- raw_mspct:
- cps_mspct:
- generic_mspct:

Note

Sometimes we rescale a spectrum to a "theoretical" value for the summary, while in other cases we rescale the spectrum to a real-world target value of e.g. a reference energy irradiance. In the first case we say that the data are expressed in relative units, while in the second case we retain actual physical units. To indicate this, this package uses an attribute, which will by default be set assuming the first of these two situations when `target == 1` and the second situation otherwise. These defaults can be overridden with an explicit logical argument passed to `set.scaled`.

See Also

Other rescaling functions: [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

Examples

```
fscale(sun.spct)
fscale(sun.spct, f = "mean") # same as default
fscale(sun.spct, f = "mean", na.rm = TRUE)
fscale(sun.spct, range = c(400, 700)) # default is whole spectrum
fscale(sun.spct, f = e_irrad, range = c(400, 700))
s400.spct <- fscale(sun.spct,
                   f = e_irrad,
                   range = c(400, 700),
                   target = 400) # a target in W m-2

s400.spct
e_irrad(s400.spct, c(400, 700))
```

fshift

Shift the scale of a spectrum using a summary function

Description

The `fshift()` methods return a spectral object of the same class as the one supplied as argument but with the spectral data on a zero-shifted scale. A range of wavelengths is taken as a zero reference and the summary calculated with `f` for this waveband is subtracted. This results in a zero shift (= additive correction) to the values in the returned object. Metadata attributes are retained unchanged.

Usage

```
fshift(x, ...)  
  
## Default S3 method:  
fshift(x, ...)  
  
## S3 method for class 'source_spct'  
fshift(  
  x,  
  range = c(min(x), min(x) + 10),  
  f = "mean",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...  
)  
  
## S3 method for class 'response_spct'  
fshift(  
  x,  
  range = c(min(x), min(x) + 10),  
  f = "mean",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...  
)  
  
## S3 method for class 'filter_spct'  
fshift(  
  x,  
  range = c(min(x), min(x) + 10),  
  f = "min",  
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),  
  ...  
)  
  
## S3 method for class 'reflector_spct'  
fshift(x, range = c(min(x), min(x) + 10), f = "min", qty.out = NULL, ...)  
  
## S3 method for class 'source_mspct'  
fshift(  
  x,  
  range = c(min(x), min(x) + 10),  
  f = "mean",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...  
)  
  
## S3 method for class 'raw_spct'  
fshift(x, range = c(min(x), min(x) + 10), f = "mean", qty.out = NULL, ...)
```

```
## S3 method for class 'cps_spct'
fshift(x, range = c(min(x), min(x) + 10), f = "mean", qty.out = NULL, ...)

## S3 method for class 'generic_spct'
fshift(x, range = c(min(x), min(x) + 10), f = "mean", col.names, ...)

## S3 method for class 'response_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "mean",
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'filter_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "min",
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'reflector_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "min",
  qty.out = NULL,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "min",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)
```



```

## S3 method for class 'cps_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "min",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'generic_mspct'
fshift(
  x,
  range = c(min(x), min(x) + 10),
  f = "min",
  col.names,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

x	An R object
...	additional named arguments passed down to f.
range	An R object on which range() returns a numeric vector of length 2 with the limits of a range of wavelengths in nm, with min and max wavelengths (nm)
f	character string "mean", "min" or "max" for scaling so that this summary value becomes the origin of the spectral data scale in the returned object, or the name of a function taking x as first argument and returning a numeric value.
unit.out	character Allowed values "energy", and "photon", or its alias "quantum"
qty.out	character Allowed values "transmittance", and "absorbance"
col.names	character vector containing the names of columns or variables to which to apply the scale shift.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of x with the spectral data values replaced with values zero-shifted.
a new object of the same class as x.

Methods (by class)

- default: Default for generic function
- source_spct:
- response_spct:
- filter_spct:
- reflector_spct:
- source_mspct:
- raw_spct:
- cps_spct:
- generic_spct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- raw_mspct:
- cps_mspct:
- generic_mspct:

See Also

Other rescaling functions: [fscale\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

generic_mspct	<i>Collection-of-spectra constructor</i>
---------------	--

Description

Converts a list of spectral objects into a "multi spectrum" object by setting the class attribute of the list of spectra to the corresponding multi-spct class, check that components of the list belong to the expected class.

Usage

```
generic_mspct(
  l = NULL,
  class = "generic_spct",
  ncol = 1,
  byrow = FALSE,
  dim = c(length(l)%/%ncol, ncol)
)

calibration_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
```

```

raw_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
cps_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
source_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
filter_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
reflector_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
object_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
response_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)
chroma_mspct(l = NULL, ncol = 1, byrow = FALSE, ...)

```

Arguments

<code>l</code>	list of generic_spct or derived classes
<code>class</code>	character The multi spectrum object class or the expected class for the elements of <code>l</code>
<code>ncol</code>	integer Number of 'virtual' columns in data
<code>byrow</code>	logical If <code>ncol > 1</code> how to read in the data
<code>dim</code>	integer vector of dimensions
<code>...</code>	ignored

Functions

- `calibration_mspct`: Specialization for collections of `calibration_spct` objects.
- `raw_mspct`: Specialization for collections of `raw_spct` objects.
- `cps_mspct`: Specialization for collections of `cps_spct` objects.
- `source_mspct`: Specialization for collections of `source_spct` objects.
- `filter_mspct`: Specialization for collections of `filter_spct` objects.
- `reflector_mspct`: Specialization for collections of `reflector_spct` objects.
- `object_mspct`: Specialization for collections of `object_spct` objects.
- `response_mspct`: Specialization for collections of `response_spct` objects.
- `chroma_mspct`: Specialization for collections of `chroma_spct` objects.

Note

Setting `class = source_spct` or `class = source_mspct` makes no difference

Examples

```
filter_mspct(list(polyester.spct, yellow_gel.spct))
```

getBSWFUsed *Get the "bswf.used" attribute*

Description

Function to read the "time.unit" attribute of an existing source_spct object

Usage

```
getBSWFUsed(x)
```

Arguments

x a source_spct object

Value

character string

Note

if x is not a source_spct object, NA is returned

See Also

Other BSWF attribute functions: [setBSWFUsed\(\)](#)

Examples

```
getBSWFUsed(sun.spct)
```

getFilterProperties *Get the "filter.properties" attribute*

Description

Function to read the "filter.properties" attribute of an existing filter_spct or a filter_mspct.

Usage

```

getFilterProperties(x, return.null, ...)

filter_properties(x, return.null, ...)

## Default S3 method:
getFilterProperties(x, return.null = FALSE, ...)

## S3 method for class 'filter_spct'
getFilterProperties(x, return.null = FALSE, ...)

## S3 method for class 'summary_filter_spct'
getFilterProperties(x, return.null = FALSE, ...)

## S3 method for class 'generic_mspct'
getFilterProperties(x, ..., idx = "spct.idx")

```

Arguments

x	a filter_spct object
return.null	logical If true, NULL is returned if the attribute is not set, otherwise the expected list is returned with all fields set to NA.
...	Allows use of additional arguments in methods for other classes.
idx	character Name of the column with the names of the members of the collection of spectra.

Value

a list with fields named "Rfr.constant", "thickness" and "attenuation.mode". If the attribute is not set, and return.null is FALSE, a list with fields set to NA is returned, otherwise, NULL.

Methods (by class)

- default: default
- filter_spct: generic_spct
- summary_filter_spct: summary_generic_spct
- generic_mspct: filter_mspct

Note

The method for collections of spectra returns the a tibble with a column of lists.

See Also

Other measurement metadata functions: [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#),

```
setInstrDesc(), setInstrSettings(), setWhatMeasured(), setWhenMeasured(), setWhereMeasured(),
spect_attr2tb(), trimInstrDesc(), trimInstrSettings()
```

Examples

```
filter_properties(polyester.spct)
```

getHowMeasured	<i>Get the "how.measured" attribute</i>
----------------	---

Description

Function to read the "how.measured" attribute of an existing generic_spct or a generic_mspct.

Usage

```
getHowMeasured(x, ...)

how_measured(x, ...)

## Default S3 method:
getHowMeasured(x, ...)

## S3 method for class 'generic_spct'
getHowMeasured(x, ...)

## S3 method for class 'summary_generic_spct'
getHowMeasured(x, ...)

## S3 method for class 'generic_mspct'
getHowMeasured(x, ..., idx = "spct.idx")
```

Arguments

x	a generic_spct object
...	Allows use of additional arguments in methods for other classes.
idx	character Name of the column with the names of the members of the collection of spectra.

Value

character vector An object containing a description of the data.

Methods (by class)

- default: default
- generic_spct: generic_spct
- summary_generic_spct: summary_generic_spct
- generic_mspct: generic_mspct

Note

The method for collections of spectra returns the a tibble with a column of character strings.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
how_measured(sun.spct)
```

getIdFactor

Get the "idfactor" attribute

Description

Function to read the "idfactor" attribute of an existing generic_spct.

Usage

```
getIdFactor(x)
```

Arguments

x a generic_spct object

Value

character

Note

If x is not a generic_spct or an object of a derived class NA is returned.

See Also

Other idfactor attribute functions: [setIdFactor\(\)](#)

Examples

```
getMultipleWl(sun.spct)
```

getInstrDesc

Get the "instr.desc" attribute

Description

Function to read the "instr.desc" attribute of an existing generic_spct object.

Usage

```
getInstrDesc(x)
```

Arguments

x a generic_spct object

Value

list (depends on instrument type)

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

getInstrSettings	<i>Get the "instr.settings" attribute</i>
------------------	---

Description

Function to read the "instr.settings" attribute of an existing generic_spct object.

Usage

```
getInstrSettings(x)
```

Arguments

x a generic_spct object

Value

list

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

getMspctVersion	<i>Get the "mspct.version" attribute</i>
-----------------	--

Description

Function to read the "mspct.version" attribute of an existing generic_mspct object.

Usage

```
getMspctVersion(x)
```

Arguments

x a generic_mspct object

Value

numeric value

Note

if `x` is not a `generic_mspct` object, `NA` is returned, and if it the attribute is missing, zero is returned with a warning.

<code>getMultipleWl</code>	<i>Get the "multiple.wl" attribute</i>
----------------------------	--

Description

Function to read the "multiple.wl" attribute of an existing `generic_spct`.

Usage

```
getMultipleWl(x)
```

Arguments

`x` a `generic_spct` object

Value

integer

Note

If `x` is not a `generic_spct` or an object of a derived class `NA` is returned.

See Also

Other multiple.wl attribute functions: [setMultipleWl\(\)](#)

Examples

```
getMultipleWl(sun.spct)
```

getNormalized	<i>Get the "normalized" attribute</i>
---------------	---------------------------------------

Description

Function to read the "normalized" attribute of an existing generic_spct object.

Usage

```
getNormalized(x)
```

```
getNormalised(x)
```

Arguments

x a generic_spct object

Value

character or numeric or logical

Note

if x is not a generic_spct object, NA is returned

getNormalised() is a synonym for this getNormalized() method.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

getRfrType	<i>Get the "Rfr.type" attribute</i>
------------	-------------------------------------

Description

Function to read the "Rfr.type" attribute of an existing reflector_spct object or object_spct object.

Usage

```
getRfrType(x)
```

Arguments

x a source_spct object

Value

character string

Note

if x is not a `filter_spct` object, NA is returned

See Also

Other Rfr attribute functions: [setRfrType\(\)](#)

getScaled

Get the "scaled" attribute

Description

Function to read the "scaled" attribute of an existing `generic_spct` object.

Usage

```
getScaled(x)
```

Arguments

x a `generic_spct` object

Value

logical

Note

if x is not a `filter_spct` object, NA is returned

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

Examples

```
scaled.spct <- fscale(sun.spct)
getScaled(scaled.spct)
```

getSpctVersion	<i>Get the "spct.version" attribute</i>
----------------	---

Description

Function to read the "spct.version" attribute of an existing generic_spct object.

Usage

```
getSpctVersion(x)
```

Arguments

x a generic_spct object

Value

integer value

Note

if x is not a generic_spct object, NA is returned, and if it the attribute is missing, zero is returned with a warning.

getTfrType	<i>Get the "Tfr.type" attribute</i>
------------	-------------------------------------

Description

Function to read the "Tfr.type" attribute of an existing filter_spct or object_spct object.

Usage

```
getTfrType(x)
```

Arguments

x a filter_spct or object_spct object

Value

character string

Note

If x is not a filter_spct or an object_spct object, NA is returned.

See Also

Other Tfr attribute functions: [setTfrType\(\)](#)

Examples

```
getTfrType(polyester.spct)
```

getTimeUnit

Get the "time.unit" attribute of an existing source_spct object

Description

Function to read the "time.unit" attribute

Usage

```
getTimeUnit(x, force.duration = FALSE)
```

Arguments

`x` a source_spct object

`force.duration` logical If TRUE a lubridate::duration is returned even if the object attribute is a character string, if no conversion is possible NA is returned.

Value

character string or a lubridate::duration

Note

if x is not a source_spct or a response_spct object, NA is returned

See Also

Other time attribute functions: [checkTimeUnit\(\)](#), [convertTfrType\(\)](#), [convertThickness\(\)](#), [convertTimeUnit\(\)](#), [setTimeUnit\(\)](#)

Examples

```
getTimeUnit(sun.spct)
```

getWhatMeasured	<i>Get the "what.measured" attribute</i>
-----------------	--

Description

Function to read the "what.measured" attribute of an existing generic_spct or a generic_mspct.

Usage

```
getWhatMeasured(x, ...)  
  
what_measured(x, ...)  
  
## Default S3 method:  
getWhatMeasured(x, ...)  
  
## S3 method for class 'generic_spct'  
getWhatMeasured(x, ...)  
  
## S3 method for class 'summary_generic_spct'  
getWhatMeasured(x, ...)  
  
## S3 method for class 'generic_mspct'  
getWhatMeasured(x, ..., idx = "spct.idx")
```

Arguments

x	a generic_spct object
...	Allows use of additional arguments in methods for other classes.
idx	character Name of the column with the names of the members of the collection of spectra.

Value

character vector An object containing a description of the data.

Methods (by class)

- default: default
- generic_spct: generic_spct
- summary_generic_spct: summary_generic_spct
- generic_mspct: generic_mspct

Note

The method for collections of spectra returns the a tibble with a column of character strings.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
what_measured(sun.spct)
```

getWhenMeasured	<i>Get the "when.measured" attribute</i>
-----------------	--

Description

Function to read the "when.measured" attribute of an existing generic_spct or a generic_mspct.

Usage

```
getWhenMeasured(x, ...)

when_measured(x, ...)

## Default S3 method:
getWhenMeasured(x, ...)

## S3 method for class 'generic_spct'
getWhenMeasured(x, ...)

## S3 method for class 'summary_generic_spct'
getWhenMeasured(x, ...)

## S3 method for class 'generic_mspct'
getWhenMeasured(x, ..., idx = "spct.idx")
```

Arguments

x	a generic_spct object
...	Allows use of additional arguments in methods for other classes.
idx	character Name of the column with the names of the members of the collection of spectra.

Value

POSIXct An object with date and time.

Methods (by class)

- default: default
- generic_spct: generic_spct
- summary_generic_spct: summary_generic_spct
- generic_mspct: generic_mspct

Note

If x is not a generic_spct or an object of a derived class NA is returned.

The method for collections of spectra returns the a tibble with the correct times in TZ = "UTC".

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
when_measured(sun.spct)
```

getWhereMeasured	<i>Get the "where.measured" attribute</i>
------------------	---

Description

Function to read the "where.measured" attribute of an existing generic_spct.

Usage

```
getWhereMeasured(x, ...)

where_measured(x, ...)

## Default S3 method:
getWhereMeasured(x, ...)

## S3 method for class 'generic_spct'
```

```

getWhereMeasured(x, ...)

## S3 method for class 'summary_generic_spct'
getWhereMeasured(x, ...)

## S3 method for class 'generic_mspct'
getWhereMeasured(x, ..., idx = "spct.idx")

```

Arguments

x	a generic_spct object
...	Allows use of additional arguments in methods for other classes.
idx	character Name of the column with the names of the members of the collection of spectra.

Value

a data.frame with a single row and at least columns "lon" and "lat".

Methods (by class)

- default: default
- generic_spct: generic_spct
- summary_generic_spct: summary_generic_spct
- generic_mspct: generic_mspct

Note

If x is not a generic_spct or an object of a derived class NA is returned.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
where_measured(sun.spct)
```

get_attributes	<i>Get the metadata attributes</i>
----------------	------------------------------------

Description

Method returning attributes of an object of class `generic_spct` or derived, or of class `waveband`. Only attributes defined and/or set by package 'photobiology' for objects of the corresponding class are returned. Parameter which can be used to subset the list of attributes.

Usage

```
get_attributes(x, which, ...)

## S3 method for class 'generic_spct'
get_attributes(x, which = NULL, allowed = all.attributes, ...)

## S3 method for class 'source_spct'
get_attributes(x, which = NULL, ...)

## S3 method for class 'filter_spct'
get_attributes(x, which = NULL, ...)

## S3 method for class 'reflector_spct'
get_attributes(x, which = NULL, ...)

## S3 method for class 'object_spct'
get_attributes(x, which = NULL, ...)

## S3 method for class 'waveband'
get_attributes(x, which = NULL, ...)
```

Arguments

<code>x</code>	a <code>generic_spct</code> object.
<code>which</code>	character vector Names of attributes to retrieve.
<code>...</code>	currently ignored
<code>allowed</code>	character vector Names of attributes accepted by which.

Details

Vectors of character strings passed as argument to `which` are parsed so that if the first member string is "-" the remaining members are removed from the `allowed`; and if it is "=" the remaining members are used if in `allowed`. If the first member is none of these three strings, the behaviour is the same as if the first string is "=". If `which` is `NULL` all the attributes in `allowed` are used. The string "" means no attributes, and has precedence over any other values in the character vector. The order of the names of annotations has no meaning: the vector is interpreted as a set except for the three possible "operators" at position 1.

Value

Named list of attribute values.

Methods (by class)

- generic_spct: generic_spct
- source_spct: source_spct
- filter_spct: filter_spct
- reflector_spct: reflector_spct
- object_spct: object_spct
- waveband: waveband

See Also

[select_spct_attributes](#)

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

get_peaks

Get peaks and valleys in a spectrum

Description

These functions find peaks (local maxima) or valleys (local minima) in a spectrum, using a user selectable size threshold relative to the tallest peak (global maximum). This a wrapper built on top of function peaks from package splus2R.

Usage

```
get_peaks(  
  x,  
  y,  
  ignore_threshold = 0,  
  span = 5,  
  strict = TRUE,  
  x_unit = "",  
  x_digits = 3,  
  na.rm = FALSE  
)  
  
get_valleys(  
  x,
```

```

y,
ignore_threshold = 0,
span = 5,
strict = TRUE,
x_unit = "",
x_digits = 3,
na.rm = FALSE
)

```

Arguments

x	numeric
y	numeric
ignore_threshold	numeric Value between 0.0 and 1.0 indicating the relative size compared to tallest peak threshold below which peaks will be ignored. Negative values set a threshold so that the tallest peaks are ignored, instead of the shortest.
span	integer A peak is defined as an element in a sequence which is greater than all other elements within a window of width span centered at that element. Use NULL for the global peak.
strict	logical If TRUE, an element must be strictly greater than all other values in its window to be considered a peak.
x_unit	character Vector of texts to be pasted at end of labels built from x value at peaks.
x_digits	numeric Number of significant digits in wavelength label.
na.rm	logical indicating whether NA values should be stripped before searching for peaks.

Value

A data frame with variables w.length and s.irrad with their values at the peaks or valleys plus a character variable of labels.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```

with(sun.spct, get_peaks(w.length, s.e.irrad))
with(sun.spct, get_valleys(w.length, s.e.irrad))

```

green_leaf.spct	<i>Green birch leaf reflectance.</i>
-----------------	--------------------------------------

Description

A dataset of spectral reflectance expressed as a fraction of one.

Usage

```
green_leaf.spct
```

Format

A reflector_spct object with 226 rows and 2 variables

Details

- w.length (nm)
- Rfr (0..1)

References

Aphalo, P. J. & Lehto, T. Effects of light quality on growth and N accumulation in birch seedlings
Tree Physiology, 1997, 17, 125-132

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
green_leaf.spct
```

head_tail	<i>Return the First and Last Part of an Object</i>
-----------	--

Description

Returns the first and last "parts" (rows or members) of a spectrum, dataframe, vector, function, table or ftable. In other words, the combined output from methods head and tail.

Usage

```
head_tail(x, n, ...)  
  
## Default S3 method:  
head_tail(x, n = 3L, ...)  
  
## S3 method for class 'data.frame'  
head_tail(x, n = 3L, ...)  
  
## S3 method for class 'matrix'  
head_tail(x, n = 3L, ...)  
  
## S3 method for class '`function`'  
head_tail(x, n = 6L, ...)  
  
## S3 method for class 'table'  
head_tail(x, n = 6L, ...)  
  
## S3 method for class 'ftable'  
head_tail(x, n = 6L, ...)
```

Arguments

x	an R object.
n	integer. If positive, n rows or members in the returned object are copied from each of "head" and "tail" of x. If negative, all except n elements of x from each of "head" and "tail" are returned.
...	arguments to be passed to or from other methods.

Details

The value returned by head_tail() is equivalent to row binding the the values returned by head() and tail(), although not implemented in this way. The same specializations as defined in package 'utils' for head() and tail() have been implemented.

Value

An object (usually) like x but smaller, except when n = 0. For ftable objects x, a transformed format(x).

Methods (by class)

- default:
- data.frame:
- matrix:
- function:
- table:
- ftable:

Note

For some types of input, like functions, the output may be confusing, however, we have opted for consistency with existing functions. The code is in part a revision of that of `head()` and `tail()` from package 'utils'. I have been missing this method especially when checking spectral data, as both ends are of interest.

`head_tail()` methods for function, table and ftable classes, are wrappers for `head()` method.

See Also

[head](#), and compare the examples and the values returned to the examples below.

Examples

```
head_tail(letters)
head_tail(letters, n = -6L)
head_tail(freeny.x, n = 10L)
head_tail(freeny.y)

head_tail(stats::ftable(Titanic))
```

insert_hinges

Insert wavelength values into spectral data.

Description

Inserting wavelengths values immediately before and after a discontinuity in the SWF, greatly reduces the errors caused by interpolating the weighted irradiance during integration of the effective spectral irradiance. This is specially true when data have a large wavelength step size.

Usage

```
insert_hinges(x, y, h)
```


Arguments

x	numeric vector (sorted in increasing order)
y	numeric vector
h	a numeric vector giving the wavelengths at which the y values should be inserted by interpolation, no interpolation is indicated by an empty vector (numeric(0))

Value

a data.frame with variables x and y. Unless the hinge values were already present in y, each inserted hinge, expands the vectors returned in the data frame by one value.

Note

Insertion is a costly operation but I have tried to optimize this function as much as possible by avoiding loops. Earlier this function was implemented in C++, but a bug was discovered and I have now rewritten it using R.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data,
     insert_hinges(w.length, s.e.irrad,
                  c(399.99, 400.00, 699.99, 700.00)))
```

insert_spct_hinges *Insert new wavelength values into a spectrum*

Description

Insert new wavelength values into a spectrum interpolating the corresponding spectral data values.

Usage

```
insert_spct_hinges(spct, hinges = NULL, byref = FALSE)
```

Arguments

spct	an object of class "generic_spct"
hinges	numeric vector of wavelengths (nm) at which the s.irrad should be inserted by interpolation, no interpolation is indicated by an empty vector (numeric(0))
byref	logical indicating if new object will be created by reference or by copy of spct

Value

a generic_spct or a derived type with variables w. length and other numeric variables.

Note

Inserting wavelengths values "hinges" immediately before and after a discontinuity in the SWF, greatly reduces the errors caused by interpolating the weighted irradiance during integration of the effective spectral irradiance. This is specially true when data has a large wavelength step size.

Examples

```
insert_spct_hinges(sun.spct, c(399.99,400.00,699.99,700.00))
insert_spct_hinges(sun.spct,
                   c(199.99,200.00,399.50,399.99,400.00,699.99,
                     700.00,799.99,1000.00))
```

integrate_spct	<i>Integrate spectral data.</i>
----------------	---------------------------------

Description

This function gives the result of integrating spectral data over wavelengths.

Usage

```
integrate_spct(spct)
```

Arguments

spct	generic_spct
------	--------------

Value

One or more numeric values with no change in scale factor: e.g. [W m⁻² nm⁻¹] -> [W m⁻²]. Each value in the returned vector corresponds to a variable in the spectral object, except for wavelength.

Examples

```
integrate_spct(sun.spct)
```

integrate_xy	<i>Gives irradiance from spectral irradiance.</i>
--------------	---

Description

This function gives the result of integrating spectral irradiance over wavelengths.

Usage

```
integrate_xy(x, y)
```

Arguments

x	numeric vector.
y	numeric vector.

Value

a single numeric value with no change in scale factor: e.g. [W m⁻² nm⁻¹] -> [W m⁻²]

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data, integrate_xy(w.length, s.e.irrad))
```

interpolate_spct	<i>Map a spectrum to new wavelength values.</i>
------------------	---

Description

This function gives the result of interpolating spectral data from the original set of wavelengths to a new one.

Usage

```
interpolate_spct(spct, w.length.out = NULL, fill = NA, length.out = NULL)
```

```
interpolate_mspct(
  mspct,
  w.length.out = NULL,
  fill = NA,
  length.out = NULL,
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

<code>spct</code>	generic_spct
<code>w.length.out</code>	numeric vector of wavelengths (nm)
<code>fill</code>	a value to be assigned to out of range wavelengths
<code>length.out</code>	numeric value
<code>mspct</code>	an object of class "generic_mspct"
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by foreach
<code>.paropts</code>	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Details

If `length.out` is a numeric value, then gives the number of rows in the output, if it is NULL, the values in the numeric vector `w.length.out` are used. If both are not NULL then the range of `w.length.out` and `length.out` are used to generate a vector of wavelength. A value of NULL for `fill` prevents extrapolation. If both `w.length.out` and `length.out` are NULL the input is returned as is. If `w.length.out` has length equal to zero, zero rows from the input are returned.

Value

A new spectral object of the same class as argument `spct`.

Note

The default `fill = NA` fills extrapolated values with NA. Giving NULL as argument for `fill` deletes wavelengths outside the input data range from the returned spectrum. A numerical value can be also be provided as `fill`. This function calls `interpolate_spectrum` for each non-wavelength column in the input spectra object.

Examples

```

interpolate_spct(sun.spct, 400:500, NA)
interpolate_spct(sun.spct, 400:500, NULL)
interpolate_spct(sun.spct, seq(200, 1000, by=0.1), 0)
interpolate_spct(sun.spct, c(400,500), length.out=201)

```

interpolate_spectrum *Calculate spectral values at a different set of wavelengths*

Description

Interpolate/re-express spectral irradiance (or other spectral quantity) values at new wavelengths values. This is a low-level function operating on numeric vectors and called by higher level functions in the package, such as mathematical operators for classes for spectral data.

Usage

```
interpolate_spectrum(w.length.in, s.irrad, w.length.out, fill = NA, ...)
```

Arguments

w.length.in	numeric vector of wavelengths (nm).
s.irrad	a numeric vector of spectral values.
w.length.out	numeric vector of wavelengths (nm).
fill	a value to be assigned to out of range wavelengths.
...	additional arguments passed to spline().

Value

a numeric vector of interpolated spectral values.

Note

The current version of interpolate uses spline if fewer than 25 data points are available. Otherwise it uses approx. In the first case a cubic spline is used, in the second case linear interpolation, which should be faster.

See Also

[splinefun](#).

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
my.w.length <- 300:700
with(sun.data, interpolate_spectrum(w.length, s.e.irrad, my.w.length))
```

interpolate_wl	<i>Map spectra to new wavelength values.</i>
----------------	--

Description

This function returns the result of interpolating spectral data from the original set of wavelengths to a new one.

Usage

```
interpolate_wl(x, w.length.out, fill, length.out, ...)

## Default S3 method:
interpolate_wl(x, w.length.out, fill, length.out, ...)

## S3 method for class 'generic_spct'
interpolate_wl(x, w.length.out = NULL, fill = NA, length.out = NULL, ...)

## S3 method for class 'generic_mspct'
interpolate_wl(
  x,
  w.length.out = NULL,
  fill = NA,
  length.out = NULL,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

x	an R object
w.length.out	numeric vector of wavelengths (nm)
fill	a value to be assigned to out of range wavelengths
length.out	numeric value
...	not used
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Details

If `length.out` is a numeric value, then gives the number of rows in the output, if it is `NULL`, the values in the numeric vector `w.length.out` are used. If both are not `NULL` then the range of `w.length.out` and `length.out` are used to generate a vector of wavelength. A value of `NULL` for `fill` prevents extrapolation.

Value

A new spectral object of the same class as argument `spct`.

Methods (by class)

- `default`: Default for generic function
- `generic_spct`: Interpolate wavelength in an object of class "generic_spct" or derived.
- `generic_mspct`: Interpolate wavelength in an object of class "generic_mspct" or derived.

Note

The default `fill = NA` fills extrapolated values with `NA`. Giving `NULL` as argument for `fill` deletes wavelengths outside the input data range from the returned spectrum. A numerical value can be also provided as `fill`. This function calls `interpolate_spectrum` for each non-wavelength column in the input spectra object.

Examples

```
interpolate_wl(sun.spct, 400:500, NA)
interpolate_wl(sun.spct, 400:500, NULL)
interpolate_wl(sun.spct, seq(200, 1000, by=0.1), 0)
interpolate_wl(sun.spct, c(400,500), length.out=201)
```

irrad

Irradiance

Description

This function returns the irradiance for a given waveband of a light source spectrum.

Usage

```
irrad(
  spct,
  w.band,
  unit.out,
  quantity,
  time.unit,
  scale.factor,
```

```
    wb.trim,
    use.cached.mult,
    use.hinges,
    allow.scaled,
    ...
  )

## Default S3 method:
irrad(
  spct,
  w.band,
  unit.out,
  quantity,
  time.unit,
  scale.factor,
  wb.trim,
  use.cached.mult,
  use.hinges,
  allow.scaled,
  ...
)

## S3 method for class 'source_spct'
irrad(
  spct,
  w.band = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = getOption("photobiology.use.hinges"),
  allow.scaled = !quantity %in% c("average", "mean", "total"),
  naming = "default",
  ...
)

## S3 method for class 'source_mspct'
irrad(
  spct,
  w.band = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
```



```

use.hinges = NULL,
allow.scaled = !quantity %in% c("average", "mean", "total"),
naming = "default",
...,
attr2tb = NULL,
idx = "spct.idx",
.parallel = FALSE,
.paropts = NULL
)

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	waveband or list of waveband objects The waveband(s) determine the region(s) of the spectrum that are summarized.
<code>unit.out</code>	character string with allowed values "energy", and "photon", or its alias "quantum".
<code>quantity</code>	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>time.unit</code>	character or lubridate::duration object.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
<code>use.cached.mult</code>	logical indicating whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>allow.scaled</code>	logical indicating whether scaled or normalized spectra as argument to <code>spct</code> are flagged as an error.
<code>...</code>	other arguments (possibly ignored)
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code> .
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra. If `naming = "long"` the names generated reflect both quantity and waveband, if `naming = "short"`, names are based only on the wavebands, and if `naming = "none"` the returned vector has no names.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used. The `time.unit` attribute is copied from the spectrum object to the output. Units are as follows: If `time.unit` is second, $[W\ m^{-2}\ nm^{-1}] \rightarrow [mol\ s^{-1}\ m^{-2}]$ or $[W\ m^{-2}\ nm^{-1}] \rightarrow [W\ m^{-2}]$ If `time.unit` is day, $[J\ d^{-1}\ m^{-2}\ nm^{-1}] \rightarrow [mol\ d^{-1}\ m^{-2}]$ or $[J\ d^{-1}\ m^{-2}\ nm^{-1}] \rightarrow [J\ m^{-2}]$

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Calculates irradiance from a `source_spct` object.
- `source_mspct`: Calculates irradiance from a `source_mspct` object.

Note

Formal parameter `allow.scaled` is used internally for calculation of ratios, as rescaling and normalization do not invalidate the calculation of ratios.

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other irradiance functions: `e_fluence()`, `e_irrad()`, `fluence()`, `q_fluence()`, `q_irrad()`

Examples

```
irrad(sun.spct, waveband(c(400,700)))
irrad(sun.spct, waveband(c(400,700)), "energy")
irrad(sun.spct, waveband(c(400,700)), "photon")
irrad(sun.spct, split_bands(c(400,700), length.out = 3))
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "total")
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "average")
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "relative")
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "relative.pc")
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "contribution")
irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "contribution.pc")
```

irradiance	<i>Photon or energy irradiance from spectral energy or photon irradiance.</i>
------------	---

Description

Energy or photon irradiance for one or more wavebands of a radiation spectrum.

Usage

```
irradiance(
  w.length,
  s.irrad,
  w.band = NULL,
  unit.out = NULL,
  unit.in = "energy",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)
```

Arguments

w.length	numeric Vector of wavelength (nm).
s.irrad	numeric vector of spectral (energy) irradiances (W m ⁻² nm ⁻¹).
w.band	waveband or list of waveband objects The waveband(s) determine the region(s) of the spectrum that are summarized.
unit.out	character Allowed values "energy", and "photon", or its alias "quantum".
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

A single numeric value or a vector of numeric values with no change in scale factor: [W m⁻² nm⁻¹]
-> [mol s⁻¹ m⁻²]

Note

The last three parameters control speed optimizations. The defaults should be suitable in most cases. If you set `check.spectrum=FALSE` then you should call `check_spectrum()` at least once for your spectrum before using any of the other functions. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector. There is no reason for setting `use.cpp.code=FALSE` other than for testing the improvement in speed, or in cases where there is no suitable C++ compiler for building the package.

See Also

Other low-level functions operating on numeric vectors.: `as_energy()`, `as_quantum_mol()`, `calc_multipliers()`, `div_spectra()`, `energy_irradiance()`, `energy_ratio()`, `insert_hinges()`, `integrate_xy()`, `interpolate_spectrum()`, `l_insert_hinges()`, `oper_spectra()`, `photon_irradiance()`, `photon_ratio()`, `photons_energy_ratio()`, `prod_spectra()`, `s_e_irrad2rgb()`, `split_energy_irradiance()`, `split_photon_irradiance()`, `subt_spectra()`, `sum_spectra()`, `trim_tails()`, `v_insert_hinges()`, `v_replace_hinges()`

Examples

```
with(sun.data, irradiance(w.length, s.e.irrad, new_waveband(400,700), "photon"))
```

is.generic_mspct	<i>Query class of spectrum objects</i>
------------------	--

Description

Functions to check if an object is of a given type of spectrum, or coerce it if possible.

Usage

```
is.generic_mspct(x)
```

```
is.calibration_mspct(x)
```

```
is.raw_mspct(x)
```

```
is.cps_mspct(x)
```

```
is.source_mspct(x)
```

```
is.response_mspct(x)
```

```
is.filter_mspct(x)
```

```
is.reflector_mspct(x)
```

```
is.object_mspct(x)
```

```
is.chroma_mspct(x)
```

```
is.any_mspct(x)
```

Arguments

x an R object.

Value

These functions return TRUE if its argument is a of the queried type of spectrum and FALSE otherwise.

Note

Derived types also return TRUE for a query for a base type such as generic_mspct.

Examples

```
my.mspct <- filter_mspct(list(polyester.spct, yellow_gel.spct))
is.any_mspct(my.mspct)
is.filter_mspct(my.mspct)
is.source_mspct(my.mspct)
```

is.generic_spct	<i>Query class of spectrum objects</i>
-----------------	--

Description

Functions to check if an object is of a given type of spectrum, or coerce it if possible.

Usage

```
is.generic_spct(x)
```

```
is.raw_spct(x)
```

```
is.calibration_spct(x)
```

```
is.cps_spct(x)
```

```
is.source_spct(x)
```

```
is.response_spct(x)
```

```
is.filter_spct(x)
```

```
is.reflector_spct(x)
```

```
is.object_spct(x)
```

```
is.chroma_spct(x)
```

```
is.any_spct(x)
```

Arguments

x an R object.

Value

These functions return TRUE if its argument is a of the queried type of spectrum and FALSE otherwise.

Note

Derived types also return TRUE for a query for a base type such as `generic_spct`.

Examples

```
is.source_spct(sun.spct)
is.filter_spct(sun.spct)
is.generic_spct(sun.spct)
is.generic_spct(sun.spct)
```

```
is.source_spct(sun.spct)
is.filter_spct(sun.spct)
is.generic_spct(sun.spct)
is.generic_spct(sun.spct)
```

is.old_spct

Query if an object has old class names

Description

Query if an object has old class names Query if an object has old class names as used in photobiology ($\geq 0.6.0$).

Usage

```
is.old_spct(object)
```

Arguments

object an R object

Value

logical

See Also

Other upgrade from earlier versions: [upgrade_spct\(\)](#), [upgrade_spectra\(\)](#)

is.solar_time *Query class*

Description

Query class

Usage

is.solar_time(x)

is.solar_date(x)

Arguments

x an R object.

See Also

Other astronomy related functions: [day_night\(\)](#), [format.solar_time\(\)](#), [format.tod_time\(\)](#), [print.solar_time\(\)](#), [print.tod_time\(\)](#), [solar_time\(\)](#), [sun_angles\(\)](#)

is.summary_generic_spct
Query class of spectrum summary objects

Description

Functions to check if an object is of a given type of spectrum, or coerce it if possible.

Usage

```
is.summary_generic_spct(x)
is.summary_raw_spct(x)
is.summary_cps_spct(x)
is.summary_source_spct(x)
is.summary_response_spct(x)
is.summary_filter_spct(x)
is.summary_reflector_spct(x)
is.summary_object_spct(x)
is.summary_chroma_spct(x)
is.any_summary_spct(x)
```

Arguments

x an R object.

Value

These functions return TRUE if its argument is a of the queried type of spectrum and FALSE otherwise.

Note

Derived types also return TRUE for a query for a base type such as generic_spct.

Examples

```
sm <- summary(sun.spct)
is.summary_source_spct(sm)
```

is.waveband	<i>Query if it is a waveband</i>
-------------	----------------------------------

Description

Functions to check if an object is waveband.

Usage

```
is.waveband(x)
```

Arguments

x any R object

Value

is.waveband returns TRUE if its argument is a waveband and FALSE otherwise.

isValidInstrDesc	<i>Check the "instr.desc" attribute</i>
------------------	---

Description

Function to validate the "instr.settings" attribute of an existing generic_spct object.

Usage

```
isValidInstrDesc(x)
```

Arguments

x a generic_spct object

Value

logical TRUE if at least instrument name and serial number is found.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

isValidInstrSettings *Check the "instr.settings" attribute*

Description

Function to validate the "instr.settings" attribute of an existing generic_spct object.

Usage

```
isValidInstrSettings(x)
```

Arguments

x a generic_spct object

Value

logical TRUE if at least integration time data is found.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

is_ absorbance_based *Query if a spectrum contains absorbance or transmittance data*

Description

Functions to check if an filter spectrum contains spectral absorbance data or spectral transmittance data.

Usage

```
is_ absorbance_based(x)
```

```
is_ absorptance_based(x)
```

```
is_ transmittance_based(x)
```

Arguments

x an R object

Value

is_absorbance_based returns TRUE if its argument is a filter_spct object that contains spectral absorbance data and FALSE if it does not contain such data, but returns NA for any other R object, including those belonging other generic_spct-derived classes.

is_absorptance_based returns TRUE if its argument is a filter_spct object that contains spectral absorptance and FALSE if it does not contain such data, but returns NA for any other R object, including those belonging other generic_spct-derived classes.

is_transmittance_based returns TRUE if its argument is a filter_spct object that contains spectral transmittance data and FALSE if it does not contain such data, but returns NA for any other R object, including those belonging other generic_spct-derived classes.

See Also

Other query units functions: [is_photon_based\(\)](#)

Examples

```
is_absorbance_based(polyester.spct)
my.spct <- T2A(polyester.spct)
is.filter_spct(my.spct)
is_absorbance_based(my.spct)

is_absorptance_based(polyester.spct)

is_transmittance_based(polyester.spct)
```

is_effective	<i>Is an R object "effective"</i>
--------------	-----------------------------------

Description

A generic function for querying if a biological spectral weighting function (BSWF) has been applied to an object or is included in its definition.

Usage

```
is_effective(x)

## Default S3 method:
is_effective(x)

## S3 method for class 'waveband'
is_effective(x)

## S3 method for class 'generic_spct'
is_effective(x)
```

```
## S3 method for class 'source_spct'  
is_effective(x)  
  
## S3 method for class 'summary_generic_spct'  
is_effective(x)  
  
## S3 method for class 'summary_source_spct'  
is_effective(x)
```

Arguments

x an R object

Value

A logical.

Methods (by class)

- default: Default method.
- waveband: Is a waveband object defining a method for calculating effective irradiance.
- generic_spct: Does a source_spct object contain effective spectral irradiance values.
- source_spct: Does a source_spct object contain effective spectral irradiance values.
- summary_generic_spct: Method for "summary_generic_spct".
- summary_source_spct: Method for "summary_source_spct".

See Also

Other waveband attributes: [labels\(\)](#), [normalization\(\)](#)

Examples

```
is_effective(summary(sun.spct))
```

is_normalized

Query whether a generic spectrum has been normalized.

Description

This function tests a generic_spct object for an attribute that signals whether the spectral data has been normalized or not after the object was created.

Usage

```
is_normalized(x)
```

```
is_normalised(x)
```

Arguments

x An R object.

Value

A logical value. If x is not normalized or x is not a `generic_spct` object the value returned is FALSE.

Note

`is_normalised()` is a synonym for this `is_normalized()` method.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

is_photon_based	<i>Query if a spectrum contains photon- or energy-based data.</i>
-----------------	---

Description

Functions to check if `source_spct` and `response_spct` objects contains photon-based or energy-based data.

Usage

```
is_photon_based(x)
```

```
is_energy_based(x)
```

Arguments

x any R object

Value

`is_photon_based` returns TRUE if its argument is a `source_spct` or a `response_spct` object that contains photon base data and FALSE if such an object does not contain such data, but returns NA for any other R object, including those belonging other `generic_spct`-derived classes.

`is_energy_based` returns TRUE if its argument is a `source_spct` or a `response_spct` object that contains energy base data and FALSE if such an object does not contain such data, but returns NA for any other R object, including those belonging other `generic_spct`-derived classes

See Also

Other query units functions: [is_absorbance_based\(\)](#)

Examples

```
colnames(sun.spct)
is_photon_based(sun.spct)
my.spct <- sun.spct[, c("w.length", "s.e.irrad")]
is_source_spct(my.spct)
is_photon_based(my.spct)
```

```
colnames(sun.spct)
is_energy_based(sun.spct)
my.spct <- sun.spct[, c("w.length", "s.q.irrad")]
is_source_spct(my.spct)
is_energy_based(my.spct)
```

is_scaled

Query whether a generic spectrum has been scaled

Description

This function tests a generic_spct object for an attribute that signals whether the spectral data has been rescaled or not after the object was created.

Usage

```
is_scaled(x)
```

Arguments

x An R object.

Value

A logical value. If x is not scaled or x is not a generic_spct object the value returned is FALSE.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

Examples

```
scaled.spct <- fscale(sun.spct)
is_scaled(sun.spct)
is_scaled(scaled.spct)
```

is_tagged	<i>Query if a spectrum is tagged</i>
-----------	--------------------------------------

Description

Functions to check if an spct object contains tags.

Usage

```
is_tagged(x)
```

Arguments

x any R object

Value

is_tagged returns TRUE if its argument is a spectrum that contains tags and FALSE if it is an untagged spectrum, but returns NA for any other R object.

See Also

Other tagging and related functions: [tag\(\)](#), [untag\(\)](#), [wb2rect_spct\(\)](#), [wb2spct\(\)](#), [wb2tagged_spct\(\)](#)

Examples

```
is_tagged(sun.spct)
```

join_mspct	<i>Join all spectra in a collection</i>
------------	---

Description

Join all the spectra contained in a homogenous collection, returning a data frame with spectral-data columns named according to the names of the spectra in the collection. By default a full join is done, filling the spectral data for missing wave lengths in individual spectra with NA.

Usage

```

join_mspct(x, type, ...)

## Default S3 method:
join_mspct(x, type = "full", ...)

## S3 method for class 'generic_mspct'
join_mspct(x, type = "full", col.name, ...)

## S3 method for class 'source_mspct'
join_mspct(x, type = "full", unit.out = "energy", ...)

## S3 method for class 'response_mspct'
join_mspct(x, type = "full", unit.out = "energy", ...)

## S3 method for class 'filter_mspct'
join_mspct(x, type = "full", qty.out = "transmittance", ...)

## S3 method for class 'reflector_mspct'
join_mspct(x, type = "full", ...)

## S3 method for class 'object_mspct'
join_mspct(x, type = "full", qty.out, ...)

```

Arguments

x	A <code>generic_mspct</code> object, or an object of a class derived from <code>generic_mspct</code> .
type	character Type of join: "left", "right", "inner" or "full" (default). See details for more information.
...	ignored (possibly used by derived methods).
col.name	character, name of the column in the spectra to be preserved, in addition to "w.length".
unit.out	character Allowed values "energy", and "photon", or its alias "quantum".
qty.out	character Allowed values "transmittance", and "absorbance".

Value

An object of class `dataframe`, with the spectra joined by wave length, with rows in addition sorted by wave length (variable `w.length`).

Methods (by class)

- default:
- `generic_mspct`:
- `source_mspct`:
- `response_mspct`:

- filter_mspct:
- reflector_mspct:
- object_mspct:

Note

Currently only generic_spct, source_mspct, response_mspct, filter_mspct, reflector_mspct and object_mspct classes have this method implemented.

labels	<i>Find labels from "waveband" object</i>
--------	---

Description

A function to obtain the name and label of objects of class "waveband".

Usage

```
## S3 method for class 'waveband'  
labels(object, ...)  
  
## S3 method for class 'generic_spct'  
labels(object, ...)
```

Arguments

object	an object of class "waveband"
...	not used in current version

Methods (by class)

- generic_spct:

See Also

Other waveband attributes: [is_effective\(\)](#), [normalization\(\)](#)

Examples

```
labels(sun.spct)
```

Ler_leaf.spct

Green Arabidopsis leaf reflectance and transmittance.

Description

A dataset of total spectral reflectance and total spectral transmittance expressed as fractions of one from the upper surface of a leaf of an Arabidopsis thaliana 'Ler' rosette.

Usage

Ler_leaf.spct

Format

An object_spct object with 2401 rows and 3 variables

Details

- w.length (nm)
- Rfr (0..1)
- Tfr (0..1)

Note

Measured with a Jaz spectrometer from Ocean Optics (USA) configured with a PX Xenon lamp module and Spectroclip double integrating spheres.

Author(s)

Aphalo, P. J. & Wang, F (unpublished data)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspect](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

Ler_leaf.spct

Ler_leaf_rfl.t.spct *Green Arabidopsis leaf spectral reflectance.*

Description

A dataset of total spectral reflectance expressed as fractions of one from the upper surface of a leaf of an Arabidopsis thaliana 'Ler' rosette.

Usage

Ler_leaf_rfl.t.spct

Format

An reflector_spct object with 1750 rows and 2 variables

Details

- w.length (nm)
- Rfr (0..1)

Note

Measured with a Jaz spectrometer from Ocean Optics (USA) configured with a PX Xenon lamp module and Spectroclip double integrating spheres.

Author(s)

Aphalo, P. J. & Wang, F (unpublished data)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

Ler_leaf_rfl.t.spct

Ler_leaf_trns.spct *Green Arabidopsis leaf spectral transmittance.*

Description

A dataset of total spectral transmittance expressed as a fraction of one from the upper surface of a leaf of an Arabidopsis thaliana 'Ler' rosette.

Usage

Ler_leaf_trns.spct

Format

An filter_spct object with 1753 rows and 2 variables

Details

- w.length (nm)
- Tfr (0..1)

Note

Measured with a Jaz spectrometer from Ocean Optics (USA) configured with a PX Xenon lamp module and Spectroclip double integrating spheres.

Author(s)

Aphalo, P. J. & Wang, F (unpublished data)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

Ler_leaf_trns.spct

Ler_leaf_trns_i.spct *Green Arabidopsis leaf spectral transmittance.*

Description

A dataset of internal spectral transmittance expressed as a fraction of one from the upper surface of a leaf of an Arabidopsis thaliana 'Ler' rosette.

Usage

Ler_leaf_trns_i.spct

Format

An `filter_spct` object with 2401 rows and 2 variables

Details

- w.length (nm)
- Tfr (0..1)

Note

Measured with a Jaz spectrometer from Ocean Optics (USA) configured with a PX Xenon lamp module and Spectroclip double integrating spheres.

Author(s)

Aphalo, P. J. & Wang, F (unpublished data)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

Ler_leaf_trns_i.spct

log

Logarithms and Exponentials

Description

Logarithms and Exponentials for Spectra. The functions are applied to the spectral data, not the wavelengths. The quantity in the spectrum to which the function is applied depends on the class of `x` and the current value of output options

Usage

```
## S3 method for class 'generic_spct'  
log(x, base = exp(1))  
  
log2.generic_spct(x)  
  
log10.generic_spct(x)  
  
## S3 method for class 'generic_spct'  
exp(x)
```

Arguments

<code>x</code>	an object of class "generic_spct"
<code>base</code>	a positive number: the base with respect to which logarithms are computed. Defaults to <code>e=exp(1)</code> .

Value

An object of the same class as `x`.

Note

In most cases a logarithm of an spectral quantity will yield off-range values. For this reason unless `x` is an object of base class `generic_spct`, checks will not be passed, resulting in warnings or errors.

See Also

Other math operators and functions: `MathFun`, `^.generic_spct()`, `convolve_each()`, `div-.generic_spct`, `minus-.generic_spct`, `mod-.generic_spct`, `plus-.generic_spct`, `round()`, `sign()`, `slash-.generic_spct`, `times-.generic_spct`

Description

`abs(x)` computes the absolute value of `x`, `sqrt(x)` computes the (principal) square root of `x`. The functions are applied to the spectral data, not the wavelengths. The quantity in the spectrum to which the function is applied depends on the class of `x` and the current value of output options.

Usage

```
## S3 method for class 'generic_spct'
sqrt(x)
```

```
## S3 method for class 'generic_spct'
abs(x)
```

Arguments

`x` an object of class "generic_spct"

See Also

Other math operators and functions: `^.generic_spct()`, `convolve_each()`, `div-.generic_spct`, `log()`, `minus-.generic_spct`, `mod-.generic_spct`, `plus-.generic_spct`, `round()`, `sign()`, `slash-.generic_spct`, `times-.generic_spct`

Description

Merge a `filter_spct` with a `reflector_spct` returning an `object_spct` object, even if wavelength values are mismatched.

Usage

```
merge2object_spct(
  x,
  y,
  by = "w.length",
  ...,
  w.length.out = x[["w.length"]],
  Tfr.type.out = "total"
)
```

Arguments

x, y	a filter_spct object and a reflector_spct object.
by	a vector of shared column names in x and y to merge on; by defaults to w.length.
...	other arguments passed to dplyr::inner_join()
w.length.out	numeric vector of wavelengths to be used for the returned object (nm).
Tfr.type.out	character string indicating whether transmittance values in the returned object should be expressed as "total" or "internal". This applies only to the case when an object_spct is returned.

Value

An object_spct is returned as the result of merging a filter_spct and a reflector_spct object.

Note

If a numeric vector is supplied as argument for w.length.out, the two spectra are interpolated to the new wavelength values before merging. The default argument for w.length.out is x[[w.length]].

See Also

[join](#)

merge_attributes	<i>Merge and copy attributes</i>
------------------	----------------------------------

Description

Merge attributes from x and y and copy them to z. Methods defined for spectral objects of classes from package 'photobiology'.

Usage

```
merge_attributes(x, y, z, which, which.not, ...)

## Default S3 method:
merge_attributes(x, y, z, which = NULL, which.not = NULL, ...)

## S3 method for class 'generic_spct'
merge_attributes(
  x,
  y,
  z,
  which = NULL,
  which.not = NULL,
  copy.class = FALSE,
  ...
)
```


Arguments

<code>x, y, z</code>	R objects. Objects <code>x</code> and <code>y</code> must be of the same class, <code>z</code> must be an object with a structure valid for this same class.
<code>which</code>	character Names of attributes to copy, if NULL all those relevant according to the class of <code>x</code> are used as default,
<code>which.not</code>	character Names of attributes not to be copied. The names passed here are removed from the list for <code>which</code> , which is most useful when we want to modify the default.
<code>...</code>	not used
<code>copy.class</code>	logical If TRUE class attributes are also copied.

Value

A copy of `z` with additional attributes set.

Methods (by class)

- `default`: Default for generic function
- `generic_spct`:

minus-.generic_spct *Arithmetic Operators*

Description

Subtraction operator for generic spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 - e2 = NULL
```

Arguments

<code>e1</code>	an object of class "generic_spct"
<code>e2</code>	an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

mod-.generic_spct *Arithmetic Operators*

Description

Reminder operator for generic spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 %% e2
```

Arguments

e1 an object of class "generic_spct"
e2 an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

msmsply *Multi-spct transform methods*

Description

Apply a function or operator to a collection of spectra.

Usage

```
msmsply(mspct, .fun, ..., .parallel = FALSE, .paropts = NULL)
```

```
msdply(
  mspct,
  .fun,
  ...,
  idx = NULL,
  col.names = NULL,
  .parallel = FALSE,
  .paropts = NULL
)
```

```
mslply(mspct, .fun, ..., .parallel = FALSE, .paropts = NULL)
```

```
msaply(mspct, .fun, ..., .drop = TRUE, .parallel = FALSE, .paropts = NULL)
```

Arguments

mspct	an object of class <code>generic_mspct</code> or a derived class
.fun	a function
...	other arguments passed to .fun
.parallel	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
.paropts	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.
idx	character Name of the column with the names of the members of the collection of spectra.
col.names	character Names to be used for data columns.
.drop	should extra dimensions of length 1 in the output be dropped, simplifying the output. Defaults to TRUE

Value

a collection of spectra in the case of `msmsply`

a data frame in the case of `msdply`

a list in the case of `mslply`

an vector in the case of `msaply`

mspct_classes	<i>Names of multi-spectra classes</i>
---------------	---------------------------------------

Description

Function that returns a vector containing the names of multi-spectra classes using for collections of spectra.

Usage

```
mspct_classes()
```

Value

A character vector of class names.

Examples

```
mspct_classes()
```

`na.omit`*Handle Missing Values in Objects*

Description

These methods are useful for dealing with NAs in e.g., `source_spct`, `response_spct`, `filter_spct` and `reflector_spct`.

Usage

```
## S3 method for class 'generic_spct'  
na.omit(object, na.action = "omit", fill = NULL, target.colnames, ...)  
  
## S3 method for class 'source_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'response_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'filter_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'reflector_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'object_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'cps_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'raw_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'chroma_spct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'generic_mspct'  
na.omit(object, na.action = "omit", fill = NULL, ...)  
  
## S3 method for class 'generic_spct'  
na.exclude(object, na.action = "exclude", fill = NULL, target.colnames, ...)  
  
## S3 method for class 'source_spct'  
na.exclude(object, na.action = "exclude", fill = NULL, ...)  
  
## S3 method for class 'response_spct'
```

```

na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'filter_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'reflector_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'object_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'cps_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'raw_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'chroma_spct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

## S3 method for class 'generic_mspct'
na.exclude(object, na.action = "exclude", fill = NULL, ...)

```

Arguments

<code>object</code>	an R object
<code>na.action</code>	character One of "omit", "exclude" or "replace".
<code>fill</code>	numeric Value used to replace NAs unless NULL, in which case interpolation is attempted.
<code>target.colnames</code>	character Vector of names for the target columns to operate upon, if present in object.
<code>...</code>	further arguments other special methods could require

Details

If `na.omit` removes cases, the row numbers of the cases form the "na.action" attribute of the result, of class "omit".

`na.exclude` differs from `na.omit` only in the class of the "na.action" attribute of the result, which is "exclude".

Note

`na.fail` and `na.pass` do not require a specialisation for spectral objects. R's definitions work as expected with no need to override them. We do not define a method `na.replace`, just pass "replace" as argument. The current implementation replaces by interpolation only individual NAs which are flanked on both sides by valid data. Runs of multiple NAs can only be replaced by a constant value passed through parameter `fill`.

See Also

[na.fail](#) and [na.action](#)

Examples

```
my_sun.spct <- sun.spct
my_sun.spct[3, "s.e.irrad"] <- NA
my_sun.spct[5, "s.q.irrad"] <- NA

head(my_sun.spct)

# rows omitted
zo <- na.omit(my_sun.spct)
head(zo)
na.action(zo)

# rows excluded
ze <- na.exclude(my_sun.spct)
head(ze)
na.action(ze)

# data in both rows replaced
zr <- na.omit(my_sun.spct, na.action = "replace")
head(zr)
na.action(zr)
```

normalization

Normalization of an R object

Description

Normalization wavelength of an R object, retrieved from the object's attributes.

Usage

```
normalization(x)

## Default S3 method:
normalization(x)

## S3 method for class 'waveband'
normalization(x)
```

Arguments

x an R object

Methods (by class)

- default: Default methods.
- waveband: Normalization of a [waveband](#) object.

See Also

Other waveband attributes: [is_effective\(\)](#), [labels\(\)](#)

normalize	<i>Normalize spectral data</i>
-----------	--------------------------------

Description

This method returns a spectral object of the same class as the one supplied as argument but with the spectral data normalized to 1.0 at a specific wavelength.

Usage

```
normalize(x, ...)
```

```
normalise(x, ...)
```

```
## Default S3 method:
```

```
normalize(x, ...)
```

```
## S3 method for class 'source_spct'
```

```
normalize(  
  x,  
  ...,  
  range = NULL,  
  norm = "max",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  na.rm = FALSE  
)
```

```
## S3 method for class 'response_spct'
```

```
normalize(  
  x,  
  ...,  
  range = NULL,  
  norm = "max",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  na.rm = FALSE  
)
```

```
## S3 method for class 'filter_spct'
```

```
normalize(  
  x,  
  ...,  
  range = NULL,  
  norm = "max",  
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),  
  na.rm = FALSE  
)  
  
## S3 method for class 'reflector_spct'  
normalize(x, ..., range = NULL, norm = "max", qty.out = NULL, na.rm = FALSE)  
  
## S3 method for class 'raw_spct'  
normalize(x, ..., range = NULL, norm = "max", na.rm = FALSE)  
  
## S3 method for class 'cps_spct'  
normalize(x, ..., range = NULL, norm = "max", na.rm = FALSE)  
  
## S3 method for class 'generic_spct'  
normalize(x, ..., range = NULL, norm = "max", col.names, na.rm = FALSE)  
  
## S3 method for class 'source_mspct'  
normalize(  
  x,  
  ...,  
  range = NULL,  
  norm = "max",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  na.rm = FALSE,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'response_mspct'  
normalize(  
  x,  
  ...,  
  range = NULL,  
  norm = "max",  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  na.rm = FALSE,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'filter_mspct'  
normalize(  
  x,
```



```
    ...,
    range = NULL,
    norm = "max",
    qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
    na.rm = FALSE,
    .parallel = FALSE,
    .paropts = NULL
)

## S3 method for class 'reflector_mspct'
normalize(
  x,
  ...,
  range = x,
  norm = "max",
  qty.out = NULL,
  na.rm = FALSE,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
normalize(
  x,
  ...,
  range = x,
  norm = "max",
  na.rm = FALSE,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'cps_mspct'
normalize(
  x,
  ...,
  range = x,
  norm = "max",
  na.rm = FALSE,
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

x	An R object
...	not used in current version
range	An R object on which range() returns a numeric vector of length 2 with the

	limits of a range of wavelengths in nm, with min and max wavelengths (nm) used to set boundaries for search for normalization.
<code>norm</code>	numeric Normalization wavelength (nm) or character string "max", or "min" for normalization at the corresponding wavelength.
<code>unit.out</code>	character Allowed values "energy", and "photon", or its alias "quantum"
<code>na.rm</code>	logical indicating whether NA values should be stripped before calculating the summary (e.g. "max") used for normalization.
<code>qty.out</code>	character string Allowed values are "transmittance", and "absorbance" indicating on which quantity to apply the normalization.
<code>col.names</code>	character vector containing the names of columns or variables to which to apply the normalization.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by foreach
<code>.paropts</code>	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Details

By default normalization is done based on the maximum of the spectral data. It is possible to also do the normalization based on a user-supplied wavelength expressed in nanometres or a wavelength retrieved using an arbitrary R function applied to the spectrum. By default the function is applied to the whole spectrum, but by passing a range of wavelengths as input, the search can be limited to a region of interest within the spectrum.

Value

A copy of `x`, with spectral data values normalized to one for the criterion specified by the argument passed to `norm`.

A copy of `x` with the values of the spectral quantity rescaled to 1 at the normalization wavelength. If the normalization wavelength is not already present in `x`, it is added by interpolation—i.e. the returned value may be one row longer than `x`.

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Normalize a `source_spct` object.
- `response_spct`: Normalize a response spectrum.
- `filter_spct`: Normalize a filter spectrum.
- `reflector_spct`: Normalize a reflector spectrum.
- `raw_spct`: Normalize a raw spectrum.
- `cps_spct`: Normalize a cps spectrum.
- `generic_spct`: Normalize a raw spectrum.
- `source_mspct`: Normalize the members of a `source_mspct` object.

- `response_mspct`: Normalize the members of a `response_mspct` object.
- `filter_mspct`: Normalize the members of a `filter_mspct` object.
- `reflector_mspct`: Normalize the members of a `reflector_mspct` object.
- `raw_mspct`: Normalize the members of a `raw_mspct` object.
- `cps_mspct`: Normalize the members of a `cps_mspct` object.

Note

`normalise()` is a synonym for this `normalize()` method.

1) By default if `x` contains one or more NA values and the normalization is based on a summary quantity, the returned spectrum will contain only NA values. If `na.rm == TRUE` then the summary quantity will be calculated after striping NA values, and only the values that were NA in `x` will be NA values in the returned spectrum.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [setNormalized\(\)](#), [setScaled\(\)](#)

Examples

```
normalize(sun.spct)
normalise(sun.spct) # equivalent

normalize(sun.spct, norm = "max")
normalize(sun.spct, norm = 400)
```

`normalized_diff_ind` *Calculate a normalized index.*

Description

This method returns a normalized difference index value for an arbitrary pair of wavebands. There are many such indexes in use, such as NDVI (normalized difference vegetation index), NDWI (normalized difference water index), NDMI (normalized difference moisture index), etc., the only difference among them is in the wavebands used.

Usage

```
normalized_diff_ind(spct, plus.w.band, minus.w.band, f, ...)

normalised_diff_ind(spct, plus.w.band, minus.w.band, f, ...)

NDxI(spct, plus.w.band, minus.w.band, f, ...)
```

```
## Default S3 method:
normalized_diff_ind(spct, plus.w.band, minus.w.band, f, ...)

## S3 method for class 'generic_spct'
normalized_diff_ind(spct, plus.w.band, minus.w.band, f, ...)

## S3 method for class 'generic_mspct'
normalized_diff_ind(spct, plus.w.band, minus.w.band, f, ...)
```

Arguments

spct	an R object
plus.w.band	waveband objects The waveband determine the region of the spectrum used in the calculations
minus.w.band	waveband objects The waveband determine the region of the spectrum used in the calculations
f	function used for integration taking spct as first argument and a list of wavebands as second argument.
...	additional arguments passed to f

Details

f is most frequently [reflectance](#), but also [transmittance](#), or even [absorbance](#), [response](#), [irradiance](#) or a user-defined function can be used if there is a good reason for it. In every case spct should be of the class expected by f. When using two wavebands of different widths do consider passing to f a suitable quantity argument. Wavebands can describe weighting functions if desired.

Value

A named numeric value for the index, or a tibble depending on whether a spectrum or a collection of spectra is passed as first argument. If the wavelength range of spct does not fully overlap with both wavebands NA is silently returned.

Methods (by class)

- default: default
- generic_spct:
- generic_mspct:

Note

Some NDxI indexes are directly based on satellite instrument data, such as those in the Landsat satellites. To simulate such indexes using spectral reflectance as input, waveband definitions provided by package [photobiologyWavebands](#) can be used.

normalised_diff_ind() is a synonym for normalized_diff_ind().

NDxI() is a shorthand for normalized_diff_ind().

normalize_range_arg *Normalize a range argument into a true numeric range*

Description

Several functions in this package and the suite accept a range argument with a flexible syntax. To ensure that all functions and methods behave in the same way this code has been factored out into a separate function.

Usage

```
normalize_range_arg(arg.range, wl.range, trim = TRUE)
```

Arguments

arg.range	a numeric vector of length two, or any other object for which function range() will return a range of wavelengths (nm).
wl.range	a numeric vector of length two, or any other object for which function range() will return a range of wavelengths (nm), missing values are not allowed.
trim	logical If TRUE the range returned is bound within wl.range while if FALSE it can be broader.

Details

The arg.range argument can contain NAs which are replaced by the value at the same position in wl.range. In addition a NULL argument for range is converted into wl.range. The wl.range is also the limit to which the returned value is trimmed if trim == TRUE. The idea is that the value supplied as wl.range is the wavelength range of the data.

Value

a numeric vector of length two, guaranteed not to have missing values.

Examples

```
normalize_range_arg(c(NA, 500), range(sun.spct))
normalize_range_arg(c(300, NA), range(sun.spct))
normalize_range_arg(c(100, 5000), range(sun.spct), FALSE)
normalize_range_arg(c(NA, NA), range(sun.spct))
normalize_range_arg(c(NA, NA), sun.spct)
```

`opaque.spct`*Theoretical spectrum of an opaque material*

Description

A dataset for a hypothetical object with transmittance 0/1 (0%)

Usage`opaque.spct`**Format**

A `filter_spct` object with 4 rows and 2 variables

Details

- `w.length` (nm).
- `Tfr` (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspect](#), [green_leaf.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples`opaque.spct`

`oper_spectra`*Binary operation on two spectra, even if the wavelengths values differ*

Description

The wavelength vectors of the two spectra are merged, and the missing spectral values are calculated by interpolation. After this, the two spectral values at each wavelength are added.

Usage

```
oper_spectra(
  w.length1,
  w.length2 = NULL,
  s.irrad1,
  s.irrad2,
  trim = "union",
  na.rm = FALSE,
  bin.oper = NULL,
  ...
)
```

Arguments

w.length1	numeric vector of wavelength (nm)
w.length2	numeric vector of wavelength (nm)
s.irrad1	a numeric vector of spectral values
s.irrad2	a numeric vector of spectral values
trim	a character string with value "union" or "intersection"
na.rm	a logical value, if TRUE, not the default, NAs in the input are replaced with zeros
bin.oper	a function defining a binary operator (for the usual math operators enclose argument in backticks)
...	additional arguments (by name) passed to bin.oper

Details

If trim=="union" spectral values are calculated for the whole range of wavelengths covered by at least one of the input spectra, and missing values are set in each input spectrum to zero before addition. If trim=="intersection" then the range of wavelengths covered by both input spectra is returned, and the non-overlapping regions discarded. If w.length2==NULL, it is assumed that both spectra are measured at the same wavelengths, and a simple addition is used, ensuring fast calculation.

Value

a dataframe with two numeric variables

w.length	A numeric vector with the wavelengths (nm) obtained by "fusing" w.length1 and w.length2. w.length contains all the unique vales, sorted in ascending order.
s.irrad	A numeric vector with the sum of the two spectral values at each wavelength.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#),

```
photons_energy_ratio(), prod_spectra(), s_e_irrad2rgb(), split_energy_irradiance(),
split_photon_irradiance(), subt_spectra(), sum_spectra(), trim_tails(), v_insert_hinges(),
v_replace_hinges()
```

Examples

```
head(sun.data)
result.data <-
  with(sun.data,
        oper_spectra(w.length, w.length, s.e.irrad, s.e.irrad, bin.oper='+'))
head(result.data)
tail(result.data)
my_fun <- function(e1, e2, k) {return((e1 + e2) / k)}
result.data <-
  with(sun.data,
        oper_spectra(w.length, w.length, s.e.irrad, s.e.irrad, bin.oper=my_fun, k=2))
head(result.data)
tail(result.data)
```

peaks

Peaks or local maxima

Description

Function that returns a subset of an R object with observations corresponding to local maxima.

Usage

```
peaks(x, span, ignore_threshold, strict, na.rm, ...)

## Default S3 method:
peaks(x, span = NA, ignore_threshold = NA, strict = NA, na.rm = FALSE, ...)

## S3 method for class 'numeric'
peaks(x, span = 5, ignore_threshold = NA, strict = TRUE, na.rm = FALSE, ...)

## S3 method for class 'data.frame'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  x.var.name = NULL,
  y.var.name = NULL,
  var.name = y.var.name,
```



```
    refine.wl = FALSE,
    method = "spline",
    ...
)

## S3 method for class 'generic_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = NULL,
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'source_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'response_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'filter_spct'
peaks(
  x,
  span = 5,
```

```
ignore_threshold = 0,
strict = TRUE,
na.rm = FALSE,
filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
refine.wl = FALSE,
method = "spline",
...
)

## S3 method for class 'reflector_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'cps_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "cps",
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'raw_spct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "counts",
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'generic_mspct'
```

```
peaks(  
  x,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  na.rm = FALSE,  
  var.name = NULL,  
  refine.wl = FALSE,  
  method = "spline",  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'source_mspct'  
peaks(  
  x,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  refine.wl = FALSE,  
  method = "spline",  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'response_mspct'  
peaks(  
  x,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  refine.wl = FALSE,  
  method = "spline",  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'filter_mspct'  
peaks(  
  x,  
  span = 5,
```

```
ignore_threshold = 0,
strict = TRUE,
na.rm = FALSE,
filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
refine.wl = FALSE,
method = "spline",
...,
.parallel = FALSE,
.paropts = NULL
)

## S3 method for class 'reflector_mspct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'cps_mspct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "cps",
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
peaks(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "counts",
```

```

  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>x</code>	an R object
<code>span</code>	integer A peak is defined as an element in a sequence which is greater than all other elements within a window of width <code>span</code> centered at that element. Use <code>NULL</code> for the global peak.
<code>ignore_threshold</code>	numeric Value between 0.0 and 1.0 indicating the relative size compared to tallest peak threshold below which peaks will be ignored. Negative values set a threshold so that the tallest peaks are ignored, instead of the shortest.
<code>strict</code>	logical If <code>TRUE</code> , an element must be strictly greater than all other values in its window to be considered a peak.
<code>na.rm</code>	logical indicating whether NA values should be stripped before searching for peaks.
<code>...</code>	ignored
<code>var.name, x.var.name, y.var.name</code>	character Name of column where to look for peaks.
<code>refine.wl</code>	logical Flag indicating if peak location should be refined by fitting a function.
<code>method</code>	character String with the name of a method. Currently only spline interpolation is implemented.
<code>unit.out</code>	character One of "energy" or "photon"
<code>filter.qty</code>	character One of "transmittance" or "absorbance"
<code>.parallel</code>	if <code>TRUE</code> , apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A subset of `x` with rows corresponding to local maxima.

Methods (by class)

- `default`: Default returning always NA.
- `numeric`: Default function usable on numeric vectors.
- `data.frame`: Method for "data.frame" objects.
- `generic_spct`: Method for "generic_spct" objects.

- source_spct: Method for "source_spct" objects.
- response_spct: Method for "response_spct" objects.
- filter_spct: Method for "filter_spct" objects.
- reflector_spct: Method for "reflector_spct" objects.
- cps_spct: Method for "cps_spct" objects.
- raw_spct: Method for "raw_spct" objects.
- generic_mspct: Method for "generic_mspct" objects.
- source_mspct: Method for "source_mspct" objects.
- response_mspct: Method for "cps_mspct" objects.
- filter_mspct: Method for "filter_mspct" objects.
- reflector_mspct: Method for "reflector_mspct" objects.
- cps_mspct: Method for "cps_mspct" objects.
- raw_mspct: Method for "raw_mspct" objects.

Note

Thresholds for ignoring peaks are applied after peaks are searched for, and negative threshold values can in some cases result in no peaks being returned.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [get_peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```
peaks(sun.spct, span = 51)
peaks(sun.spct, span = NULL)
peaks(sun.spct, span = 51, refine.wl = TRUE)

peaks(sun.spct)
```

photodiode.spct

Spectral response of a GaAsP photodiode

Description

A dataset containing wavelengths at a 1 nm interval and spectral response as $A/(W/nm)$ for GaAsP photodiode type G6262 from Hamamatsu. Data digitized from manufacturer's data sheet. The value at the peak is $0.19 A/W$.

Usage

```
photodiode.spct
```

Format

A response_spct object with 94 rows and 2 variables

Details

- w.length (nm).
- s.e.response (A/W)

References

Hamamatsu (2011) Datasheet: GaAsP Photodiodes G5645 G5842 G6262. Hamamatsu Photonics KK, Hamamatsu, City. <http://www.hamamatsu.com/jp/en/G6262.html>. Visited 2017-12-15.

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspt](#), [green_leaf.spct](#), [opaque.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
photodiode.spct
```

photons_energy_ratio *Photon:energy ratio*

Description

This function gives the photons:energy ratio between for one given waveband of a radiation spectrum.

Usage

```
photons_energy_ratio(  
  w.length,  
  s.irrad,  
  w.band = NULL,  
  unit.in = "energy",  
  check.spectrum = TRUE,  
  use.cached.mult = FALSE,  
  use.hinges = getOption("photobiology.use.hinges", default = NULL)  
)
```

Arguments

w.length	numeric vector of wavelength (nm).
s.irrad	numeric vector of spectral (energy) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$).
w.band	waveband object.
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
check.spectrum	logical Flag telling whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag telling whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

A single numeric value giving the ratio moles-photons per Joule.

Note

The default for the w.band parameter is a waveband covering the whole range of w.length.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
# photons:energy ratio
with(sun.data, photons_energy_ratio(w.length, s.e.irrad, new_waveband(400,500)))
# photons:energy ratio for whole spectrum
with(sun.data, photons_energy_ratio(w.length, s.e.irrad))
```

photon_irradiance *Photon irradiance*

Description

This function returns the photon irradiance for a given waveband of a radiation spectrum, optionally applies a BSWF.

Usage

```
photon_irradiance(  
  w.length,  
  s.irrad,  
  w.band = NULL,  
  unit.in = "energy",  
  check.spectrum = TRUE,  
  use.cached.mult = FALSE,  
  use.hinges = getOption("photobiology.use.hinges", default = NULL)  
)
```

Arguments

w.length	numeric vector of wavelength (nm).
s.irrad	numeric vector of spectral irradiances, by default as energy (W m ⁻² nm ⁻¹).
w.band	waveband.
unit.in	character Values recognized "photon" or "energy".
check.spectrum	logical Flag telling whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag telling whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

A single numeric value with no change in scale factor: [mol s⁻¹ m⁻² nm⁻¹] -> [mol s⁻¹ m⁻²].

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data, photon_irradiance(w.length, s.e.irrad))  
with(sun.data, photon_irradiance(w.length, s.e.irrad, new_waveband(400,700)))
```

photon_ratio	<i>Photo:photon ratio</i>
--------------	---------------------------

Description

This function gives the photon ratio between two given wavebands of a radiation spectrum.

Usage

```
photon_ratio(
  w.length,
  s.irrad,
  w.band.num = NULL,
  w.band.denom = NULL,
  unit.in = "energy",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)
```

Arguments

w.length	numeric vector of wavelength (nm).
s.irrad	numeric vector of spectral (energy or photon) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$) or ($\text{mol s}^{-1} \text{m}^{-2} \text{nm}^{-1}$).
w.band.num	waveband object used to compute the numerator of the ratio.
w.band.denom	waveband object used to compute the denominator of the ratio.
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
check.spectrum	logical Flag telling whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag telling whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

a single numeric value giving the unitless ratio.

Note

The default for both w.band parameters is a waveband covering the whole range of w.length.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
with(sun.data,
     photon_ratio(w.length, s.e.irrad, new_waveband(400,500), new_waveband(400,700)))
```

plus-.generic_spct *Arithmetic Operators*

Description

Division operator for generic spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 + e2 = NULL
```

Arguments

e1	an object of class "generic_spct"
e2	an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

polyester.spct *Transmittance spectrum of clear polyester film*

Description

A dataset containing the wavelengths at a 1 nm interval and fractional total transmittance for polyester film.

Usage

```
polyester.spct
```

Format

A filter_spct object with 611 rows and 2 variables

Details

- w.length (nm).
- Tfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
polyester.spct
```

print *Print a spectral object*

Description

Print method for objects of spectral classes.

Usage

```
## S3 method for class 'generic_spct'
print(x, ..., n = NULL, width = NULL)

## S3 method for class 'generic_mspct'
print(x, ..., n = NULL, width = NULL, n.members = 10)
```

Arguments

x	An object of one of the summary classes for spectra
...	not used in current version
n	Number of rows to show. If NULL, the default, will print all rows if less than option dplyr.print_max. Otherwise, will print dplyr.print_min
width	Width of text output to generate. This defaults to NULL, which means use getOption("width") and only display the columns that fit on one screen. You can also set option(dplyr.width = Inf) to override this default and always print all columns.
n.members	numeric Number of members of the collection to print.

Value

Returns x invisibly.

Methods (by class)

- generic_mspct:

Note

At the moment just a modified copy of dplyr:::print.tbl_df.

Examples

```
print(sun.spct)
print(sun.spct, n = 5)
```

print.solar_time *Print solar time and solar date objects*

Description

Print solar time and solar date objects

Usage

```
## S3 method for class 'solar_time'
print(x, ...)

## S3 method for class 'solar_date'
print(x, ...)
```

Arguments

x an R object
... passed to format method

Note

Default is to print the underlying POSIXct as a solar time.

See Also

Other astronomy related functions: [day_night\(\)](#), [format.solar_time\(\)](#), [format.tod_time\(\)](#), [is.solar_time\(\)](#), [print.tod_time\(\)](#), [solar_time\(\)](#), [sun_angles\(\)](#)

```
print.summary_generic_spct  
                          Print spectral summary
```

Description

A function to nicely print objects of classes "summary...spct".

Usage

```
## S3 method for class 'summary_generic_spct'  
print(x, ...)
```

Arguments

x An object of one of the summary classes for spectra
... not used in current version

Examples

```
print(summary(sun.spct))
```

print.tod_time	<i>Print time-of-day objects</i>
----------------	----------------------------------

Description

Print time-of-day objects

Usage

```
## S3 method for class 'tod_time'  
print(x, ...)
```

Arguments

x	an R object
...	passed to format method

Note

Default is to print the underlying numeric vector as a solar time.

See Also

Other astronomy related functions: [day_night\(\)](#), [format.solar_time\(\)](#), [format.tod_time\(\)](#), [is.solar_time\(\)](#), [print.solar_time\(\)](#), [solar_time\(\)](#), [sun_angles\(\)](#)

print.waveband	<i>Print a "waveband" object</i>
----------------	----------------------------------

Description

A function to more nicely print objects of class "waveband".

Usage

```
## S3 method for class 'waveband'  
print(x, ...)
```

Arguments

x	an object of class "waveband"
...	not used in current version

prod_spectra	<i>Multiply two spectra, even if the wavelengths values differ</i>
--------------	--

Description

The wavelength vectors of the two spectra are merged, and the missing spectral values are calculated by interpolation. After this, the two spectral values at each wavelength are added.

Usage

```
prod_spectra(
  w.length1,
  w.length2 = NULL,
  s.irrad1,
  s.irrad2,
  trim = "union",
  na.rm = FALSE
)
```

Arguments

w.length1	numeric vector of wavelength (nm).
w.length2	numeric vector of wavelength (nm).
s.irrad1	a numeric vector of spectral values.
s.irrad2	a numeric vector of spectral values.
trim	a character string with value "union" or "intersection".
na.rm	a logical value, if TRUE, not the default, NAs in the input are replaced with zeros.

Details

If trim=="union" spectral values are calculated for the whole range of wavelengths covered by at least one of the input spectra, and missing values are set in each input spectrum to zero before addition. If trim=="intersection" then the range of wavelengths covered by both input spectra is returned, and the non-overlapping regions discarded. If w.length2==NULL, it is assumed that both spectra are measured at the same wavelengths, and a simple addition is used, ensuring fast calculation.

Value

a dataframe with two numeric variables

w.length	A numeric vector with the wavelengths (nm) obtained by "fusing" w.length1 and w.length2. w.length contains all the unique vales, sorted in ascending order.
s.irrad	A numeric vector with the sum of the two spectral values at each wavelength.

See Also

Other low-level functions operating on numeric vectors.: `as_energy()`, `as_quantum_mol()`, `calc_multipliers()`, `div_spectra()`, `energy_irradiance()`, `energy_ratio()`, `insert_hinges()`, `integrate_xy()`, `interpolate_spectrum()`, `irradiance()`, `l_insert_hinges()`, `oper_spectra()`, `photon_irradiance()`, `photon_ratio()`, `photons_energy_ratio()`, `s_e_irrad2rgb()`, `split_energy_irradiance()`, `split_photon_irradiance()`, `subt_spectra()`, `sum_spectra()`, `trim_tails()`, `v_insert_hinges()`, `v_replace_hinges()`

Examples

```
head(sun.data)
square.sun.data <-
  with(sun.data, prod_spectra(w.length, w.length, s.e.irrad, s.e.irrad))
head(square.sun.data)
tail(square.sun.data)
```

q2e

Convert photon-based quantities into energy-based quantities

Description

Function that converts spectral photon irradiance (molar) into spectral energy irradiance.

Usage

```
q2e(x, action, byref, ...)

## Default S3 method:
q2e(x, action = "add", byref = FALSE, ...)

## S3 method for class 'source_spct'
q2e(x, action = "add", byref = FALSE, ...)

## S3 method for class 'response_spct'
q2e(x, action = "add", byref = FALSE, ...)

## S3 method for class 'source_mspct'
q2e(x, action = "add", byref = FALSE, ..., .parallel = FALSE, .paropts = NULL)

## S3 method for class 'response_mspct'
q2e(x, action = "add", byref = FALSE, ..., .parallel = FALSE, .paropts = NULL)
```

Arguments

x	an R object
action	a character string
byref	logical indicating if new object will be created by reference or by copy of x
...	not used in current version
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Methods (by class)

- default: Default method
- source_spct: Method for spectral irradiance
- response_spct: Method for spectral responsiveness
- source_mspct: Method for collections of (light) source spectra
- response_mspct: Method for collections of response spectra

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#)

qe_ratio

Photon:energy ratio

Description

This function returns the photon to energy ratio for each waveband of a light source spectrum.

Usage

```
qe_ratio(spct, w.band, scale.factor, wb.trim, use.cached.mult, use.hinges, ...)

## Default S3 method:
qe_ratio(spct, w.band, scale.factor, wb.trim, use.cached.mult, use.hinges, ...)

## S3 method for class 'source_spct'
qe_ratio(
  spct,
  w.band = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
```

```

    use.cached.mult = FALSE,
    use.hinges = NULL,
    naming = "short",
    name.tag = ifelse(naming != "none", "[q:e]", ""),
    ...
)

## S3 method for class 'source_mspct'
qe_ratio(
  spct,
  w.band = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = FALSE,
  use.hinges = NULL,
  naming = "short",
  name.tag = ifelse(naming != "none", "[q:e]", ""),
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	source_spct.
<code>w.band</code>	waveband or list of waveband objects.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
<code>use.cached.mult</code>	logical Flag telling whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>name.tag</code>	character Used to tag the name of the returned values.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>

`.paropts` a list of additional options passed into the `foreach` function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the `.export` and `.packages` arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

Computed values are ratios between photon irradiance and energy irradiance for a given waveband. A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used, with "q:e" prepended. Units [mol J-1].

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Method for `source_spct` objects
- `source_mspct`: Calculates photon:energy ratio from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use_cached_mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other photon and energy ratio functions: [e_ratio\(\)](#), [eq_ratio\(\)](#), [q_ratio\(\)](#)

Examples

```
qe_ratio(sun.spct, new_waveband(400,700))
```

q_fluence	<i>Photon fluence</i>
-----------	-----------------------

Description

Photon irradiance (i.e. quantum irradiance) for one or more waveband of a light source spectrum.

Usage

```
q_fluence(  
  spct,  
  w.band,  
  exposure.time,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  allow.scaled,  
  ...  
)  
  
## Default S3 method:  
q_fluence(  
  spct,  
  w.band,  
  exposure.time,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  allow.scaled,  
  ...  
)  
  
## S3 method for class 'source_spct'  
q_fluence(  
  spct,  
  w.band = NULL,  
  exposure.time,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),  
  use.hinges = NULL,  
  allow.scaled = FALSE,  
  naming = "default",  
  ...  
)
```

```
## S3 method for class 'source_mspct'
q_fluence(
  spct,
  w.band = NULL,
  exposure.time,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),
  use.hinges = NULL,
  allow.scaled = FALSE,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

spct	an R object.
w.band	a list of waveband objects or a waveband object
exposure.time	lubridate::duration object.
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
use.cached.mult	logical indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
allow.scaled	logical indicating whether scaled or normalized spectra as argument to spct are flagged as an error.
...	other arguments (possibly ignored).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

One numeric value for each waveband with no change in scale factor, with name attribute set to the name of each waveband unless a named list is supplied in which case the names of the list elements are used. The exposure.time is copied from the spectrum object to the output as an attribute. Units are as follows: moles of photons per exposure.

Methods (by class)

- default: Default for generic function
- source_spct: Calculate photon fluence from a source_spct object and the duration of the exposure
- source_mspct: Calculates photon (quantum) fluence from a source_mspct object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting use_cached_mult=TRUE. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the w.length vector.

See Also

Other irradiance functions: [e_fluence\(\)](#), [e_irrad\(\)](#), [fluence\(\)](#), [irrad\(\)](#), [q_irrad\(\)](#)

Examples

```
library(lubridate)
q_fluence(sun.spct,
          w.band = waveband(c(400,700)),
          exposure.time = lubridate::duration(3, "minutes") )
```

q_irrad

Photon irradiance

Description

Photon irradiance (i.e. quantum irradiance) for one or more wavebands of a light source spectrum.

Usage

```
q_irrad(
  spct,
  w.band,
  quantity,
  time.unit,
```

```
    scale.factor,  
    wb.trim,  
    use.cached.mult,  
    use.hinges,  
    allow.scaled,  
    ...  
  )  
  
## Default S3 method:  
q_irrad(  
  spct,  
  w.band,  
  quantity,  
  time.unit,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  allow.scaled,  
  ...  
)  
  
## S3 method for class 'source_spct'  
q_irrad(  
  spct,  
  w.band = NULL,  
  quantity = "total",  
  time.unit = NULL,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),  
  use.hinges = NULL,  
  allow.scaled = !quantity %in% c("average", "mean", "total"),  
  naming = "default",  
  ...  
)  
  
## S3 method for class 'source_mspct'  
q_irrad(  
  spct,  
  w.band = NULL,  
  quantity = "total",  
  time.unit = NULL,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = getOption("photobiology.use.cached.mult", default = FALSE),  
  use.hinges = NULL,  
  allow.scaled = !quantity %in% c("average", "mean", "total"),
```



```

    naming = "default",
    ...,
    attr2tb = NULL,
    idx = "spct.idx",
    .parallel = FALSE,
    .paropts = NULL
  )

```

Arguments

spct	an R object.
w.band	a list of waveband objects or a waveband object.
quantity	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
time.unit	character or lubridate::duration object.
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
use.cached.mult	logical indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
allow.scaled	logical indicating whether scaled or normalized spectra as argument to spct are flagged as an error.
...	other arguments (possibly ignored).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter w.band. A data.frame in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and

optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used. The `time.unit` attribute is copied from the spectrum object to the output. Units are as follows: If `time.unit` is second, [W m⁻² nm⁻¹] -> [mol s⁻¹ m⁻²] If `time.unit` is day, [J d⁻¹ m⁻² nm⁻¹] -> [mol d⁻¹ m⁻²]

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Calculates photon irradiance from a `source_spct` object.
- `source_mspct`: Calculates photon (quantum) irradiance from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use_cached_mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other irradiance functions: `e_fluence()`, `e_irrad()`, `fluence()`, `irrad()`, `q_fluence()`

Examples

```
q_irrad(sun.spct, waveband(c(400,700)))
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3))
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "total")
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "average")
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "relative")
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "relative.pc")
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "contribution")
q_irrad(sun.spct, split_bands(c(400,700), length.out = 3), quantity = "contribution.pc")
```

q_ratio

Photon:photon ratio

Description

This function returns the photon ratio for a given pair of wavebands of a light source spectrum.

Usage

```
q_ratio(  
  spct,  
  w.band.num,  
  w.band.denom,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  ...  
)  
  
## Default S3 method:  
q_ratio(  
  spct,  
  w.band.num,  
  w.band.denom,  
  scale.factor,  
  wb.trim,  
  use.cached.mult,  
  use.hinges,  
  ...  
)  
  
## S3 method for class 'source_spct'  
q_ratio(  
  spct,  
  w.band.num = NULL,  
  w.band.denom = NULL,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = FALSE,  
  use.hinges = NULL,  
  naming = "short",  
  name.tag = ifelse(naming != "none", "[q:q]", ""),  
  ...  
)  
  
## S3 method for class 'source_mspct'  
q_ratio(  
  spct,  
  w.band.num = NULL,  
  w.band.denom = NULL,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.cached.mult = FALSE,  
  use.hinges = NULL,  
  naming = "short",
```

```

name.tag = ifelse(naming != "none", "[q:q]", ""),
...,
attr2tb = NULL,
idx = "spct.idx",
.parallel = FALSE,
.paropts = NULL
)

```

Arguments

<code>spct</code>	an object of class "source_spct".
<code>w.band.num</code>	waveband object or a list of waveband objects used to compute the numerator(s) of the ratio(s).
<code>w.band.denom</code>	waveband object or a list of waveband objects used to compute the denominator(s) of the ratio(s).
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded
<code>use.cached.mult</code>	logical indicating whether multiplier values should be cached between calls
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly ignored)
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>name.tag</code>	character Used to tag the name of the returned values.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

In the case of methods for individual spectra, a numeric vector of adimensional values giving a photon ratio between integrated photon irradiances for pairs of wavebands, with name attribute set to the name of the wavebands unless a named list of wavebands is supplied in which case the names of the list elements are used, with "(q:q)" appended. A `data.frame` in the case of collections of spectra, containing one column for each ratio definition, an index column with the names of the

spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

Ratio definitions are "assembled" from the arguments passed to `w.band.num` and `w.band.denom`. If both arguments are of equal length, then the wavebands are paired to obtain as many ratios as the number of wavebands in each list. Recycling for wavebands takes place when the number of denominator and numerator wavebands differ.

Methods (by class)

- `default`: Default for generic function
- `source_spct`: Method for `source_spct` objects
- `source_mspct`: Calculates photon:photon from a `source_mspct` object.

Note

The last two parameters control speed optimizations. The defaults should be suitable in most cases. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other photon and energy ratio functions: [e_ratio\(\)](#), [eq_ratio\(\)](#), [qe_ratio\(\)](#)

Examples

```
q_ratio(sun.spct, new_waveband(400,500), new_waveband(400,700))
```

q_response

Photon-based photo-response

Description

This function returns the mean response for a given waveband and a response spectrum.

Usage

```
q_response(
  spct,
  w.band,
  quantity,
  time.unit,
  scale.factor,
  wb.trim,
  use.hinges,
```

```

    ...
  )

## Default S3 method:
q_response(
  spct,
  w.band,
  quantity,
  time.unit,
  scale.factor,
  wb.trim,
  use.hinges,
  ...
)

## S3 method for class 'response_spct'
q_response(
  spct,
  w.band = NULL,
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
  naming = "default",
  ...
)

## S3 method for class 'response_mspct'
q_response(
  spct,
  w.band = NULL,
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

spct an R object.

w.band	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
quantity	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
time.unit	character or lubridate::duration object.
scale.factor	numeric vector of length 1, or length equal to that of w.band. Numeric multiplier applied to returned values.
wb.trim	logical if TRUE wavebands crossing spectral data boundaries are trimmed, if FALSE, they are discarded.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
...	other arguments (possibly used by derived methods).
naming	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
attr2tb	character vector, see add_attr2tb for the syntax for attr2tb passed as is to formal parameter col.names.
idx	character Name of the column with the names of the members of the collection of spectra.
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter w.band. A data.frame in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter quantity they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- default: Default method for generic function
- response_spct: Method for response spectra.
- response_mspct: Calculates photon (quantum) response from a response_mspct

Note

The parameter `use.hinges` controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

See Also

Other response functions: [e_response\(\)](#), [response\(\)](#)

Examples

```
q_response(ccd.spct, new_waveband(200,300))
q_response(photodiode.spct)
```

rbindspct

Row-bind spectra

Description

A wrapper on `dplyr::rbind_fill` that preserves class and other attributes of spectral objects.

Usage

```
rbindspct(
  l,
  use.names = TRUE,
  fill = TRUE,
  idfactor = TRUE,
  attrs.source = NULL
)
```

Arguments

- | | |
|-----------|--|
| l | A <code>source_mspct</code> , <code>filter_mspct</code> , <code>reflector_mspct</code> , <code>response_mspct</code> , <code>chroma_mspct</code> , <code>cps_mspct</code> , <code>generic_mspct</code> object or a list containing <code>source_spct</code> , <code>filter_spct</code> , <code>reflector_spct</code> , <code>response_spct</code> , <code>chroma_spct</code> , <code>cps_spct</code> , or <code>generic_spct</code> objects. |
| use.names | logical If TRUE items will be bound by matching column names. By default TRUE for <code>rbindspct</code> . Columns with duplicate names are bound in the order of occurrence, similar to <code>base</code> . When TRUE, at least one item of the input list has to have non-null column names. |
| fill | logical If TRUE fills missing columns with NAs. By default TRUE. When TRUE, <code>use.names</code> has also to be TRUE, and all items of the input list have to have non-null column names. |

idfactor	logical or character	Generates an index column of factor type. Default is (idfactor=TRUE) for both lists and <code>_mspct</code> objects. If idfactor=TRUE then the column is auto named <code>spct.idx</code> . Alternatively the column name can be directly provided to idfactor as a character string.
attrs.source	integer	Index into the members of the list from which attributes should be copied. If NULL, all attributes are merged.

Details

Each item of `l` should be a spectrum, including NULL (skipped) or an empty object (0 rows). `rbindspc` is most useful when there are a variable number of (potentially many) objects to stack. `rbindspct` always returns at least a `generic_spct` as long as all elements in `l` are spectra.

Value

An spectral object of a type common to all bound items containing a concatenation of all the items passed in. If the argument 'idfactor' is TRUE, then a factor 'spct.idx' will be added to the returned spectral object.

Note

Note that any additional 'user added' attributes that might exist on individual items of the input list will not be preserved in the result. The attributes used by the `photobiology` package are preserved, and if they are not consistent across the bound spectral objects, a warning is issued.

`dplyr::rbind_fill` is called internally and the result returned is the highest class in the inheritance hierarchy which is common to all elements in the list. If not all members of the list belong to one of the `_spct` classes, an error is triggered. The function sets all data in `source_spct` and `response_spct` objects supplied as arguments into energy-based quantities, and all data in `filter_spct` objects into transmittance before the row binding is done. If any member spectrum is tagged, it is untagged before row binding.

Examples

```
# default, adds factor 'spct.idx' with letters as levels
spct <- rbindspct(list(sun.spct, sun.spct))
spct
class(spct)

# adds factor 'spct.idx' with letters as levels
spct <- rbindspct(list(sun.spct, sun.spct), idfactor = TRUE)
head(spct)
class(spct)

# adds factor 'spct.idx' with the names given to the spectra in the list
# supplied as formal argument 'l' as levels
spct <- rbindspct(list(one = sun.spct, two = sun.spct), idfactor = TRUE)
head(spct)
class(spct)

# adds factor 'ID' with the names given to the spectra in the list
```

```
# supplied as formal argument 'l' as levels
spct <- rbindspct(list(one = sun.spct, two = sun.spct),
                  idfactor = "ID")
head(spct)
class(spct)
```

 reflectance

Reflectance

Description

Function to calculate the mean, total, or other summary of reflectance for spectral data stored in a reflector_spct or in an object_spct.

Usage

```
reflectance(spct, w.band, quantity, wb.trim, use.hinges, ...)
```

```
## Default S3 method:
```

```
reflectance(spct, w.band, quantity, wb.trim, use.hinges, ...)
```

```
## S3 method for class 'reflector_spct'
```

```
reflectance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)
```

```
## S3 method for class 'object_spct'
```

```
reflectance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)
```

```
## S3 method for class 'reflector_mspct'
```

```
reflectance(
  spct,
```

```

    w.band = NULL,
    quantity = "average",
    wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
    use.hinges = NULL,
    naming = "default",
    ...,
    attr2tb = NULL,
    idx = "spct.idx",
    .parallel = FALSE,
    .paropts = NULL
)

## S3 method for class 'object_mspct'
reflectance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object
<code>w.band</code>	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
<code>quantity</code>	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc"
<code>wb.trim</code>	logical Flag telling if wavebands crossing spectral data boundaries are trimmed or ignored
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.

`.parallel` if TRUE, apply function in parallel, using parallel backend provided by foreach
`.paropts` a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the `.export` and `.packages` arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- `default`: Default for generic function
- `reflector_spct`: Specialization for `reflector_spct`
- `object_spct`: Specialization for `object_spct`
- `reflector_mspct`: Calculates reflectance from a `reflector_mspct`
- `object_mspct`: Calculates reflectance from a `object_mspct`

Note

The `use.hinges` parameter controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

Examples

```
reflectance(black_body.spct, waveband(c(400,700)))
reflectance(white_body.spct, waveband(c(400,700)))
```

relative_AM

Relative Air Mass (AM)

Description

Approximate relative air mass (AM) from sun elevation or sun zenith angle.

Usage

```
relative_AM(elevation.angle = NULL, zenith.angle = NULL, occluded.value = NA)
```

Arguments

elevation.angle, zenith.angle
numeric vector Angle in degrees for the sun position. An argument should be passed to one and only one of elevation_angle or zenith_angle.

occluded.value numeric Value to return when elevation angle is negative (sun below the horizon).

Details

This is an implementation of equation (3) in Kasten and Young (1989). This equation is only an approximation to the tabulated values in the same paper. Returned values are rounded to three significant digits.

Note

Although relative air mass is not defined when the sun is not visible, returning a value different from the default NA might be useful in some cases.

References

F. Kasten, A. T. Young (1989) Revised optical air mass tables and approximation formula. Applied Optics, 28, 4735-. doi:10.1364/ao.28.004735.

Examples

```
relative_AM(c(90, 60, 30, 1, -10))
relative_AM(c(90, 60, 30, 1, -10), occluded.value = Inf)
relative_AM(zenith.angle = 0)
```

replace_bad_pixs *Replace bad pixels in a spectrum*

Description

This function replaces data for bad pixels by a local estimate, by either simple interpolation or using the algorithm of Whitaker and Hayes (2018).

Usage

```
replace_bad_pixs(  
  x,  
  bad.pix.idx = FALSE,  
  window.width = 11,  
  method = "run.mean",  
  na.rm = TRUE  
)
```

Arguments

<code>x</code>	numeric vector containing spectral data.
<code>bad.pix.idx</code>	logical vector or integer. Index into bad pixels in <code>x</code> .
<code>window.width</code>	integer. The full width of the window used for the running mean.
<code>method</code>	character The name of the method: "run.mean" is running mean as described in Whitaker and Hayes (2018); "adj.mean" is mean of adjacent neighbors (isolated bad pixels only).
<code>na.rm</code>	logical Treat NA values as additional bad pixels and replace them.

Details

Simple interpolation replaces values of isolated bad pixels by the mean of their two closest neighbors. The running mean approach allows the replacement of short runs of bad pixels by the running mean of neighboring pixels within a window of user-specified width. The first approach works well for spectra from array spectrometers to correct for hot and dead pixels in an instrument. The second approach is most suitable for Raman spectra in which spikes triggered by radiation are wider than a single pixel but usually not more than five pixels wide.

Value

A logical vector of the same length as `x`. Values that are TRUE correspond to local spikes in the data.

Note

In the current implementation NA values are not removed, and if they are in the neighborhood of bad pixels, they will result in the generation of additional NAs during their replacement.

References

Whitaker, D. A.; Hayes, K. (2018) A simple algorithm for despiking Raman spectra. *Chemometrics and Intelligent Laboratory Systems*, 179, 82-84.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [spikes\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```
# in a vector
replace_bad_pixs(c(1, 1, 45, 1, 1), bad.pix.idx = 3)

# before replacement
white_led.raw_spct$counts_3[120:125]

# replacing bad pixels at index positions 123 and 1994
with(white_led.raw_spct,
      replace_bad_pixs(counts_3, bad.pix.idx = c(123, 1994)))[120:125]
```

response	<i>Integrated response</i>
----------	----------------------------

Description

Calculate average photon- or energy-based photo-response.

Usage

```
response(  
  spct,  
  w.band,  
  unit.out,  
  quantity,  
  time.unit,  
  scale.factor,  
  wb.trim,  
  use.hinges,  
  ...  
)  
  
## Default S3 method:  
response(  
  spct,  
  w.band,  
  unit.out,  
  quantity,  
  time.unit,  
  scale.factor,  
  wb.trim,  
  use.hinges,  
  ...  
)  
  
## S3 method for class 'response_spct'  
response(  
  spct,  
  w.band = NULL,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  quantity = "total",  
  time.unit = NULL,  
  scale.factor = 1,  
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),  
  use.hinges = getOption("photobiology.use.hinges", default = NULL),  
  naming = "default",
```

```

    ...
  )

## S3 method for class 'response_mspct'
response(
  spct,
  w.band = NULL,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  quantity = "total",
  time.unit = NULL,
  scale.factor = 1,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>spct</code>	an R object of class "generic_spct".
<code>w.band</code>	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
<code>unit.out</code>	character Allowed values "energy", and "photon", or its alias "quantum".
<code>quantity</code>	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>time.unit</code>	character or lubridate::duration object.
<code>scale.factor</code>	numeric vector of length 1, or length equal to that of <code>w.band</code> . Numeric multiplier applied to returned values.
<code>wb.trim</code>	logical Flag telling if wavebands crossing spectral data boundaries are trimmed or ignored.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	other arguments (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.

<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by foreach
<code>.paropts</code>	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A `data.frame` in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

Whether returned values are expressed in energy-based or photon-based units depends on `unit.out`. By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, `names` attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- `default`: Default for generic function
- `response_spct`: Method for response spectra.
- `response_mspct`: Calculates response from a `response_mspct`

Note

The parameter `use.hinges` controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

See Also

Other response functions: [e_response\(\)](#), [q_response\(\)](#)

Rfr_from_n

Reflectance at a planar boundary

Description

The reflectance at the planar boundary between two media, or interface, can be computed from the relative refractive index. Reflectance depends on polarization, and the process of reflection can generate polarized light through selective reflection of s and p components. A perfectly flat (i.e. polished) interface creates specular reflection, and this is the case that these functions describe. These function describe a single interface, and for example in a glass pane, a light beam will cross two air-glass interfaces.

Usage

```
Rfr_from_n(angle_deg, angle = angle_deg/180 * pi, n = 1.5, p_fraction = 0.5)
```

```
Rfr_p_from_n(angle_deg, angle = angle_deg/180 * pi, n = 1.5)
```

```
Rfr_s_from_n(angle_deg, angle = angle_deg/180 * pi, n = 1.5)
```

Arguments

angle_deg, angle	numeric vector Angle of incidence of the light beam, in degrees or radians. If both are supplied, radians take precedence.
n	numeric vector, or generic_spct object Relative refractive index. The default 1.5 is suitable for crown glass or acrylic interacting with visible light. n depends on wavelength, more or less strongly depending on the material.
p_fraction	numeric in range 0 to 1. Polarization, defaults to 0.5 assuming light that is not polarized.

Details

These functions implement Fresnel's formulae. All parameters accept vectors as arguments. If both n and angle are vectors with length different from one, they should both have the same length. Reflectance depends on polarization, the R_{ss} and R_{p} components need to be computed separately and added up. Rfr_from_n() is for non-polarized light, i.e., with equal contribution of the two components.

Value

If n is a numeric vector the returned value is a vector of reflectances, while if n is a generic_spct object the returned value is a reflector_spct object.

Examples

```
Rfr_from_n(0:90)
Rfr_from_n(0:90, p_fraction = 1)
Rfr_from_n(0:90, n = 1.333) # water
```

 rgb_spct

RGB color values

Description

This function returns the RGB values for a source spectrum.

Usage

```
rgb_spct(spct, sens = photobiology::ciexyzCMF2.spct, color.name = NULL)
```

Arguments

spct	an object of class "source_spct"
sens	a chroma_spct object with variables w.length, x, y, and z, giving the CC or CMF definition (default is the proposed human CMF according to CIE 2006.)
color.name	character string for naming the rgb color definition

Value

A color defined using `rgb()`. The numeric values of the RGB components can be obtained

See Also

Other color functions: [w_length2rgb\(\)](#), [w_length_range2rgb\(\)](#)

Examples

```
rgb_spct(sun.spct)
```

rmDerivedMspct	<i>Remove "generic_mspct" and derived class attributes.</i>
----------------	---

Description

Removes from a spectrum object the class attributes "generic_mspct" and any derived class attribute such as "source_mspct". **This operation is done by reference!**

Usage

```
rmDerivedMspct(x)
```

Arguments

x	an R object.
---	--------------

Value

A character vector containing the removed class attribute values. This is different to the behaviour of function `unlist` in base R!

Note

If `x` is an object of any of the multi spectral classes defined in this package, this function changes by reference the multi spectrum object into the underlying list object. Otherwise, it just leaves `x` unchanged. The modified `x` is also returned invisibly.

See Also

Other set and unset 'multi spectral' class functions: [shared_member_class\(\)](#)

rmDerivedSpct	<i>Remove "generic_spct" and derived class attributes.</i>
---------------	--

Description

Removes from a spectrum object the class attributes "generic_spct" and any derived class attribute such as "source_spct". **This operation is done by reference!**

Usage

```
rmDerivedSpct(x, keep.classes = NULL)
```

Arguments

x	an R object.
keep.classes	character vector Names of classes to keep. Can be used to retain base class "generic_spct".

Value

A character vector containing the removed class attribute values. This is different to the behaviour of function `unlist` in base R!

Note

If x is an object of any of the spectral classes defined in this package, this function changes by reference the spectrum object into the underlying data.frame object. Otherwise, it just leaves x unchanged.

This function alters x itself by reference. If x is not a generic_spct object, x is not modified.

See Also

Other set and unset spectral class functions: [setGenericSpct\(\)](#)

Examples

```
my.spct <- sun.spct
removed <- rmDerivedSpct(my.spct)
removed
class(sun.spct)
class(my.spct)
```

round

*Rounding of Numbers***Description**

`ceiling` takes a single numeric argument `x` and returns a numeric vector containing the smallest integers not less than the corresponding elements of `x`. `\ floor` takes a single numeric argument `x` and returns a numeric vector containing the largest integers not greater than the corresponding elements of `x`. `\ trunc` takes a single numeric argument `x` and returns a numeric vector containing the integers formed by truncating the values in `x` toward 0. `\ round` rounds the values in its first argument to the specified number of decimal places (default 0). `\ signif` rounds the values in its first argument to the specified number of significant digits. The functions are applied to the spectral data, not the wavelengths. The quantity in the spectrum to which the function is applied depends on the class of `x` and the current value of output options.

Usage

```
## S3 method for class 'generic_spct'
round(x, digits = 0)

## S3 method for class 'generic_spct'
signif(x, digits = 6)

## S3 method for class 'generic_spct'
ceiling(x)

## S3 method for class 'generic_spct'
floor(x)

## S3 method for class 'generic_spct'
trunc(x, ...)
```

Arguments

<code>x</code>	an object of class "generic_spct" or a derived class.
<code>digits</code>	integer indicating the number of decimal places (round) or significant digits (signif) to be used. Negative values are allowed (see 'Details').
<code>...</code>	arguments to be passed to methods.

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

 select_spct_attributes

Merge user supplied attribute names with default ones

Description

Allow users to add and subtract from default attributes in addition to providing a given set of attributes.

Usage

```
select_spct_attributes(attributes, attributes.default = spct_attributes())
```

```
spct_attributes(.class = "all", attributes = "*")
```

Arguments

attributes, attributes.default	character vector or a list of character vectors.
.class	character Name of spectral class.

Details

Vectors of character strings passed as argument to attributes are parsed so that if the first member string is "+", the remaining members are added to those in attributes.default; if it is "-" the remaining members are removed from in attributes.default; and if it is "=" the remaining members replace those in in attributes.default. If the first member is none of these three strings, the behaviour is the same as when the first string is "=". If attributes is NULL all the attributes in attributes.default are used and if it is "" no attribute names are returned, "" has precedence over other member values. The order of the names of annotations has no meaning: the vector is interpreted as a set except for the three possible "operators" at position 1.

Value

A character vector of attribute names.

See Also

[get_attributes](#)

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

setBSWFUsed	<i>Set the "bswf.used" attribute</i>
-------------	--------------------------------------

Description

Function to set by reference the "time.unit" attribute of an existing source_spct object

Usage

```
setBSWFUsed(x, bswf.used = c("none", "unknown"))
```

Arguments

x	a source_spct object
bswf.used	a character string, either "none" or the name of a BSWF

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a source_spct, x is not modified. The behaviour of this function is 'unusual' in that the default for parameter bswf.used is used only if x does not already have this attribute set. time.unit = "hour" is currently not fully supported.

See Also

Other BSWF attribute functions: [getBSWFUsed\(\)](#)

setFilterProperties	<i>Set the "filter.properties" attribute</i>
---------------------	--

Description

Function to set by reference the "filter.properties" attribute of an existing filter_spct object.

Usage

```

setFilterProperties(
  x,
  filter.properties = NULL,
  pass.null = FALSE,
  Rfr.constant = NA_real_,
  thickness = NA_real_,
  attenuation.mode = NA
)

filter_properties(x) <- value

```

Arguments

x	a filter_spct object
filter.properties, value	a list with fields named "Rfr.constant", "thickness" and "attenuation.mode".
pass.null	logical If TRUE, the parameters to the next three parameters will be always ignored, otherwise they will be used to build an object of class "filter.properties" when the argument to filter.properties is NULL.
Rfr.constant	numeric The value of the reflection factor (/1).
thickness	numeric The thickness of the material.
attenuation.mode	character One of "reflection", "absorption" or "mixed".

Details

Storing filter properties allows inter-conversion between internal and total transmittance, as well as computation of transmittance for arbitrary thickness of the material. Whether computations are valid depend on the homogeneity of the material. The parameter `pass.null` makes it possible to remove the attribute.

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a filter_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
my.spct <- polyester.spct
filter_properties(my.spct)
filter_properties(my.spct) <- NULL
filter_properties(my.spct)
filter_properties(my.spct, return.null = TRUE)
filter_properties(my.spct) <- list(Rfr.constant = 0.01,
                                   thickness = 125e-6,
                                   attenuation.mode = "absorption")

filter_properties(my.spct)
```

setGenericSpct	<i>Convert an R object into a spectrum object.</i>
----------------	--

Description

Sets the class attribute of a data.frame or an object of a derived class to "generic_spct".

Usage

```
setGenericSpct(x, multiple.wl = 1L, idfactor = NULL)

setCalibrationSpct(
  x,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL
)

setRawSpct(
  x,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL
)

setCpsSpct(
  x,
  time.unit = "second",
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL
)

setFilterSpct(
```

```

x,
Tfr.type = c("total", "internal"),
Rfr.constant = NA_real_,
thickness = NA_real_,
attenuation.mode = NA,
strict.range = getOption("photobiology.strict.range", default = FALSE),
multiple.wl = 1L,
idfactor = NULL
)

setReflectorSpct(
x,
Rfr.type = c("total", "specular"),
strict.range = getOption("photobiology.strict.range", default = FALSE),
multiple.wl = 1L,
idfactor = NULL
)

setObjectSpct(
x,
Tfr.type = c("total", "internal"),
Rfr.type = c("total", "specular"),
strict.range = getOption("photobiology.strict.range", default = FALSE),
multiple.wl = 1L,
idfactor = NULL
)

setResponseSpct(x, time.unit = "second", multiple.wl = 1L, idfactor = NULL)

setSourceSpct(
x,
time.unit = "second",
bswf.used = c("none", "unknown"),
strict.range = getOption("photobiology.strict.range", default = FALSE),
multiple.wl = 1L,
idfactor = NULL
)

setChromaSpct(x, multiple.wl = 1L, idfactor = NULL)

```

Arguments

<code>x</code>	data.frame, list or <code>generic_spct</code> and derived classes
<code>multiple.wl</code>	numeric Maximum number of repeated w.length entries with same value.
<code>idfactor</code>	character Name of factor distinguishing multiple spectra when stored longitudinally (required if <code>multiple.wl > 1</code>).
<code>strict.range</code>	logical Flag indicating whether off-range values result in an error instead of a warning.

time.unit	character	A string "second", "day" or "exposure".
Tfr.type	character	A string, either "total" or "internal".
Rfr.constant	numeric	The value of the reflection factor (/1).
thickness	numeric	The thickness of the material.
attenuation.mode	character	One of "reflection", "absorption" or "mixed".
Rfr.type	character	A string, either "total" or "specular".
bswf.used	character	A string, either "none" or the name of a BSWF.

Value

x

Functions

- setCalibrationSpct: Set class of a an object to "calibration_spct".
- setRawSpct: Set class of a an object to "raw_spct".
- setCpsSpct: Set class of a an object to "cps_spct".
- setFilterSpct: Set class of an object to "filter_spct".
- setReflectorSpct: Set class of a an object to "reflector_spct".
- setObjectSpct: Set class of an object to "object_spct".
- setResponseSpct: Set class of an object to "response_spct".
- setSourceSpct: Set class of an object to "source_spct".
- setChromaSpct: Set class of an object to "chroma_spct".

Note

This method alters x itself by reference and in addition returns x invisibly.

For non-diffusing materials like glass an approximate Rfr.constant value can be used to interconvert "total" and "internal" transmittance values. Use NA if not known, or not applicable, e.g., for materials subject to internal scattering.

See Also

Other set and unset spectral class functions: [rmDerivedSpct\(\)](#)

Examples

```
my.df <- data.frame(w.length = 300:309, s.e.irrad = rep(100, 10))
is.source_spct(my.df)
setSourceSpct(my.df)
is.source_spct(my.df)
```

setHowMeasured	<i>Set the "how.measured" attribute</i>
----------------	---

Description

Function to set by reference the "how.measured" attribute of an existing generic_spct or derived-class object.

Usage

```
setHowMeasured(x, how.measured)
```

```
how_measured(x) <- value
```

Arguments

x a generic_spct object
how.measured, value a list

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
my.spct <- sun.spct  
how_measured(my.spct)  
how_measured(my.spct) <- "simulated with a radiation transfer model"  
how_measured(my.spct)
```

setIdFactor	<i>Set the "idfactor" attribute</i>
-------------	-------------------------------------

Description

Function to set by reference the "idfactor" attribute of an existing generic_spct or an object of a class derived from generic_spct.

Usage

```
setIdFactor(x, idfactor)
```

Arguments

x	a generic_spct object
idfactor	character The name of a factor identifying multiple spectra stored longitudinally.

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct or an object of a class derived from generic_spct, x is not modified.

See Also

Other idfactor attribute functions: [getIdFactor\(\)](#)

setInstrDesc	<i>Set the "instr.desc" attribute</i>
--------------	---------------------------------------

Description

Function to set by reference the "instr.desc" attribute of an existing generic_spct or derived-class object.

Usage

```
setInstrDesc(x, instr.desc)
```

Arguments

x	a generic_spct object
instr.desc	a list

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

setInstrSettings	<i>Set the "instr.settings" attribute</i>
------------------	---

Description

Function to set by reference the "what.measured" attribute of an existing generic_spct or derived-class object.

Usage

```
setInstrSettings(x, instr.settings)
```

Arguments

x a generic_spct object
instr.settings a list

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

setMultipleWl	<i>Set the "multiple.wl" attribute</i>
---------------	--

Description

Function to set by reference the "multiple.wl" attribute of an existing generic_spct or an object of a class derived from generic_spct.

Usage

```
setMultipleWl(x, multiple.wl = NULL)
```

Arguments

x	a generic_spct object
multiple.wl	numeric ≥ 1 If multiple.wl is NULL, the default, the attribute is not modified if it is already present and valid, and set to 1 otherwise.

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct or an object of a class derived from generic_spct, x is not modified. If multiple.wl

See Also

Other multiple.wl attribute functions: [getMultipleWl\(\)](#)

setNormalized	<i>Set the "normalized" attribute</i>
---------------	---------------------------------------

Description

Function to write the "normalized" attribute of an existing generic_spct object.

Usage

```
setNormalized(x, norm = FALSE)
```

```
setNormalised(x, norm = FALSE)
```

Arguments

x a generic_spct object
 norm numeric or logical

Note

if x is not a generic_spct object, x is not modified.
 setNormalised() is a synonym for this setNormalized() method.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setScaled\(\)](#)

setRfrType	<i>Set the "Rfr.type" attribute</i>
------------	-------------------------------------

Description

Function to set by reference the "Rfr.type" attribute of an existing reflector_spct or object_spct object.

Usage

```
setRfrType(x, Rfr.type = c("total", "specular"))
```

Arguments

x a reflector_spct or an object_spct object
 Rfr.type a character string, either "total" or "specular"

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a reflector_spct or object_spct object, x is not modified. The behaviour of this function is 'unusual' in that the default for parameter Rfr.type is used only if x does not already have this attribute set.

See Also

Other Rfr attribute functions: [getRfrType\(\)](#)

Examples

```
my.spct <- reflector_spct(w.length = 400:409, Rfr = 0.1)
getRfrType(my.spct)
setRfrType(my.spct, "specular")
getRfrType(my.spct)
```

setScaled	<i>Set the "scaled" attribute</i>
-----------	-----------------------------------

Description

Function to write the "scaled" attribute of an existing generic_spct object.

Usage

```
setScaled(x, ...)

## Default S3 method:
setScaled(x, ...)

## S3 method for class 'generic_spct'
setScaled(x, ..., scaled = FALSE)

## S3 method for class 'summary_generic_spct'
setScaled(x, ..., scaled = FALSE)

## S3 method for class 'generic_mspct'
setScaled(x, ..., scaled = FALSE)
```

Arguments

x	a generic_spct object.
...	currently ignored.
scaled	logical with FALSE meaning that values are expressed in absolute physical units and TRUE meaning that relative units are used. If NULL the attribute is not modified.

Value

a new object of the same class as x.
a new object of the same class as x.
a new object of the same class as x.
a new object of the same class as x.

Methods (by class)

- `default`: Default for generic function
- `generic_spct`: Specialization for `generic_spct`
- `summary_generic_spct`: Specialization for `summary_generic_spct`
- `generic_mspct`: Specialization for `generic_mspct`

Note

if `x` is not a `generic_spct` object, `x` is not modified.

See Also

Other rescaling functions: [fscale\(\)](#), [fshift\(\)](#), [getNormalized\(\)](#), [getScaled\(\)](#), [is_normalized\(\)](#), [is_scaled\(\)](#), [normalize\(\)](#), [setNormalized\(\)](#)

 setTfrType

Set the "Tfr.type" attribute

Description

Function to set by reference the "Tfr.type" attribute of an existing `filter_spct` or `object_spct` object

Usage

```
setTfrType(x, Tfr.type = c("total", "internal"))
```

Arguments

<code>x</code>	a <code>filter_spct</code> or an <code>object_spct</code> object
<code>Tfr.type</code>	a character string, either "total" or "internal"

Value

`x`

Note

This function alters `x` itself by reference and in addition returns `x` invisibly. If `x` is not a `filter_spct` or an `object_spct` object, `x` is not modified. The behaviour of this function is 'unusual' in that the default for parameter `Tfr.type` is used only if `x` does not already have this attribute set.

See Also

Other Tfr attribute functions: [getTfrType\(\)](#)

Examples

```
my.spct <- polyester.spct
getTfrType(my.spct)
setTfrType(my.spct, "internal")
getTfrType(my.spct)
```

setTimeUnit

Set the "time.unit" attribute of an existing source_spct object

Description

Function to set by reference the "time.unit" attribute

Usage

```
setTimeUnit(
  x,
  time.unit = c("second", "hour", "day", "exposure", "none"),
  override.ok = FALSE
)
```

Arguments

x	a source_spct object
time.unit	a character string, either "second", "hour", "day", "exposure" or "none", or a lubridate::duration
override.ok	logical Flag that can be used to silence warning when overwriting an existing attribute value (used internally)

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a source_spct or response_spct object, x is not modified. The behaviour of this function is 'unusual' in that the default for parameter time.unit is used only if x does not already have this attribute set. time.unit = "hour" is currently not fully supported.

See Also

Other time attribute functions: [checkTimeUnit\(\)](#), [convertTfrType\(\)](#), [convertThickness\(\)](#), [convertTimeUnit\(\)](#), [getTimeUnit\(\)](#)

Examples

```
my.spct <- sun.spct
setTimeUnit(my.spct, time.unit = "second")
setTimeUnit(my.spct, time.unit = lubridate::duration(1, "seconds"))
```

setWhatMeasured	<i>Set the "what.measured" attribute</i>
-----------------	--

Description

Function to set by reference the "what.measured" attribute of an existing generic_spct or derived-class object.

Usage

```
setWhatMeasured(x, what.measured)
```

```
what_measured(x) <- value
```

Arguments

x	a generic_spct object
what.measured, value	a list

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
my.spct <- sun.spct
what_measured(my.spct)
what_measured(my.spct) <- "Sun"
what_measured(my.spct)
```

setWhenMeasured	<i>Set the "when.measured" attribute</i>
-----------------	--

Description

Function to set by reference the "when" attribute of an existing `generic_spct` or an object of a class derived from `generic_spct`.

Usage

```
setWhenMeasured(x, when.measured, ...)  
  
when_measured(x) <- value  
  
## Default S3 method:  
setWhenMeasured(x, when.measured, ...)  
  
## S3 method for class 'generic_spct'  
setWhenMeasured(x, when.measured = lubridate::now(tzone = "UTC"), ...)  
  
## S3 method for class 'summary_generic_spct'  
setWhenMeasured(x, when.measured = lubridate::now(tzone = "UTC"), ...)  
  
## S3 method for class 'generic_mspct'  
setWhenMeasured(x, when.measured = lubridate::now(tzone = "UTC"), ...)
```

Arguments

x	a <code>generic_spct</code> object
when.measured, value	POSIXct to add as attribute, or a list of POSIXct.
...	Allows use of additional arguments in methods for other classes.

Value

x

Methods (by class)

- default: default
- `generic_spct`: `generic_spct`
- `summary_generic_spct`: `summary_generic_spct`
- `generic_mspct`: `generic_mspct`

Note

This method alters `x` itself by reference and in addition returns `x` invisibly. If `x` is not a `generic_spct` or an object of a class derived from `generic_spct`, `x` is not modified. If `when` is not a `POSIXct` object or `NULL` an error is triggered. A `POSIXct` describes an instant in time (date plus time-of-day plus time zone).

See Also

Other measurement metadata functions: `getFilterProperties()`, `getHowMeasured()`, `getInstrDesc()`, `getInstrSettings()`, `getWhatMeasured()`, `getWhenMeasured()`, `getWhereMeasured()`, `get_attributes()`, `isValidInstrDesc()`, `isValidInstrSettings()`, `select_spct_attributes()`, `setFilterProperties()`, `setHowMeasured()`, `setInstrDesc()`, `setInstrSettings()`, `setWhatMeasured()`, `setWhereMeasured()`, `spct_attr2tb()`, `trimInstrDesc()`, `trimInstrSettings()`

Examples

```
my.spct <- sun.spct
when_measured(my.spct)
when_measured(my.spct) <- lubridate::ymd_hms("2020-01-01 08:00:00")
when_measured(my.spct)
```

setWhereMeasured	<i>Set the "where.measured" attribute</i>
------------------	---

Description

Function to set by reference the "where.measured" attribute of an existing `generic_spct` or an object of a class derived from `generic_spct`.

Usage

```
setWhereMeasured(x, where.measured, lat, lon, address, ...)

where_measured(x) <- value

## Default S3 method:
setWhereMeasured(x, where.measured, lat, lon, address, ...)

## S3 method for class 'generic_spct'
setWhereMeasured(x, where.measured = NA, lat = NA, lon = NA, address = NA, ...)

## S3 method for class 'summary_generic_spct'
setWhereMeasured(x, where.measured = NA, lat = NA, lon = NA, address = NA, ...)

## S3 method for class 'generic_mspct'
setWhereMeasured(x, where.measured = NA, lat = NA, lon = NA, address = NA, ...)
```

Arguments

x	a generic_spct object
where.measured, value	A one row data.frame such as returned by function geocode from package 'ggmap' for a location search.
lat	numeric Latitude in decimal degrees North
lon	numeric Longitude in decimal degrees West
address	character Human readable address
...	Allows use of additional arguments in methods for other classes.

Value

x

Methods (by class)

- default: default
- generic_spct: generic_spct
- summary_generic_spct: summary_generic_spct
- generic_mspct: generic_mspct

Note

This method alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct or an object of a class derived from generic_spct, x is not modified. If where is not a POSIXct object or NULL an error is triggered. A POSIXct describes an instant in time (date plus time-of-day plus time zone). As expected passing NULL as argument for where.measured unsets the attribute.

Method for collections of spectra recycles the location information only if it is of length one.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

Examples

```
my.spct <- sun.spct
where_measured(my.spct)
where_measured(my.spct) <- data.frame(lon = 0, lat = -60)
where_measured(my.spct)
```

`shared_member_class` *Classes common to all collection members.*

Description

Finds the set intersection among the class attributes of all collection member as a target set of class names.

Usage

```
shared_member_class(l, target.set = spct_classes())
```

Arguments

`l` a list or a `generic_mspect` object or of a derived class.
`target.set` character The target set of classes within which to search for classes common to all members.

Value

A character vector containing the class attribute values.

See Also

Other set and unset 'multi spectral' class functions: [rmDerivedMspect\(\)](#)

`sign` *Sign*

Description

`sign` returns a vector with the signs of the corresponding elements of `x` (the sign of a real number is 1, 0, or -1 if the number is positive, zero, or negative, respectively).

Usage

```
## S3 method for class 'generic_spct'  
sign(x)
```

Arguments

`x` an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

 slash-.generic_spct *Arithmetic Operators*

Description

Division operator for generic spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 / e2
```

Arguments

e1 an object of class "generic_spct"
 e2 an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [times-.generic_spct](#)

 smooth_spct *Smooth a spectrum*

Description

These functions implement one original methods and acts as a wrapper for other common R smoothing functions. The advantage of using this function for smoothing spectral objects is that it simplifies the user interface and sets, when needed, defaults suitable for spectral data.

Usage

```
smooth_spct(x, method, strength, ...)
```

Default S3 method:
 smooth_spct(x, method, strength, ...)

S3 method for class 'source_spct'
 smooth_spct(x, method = "custom", strength = 1, na.rm = FALSE, ...)

S3 method for class 'filter_spct'
 smooth_spct(x, method = "custom", strength = 1, na.rm = FALSE, ...)

```
## S3 method for class 'reflector_spct'
smooth_spct(x, method = "custom", strength = 1, na.rm = FALSE, ...)

## S3 method for class 'response_spct'
smooth_spct(x, method = "custom", strength = 1, na.rm = FALSE, ...)

## S3 method for class 'generic_mspct'
smooth_spct(x, method = "custom", strength = 1, na.rm = FALSE, ...)
```

Arguments

x	an R object.
method	a character string "custom", "lowess", "supsmu".
strength	numeric value to adjust the degree of smoothing.
...	other parameters passed to the underlying smoothing functions.
na.rm	logical A value indicating whether NA values should be stripped before the computation proceeds.

Value

A copy of x with spectral data values replaced by smoothed ones.

Methods (by class)

- default: Default for generic function
- source_spct: Smooth a source spectrum
- filter_spct: Smooth a filter spectrum
- reflector_spct: Smooth a reflector spectrum
- response_spct: Smooth a response spectrum
- generic_mspct:

Note

Method "custom" is our home-brewed method which applies strong smoothing to low signal regions of the spectral data, and weaker or no smoothing to the high signal areas. Values very close to zero are set to zero with a limit which depends on the local variation. This method is an ad-hock method suitable for smoothing spectral data obtained with spectrometers. In the case of methods "lowess" and "supsmu" the current function behaves like a wrapper of the functions of the same names from base R.

Examples

```
my.spct <- clip_wl(sun.spct, c(400, 500))
smooth_spct(my.spct)
smooth_spct(my.spct, method = "supsmu", strength = 4)
```

solar_time	<i>Local solar time</i>
------------	-------------------------

Description

`solar_time` computes from a time and geocode, the time of day expressed in seconds since midnight. `solar_date` returns the same instant in time as a date-time object. Solar time is useful when we want to plot data according to the local solar time of day, irrespective of the date. Solar date is useful when we want to plot a time series stretching for several days using the local solar time but distinguishing between days.

Usage

```
solar_time(  
  time = lubridate::now(),  
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),  
  unit.out = "time"  
)
```

Arguments

<code>time</code>	POSIXct Time, any valid time zone (TZ) is allowed, default is current time
<code>geocode</code>	data frame with variables <code>lon</code> and <code>lat</code> as numeric values (degrees).
<code>unit.out</code>	character string, One of "datetime", "hour", "minute", or "second".

Value

For `solar_time()` numeric value in seconds from midnight but with an additional class attribute "solar.time".

Warning!

Returned values are computed based on the time zone of the argument for parameter `time`. In the case of solar time, this timezone does not affect the result. However, in the case of solar dates the date part may be off by one day, if the time zone does not match the coordinates of the geocode value provided as argument.

Note

The algorithm is approximate, it calculates the difference between local solar noon and noon in the time zone of `time` and uses this value for the whole day when converting times into solar time. Days are not exactly 24 h long. Between successive days the shift is only a few seconds, and this leads to a small jump at midnight.

See Also

Other astronomy related functions: [day_night\(\)](#), [format.solar_time\(\)](#), [format.tod_time\(\)](#), [is.solar_time\(\)](#), [print.solar_time\(\)](#), [print.tod_time\(\)](#), [sun_angles\(\)](#)

Examples

```

BA.geocode <-
  data.frame(lon = -58.38156, lat = -34.60368, address = "Buenos Aires, Argentina")
sol_t <- solar_time(lubridate::dmy_hms("21/06/2016 10:00:00", tz = "UTC"),
                  BA.geocode)

sol_t
class(sol_t)

sol_d <- solar_time(lubridate::dmy_hms("21/06/2016 10:00:00", tz = "UTC"),
                  BA.geocode,
                  unit.out = "datetime")

sol_d
class(sol_d)

```

source_spct

Spectral-object constructor

Description

These functions can be used to create spectral objects derived from `generic_spct`. They take as arguments numeric vectors for the data character scalars for attributes, and a logical flag.

Usage

```

source_spct(
  w.length = NULL,
  s.e.irrad = NULL,
  s.q.irrad = NULL,
  time.unit = c("second", "day", "exposure"),
  bswf.used = c("none", "unknown"),
  comment = NULL,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL,
  ...
)

calibration_spct(
  w.length = NULL,
  irrad.mult = NA_real_,
  comment = NULL,
  instr.desc = NA,
  multiple.wl = 1L,
  idfactor = NULL,
  ...
)

```

```
raw_spct(  
  w.length = NULL,  
  counts = NA_real_,  
  comment = NULL,  
  instr.desc = NA,  
  instr.settings = NA,  
  multiple.wl = 1L,  
  idfactor = NULL,  
  ...  
)  
  
cps_spct(  
  w.length = NULL,  
  cps = NA_real_,  
  comment = NULL,  
  instr.desc = NA,  
  instr.settings = NA,  
  multiple.wl = 1L,  
  idfactor = NULL,  
  ...  
)  
  
generic_spct(  
  w.length = NULL,  
  comment = NULL,  
  multiple.wl = 1L,  
  idfactor = NULL,  
  ...  
)  
  
response_spct(  
  w.length = NULL,  
  s.e.response = NULL,  
  s.q.response = NULL,  
  time.unit = c("second", "day", "exposure"),  
  comment = NULL,  
  multiple.wl = 1L,  
  idfactor = NULL,  
  ...  
)  
  
filter_spct(  
  w.length = NULL,  
  Tfr = NULL,  
  Tpc = NULL,  
  Afr = NULL,  
  A = NULL,  
  ...  
)
```

```
Tfr.type = c("total", "internal"),
comment = NULL,
strict.range = getOption("photobiology.strict.range", default = FALSE),
multiple.wl = 1L,
idfactor = NULL,
...
)

reflector_spct(
  w.length = NULL,
  Rfr = NULL,
  Rpc = NULL,
  Rfr.type = c("total", "specular"),
  comment = NULL,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL,
  ...
)

object_spct(
  w.length = NULL,
  Rfr = NULL,
  Tfr = NULL,
  Afr = NULL,
  Tfr.type = c("total", "internal"),
  Rfr.type = c("total", "specular"),
  comment = NULL,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL,
  ...
)

chroma_spct(
  w.length = NULL,
  x,
  y,
  z,
  comment = NULL,
  strict.range = getOption("photobiology.strict.range", default = FALSE),
  multiple.wl = 1L,
  idfactor = NULL,
  ...
)
```

Arguments

w.length numeric vector with wavelengths in nanometres

s.e.irrad	numeric vector with spectral energy irradiance in [W m ⁻² nm ⁻¹] or [J d ⁻¹ m ⁻² nm ⁻¹]
s.q.irrad	numeric A vector with spectral photon irradiance in [mol s ⁻¹ m ⁻² nm ⁻¹] or [mol d ⁻¹ m ⁻² nm ⁻¹].
time.unit	character string indicating the time unit used for spectral irradiance or exposure ("second" , "day" or "exposure") or an object of class duration as defined in package lubridate.
bswf.used	character A string indicating the BSWF used, if any, for spectral effective irradiance or exposure ("none" or the name of the BSWF).
comment	character A string to be added as a comment attribute to the object created.
strict.range	logical Flag indicating whether off-range values result in an error instead of a warning.
multiple.wl	numeric Maximum number of repeated w.length entries with same value.
idfactor	character Name of factor distinguishing multiple spectra when stored logarithmically (required if multiple.wl > 1).
...	other arguments passed to tibble()
irrad.mult	numeric vector with multipliers for each detector pixel.
instr.desc	a list
counts	numeric vector with raw counts expressed per scan
instr.settings	a list
cps	numeric vector with linearized raw counts expressed per second
s.e.response	numeric vector with spectral energy irradiance in W m ⁻² nm ⁻¹ or J d ⁻¹ m ⁻² nm ⁻¹
s.q.response	numeric vector with spectral photon irradiance in mol s ⁻¹ m ⁻² nm ⁻¹ or mol d ⁻¹ m ⁻² nm ⁻¹
Tfr	numeric vector with spectral transmittance as fraction of one
Tpc	numeric vector with spectral transmittance as percent values
Afr	numeric vector of absorptance as fraction of one
A	numeric vector of absorbance values (log ₁₀ based a.u.)
Tfr.type	character string indicating whether transmittance and absorptance values are "total" or "internal" values
Rfr	numeric vector with spectral reflectance as fraction of one
Rpc	numeric vector with spectral reflectance as percent values
Rfr.type	character A string, either "total" or "specular".
x, y, z	numeric colour coordinates

Value

A object of class generic_spct or a class derived from it, depending on the function used. In other words an object of a class with the same name as the constructor function.

Note

The functions can be used to add only one spectral quantity to a spectral object. Some of the functions have different arguments, for the same quantity expressed in different units. An actual parameter can be supplied to only one of these formal parameters in a given call to any of these functions.

"internal" transmittance is defined as the transmittance of the material body itself, while "total" transmittance includes the effects of surface reflectance on the amount of light transmitted.

See Also

Other constructors of spectral objects: [as.calibration_spct\(\)](#), [as.chroma_spct\(\)](#), [as.cps_spct\(\)](#), [as.filter_spct\(\)](#), [as.generic_spct\(\)](#), [as.object_spct\(\)](#), [as.raw_spct\(\)](#), [as.reflector_spct\(\)](#), [as.response_spct\(\)](#), [as.source_spct\(\)](#)

spct_attr2tb	<i>Copy attributes into a tibble</i>
--------------	--------------------------------------

Description

Method returning attributes of an object of class `generic_spct` or derived, or of class `waveband`. Only attributes defined and/or set by package 'photobiology' for objects of the corresponding class are returned.

Usage

```
spct_attr2tb(
  x,
  which = c("-", "names", "row.names", "spct.tags", "spct.version", "comment"),
  ...
)
```

Arguments

x	a <code>generic_spct</code> object.
which	character vector Names of attributes to retrieve.
...	currently ignored

Value

A tibble with the values stored in the attributes whose names were selected through the argument to which if present in x.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [trimInstrDesc\(\)](#), [trimInstrSettings\(\)](#)

 spct_classes

Function that returns a vector containing the names of spectra classes.

Description

Function that returns a vector containing the names of spectra classes.

Usage

```
spct_classes()
```

Value

A character vector of class names.

Examples

```
spct_classes()
```

 spikes

Spikes

Description

Function that returns a subset of an R object with observations corresponding to spikes. Spikes are values in spectra that are unusually high compared to neighbors. They are usually individual values or very short runs of similar "unusual" values. Spikes caused by cosmic radiation are a frequent problem in Raman spectra. Another source of spikes are "hot pixels" in CCD and diode arrays.

Usage

```
spikes(x, z.threshold, max.spike.width, na.rm, ...)  
  
## Default S3 method:  
spikes(x, z.threshold = NA, max.spike.width = 8, na.rm = FALSE, ...)  
  
## S3 method for class 'numeric'  
spikes(x, z.threshold = NA, max.spike.width = 8, na.rm = FALSE, ...)  
  
## S3 method for class 'data.frame'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  ...,  
  y.var.name = NULL,  
  var.name = y.var.name  
)  
  
## S3 method for class 'generic_spct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  ...,  
  var.name = NULL  
)  
  
## S3 method for class 'source_spct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...  
)  
  
## S3 method for class 'response_spct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...  
)
```

```
)

## S3 method for class 'filter_spct'
spikes(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  na.rm = FALSE,
  filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  ...
)

## S3 method for class 'reflector_spct'
spikes(x, z.threshold = 9, max.spike.width = 8, na.rm = FALSE, ...)

## S3 method for class 'cps_spct'
spikes(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  na.rm = FALSE,
  ...,
  var.name = "cps"
)

## S3 method for class 'raw_spct'
spikes(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  na.rm = FALSE,
  ...,
  var.name = "counts"
)

## S3 method for class 'generic_mspct'
spikes(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  na.rm = FALSE,
  ...,
  var.name = NULL,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'source_mspct'
```

```
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'response_mspct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'filter_mspct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'reflector_mspct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'cps_mspct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'cps_mspct'  
spikes(  
  x,  
  z.threshold = 9,  
  max.spike.width = 8,  
  na.rm = FALSE,  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)
```

```

x,
z.threshold = 9,
max.spike.width = 8,
na.rm = FALSE,
...,
var.name = "cps",
.parallel = FALSE,
.paropts = NULL
)

## S3 method for class 'raw_mspct'
spikes(
  x,
  z.threshold = 9,
  max.spike.width = 8,
  na.rm = FALSE,
  ...,
  var.name = "counts",
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>x</code>	an R object
<code>z.threshold</code>	numeric Modified Z values larger than <code>z.threshold</code> are considered to correspond to spikes.
<code>max.spike.width</code>	integer Wider regions with high Z values are not detected as spikes.
<code>na.rm</code>	logical indicating whether NA values should be stripped before searching for spikes.
<code>...</code>	ignored
<code>var.name, y.var.name</code>	character Name of column where to look for spikes.
<code>unit.out</code>	character One of "energy" or "photon"
<code>filter.qty</code>	character One of "transmittance" or "absorbance"
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by foreach
<code>.paropts</code>	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A subset of `x` with rows corresponding to spikes.

Methods (by class)

- `default`: Default returning always NA.
- `numeric`: Default function usable on numeric vectors.
- `data.frame`: Method for "data.frame" objects.
- `generic_spct`: Method for "generic_spct" objects.
- `source_spct`: Method for "source_spct" objects.
- `response_spct`: Method for "response_spct" objects.
- `filter_spct`: Method for "filter_spct" objects.
- `reflector_spct`: Method for "reflector_spct" objects.
- `cps_spct`: Method for "cps_spct" objects.
- `raw_spct`: Method for "raw_spct" objects.
- `generic_mspct`: Method for "generic_mspct" objects.
- `source_mspct`: Method for "source_mspct" objects.
- `response_mspct`: Method for "cps_mspct" objects.
- `filter_mspct`: Method for "filter_mspct" objects.
- `reflector_mspct`: Method for "reflector_mspct" objects.
- `cps_mspct`: Method for "cps_mspct" objects.
- `raw_mspct`: Method for "raw_mspct" objects.

See Also

See the documentation for [find_spikes](#) for details of the algorithm and implementation.

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [valleys\(\)](#), [wls_at_target\(\)](#)

Examples

```
spikes(sun.spct)
```

split2mspct

Convert a 'wide' or untidy data frame into a collection of spectra

Description

Convert a data frame object into a "multi spectrum" object by constructing a an object of a multi-spct class, converting numeric columns other than wavelength into individual spct objects.

Usage

```
split2mspct(  
  x,  
  member.class = NULL,  
  spct.data.var = NULL,  
  w.length.var = "w.length",  
  idx.var = NULL,  
  ncol = 1,  
  byrow = FALSE,  
  ...  
)  
  
split2source_mspct(  
  x,  
  spct.data.var = "s.e.irrad",  
  w.length.var = "w.length",  
  idx.var = NULL,  
  ncol = 1,  
  byrow = FALSE,  
  ...  
)  
  
split2response_mspct(  
  x,  
  spct.data.var = "s.e.response",  
  w.length.var = "w.length",  
  idx.var = NULL,  
  ncol = 1,  
  byrow = FALSE,  
  ...  
)  
  
split2filter_mspct(  
  x,  
  spct.data.var = "Tfr",  
  w.length.var = "w.length",  
  idx.var = NULL,  
  ncol = 1,  
  byrow = FALSE,  
  ...  
)  
  
split2reflector_mspct(  
  x,  
  spct.data.var = "Rfr",  
  w.length.var = "w.length",  
  idx.var = NULL,  
  ncol = 1,
```

```

    byrow = FALSE,
    ...
)

split2cps_mspct(
  x,
  spct.data.var = "cps",
  w.length.var = "w.length",
  idx.var = NULL,
  ncol = 1,
  byrow = FALSE,
  ...
)

split2raw_mspct(
  x,
  spct.data.var = "count",
  w.length.var = "w.length",
  idx.var = NULL,
  ncol = 1,
  byrow = FALSE,
  ...
)

split2calibration_mspct(
  x,
  spct.data.var = "irrad.mult",
  w.length.var = "w.length",
  idx.var = NULL,
  ncol = 1,
  byrow = FALSE,
  ...
)

```

Arguments

<code>x</code>	data frame
<code>member.class</code>	character Class of the collection members
<code>spct.data.var</code>	character Name of the spectral data argument in the object constructor for <code>member.class</code>
<code>w.length.var</code>	character Name of column containing wavelength data in nanometres
<code>idx.var</code>	character Name of column containing data to be copied unchanged to each <code>spct</code> object
<code>ncol</code>	integer Number of 'virtual' columns in data
<code>byrow</code>	logical If <code>ncol > 1</code> how to read in the data
<code>...</code>	additional named arguments passed to the member constructor function.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [subset2mspct\(\)](#)

split_bands

*List-of-wavebands constructor***Description**

Build a list of unweighted "waveband" objects that can be used as input when calculating irradiances.

Usage

```
split_bands(
  x,
  list.names = NULL,
  short.names = is.null(list.names),
  length.out = NULL
)
```

Arguments

<code>x</code>	a numeric vector of wavelengths to split at (nm), or a range of wavelengths or a <code>generic_spct</code> or a <code>waveband</code> .
<code>list.names</code>	character vector with names for the component wavebands in the returned list (in order of increasing wavelength)
<code>short.names</code>	logical indicating whether to use short or long names for wavebands
<code>length.out</code>	numeric giving the number of regions to split the range into (ignored if <code>w.length</code> is not numeric).

Value

an un-named list of waveband objects

Note

`list.names` is used to assign names to the elements of the list, while the waveband objects themselves always retain their `wb.label` and `wb.name` as generated during their creation.

See Also

Other waveband constructors: [waveband\(\)](#)

Examples

```

split_bands(c(400,500,600))
split_bands(list(c(400,500),c(550,650)))
split_bands(list(A=c(400,500),B=c(550,650)))
split_bands(c(400,500,600), short.names=FALSE)
split_bands(c(400,500,600), list.names=c("a","b"))
split_bands(c(400,700), length.out=6)
split_bands(400:700, length.out=3)
split_bands(sun.spct, length.out=10)
split_bands(waveband(c(400,700)), length.out=5)

```

split_energy_irradiance

Energy irradiance for split spectrum regions

Description

This function returns the energy irradiance for a series of contiguous wavebands from a radiation-source spectrum. The returned values can be either absolute or relative to their sum.

Usage

```

split_energy_irradiance(
  w.length,
  s.irrad,
  cut.w.length = range(w.length),
  unit.in = "energy",
  scale = "absolute",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)

```

Arguments

w.length	numeric vector of wavelengths (nm).
s.irrad	numeric vector of spectral (energy or photon) irradiance values (W m ⁻² nm ⁻¹) or (mol s ⁻¹ m ⁻² nm ⁻¹).
cut.w.length	numeric vector of wavelengths (nm).
unit.in	character string with allowed values "energy", and "photon", or its alias "quantum".
scale	character string indicating the scale used for the returned values ("absolute", "relative", "percent").
check.spectrum	logical indicating whether to sanity check input data, default is TRUE.

<code>use.cached.mult</code>	logical Flag indicating whether multiplier values should be cached between calls.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

a numeric vector of irradiances with no change in scale factor: [W m⁻² nm⁻¹] -> [W m⁻²] or [mol s⁻¹ m⁻²] -> [W m⁻²] or relative values (fraction of one) if scale = "relative" or scale = "percent".

Note

The last three parameters control speed optimizations. The defaults should be suitable in most cases. If you set `check.spectrum=FALSE` then you should call `check_spectrum` at least once for your spectrum before using any of the other functions. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other low-level functions operating on numeric vectors.: `as_energy()`, `as_quantum_mol()`, `calc_multipliers()`, `div_spectra()`, `energy_irradiance()`, `energy_ratio()`, `insert_hinges()`, `integrate_xy()`, `interpolate_spectrum()`, `irradiance()`, `l_insert_hinges()`, `oper_spectra()`, `photon_irradiance()`, `photon_ratio()`, `photons_energy_ratio()`, `prod_spectra()`, `s_e_irrad2rgb()`, `split_photon_irradiance()`, `subt_spectra()`, `sum_spectra()`, `trim_tails()`, `v_insert_hinges()`, `v_replace_hinges()`

Examples

```
with(sun.data,
     split_energy_irradiance(w.length, s.e.irrad,
                            cut.w.length = c(300, 400, 500, 600, 700)))
```

<code>split_irradiance</code>	<i>Energy or photon irradiance for split spectrum regions</i>
-------------------------------	---

Description

This function returns the energy or photon irradiance for a series of contiguous wavebands from a radiation spectrum. The returned values can be either absolute or relative to their sum.

Usage

```

split_irradiance(
  w.length,
  s.irrad,
  cut.w.length = range(w.length),
  unit.out = getOption("photobiology.base.unit", default = "energy"),
  unit.in = "energy",
  scale = "absolute",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)

```

Arguments

w.length	numeric Vector of wavelengths (nm).
s.irrad	numeric vector of spectral (energy or photon) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$) or ($\text{mol s}^{-1} \text{m}^{-2} \text{nm}^{-1}$).
cut.w.length	numeric Vector of wavelengths (nm).
unit.out	character Allowed values "energy", and "photon", or its alias "quantum".
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
scale	a character A string indicating the scale used for the returned values ("absolute", "relative", "percent").
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

A numeric vector of irradiances with no change in scale factor: $[\text{W m}^{-2} \text{nm}^{-1}] \rightarrow [\text{mol s}^{-1} \text{m}^{-2}]$ or $[\text{mol s}^{-1} \text{m}^{-2} \text{nm}^{-1}] \rightarrow [\text{mol s}^{-1} \text{m}^{-2}]$ or relative values (as fraction of one if scale == "relative" or percentages if scale == "percent").

Note

The last three parameters control speed optimizations. The defaults should be suitable in most cases. If you set `check.spectrum=FALSE` then you should call `check_spectrum` at least once for your spectrum before using any of the other functions. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

Examples

```
with(sun.data,
     split_irradiance(w.length, s.e.irrad,
                      cut.w.length = c(300, 400, 500, 600, 700),
                      unit.out = "photon"))
```

split_photon_irradiance

Photon irradiance for split spectrum regions

Description

This function returns the photon irradiance for a series of contiguous wavebands from a radiation spectrum. The returned values can be either absolute or relative to their sum.

Usage

```
split_photon_irradiance(
  w.length,
  s.irrad,
  cut.w.length = range(w.length),
  unit.in = "energy",
  scale = "absolute",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)
```

Arguments

w.length	numeric vector of wavelengths (nm).
s.irrad	numeric vector of spectral (energy or photon) irradiance values ($\text{W m}^{-2} \text{nm}^{-1}$).
cut.w.length	numeric vector of wavelengths (nm).
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
scale	a character A string indicating the scale used for the returned values ("absolute", "relative", "percent").
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

a numeric vector of photon irradiances with no change in scale factor: [W m⁻² nm⁻¹] -> [mol s⁻¹ m⁻²], [mol s⁻¹ m⁻² nm⁻¹] -> [mol s⁻¹ m⁻²] or relative values (fraction of one based on photon units) if scale = "relative" or scale = "percent".

Note

The last three parameters control speed optimizations. The defaults should be suitable in most cases. If you set `check.spectrum=FALSE` then you should call `check_spectrum` at least once for your spectrum before using any of the other functions. If you will use repeatedly the same SWFs on many spectra measured at exactly the same wavelengths you may obtain some speed up by setting `use.cached.mult=TRUE`. However, be aware that you are responsible for ensuring that the wavelengths are the same in each call, as the only test done is for the length of the `w.length` vector.

See Also

Other low-level functions operating on numeric vectors.: `as_energy()`, `as_quantum_mol()`, `calc_multipliers()`, `div_spectra()`, `energy_irradiance()`, `energy_ratio()`, `insert_hinges()`, `integrate_xy()`, `interpolate_spectrum()`, `irradiance()`, `l_insert_hinges()`, `oper_spectra()`, `photon_irradiance()`, `photon_ratio()`, `photons_energy_ratio()`, `prod_spectra()`, `s_e_irrad2rgb()`, `split_energy_irradiance()`, `subt_spectra()`, `sum_spectra()`, `trim_tails()`, `v_insert_hinges()`, `v_replace_hinges()`

Examples

```
with(sun.data,
     split_photon_irradiance(w.length, s.e.irrad,
                            cut.w.length = c(300, 400, 500, 600, 700)))
with(sun.data,
     split_photon_irradiance(w.length, s.e.irrad))
```

spread

Expanse

Description

A function that returns the expanse ($\max(x) - \min(x)$) for R objects.

Usage

```
spread(x, ...)
```

```
wl_expanse(x, ...)
```

```
expanse(x, ...)
```

```
## Default S3 method:
```

```
expanse(x, ...)  
  
## S3 method for class 'numeric'  
expanse(x, ...)  
  
## S3 method for class 'waveband'  
expanse(x, ...)  
  
## S3 method for class 'generic_spct'  
expanse(x, ...)  
  
## S3 method for class 'generic_mspct'  
expanse(x, ..., idx = "spct.idx")
```

Arguments

x	an R object
...	not used in current version
idx	character Name of the column with the names of the members of the collection of spectra.

Value

A numeric value equal to $\max(x) - \min(x)$. In the case of spectral objects wavelength difference in nm. For any other R object, according to available definitions of [min](#) and [max](#).

Methods (by class)

- default: Default method for generic function
- numeric: Method for "numeric"
- waveband: Method for "waveband"
- generic_spct: Method for "generic_spct"
- generic_mspct: Method for "generic_mspct" objects.

Examples

```
expanse(10:20)  
expanse(sun.spct)  
wl_expanse(sun.spct)  
  
expanse(sun.spct)
```

Subset

Subsetting spectra

Description

Return subsets of spectra stored in class `generic_spct` or derived from it.

Usage

```
## S3 method for class 'generic_spct'  
subset(x, subset, select, drop = FALSE, ...)
```

Arguments

<code>x</code>	object to be subsetted.
<code>subset</code>	logical expression indicating elements or rows to keep: missing values are taken as false.
<code>select</code>	expression, indicating columns to select from a spectrum.
<code>drop</code>	passed on to <code>[]</code> indexing operator.
<code>...</code>	further arguments to be passed to or from other methods.

Value

An object similar to `x` containing just the selected rows and columns. Depending on the columns remaining after subsetting the class of the object will be simplified to the most derived parent class.

Note

This method is copied from `base::subset.data.frame()` but ensures that all metadata stored in attributes of spectral objects are copied to the returned value.

Examples

```
subset(sun.spct, w.length > 400)
```


subset2mspct

*Convert 'long' or tidy spectral data into a collection of spectra***Description**

Convert a data frame object or spectral object into a collection of spectra object of the corresponding class. For data frames converting numeric columns other than wavelength into individual spct objects.

Usage

```
subset2mspct(
  x,
  member.class = NULL,
  idx.var = attr(x, "idfactor"),
  drop.idx = TRUE,
  ncol = 1,
  byrow = FALSE,
  ...
)
```

Arguments

x	a generic_spct object or a derived class, or a data frame
member.class	character string
idx.var	character Name of column containing data to be copied unchanged to each spct object
drop.idx	logical Flag indicating whether to drop or keep idx.var in the collection members.
ncol	integer Number of 'virtual' columns in data
byrow	logical If ncol > 1 how to read in the data
...	additional named arguments passed to the member constructor function.

Value

A collection of spectral objects, each with attributes set if x is a spectral object in long form with metadata attributes. If this object was created by row binding with 'photobiology' 0.9.14 or later then all metadata for each individual spectrum will be preserved, except for comments which are merged.

Note

A non-null value for member.class is mandatory only when x is a data frame.

See Also

Other Coercion methods for collections of spectra: [as.calibration_mspct\(\)](#), [as.chroma_mspct\(\)](#), [as.cps_mspct\(\)](#), [as.filter_mspct\(\)](#), [as.generic_mspct\(\)](#), [as.object_mspct\(\)](#), [as.raw_mspct\(\)](#), [as.reflector_mspct\(\)](#), [as.response_mspct\(\)](#), [as.source_mspct\(\)](#), [split2mspct\(\)](#)

subt_spectra	<i>Subtract two spectra</i>
--------------	-----------------------------

Description

The wavelength vectors of the two spectra are merged, and the missing spectral values are calculated by interpolation. After this, the two spectral values at each wavelength are added. This is 'parallel' operation between two spectra.

Usage

```
subt_spectra(
  w.length1,
  w.length2 = NULL,
  s.irrad1,
  s.irrad2,
  trim = "union",
  na.rm = FALSE
)
```

Arguments

w.length1	numeric vector of wavelength (nm).
w.length2	numeric vector of wavelength (nm).
s.irrad1	a numeric vector of spectral values.
s.irrad2	a numeric vector of spectral values.
trim	a character string with value "union" or "intersection".
na.rm	a logical value, if TRUE, not the default, NAs in the input are replaced with zeros.

Details

If trim=="union" spectral values are calculated for the whole range of wavelengths covered by at least one of the input spectra, and missing values are set in each input spectrum to zero before addition. If trim=="intersection" then the range of wavelengths covered by both input spectra is returned, and the non-overlapping regions discarded. If w.length2==NULL, it is assumed that both spectra are measured at the same wavelengths, and a simple addition is used, ensuring fast calculation.

Value

a data frame with two numeric variables

`w.length` A numeric vector with the wavelengths (nm) obtained by "fusing" `w.length1` and `w.length2`. `w.length` contains all the unique vales, sorted in ascending order.

`s.irrad` A numeric vector with the sum of the two spectral values at each wavelength.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
head(sun.data)
zero.data <- with(sun.data, subt_spectra(w.length, w.length, s.e.irrad, s.e.irrad))
head(zero.data)
tail(zero.data)
```

summary

Summary of a spectral object

Description

Methods of generic function `summary` for objects of spectral classes.

Usage

```
## S3 method for class 'generic_spct'
summary(object, maxsum = 7, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

`object` An object of one of the spectral classes for which a summary is desired

`maxsum` integer Indicates how many levels should be shown for factors.

`digits` integer Used for number formatting with [format\(\)](#).

`...` additional arguments affecting the summary produced, ignored in current version

Value

A summary object matching the class of `object`.

Examples

```
summary(sun.spct)
```

summary_spct_classes	<i>Function that returns a vector containing the names of spectral summary classes.</i>
----------------------	---

Description

Function that returns a vector containing the names of spectral summary classes.

Usage

```
summary_spct_classes()
```

Value

A character vector of class names.

sum_spectra	<i>Add two spectra</i>
-------------	------------------------

Description

Merge wavelength vectors of two spectra are merged, and the missing spectral values are calculated by interpolation. After this, the two spectral values at each wavelength are added. This is a 'parallel' operation between two spectra.

Usage

```
sum_spectra(
  w.length1,
  w.length2 = NULL,
  s.irrad1,
  s.irrad2,
  trim = "union",
  na.rm = FALSE
)
```

Arguments

w.length1	numeric vector of wavelength (nm).
w.length2	numeric vector of wavelength (nm).
s.irrad1	a numeric vector of spectral values.
s.irrad2	a numeric vector of spectral values.
trim	a character string with value "union" or "intersection".
na.rm	a logical value, if TRUE, not the default, NAs in the input are replaced with zeros.

Details

If trim=="union" spectral values are calculated for the whole range of wavelengths covered by at least one of the input spectra, and missing values are set in each input spectrum to zero before addition. If trim=="intersection" then the range of wavelengths covered by both input spectra is returned, and the non-overlapping regions discarded. If w.length2==NULL, it is assumed that both spectra are measured at the same wavelengths, and a simple addition is used, ensuring fast calculation.

Value

a dataframe with two numeric variables

w.length	A numeric vector with the wavelengths (nm) obtained by "fusing" w.length1 and w.length2. w.length contains all the unique vales, sorted in ascending order.
s.irrad	A numeric vector with the sum of the two spectral values at each wavelength.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
head(sun.data)
twice.sun.data <- with(sun.data, sum_spectra(w.length, w.length, s.e.irrad, s.e.irrad))
head(twice.sun.data)
tail(twice.sun.data)
```

`sun.daily.data`*Daily solar spectral irradiance (simulated)*

Description

A dataset containing the wavelengths at a 1 nm interval and the corresponding spectral (energy) irradiance. Values simulated for 2 June 2012, at Helsinki, under clear sky conditions. The variables are as follows:

Usage`sun.daily.data`**Format**

A data.frame object with 511 rows and 3 variables

Details

- w.length (nm), range 290 to 800 nm.
- s.e.irrad (J d-1 m-2 nm-1)
- s.q.irrad (mol d-1 m-2 nm-1)

Author(s)

Anders K. Lindfors (data)

References

Lindfors, A.; Heikkilä, A.; Kaurola, J.; Koskela, T. & Lakkala, K. (2009) Reconstruction of Solar Spectral Surface UV Irradiances Using Radiative Transfer Simulations. *Photochemistry and Photobiology*, 85: 1233-1239

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples`sun.daily.spct`

sun.daily.spct	<i>Daily solar spectral irradiance (simulated)</i>
----------------	--

Description

A dataset containing the wavelengths at a 1 nm interval and the corresponding spectral (energy) irradiance. Values simulated for 2 June 2012, at Helsinki, under clear sky conditions. The variables are as follows:

Usage

```
sun.daily.spct
```

Format

A source_spct object with 511 rows and 3 variables

Details

- w.length (nm), range 290 to 800 nm.
- s.e.irrad (J d-1 m-2 nm-1)
- s.q.irrad (mol d-1 m-2 nm-1)

Note

The simulations are based on libRadTran using hourly mean global radiation measurements to estimate cloud cover. The simulations were for each hour and the results integrated for the whole day.

Author(s)

Anders K. Lindfors (data)

References

Lindfors, A.; Heikkilä, A.; Kaurola, J.; Koskela, T. & Lakkala, K. (2009) Reconstruction of Solar Spectral Surface UV Irradiances Using Radiative Transfer Simulations. *Photochemistry and Photobiology*, 85: 1233-1239

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

sun.daily.spct

sun.data

Solar spectral irradiance (simulated)

Description

A dataset containing the wavelengths at a 1 nm interval and the corresponding spectral (energy) irradiance and spectral photon irradiance. Values simulated for 22 June 2010, near midday, at Helsinki, under partly cloudy conditions. The variables are as follows:

Usage

sun.data

Format

A data.frame object with 508 rows and 3 variables

Details

- w.length (nm), range 293 to 800 nm.
- s.e.irrad (W m⁻² nm⁻¹)
- s.q.irrad (mol m⁻² nm⁻¹)

Author(s)

Anders K. Lindfors (data)

References

Lindfors, A.; Heikkilä, A.; Kaurola, J.; Koskela, T. & Lakkala, K. (2009) Reconstruction of Solar Spectral Surface UV Irradiances Using Radiative Transfer Simulations. *Photochemistry and Photobiology*, 85: 1233-1239

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.spct](#), [white_body.spct](#), [white_led.cps.spct](#), [white_led.raw.spct](#), [white_led.source.spct](#), [yellow_gel.spct](#)

Examples

sun.data

sun.spct	<i>Solar spectral irradiance (simulated)</i>
----------	--

Description

A dataset containing the wavelengths at a 1 nm interval and the corresponding spectral (energy) irradiance and spectral photon irradiance. Values simulated for 22 June 2010, near midday, at Helsinki, under partly cloudy conditions. The variables are as follows:

Usage

```
sun.spct
```

Format

A source_spct object with 508 rows and 3 variables

Details

- w.length (nm), range 293 to 800 nm.
- s.e.irrad (W m⁻² nm⁻¹)
- s.q.irrad (mol m⁻² nm⁻¹)

Author(s)

Anders K. Lindfors (data)

References

Lindfors, A.; Heikkilä, A.; Kaurola, J.; Koskela, T. & Lakkala, K. (2009) Reconstruction of Solar Spectral Surface UV Irradiances Using Radiative Transfer Simulations. *Photochemistry and Photobiology*, 85: 1233-1239

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspect](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
sun.spct
```

`sun_angles`*Solar angles*

Description

This function returns the solar angles at a given time and location.

Usage

```
sun_angles(  
  time = lubridate::now(tzone = "UTC"),  
  tz = lubridate::tz(time),  
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),  
  use.refraction = FALSE  
)
```

```
sun_angles_fast(time, tz, geocode, use.refraction)
```

```
sun_elevation(  
  time = lubridate::now(),  
  tz = lubridate::tz(time),  
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),  
  use.refraction = FALSE  
)
```

```
sun_zenith_angle(  
  time = lubridate::now(),  
  tz = lubridate::tz(time),  
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),  
  use.refraction = FALSE  
)
```

```
sun_azimuth(  
  time = lubridate::now(),  
  tz = lubridate::tz(time),  
  geocode = tibble::tibble(lon = 0, lat = 51.5, address = "Greenwich"),  
  use.refraction = FALSE  
)
```

Arguments

<code>time</code>	A "vector" of POSIXct Time, with any valid time zone (TZ) is allowed, default is current time.
<code>tz</code>	character string indicating time zone to be used in output.
<code>geocode</code>	data frame with variables <code>lon</code> and <code>lat</code> as numeric values (degrees), <code>nrow > 1</code> , allowed.
<code>use.refraction</code>	logical Flag indicating whether to correct for fraction in the atmosphere.

Details

This function is an implementation of Meeus equations as used in NOAAs on-line web calculator, which are precise and valid for a very broad range of dates (years -1000 to 3000 at least). The apparent solar elevations near sunrise and sunset are affected by refraction in the atmosphere, which does in turn depend on weather conditions. The effect of refraction on the apparent position of the sun is only an estimate based on "typical" conditions for the atmosphere. The computation is not defined for latitudes 90 and -90 degrees, i.e. exactly at the poles.

In the current implementation functions `sun_azimuth`, `sun_elevation`, and `sun_zenith_angle` are wrappers on `sun_angles`, so if more than one angle is needed it is preferable to directly call `sun_angles` as it will be faster.

Value

A data.frame with variables `time` (in same TZ as input), `TZ`, `solartime`, `longitude`, `latitude`, `address`, `azimuth`, and `elevation`. If a data frame with multiple rows is passed to `geocode` and a vector of times longer than one is passed to `time`, sun position for all combinations of locations and times are returned are returned by `sun_angles`. In contrast, convenience functions returning a vector.

Note

There exists a different R implementation of the same algorithms called "AstroCalcPureR" available as function `astrocalc4r` in package 'fishmethods'. Although the equations used are almost all the same, the function signatures and which values are returned differ. In particular, the present implementation splits the calculation into two separate functions, one returning angles at given instants in time, and a separate one returning the timing of events for given dates.

References

The primary source for the algorithm used is the book: Meeus, J. (1998) *Astronomical Algorithms*, 2 ed., Willmann-Bell, Richmond, VA, USA. ISBN 978-0943396613.

A different implementation is available at <https://www.nefsc.noaa.gov/AstroCalc4R/> and in R package `astrocalc4r`. In 'fishmethods' (= 1.11-0) there is a bug in function `astrocalc4r()` that affects sunrise and sunset times.

An interactive web page using the same algorithms is available at <https://www.esrl.noaa.gov/gmd/grad/solcalc/>. There are small differences in the returned times compared to our function that seem to be related to the estimation of atmospheric refraction (about 0.1 degrees).

See Also

Other astronomy related functions: `day_night()`, `format.solar_time()`, `format.tod_time()`, `is.solar_time()`, `print.solar_time()`, `print.tod_time()`, `solar_time()`

Examples

```
library(lubridate)
sun_angles()
sun_azimuth()
sun_elevation()
```

```

sun_zenith_angle()
sun_angles(ymd_hms("2014-09-23 12:00:00"))
sun_angles(ymd_hms("2014-09-23 12:00:00"),
           geocode = data.frame(lat=60, lon=0))
sun_angles(ymd_hms("2014-09-23 12:00:00") + minutes((0:6) * 10))

```

s_e_irrad2rgb

Spectral irradiance to rgb color conversion

Description

Calculates rgb values from spectra based on human color matching functions (CMF) or chromaticity coordinates (CC). A CMF takes into account luminous sensitivity, while a CC only the color hue. This function, in contrast to that in package pavo does not normalize the values to equal luminosity, so using a CMF as input gives the expected result. Another difference is that it allows the user to choose the chromaticity data to be used. The data used by default is different, and it corresponds to the whole range of CIE standard, rather than the reduced range 400 nm to 700 nm. The wavelength limits are not hard coded, so the function could be used to simulate vision in other organisms as long as pseudo CMF or CC data are available for the simulation.

Usage

```

s_e_irrad2rgb(
  w.length,
  s.e.irrad,
  sens = photobiology::ciexyzCMF2.spct,
  color.name = NULL,
  check = TRUE
)

```

Arguments

w.length	numeric vector of wavelengths (nm).
s.e.irrad	numeric vector of spectral irradiance values.
sens	a chroma_spct object with variables w.length, x, y, and z, giving the CC or CMF definition (default is the proposed human CMF according to CIE 2006.).
color.name	character string for naming the rgb color definition.
check	logical indicating whether to check or not spectral data.

Value

A color defined using [rgb](#). The numeric values of the RGB components can be obtained using function [col2rgb](#).

Note

Very heavily modified from Chad Eliason's <cme16@zips.uakron.edu> spec2rgb function in package Pavo.

References

CIE(1932). Commission Internationale de l'Eclairage Proceedings, 1931. Cambridge: Cambridge University Press.

Color matching functions obtained from Colour and Vision Research Laboratory online data repository at <http://www.cvr1.org/>.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
my.color <-
  with(sun.data,
       s_e_irrad2rgb(w.length, s.e.irrad, color.name = "sunWhite"))
col2rgb(my.color)
```

s_mean

Mean from collection of spectra

Description

A method to compute the mean of values across members of a collections of spectra. Computes the mean at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_mean(x, trim, na.rm, ...)

## Default S3 method:
s_mean(x, trim = 0, na.rm = FALSE, ...)

## S3 method for class 'source_mspct'
s_mean(x, trim = 0, na.rm = FALSE, ...)

## S3 method for class 'response_mspct'
```

```
s_mean(x, trim = 0, na.rm = FALSE, ...)  
  
## S3 method for class 'filter_mspct'  
s_mean(x, trim = 0, na.rm = FALSE, ...)  
  
## S3 method for class 'reflector_mspct'  
s_mean(x, trim = 0, na.rm = FALSE, ...)  
  
## S3 method for class 'calibration_mspct'  
s_mean(x, trim = 0, na.rm = FALSE, ...)
```

Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
trim	numeric. The fraction (0 to 0.5) of observations to be trimmed from each end of x before the mean is computed. Values of trim outside that range are taken as the nearest endpoint.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

If x is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spect", containing the mean spectrum.

Methods (by class)

- default:
- source_mspct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Trimming of extreme values and omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in x must share the same set of wavelengths.

See Also

See [mean](#) for the mean() method used for the computations.

`s_mean_se`*Mean and standard error from collection of spectra*

Description

A method to compute the mean of values across members of a collections of spectra. Computes the mean at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_mean_se(x, na.rm, mult, ...)  
  
## Default S3 method:  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)  
  
## S3 method for class 'filter_mspct'  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)  
  
## S3 method for class 'source_mspct'  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)  
  
## S3 method for class 'response_mspct'  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)  
  
## S3 method for class 'reflector_mspct'  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)  
  
## S3 method for class 'calibration_mspct'  
s_mean_se(x, na.rm = FALSE, mult = 1, ...)
```

Arguments

<code>x</code>	An R object. Currently this package defines methods for collections of spectral objects.
<code>na.rm</code>	logical. A value indicating whether NA values should be stripped before the computation proceeds.
<code>mult</code>	numeric number of multiples of standard error
<code>...</code>	Further arguments passed to or from other methods.

Value

If `x` is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spct", containing the mean spectrum.

Methods (by class)

- default:
- filter_mspct:
- source_mspct:
- response_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Trimming of extreme values and omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in `x` must share the same set of wavelengths.

See Also

See [mean](#) for the `mean()` method used for the computations.

`s_median`*Median of a collection of spectra*

Description

A method to compute the median of values across members of a collections of spectra. Computes the median at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_median(x, na.rm, ...)  
  
## Default S3 method:  
s_median(x, na.rm = FALSE, ...)  
  
## S3 method for class 'source_mspct'  
s_median(x, na.rm = FALSE, ...)  
  
## S3 method for class 'response_mspct'  
s_median(x, na.rm = FALSE, ...)  
  
## S3 method for class 'filter_mspct'  
s_median(x, na.rm = FALSE, ...)  
  
## S3 method for class 'reflector_mspct'  
s_median(x, na.rm = FALSE, ...)  
  
## S3 method for class 'calibration_mspct'  
s_median(x, na.rm = FALSE, ...)
```


Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

If x is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spect", containing the median spectrum.

Methods (by class)

- default:
- source_mspct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in x must share the same set of wavelengths.

See Also

See [median](#) for the median() method used for the computations.

s_prod

Product from collection of spectra

Description

A method to compute the product of values across members of a collections of spectra. Computes the product at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_prod(x, na.rm, ...)
```

```
## Default S3 method:
s_prod(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'source_mspct'
s_prod(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'response_mspct'
s_prod(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'filter_mspct'
s_prod(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'reflector_mspct'
s_prod(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'calibration_mspct'
s_prod(x, na.rm = FALSE, ...)
```

Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

If *x* is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spect", containing the product of the spectra.

Methods (by class)

- default:
- source_mspct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in *x* must share the same set of wavelengths.

A product of spectral irradiance or spectral response is no longer a well defined physical quantity, and these product operations return an object of class `generic_spct`.

See Also

See [prod](#) for the `prod()` method used for the computations.

<code>s_range</code>	<i>Range of a collection of spectra</i>
----------------------	---

Description

A method to compute the range of values across members of a collection of spectra. Computes the max and min at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_range(x, na.rm, ...)
```

```
## Default S3 method:
s_range(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'filter_mspct'
s_range(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'source_mspct'
s_range(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'response_mspct'
s_range(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'reflector_mspct'
s_range(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'calibration_mspct'
s_range(x, na.rm = FALSE, ...)
```

Arguments

<code>x</code>	An R object. Currently this package defines methods for collections of spectral objects.
<code>na.rm</code>	logical. A value indicating whether NA values should be stripped before the computation proceeds.
<code>...</code>	Further arguments passed to or from other methods.

Value

If `x` is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spect", containing the mean spectrum.

Methods (by class)

- default:
- filter_mspct:
- source_mspct:
- response_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Trimming of extreme values and omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in `x` must share the same set of wavelengths.

See Also

See [Extremes](#) details on the `min()` and `max()` methods used for the computations.

s_sd

Standard Deviation of a collection of spectra

Description

A method to compute the standard deviation of values across members of a collections of spectra. Computes the standard deviation at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_sd(x, na.rm, ...)
```

```
## Default S3 method:
s_sd(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'filter_mspct'
s_sd(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'source_mspct'
s_sd(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'response_mspct'
```

```
s_sd(x, na.rm = FALSE, ...)

## S3 method for class 'reflector_mspct'
s_sd(x, na.rm = FALSE, ...)
```

Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

If *x* is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of class "generic_spect", containing the standard deviation among the spectra at each wavelength in a column with name ending in ".sd".

Methods (by class)

- default:
- filter_mspct:
- source_mspct:
- response_mspct:
- reflector_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in *x* must share the same set of wavelengths.

See Also

See [sd](#) for details about `sd()` methods for other classes.

s_se

Standard Error of a collection of spectra

Description

A method to compute the standard error of values across members of a collections of spectra. Computes the standard error at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_se(x, na.rm, ...)  
  
## Default S3 method:  
s_se(x, na.rm = FALSE, ...)  
  
## S3 method for class 'source_mspct'  
s_se(x, na.rm = FALSE, ...)  
  
## S3 method for class 'response_mspct'  
s_se(x, na.rm = FALSE, ...)  
  
## S3 method for class 'filter_mspct'  
s_se(x, na.rm = FALSE, ...)  
  
## S3 method for class 'reflector_mspct'  
s_se(x, na.rm = FALSE, ...)  
  
## S3 method for class 'calibration_mspct'  
s_se(x, na.rm = FALSE, ...)
```

Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Value

If x is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of class "generic_spect", containing the standard error among the spectra at each wavelength in a column with name ending in ".se".

Methods (by class)

- default:
- source_mspct:
- response_mspct:
- filter_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in `x` must share the same set of wavelengths.

s_sum	<i>Sum from collection of spectra</i>
-------	---------------------------------------

Description

A method to compute the sum of values across members of a collections of spectra. Computes the sum at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_sum(x, na.rm, ...)
```

Default S3 method:
s_sum(x, na.rm = FALSE, ...)

S3 method for class 'filter_mspct'
s_sum(x, na.rm = FALSE, ...)

S3 method for class 'source_mspct'
s_sum(x, na.rm = FALSE, ...)

S3 method for class 'response_mspct'
s_sum(x, na.rm = FALSE, ...)

S3 method for class 'reflector_mspct'
s_sum(x, na.rm = FALSE, ...)

S3 method for class 'calibration_mspct'
s_sum(x, na.rm = FALSE, ...)

Arguments

<code>x</code>	An R object. Currently this package defines methods for collections of spectral objects.
<code>na.rm</code>	logical. A value indicating whether NA values should be stripped before the computation proceeds.
<code>...</code>	Further arguments passed to or from other methods.

Value

If `x` is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of same class as the members of the collection, such as "filter_spect", containing the sum of the spectra.

Methods (by class)

- default:
- filter_mspct:
- source_mspct:
- response_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in `x` must share the same set of wavelengths.

A sum of transmittances or reflectances is no longer a well defined physical quantity, and these sum operations return an object of class `generic_spct`.

See Also

See [sum](#) for the `sum()` method used for the computations.

s_var

Variance of a collection of spectra

Description

A method to compute the variance of values across members of a collection of spectra. Computes the variance at each wavelength across all the spectra in the collection returning a spectral object.

Usage

```
s_var(x, na.rm, ...)
```

```
## Default S3 method:
s_var(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'filter_mspct'
s_var(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'source_mspct'
s_var(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'response_mspct'
s_var(x, na.rm = FALSE, ...)
```

```
## S3 method for class 'reflector_mspct'
s_var(x, na.rm = FALSE, ...)
```



```
## S3 method for class 'calibration_mspct'  
s_var(x, na.rm = FALSE, ...)
```

Arguments

x	An R object. Currently this package defines methods for collections of spectral objects.
na.rm	logical. A value indicating whether NA values should be stripped before the computation proceeds.
...	Further arguments passed to or from other methods.

Details

Variance method for collections of spectra. Computes the variance at each wavelength across all the spectra in the collection.

Value

If x is a collection spectral of objects, such as a "filter_mspct" object, the returned object is of class "generic_spect", containing the variance among the spectra at each wavelength in a column with name ending in ".var".

Methods (by class)

- default:
- filter_mspct:
- source_mspct:
- response_mspct:
- reflector_mspct:
- calibration_mspct:

Note

Omission of NAs is done separately at each wavelength. Interpolation is not applied, so all spectra in x must share the same set of wavelengths.

See Also

See [cor](#) for details about `var()`, which is used for the computations.

T2A

*Convert transmittance into absorbance.***Description**

Function that converts transmittance (fraction) into absorbance (a.u.).

Usage

```
T2A(x, action, byref, clean, ...)

## Default S3 method:
T2A(x, action = NULL, byref = FALSE, ...)

## S3 method for class 'numeric'
T2A(x, action = NULL, byref = FALSE, clean = TRUE, ...)

## S3 method for class 'filter_spct'
T2A(x, action = "add", byref = FALSE, clean = TRUE, ...)

## S3 method for class 'filter_mspct'
T2A(
  x,
  action = "add",
  byref = FALSE,
  clean = TRUE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)
```

Arguments

<code>x</code>	an R object
<code>action</code>	character Allowed values "replace" and "add"
<code>byref</code>	logical indicating if new object will be created by reference or by copy of <code>x</code>
<code>clean</code>	logical replace off-boundary values before conversion
<code>...</code>	not used in current version
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of x with a column A added and other columns possibly deleted except for $w.length$. If $action = "replace"$, in all cases, the additional columns are removed, even if no column needs to be added.

Methods (by class)

- `default`: Default method for generic function
- `numeric`: Method for numeric vectors
- `filter_spct`: Method for filter spectra
- `filter_mspct`: Method for collections of filter spectra

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2Afr\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

T2Afr	<i>Convert transmittance into absorptance.</i>
-------	--

Description

Function that converts transmittance (fraction) into absorptance (fraction). If reflectance (fraction) is available, it allows conversions between internal and total absorptance.

Usage

```
T2Afr(x, action, byref, clean, ...)

## Default S3 method:
T2Afr(x, action = NULL, byref = FALSE, clean = FALSE, ...)

## S3 method for class 'numeric'
T2Afr(x, action = NULL, byref = FALSE, clean = FALSE, Rfr = NA_real_, ...)

## S3 method for class 'filter_spct'
T2Afr(x, action = "add", byref = FALSE, clean = FALSE, ...)

## S3 method for class 'object_spct'
T2Afr(x, action = "add", byref = FALSE, clean = FALSE, ...)

## S3 method for class 'filter_mspct'
T2Afr(
  x,
  action = "add",
  byref = FALSE,
```

```

    clean = FALSE,
    ...,
    .parallel = FALSE,
    .paropts = NULL
)

## S3 method for class 'object_mspct'
T2Afr(
  x,
  action = "add",
  byref = FALSE,
  clean = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

x	an R object
action	character Allowed values "replace" and "add"
byref	logical indicating if new object will be created by reference or by copy of x
clean	logical replace off-boundary values before conversion
...	not used in current version
Rfr	numeric vector. Spectral reflectance o reflectance factor. Set to zero if x is internal reflectance,
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of x with a column Afr added and other columns possibly deleted except for w.length. If action = "replace", in all cases, the additional columns are removed, even if no column needs to be added.

Methods (by class)

- default: Default method for generic function
- numeric: Default method for generic function
- filter_spct: Method for filter spectra
- object_spct: Method for object spectra
- filter_mspct: Method for collections of filter spectra
- object_mspct: Method for collections of object spectra

See Also

Other quantity conversion functions: [A2T\(\)](#), [Afr2T\(\)](#), [T2A\(\)](#), [any2T\(\)](#), [as_quantum\(\)](#), [e2qmol_multipliers\(\)](#), [e2quantum_multipliers\(\)](#), [e2q\(\)](#), [q2e\(\)](#)

Examples

```
T2Afr(Ler_leaf.spct)
```

tag	<i>Tag a spectrum</i>
-----	-----------------------

Description

Spectra are tagged by adding variables and attributes containing color definitions, labels, and a factor following the wavebands given in `w.band`. This methods are most useful for plotting realistic computed colors from spectral data.

Usage

```
tag(x, ...)

## Default S3 method:
tag(x, ...)

## S3 method for class 'generic_spct'
tag(
  x,
  w.band = NULL,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = TRUE,
  short.names = TRUE,
  chroma.type = "CMF",
  byref = FALSE,
  ...
)

## S3 method for class 'generic_mspct'
tag(
  x,
  w.band = NULL,
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = TRUE,
  short.names = TRUE,
  chroma.type = "CMF",
  byref = FALSE,
  ...,
)
```

```

    .parallel = FALSE,
    .paropts = NULL
  )

```

Arguments

<code>x</code>	an R object.
<code>...</code>	ignored (possibly used by derived methods).
<code>w.band</code>	waveband or list of waveband objects. The waveband(s) determine the region(s) of the spectrum that are tagged
<code>wb.trim</code>	logical Flag telling if wavebands crossing spectral data boundaries are trimmed or ignored
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>short.names</code>	logical Flag indicating whether to use short or long names for wavebands
<code>chroma.type</code>	character telling whether "CMF", "CC", or "both" should be returned for human vision, or an object of class <code>chroma_spct</code> for any other trichromatic visual system.
<code>byref</code>	logical Flag indicating if new object will be created <i>by reference</i> or <i>by copy</i> of <code>x</code>
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A copy of `x` expanded with additional columns with color-related information.

Methods (by class)

- `default`: Default method for generic
- `generic_spct`: Tag one of `generic_spct`, and derived classes including `source_spct`, `filter_spct`, `reflector_spct`, `object_spct`, and `response_spct`.
- `generic_mspct`: Tag one of `generic_mspct`, and derived classes including `source_mspct`, `filter_mspct`, `reflector_mspct`, `object_mspct`, and `response_mspct`.

Note

NULL as `w.band` argument does not add any new tags, instead it removes existing tags if present. NA, the default, as `w.band` argument removes existing waveband tags if present and sets the `wl.color` variable. If a waveband object or a list of wavebands is supplied as argument then tagging is based on them, and `wl.color` is also set.

See Also

Other tagging and related functions: `is_tagged()`, `untag()`, `wb2rect_spct()`, `wb2spct()`, `wb2tagged_spct()`

Examples

```
tag(sun.spct)
tag(sun.spct, list(A = waveband(c(300,3005))))
```

thin_wl	<i>Thin the density of wavelength values</i>
---------	--

Description

Increase the wavelength step in stored spectral data in featureless regions to save storage space.

Usage

```
thin_wl(x, ...)

## Default S3 method:
thin_wl(x, ...)

## S3 method for class 'generic_spct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, col.names, ...)

## S3 method for class 'source_spct'
thin_wl(
  x,
  max.wl.step = 10,
  max.slope.delta = 0.001,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'response_spct'
thin_wl(
  x,
  max.wl.step = 10,
  max.slope.delta = 0.001,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'filter_spct'
thin_wl(
  x,
  max.wl.step = 10,
  max.slope.delta = 0.001,
  qty.out = getOption("photobiology.filter.qty", default = "transmittance"),
```

```

    ...
  )

## S3 method for class 'reflector_spct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, ...)

## S3 method for class 'raw_spct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, col.names, ...)

## S3 method for class 'cps_spct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, col.names, ...)

## S3 method for class 'object_spct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, col.names, ...)

## S3 method for class 'chroma_spct'
thin_wl(x, ...)

## S3 method for class 'calibration_spct'
thin_wl(x, ...)

## S3 method for class 'generic_mspct'
thin_wl(x, max.wl.step = 10, max.slope.delta = 0.001, ...)

## S3 method for class 'chroma_mspct'
thin_wl(x, ...)

## S3 method for class 'calibration_mspct'
thin_wl(x, ...)

```

Arguments

<code>x</code>	An R object
<code>...</code>	additional named arguments passed down to <code>f</code> .
<code>max.wl.step</code>	numeric. Largest allowed wavelength difference between adjacent spectral values in nanometres (nm).
<code>max.slope.delta</code>	numeric in 0 to 1. Largest allowed change in relative slope of the spectral quantity per nm between adjacent pairs of values.
<code>col.names</code>	character. Name of the column of <code>x</code> containing the spectral data to check against <code>max.slope.delta</code> . Currently only one column supported.
<code>unit.out</code>	character Allowed values "energy", and "photon", or its alias "quantum".
<code>qty.out</code>	character Allowed values "transmittance", and "absorbance".

Details

The algorithm used for spectra is "naive" in an effort to keep it efficient. It works by iteratively attempting to delete every other observation along wavelengths, based on the criteria for maximum

wavelength step and maximum relative step in the spectral variable between adjacent data values.

Value

An object of the same class as `x` but with a reduced density of wavelength values in those regions where slope is shallow and featureless.

Methods (by class)

- `default`: Default for generic function
- `generic_spct`:
- `source_spct`:
- `response_spct`:
- `filter_spct`:
- `reflector_spct`:
- `raw_spct`:
- `cps_spct`:
- `object_spct`:
- `chroma_spct`:
- `calibration_spct`:
- `generic_mspct`:
- `chroma_mspct`:
- `calibration_mspct`:

Note

The value of `max.slope.delta` is expressed as relative change in the slope of spectral variable per nanometre. This means that values between 0.0005 and 0.005 tend to work reasonably well. The best value will depend on the wavelength step of the input and noise in data. A moderate smoothing before thinning can sometimes help in the case of noisy data. The amount of thinning is almost always less than the value of `criteria` passed as argument as it is based on existing wavelength values. For example if we start with a spectrum with a uniform wavelength step of 1 nm, possible steps in the thinned spectrum are 2, 4, 8, 16, 32, etc. nm. The algorithm, does work with any step sizes, regular or variable in the input. Thinning is most effective for spectra with large "featureless" regions as the algorithm attempts not to discard information, contrary to smoothing or interpolation.

See Also

Other experimental utility functions: [uncollect\(\)](#)

Examples

```
nrow(yellow_gel.spct)
wl_stepsize(yellow_gel.spct)
thinned.spct <- thin_wl(yellow_gel.spct)
nrow(thinned.spct)
wl_stepsize(thinned.spct)
```

times-.generic_spct *Arithmetic Operators*

Description

Multiplication operator for spectra.

Usage

```
## S3 method for class 'generic_spct'
e1 * e2
```

Arguments

e1 an object of class "generic_spct"
e2 an object of class "generic_spct"

See Also

Other math operators and functions: [MathFun](#), [^.generic_spct\(\)](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#)

transmittance *Transmittance*

Description

Summary transmittance for supplied wavebands from filter or object spectrum.

Usage

```
transmittance(spct, w.band, quantity, wb.trim, use.hinges, ...)

## Default S3 method:
transmittance(spct, w.band, quantity, wb.trim, use.hinges, ...)

## S3 method for class 'filter_spct'
transmittance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)

## S3 method for class 'object_spct'
transmittance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = NULL,
  naming = "default",
  ...
)

## S3 method for class 'filter_mspct'
transmittance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
  naming = "default",
  ...,
  attr2tb = NULL,
  idx = "spct.idx"
)

## S3 method for class 'object_mspct'
transmittance(
  spct,
  w.band = NULL,
  quantity = "average",
  wb.trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = getOption("photobiology.use.hinges", default = NULL),
```

```

    naming = "default",
    ...,
    attr2tb = NULL,
    idx = "spct.idx",
    .parallel = FALSE,
    .paropts = NULL
  )

```

Arguments

<code>spct</code>	an R object.
<code>w.band</code>	waveband or list of waveband objects or a numeric vector of length two. The waveband(s) determine the region(s) of the spectrum that are summarized. If a numeric range is supplied a waveband object is constructed on the fly from it.
<code>quantity</code>	character string One of "total", "average" or "mean", "contribution", "contribution.pc", "relative" or "relative.pc".
<code>wb.trim</code>	logical Flag indicating if wavebands crossing spectral data boundaries are trimmed or ignored.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>...</code>	ignored (possibly used by derived methods).
<code>naming</code>	character one of "long", "default", "short" or "none". Used to select the type of names to assign to returned value.
<code>attr2tb</code>	character vector, see add_attr2tb for the syntax for <code>attr2tb</code> passed as is to formal parameter <code>col.names</code> .
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A named numeric vector in the case of methods for individual spectra, with one value for each waveband passed to parameter `w.band`. A data.frame in the case of collections of spectra, containing one column for each waveband object, an index column with the names of the spectra, and optionally additional columns with metadata values retrieved from the attributes of the member spectra.

By default values are only integrated, but depending on the argument passed to parameter `quantity` they can be re-expressed as relative fractions or percentages. In the case of vector output, names attribute is set to the name of the corresponding waveband unless a named list is supplied in which case the names of the list members are used.

Methods (by class)

- default: Default method
- filter_spct: Method for filter spectra
- object_spct: Method for object spectra
- filter_mspct: Calculates transmittance from a filter_mspct
- object_mspct: Calculates transmittance from a object_mspct

Note

The use.hinges parameter controls speed optimization. The defaults should be suitable in most cases. Only the range of wavelengths in the wavebands is used and all BSWFs are ignored.

Examples

```
transmittance(polyester.spct, waveband(c(280, 315)))
transmittance(polyester.spct, waveband(c(315, 400)))
transmittance(polyester.spct, waveband(c(400, 700)))
```

Trig

Trigonometric Functions

Description

Trigonometric functions for object of generic_spct and derived classes. \ The functions are applied to the spectral data, not the wavelengths. The quantity in the spectrum to which the function is applied depends on the class of x and the current value of output options.

Usage

```
## S3 method for class 'generic_spct'
cos(x)

## S3 method for class 'generic_spct'
sin(x)

## S3 method for class 'generic_spct'
tan(x)

## S3 method for class 'generic_spct'
acos(x)

## S3 method for class 'generic_spct'
asin(x)

## S3 method for class 'generic_spct'
atan(x)
```

Arguments

x an object of class "generic_spct" or a derived class.

trimInstrDesc	<i>Trim the "instr.desc" attribute</i>
---------------	--

Description

Function to trim the "instr.desc" attribute of an existing generic_spct object, discarding all fields except for 'spectrometer.name', 'spectrometer.sn', 'bench.grating', 'bench.slit', and calibration name.

Usage

```
trimInstrDesc(
  x,
  fields = c("time", "spectrometer.name", "spectrometer.sn", "bench.grating",
            "bench.slit")
)
```

Arguments

x a generic_spct object

fields a character vector with the names of the fields to keep, or if first member is "-.", the names of fields to delete; "*" as first member of the vector makes the function a no-op, leaving the spectrum object unaltered.

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrSettings\(\)](#)

trimInstrSettings	<i>Trim the "instr.settings" attribute</i>
-------------------	--

Description

Function to trim the "instr.settings" attribute of an existing generic_spct object, by discarding some fields.

Usage

```
trimInstrSettings(x, fields = "*")
```

Arguments

x	a generic_spct object
fields	a character vector with the names of the fields to keep, or if first member is "-", the names of fields to delete; "*" as first member of the vector makes the function a no-op, leaving the spectrum object unaltered.

Value

x

Note

This function alters x itself by reference and in addition returns x invisibly. If x is not a generic_spct object, x is not modified.

See Also

Other measurement metadata functions: [getFilterProperties\(\)](#), [getHowMeasured\(\)](#), [getInstrDesc\(\)](#), [getInstrSettings\(\)](#), [getWhatMeasured\(\)](#), [getWhenMeasured\(\)](#), [getWhereMeasured\(\)](#), [get_attributes\(\)](#), [isValidInstrDesc\(\)](#), [isValidInstrSettings\(\)](#), [select_spct_attributes\(\)](#), [setFilterProperties\(\)](#), [setHowMeasured\(\)](#), [setInstrDesc\(\)](#), [setInstrSettings\(\)](#), [setWhatMeasured\(\)](#), [setWhenMeasured\(\)](#), [setWhereMeasured\(\)](#), [spct_attr2tb\(\)](#), [trimInstrDesc\(\)](#)

trim_spct	<i>Trim (or expand) head and/or tail of a spectrum</i>
-----------	--

Description

Trim head and tail of a spectrum based on wavelength limits, interpolating the values at the boundaries of the range. Trimming is needed for example to remove short wavelength noise when the measured spectrum extends beyond the known emission spectrum of the measured light source. Occasionally one may want also to expand the wavelength range.

Usage

```
trim_spct(  
  spct,  
  range = NULL,  
  low.limit = NULL,  
  high.limit = NULL,  
  use.hinges = TRUE,  
  fill = NULL,  
  byref = FALSE,  
  verbose = getOption("photobiology.verbose")  
)  
  
trim_mspct(  
  mspct,  
  range = NULL,  
  low.limit = NULL,  
  high.limit = NULL,  
  use.hinges = TRUE,  
  fill = NULL,  
  byref = FALSE,  
  verbose = getOption("photobiology.verbose"),  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
trim2overlap(  
  mspct,  
  use.hinges = TRUE,  
  verbose = getOption("photobiology.verbose"),  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
extend2extremes(  
  mspct,  
  use.hinges = TRUE,  
  fill = NA,  
  verbose = getOption("photobiology.verbose"),  
  .parallel = FALSE,  
  .paropts = NULL  
)
```

Arguments

spct	an object of class "generic_spct".
range	a numeric vector of length two, or any other object for which method range() will return a numeric vector of length two.
low.limit	shortest wavelength to be kept (defaults to shortest w.length value).

high.limit	longest wavelength to be kept (defaults to longest w.length value).
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
fill	if fill==NULL then tails are deleted, otherwise tails or s.irrad are filled with the value of fill.
byref	logical indicating if new object will be created by reference or by copy of spct.
verbose	logical.
mspct	an object of class "generic_mspct"
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

a spectrum of same class as input with its tails trimmed or expanded.

Note

When expanding a spectrum, if fill==NULL, then expansion is not performed. Range can be "waveband" object, a numeric vector or a list of numeric vectors, or any other user-defined or built-in object for which range() returns a numeric vector of length two, that can be interpreted as wavelengths expressed in nm.

See Also

Other trim functions: [clip_wl\(\)](#), [trim_waveband\(\)](#), [trim_wl\(\)](#)

Examples

```
trim_spct(sun.spct, low.limit=300)
trim_spct(sun.spct, low.limit=300, fill=NULL)
trim_spct(sun.spct, low.limit=300, fill=NA)
trim_spct(sun.spct, low.limit=300, fill=0.0)
trim_spct(sun.spct, range = c(300, 400))
trim_spct(sun.spct, range = c(300, NA))
trim_spct(sun.spct, range = c(NA, 400))
```

`trim_tails`*Trim (or expand) head and/or tail*

Description

Trim tails of a spectrum based on wavelength limits, interpolating the values at the boundaries. Trimming is needed for example to remove short wavelength noise when the measured spectrum extends beyond the known emission spectrum of the measured light source. Occasionally one may want also to expand the wavelength range.

Usage

```
trim_tails(  
  x,  
  y,  
  low.limit = min(x),  
  high.limit = max(x),  
  use.hinges = TRUE,  
  fill = NULL,  
  verbose = TRUE  
)
```

Arguments

<code>x</code>	numeric vector of wavelengths.
<code>y</code>	numeric vector of values for a spectral quantity.
<code>low.limit</code>	smallest x-value to be kept (defaults to smallest x-value in input).
<code>high.limit</code>	largest x-value to be kept (defaults to largest x-value in input).
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>fill</code>	if <code>fill == NULL</code> then tails are deleted, otherwise tails of <code>y</code> are filled with the value of <code>fill</code> .
<code>verbose</code>	logical Use to suppress warnings.

Value

A data.frame with variables `x` and `y`.

Note

When expanding a spectrum, if `fill == NULL`, expansion is not performed with a warning.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [v_insert_hinges\(\)](#), [v_replace_hinges\(\)](#)

Examples

```
head(sun.data)
head(with(sun.data,
  trim_tails(w.length, s.e.irrad, low.limit=300)))
head(with(sun.data,
  trim_tails(w.length, s.e.irrad, low.limit=300, fill=NULL)))
```

trim_waveband	<i>Trim (or expand) head and/or tail</i>
---------------	--

Description

Trimming of waveband boundaries can be needed when the spectral data do not cover the whole waveband, or wavebands may have to be removed altogether.

Usage

```
trim_waveband(
  w.band,
  range = NULL,
  low.limit = 0,
  high.limit = Inf,
  trim = getOption("photobiology.waveband.trim", default = TRUE),
  use.hinges = TRUE,
  trunc.labels = getOption("photobiology.brief.trunc.names", default = c("[", "[")
)
```

Arguments

w.band	an object of class "waveband" or a list of such objects.
range	a numeric vector of length two, or any other object for which function range() will return a numeric vector of two wavelengths (nm).
low.limit	shortest wavelength to be kept (defaults to 0 nm).
high.limit	longest wavelength to be kept (defaults to Inf nm).
trim	logical (default is TRUE which trims the wavebands at the boundary, while FALSE discards wavebands that are partly off-boundary).

use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
trunc.labels	character vector of length one or two. The first string will be prepended to the waveband name and label on left truncation and the second appended on right truncation. If the vector is of length one, the same string will be used in both cases.

Details

This function will accept both individual wavebands or list of wavebands. When the input is a list, wavebands outside the range of the range will be removed from the list, and those partly outside the target range either "trimmed" to this edge truncated if `trim = TRUE` is passed or excluded if `trim = FALSE`). Waveband objects contain a name and a label that are used to label the returned values of calculations that make use of them. When a waveband object is truncated so that the definition changes, the name and label are also modified so that the change is visible when they are used. The name and label have a string prepended or appended, and what strings are used can be set with an R option.

Value

The returned value is a waveband object or a list of waveband objects depending on whether a single waveband object or a list of waveband objects was supplied as argument to formal parameter `w.band`. If no waveband is retained, in the first case, a NULL waveband object is returned, and in the second case, a list of length zero is returned. If the input is a named list, names are preserved in the returned list.

Note

Modification of the name and label stored in the wavebands passed as input is done so that summaries produced with the modified objects can be recognized as different from those computed using the original definitions when the waveband objects are used. When the input is a named list, the names of the retained members of the list are not modified as these are not part of the definitions.

See Also

Other trim functions: `clip_wl()`, `trim_spct()`, `trim_wl()`

Examples

```
VIS <- waveband(c(380, 760)) # manometers

trim_waveband(VIS, c(400,700))
trim_waveband(VIS, low.limit = 400)
trim_waveband(VIS, high.limit = 700)
trim_waveband(VIS, c(400,700), trunc.labels = c(">", "<"))
trim_waveband(VIS, c(400,700), trunc.labels = "!")
```

trim_wl	<i>Trim head and/or tail of a spectrum</i>
---------	--

Description

Trim head and tail of a spectrum based on wavelength limits, with interpolation at range boundaries used by default. Expansion is also possible.

Usage

```
trim_wl(x, range, use.hinges, fill, ...)  
  
## Default S3 method:  
trim_wl(x, range, use.hinges, fill, ...)  
  
## S3 method for class 'generic_spct'  
trim_wl(x, range = NULL, use.hinges = TRUE, fill = NULL, ...)  
  
## S3 method for class 'generic_mspct'  
trim_wl(  
  x,  
  range = NULL,  
  use.hinges = TRUE,  
  fill = NULL,  
  ...,  
  .parallel = FALSE,  
  .paropts = NULL  
)  
  
## S3 method for class 'waveband'  
trim_wl(  
  x,  
  range = NULL,  
  use.hinges = TRUE,  
  fill = NULL,  
  trim = getOption("photobiology.waveband.trim", default = TRUE),  
  ...  
)  
  
## S3 method for class 'list'  
trim_wl(  
  x,  
  range = NULL,  
  use.hinges = TRUE,  
  fill = NULL,  
  trim = getOption("photobiology.waveband.trim", default = TRUE),  
  ...  
)
```

)

Arguments

<code>x</code>	an R object.
<code>range</code>	a numeric vector of length two, or any other object for which function <code>range()</code> will return two.
<code>use.hinges</code>	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
<code>fill</code>	if <code>fill == NULL</code> then tails are deleted, otherwise tails are filled with the value of <code>fill</code> .
<code>...</code>	ignored (possibly used by derived methods).
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by <code>foreach</code>
<code>.paropts</code>	a list of additional options passed into the <code>foreach</code> function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.
<code>trim</code>	logical (default is TRUE which trims the wavebands at the boundary, while FALSE discards wavebands that are partly off-boundary).

Value

A copy of `x`, usually trimmed or expanded to a different length, either shorter or longer. Possibly with some of the original spectral data values replaced with `fill`.

Methods (by class)

- `default`: Default for generic function
- `generic_spct`: Trim an object of class "generic_spct" or derived.
- `generic_mspct`: Trim an object of class "generic_mspct" or derived.
- `waveband`: Trim an object of class "waveband".
- `list`: Trim a list (of "waveband" objects).

Note

By default the `w.length` values for the first and last rows in the returned object are the values supplied as `range`.

`trim_wl` when applied to waveband objects always inserts hinges when trimming.

`trim_wl` when applied to waveband objects always inserts hinges when trimming.

See Also

Other trim functions: [clip_wl\(\)](#), [trim_spct\(\)](#), [trim_waveband\(\)](#)

Examples

```
trim_wl(sun.spct, range = c(400, 500))
trim_wl(sun.spct, range = c(NA, 500))
trim_wl(sun.spct, range = c(400, NA))
```

tz_time_diff	<i>Time difference between two time zones</i>
--------------	---

Description

Returns the time difference in hours between two time zones at a given instant in time.

Usage

```
tz_time_diff(
  when = lubridate::now(),
  tz.target = lubridate::tz(when),
  tz.reference = "UTC"
)
```

Arguments

when	datetime	A time instant
tz.target, tz.reference	character	Two time zones using names recognized by functions from package 'lubridate'

Value

A numeric value.

uncollect	<i>Extract all members from a collection</i>
-----------	--

Description

Extract all members from a collection into separate objects in the parent frame of the call.

Usage

```

uncollect(x, ...)

## Default S3 method:
uncollect(x, ...)

## S3 method for class 'generic_mspct'
uncollect(
  x,
  name.tag = ".spct",
  ignore.case = FALSE,
  check.names = TRUE,
  check.override = TRUE,
  ...
)

```

Arguments

<code>x</code>	An R object
<code>...</code>	additional named arguments passed down to <code>f</code> .
<code>name.tag</code>	character. A string used as tag for the names of the objects. If of length zero, names of members are used as named of objects. Otherwise the tag is appended, unless already present in the member name.
<code>ignore.case</code>	logical. If <code>FALSE</code> , the pattern matching used for <code>name.tag</code> is case sensitive and if <code>TRUE</code> , case is ignored during matching.
<code>check.names</code>	logical. If <code>TRUE</code> then the names of the objects created are checked to ensure that they are syntactically valid variable names and unique. If necessary they are adjusted (by <code>make.names</code>) so that they are, and if <code>FALSE</code> names are used as is.
<code>check.override</code>	logical. If <code>TRUE</code> trigger an error if an existing object would be overwritten, and if <code>FALSE</code> silently overwrite objects.

Value

Utility used for its side effects, invisibly returns a character vector with the names of the objects created.

Methods (by class)

- `default`: Default for generic function
- `generic_mspct`:

See Also

Other experimental utility functions: [thin_wl\(\)](#)

Examples

```
my.msct <- source_mspt(list(sun1 = sun.spct, sun2 = sun.spct))
uncollect(my.msct)
ls(pattern = "*.spct")
```

untag	<i>Remove tags</i>
-------	--------------------

Description

Remove tags from an R object if present, otherwise return the object unchanged.

Usage

```
untag(x, ...)
```

Default S3 method:
untag(x, ...)

S3 method for class 'generic_spct'
untag(x, byref = FALSE, ...)

S3 method for class 'generic_mspt'
untag(x, byref = FALSE, ...)

Arguments

x	an R object.
...	ignored (possibly used by derived methods).
byref	logical indicating if new object will be created by reference or by copy of x

Value

if x contains tag data they are removed and the "spct.tags" attribute is set to NA, while if x has no tags, it is not modified. In either case, the byref argument is respected: in all cases if byref = FALSE a copy of x is returned.

Methods (by class)

- default: Default for generic function
- generic_spct: Specialization for generic_spct
- generic_mspt: Specialization for generic_mspt

See Also

Other tagging and related functions: [is_tagged\(\)](#), [tag\(\)](#), [wb2rect_spct\(\)](#), [wb2spct\(\)](#), [wb2tagged_spct\(\)](#)

upgrade_spct	<i>Upgrade one spectral object</i>
--------------	------------------------------------

Description

Update the spectral class names of objects to those used in photobiology ($\geq 0.6.0$) and add 'version' attribute as used in photobiology (≥ 0.70).

Usage

```
upgrade_spct(object)
```

Arguments

object generic.spct A single object to upgrade

Value

The modified object (invisibly).

Note

The object is modified by reference. The class names with ending ".spct" replaced by their new equivalents ending in "_spct".

See Also

Other upgrade from earlier versions: [is.old_spct\(\)](#), [upgrade_spectra\(\)](#)

upgrade_spectra	<i>Upgrade one or more spectral objects</i>
-----------------	---

Description

Update the spectral class names of objects to those used in photobiology ($\geq 0.6.0$).

Usage

```
upgrade_spectra(obj.names = ls(parent.frame()))
```

Arguments

obj.names char Names of objects to upgrade as a vector of character strings

Value

The modified object (invisibly).

Note

The objects are modified by reference. The class names with ending ".spct" are replaced by their new equivalents ending in "_spct". `object.names` can safely include names of any R object. Names of objects which do not belong to any the old `.spct` classes are ignored. This makes it possible to supply as argument the output from `ls`, the default, or its equivalent objects.

See Also

Other upgrade from earlier versions: [is.old_spct\(\)](#), [upgrade_spct\(\)](#)

using_Tfr	<i>Use photobiology options</i>
-----------	---------------------------------

Description

Execute an R expression, possibly compound, using a certain setting for spectral data related options.

Usage

```
using_Tfr(expr)
```

```
using_Afr(expr)
```

```
using_A(expr)
```

```
using_energy(expr)
```

```
using_photon(expr)
```

```
using_quantum(expr)
```

Arguments

`expr` an R expression to execute.

Value

The value returned by the execution of expression.

References

Based on `withOptions()` as offered by Thomas Lumley, and listed in <http://www.burns-stat.com/the-options-mechanism-in-r/>, section Deep End, of "The Options mechanism in R" by Patrick Burns.

validate_geocode	<i>Validate a geocode</i>
------------------	---------------------------

Description

Test validity of a geocode or ensure that a geocode is valid.

Usage

```
validate_geocode(geocode)
```

```
is_valid_geocode(geocode)
```

```
length_geocode(geocode)
```

```
na_geocode()
```

Arguments

geocode data.frame with geocode data in columns "lat", "lon", and possibly also "address".

Details

validate_geocode Converts to tibble, checks data bounds, converts address to character if it is not already a character vector, or add character NAs if the address column is missing.

is_valid_geocode Checks if a geocode is valid, returning 0L if not, and the number of row otherwise.

Value

A valid geocode stored in a tibble.

FALSE for invalid, TRUE for valid.

FALSE for invalid, number of rows for valid.

A geo_code tibble with all fields set to suitable NAs.

Examples

```
validate_geocode(NA)
validate_geocode(data.frame(lon = -25, lat = 66))
```

```
is_valid_geocode(NA)
is_valid_geocode(1L)
is_valid_geocode(data.frame(lon = -25, lat = 66))
```

```
na_geocode()
```

valleys	<i>Valleys or local minima</i>
---------	--------------------------------

Description

Function that returns a subset of an R object with observations corresponding to local maxima.

Usage

```
valleys(x, span, ignore_threshold, strict, ...)  
  
## Default S3 method:  
valleys(x, span = NA, ignore_threshold = NA, strict = NA, na.rm = FALSE, ...)  
  
## Default S3 method:  
valleys(x, span = NA, ignore_threshold = NA, strict = NA, na.rm = FALSE, ...)  
  
## S3 method for class 'numeric'  
valleys(x, span = 5, ignore_threshold, strict = TRUE, na.rm = FALSE, ...)  
  
## S3 method for class 'data.frame'  
valleys(  
  x,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  na.rm = FALSE,  
  x.var.name = NULL,  
  y.var.name = NULL,  
  var.name = y.var.name,  
  refine.wl = FALSE,  
  method = "spline",  
  ...  
)  
  
## S3 method for class 'generic_spct'  
valleys(  
  x,  
  span = 5,  
  ignore_threshold = 0,  
  strict = TRUE,  
  na.rm = FALSE,  
  var.name = NULL,  
  refine.wl = FALSE,  
  method = "spline",  
  ...  
)
```

```
## S3 method for class 'source_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'response_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'filter_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'reflector_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  refine.wl = FALSE,
```

```
    method = "spline",
    ...
)

## S3 method for class 'cps_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'raw_spct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "counts",
  refine.wl = FALSE,
  method = "spline",
  ...
)

## S3 method for class 'generic_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = NULL,
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'source_mspct'
valleys(
  x,
  span = 5,
```

```
ignore_threshold = 0,
strict = TRUE,
na.rm = FALSE,
unit.out = getOption("photobiology.radiation.unit", default = "energy"),
refine.wl = FALSE,
method = "spline",
...,
.parallel = FALSE,
.paropts = NULL
)

## S3 method for class 'response_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'filter_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'reflector_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
```



```

    refine.wl = FALSE,
    method = "spline",
    ...,
    .parallel = FALSE,
    .paropts = NULL
  )

## S3 method for class 'cps_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "cps",
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

## S3 method for class 'raw_mspct'
valleys(
  x,
  span = 5,
  ignore_threshold = 0,
  strict = TRUE,
  na.rm = FALSE,
  var.name = "counts",
  refine.wl = FALSE,
  method = "spline",
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

<code>x</code>	an R object
<code>span</code>	integer A valley is defined as an element in a sequence which is smaller than all other elements within a window of width <code>span</code> centered at that element. Use <code>NULL</code> for the global peak.
<code>ignore_threshold</code>	numeric Value between 0.0 and 1.0 indicating the relative size compared to tallest peak threshold below which peaks will be ignored. Negative values set a threshold so that the tallest peaks are ignored, instead of the shortest.
<code>strict</code>	logical If <code>TRUE</code> , an element must be strictly greater than all other values in its

	window to be considered a peak.
...	ignored
na.rm	logical indicating whether NA values should be stripped before searching for peaks.
var.name, x.var.name, y.var.name	character Name of column where to look for valleys.
refine.wl	logical Flag indicating if valley location should be refined by fitting a function.
method	character String with the name of a method. Currently only spline interpolation is implemented.
unit.out	character One of "energy" or "photon"
filter.qty	character One of "transmittance" or "absorbance"
.parallel	if TRUE, apply function in parallel, using parallel backend provided by foreach
.paropts	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the .export and .packages arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A subset of x with rows corresponding to local minima.

Methods (by class)

- default: Default function usable on numeric vectors.
- default: Default returning always NA.
- numeric: Default function usable on numeric vectors.
- data.frame: Method for "data.frame" objects.
- generic_spct: Method for "generic_spct" objects.
- source_spct: Method for "source_spct" objects.
- response_spct: Method for "response_spct" objects.
- filter_spct: Method for "filter_spct" objects.
- reflector_spct: Method for "reflector_spct".
- cps_spct: Method for "cps_spct" objects.
- raw_spct: Method for "raw_spct" objects.
- generic_mspct: Method for "generic_mspct" objects.
- source_mspct: Method for "source_mspct" objects.
- response_mspct: Method for "cps_mspct" objects.
- filter_mspct: Method for "filter_mspct" objects.
- reflector_mspct: Method for "reflector_mspct" objects.
- cps_mspct: Method for "cps_mspct" objects.
- raw_mspct: Method for "raw_mspct" objects.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [wls_at_target\(\)](#)

Examples

```
valleys(sun.spct, span = 50)
```

```
valleys(sun.spct)
```

verbose_as_default *Set error reporting options*

Description

Set error reporting related options easily.

Usage

```
verbose_as_default(flag = TRUE)
```

```
strict_range_as_default(flag = TRUE)
```

Arguments

flag logical.

Value

Previous value of the modified option.

v_insert_hinges *Insert spectral data values at new wavelength values.*

Description

Inserting wavelengths values immediately before and after a discontinuity in the SWF, greatly reduces the errors caused by interpolating the weighted irradiance during integration of the effective spectral irradiance. This is specially true when data have a relatively large wavelength step size and/or when the weighting function used has discontinuities in its value or slope. This function differs from `insert_hinges()` in that it returns a vector of y values instead of a tibble.

Usage

```
v_insert_hinges(x, y, h)
```

Arguments

x	numeric vector (sorted in increasing order).
y	numeric vector.
h	a numeric vector giving the wavelengths at which the y values should be inserted by interpolation, no interpolation is indicated by an empty numeric vector (numeric(0)).

Value

A numeric vector with the numeric values of y, but longer. Unless the hinge values were already present in y, each inserted hinge, expands the vector by two values.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_replace_hinges\(\)](#)

v_replace_hinges

Overwrite spectral data values at existing wavelength values.

Description

Overwriting spectral data with interpolated values at wavelengths values containing bad data is needed when cleaning spectral data. This function differs from `insert_hinges()` in that it returns a vector of y values instead of a tibble.

Usage

```
v_replace_hinges(x, y, h)
```

Arguments

x	numeric vector (sorted in increasing order).
y	numeric vector.
h	a numeric vector giving the wavelengths at which the y values should be replaced by interpolation, no interpolation is indicated by an empty numeric vector (numeric(0)).

Value

A numeric vector with the numeric values of y with values at the hinges replaced by interpolation of neighbours.

See Also

Other low-level functions operating on numeric vectors.: [as_energy\(\)](#), [as_quantum_mol\(\)](#), [calc_multipliers\(\)](#), [div_spectra\(\)](#), [energy_irradiance\(\)](#), [energy_ratio\(\)](#), [insert_hinges\(\)](#), [integrate_xy\(\)](#), [interpolate_spectrum\(\)](#), [irradiance\(\)](#), [l_insert_hinges\(\)](#), [oper_spectra\(\)](#), [photon_irradiance\(\)](#), [photon_ratio\(\)](#), [photons_energy_ratio\(\)](#), [prod_spectra\(\)](#), [s_e_irrad2rgb\(\)](#), [split_energy_irradiance\(\)](#), [split_photon_irradiance\(\)](#), [subt_spectra\(\)](#), [sum_spectra\(\)](#), [trim_tails\(\)](#), [v_insert_hinges\(\)](#)

 water_vp_sat

Water vapour pressure

Description

Approximate water pressure in air as a function of temperature, and its inverse the calculation of dewpoint.

Usage

```
water_vp_sat(
  temperature,
  over.ice = FALSE,
  method = "tetens",
  check.range = TRUE
)
```

```
water_dp(water.vp, over.ice = FALSE, method = "tetens", check.range = TRUE)
```

```
water_fp(water.vp, over.ice = TRUE, method = "tetens", check.range = TRUE)
```

```
water_vp2mvc(water.vp, temperature)
```

```
water_mvc2vp(water.mvc, temperature)
```

```
water_vp2RH(
  water.vp,
  temperature,
  over.ice = FALSE,
  method = "tetens",
  pc = TRUE,
  check.range = TRUE
)
```

```
water_RH2vp(
  relative.humidity,
  temperature,
  over.ice = FALSE,
  method = "tetens",
```

```

    pc = TRUE,
    check.range = TRUE
)

```

Arguments

temperature	numeric vector of air temperatures (C).
over.ice	logical Is the estimate for equilibrium with liquid water or with ice.
method	character Currently "tetens", modified "magnus", "wexler" and "goff.gratch" equations are supported.
check.range	logical Flag indicating whether to check or not that arguments for temperature are within the range of validity of the method used.
water.vp	numeric vector of water vapour pressure in air (Pa).
water.mvc	numeric vector of water vapour concentration as mass per volume (g m ⁻³).
pc	logical flag for result returned as percent or not.
relative.humidity	numeric Relative humidity as fraction of 1.

Details

Function `water_vp_sat()` provides implementations of several well known equations for the estimation of saturation vapor pressure in air. Functions `water_dp()` and `water_fp()` use the inverse of these equations to compute the dew point or frost point from water vapour pressure in air. The inverse functions are either analytical solutions or fitted approximations. None of these functions are solved numerically by iteration.

Method "tetens" implements Tetens' (1930) equation for the cases of equilibrium with a water and an ice surface. Method "magnus" implements the modified Magnus equations of Alduchov and Eskridge (1996, eqs. 21 and 23). Method "wexler" implements the equations proposed by Wexler (1976, 1977), and their inverse according to Hardy (1998). Method "goff.gratch" implements the equations of Groff and Gratch (1946) with the minor updates of Groff (1956).

The equations are approximations, and in spite of their different names, Tetens' and Magnus' equations have the same form with the only difference in the values of the parameters. However, the modified Magnus equation is more accurate as Tetens equation suffers from some bias errors at extreme low temperatures (< -40 C). In contrast Magnus equations with recently fitted values for the parameters are usable for temperatures from -80 C to +50 C over water and -80 C to 0 C over ice. The Groff Gratch equation is more complex and is frequently used as a reference in comparison as it is considered reliable over a broad range of temperatures. Wexler's equations are computationally simpler and fitted to relatively recent data. There is little difference at temperatures in the range -20 C to +50 C, and differences become large at extreme temperatures. Temperatures outside the range where estimations are highly reliable for each equation return NA, unless extrapolation is enabled by passing FALSE as argument to parameter `check.range`.

The switch between equations for ice or water cannot be based on air temperature, as it depends on the presence or not of a surface of liquid water. It must be set by passing an argument to parameter `over.ice` which defaults to FALSE.

Tetens equation is still very frequently used, and is for example the one recommended by FAO for computing potential evapotranspiration. For this reason it is used as default here.

Value

A numeric vector of partial pressures in pascal (P) for water_vp_sat and water_mvc2vp, a numeric vector of dew point temperatures (C) for water_dp and numeric vector of mass per volume concentrations (g m⁻³) for water_vp2mvc.

Note

The inverse of the Goff Gratch equation has yet to be implemented.

References

Tetens, O., 1930. Uber einige meteorologische Begriffe. Zeitschrift fur Geophysik, Vol. 6:297.

Goff, J. A., and S. Gratch (1946) Low-pressure properties of water from -160 to 212 F, in Transactions of the American Society of Heating and Ventilating Engineers, pp 95-122, presented at the 52nd annual meeting of the American Society of Heating and Ventilating Engineers, New York, 1946.

Wexler, A. (1976) Vapor Pressure Formulation for Water in Range 0 to 100°C. A Revision, Journal of Research of the National Bureau of Standards: A. Physics and Chemistry, September-December 1976, Vol. 80A, Nos.5 and 6, 775-785

Wexler, A., Vapor Pressure Formulation for Ice, Journal of Research of the National Bureau of Standards - A. Physics and Chemistry, January - February 1977, Vol. 81A, No. 1, 5-19

Alduchov, O. A., Eskridge, R. E., 1996. Improved Magnus Form Approximation of Saturation Vapor Pressure. Journal of Applied Meteorology, 35: 601-609 .

Hardy, Bob (1998) ITS-90 formulations for vapor pressure, frostpoint temperature, dewpoint temperature, and enhancement factors in the range -100 TO +100 C. The Proceedings of the Third International Symposium on Humidity & Moisture, Teddington, London, England, April 1998. <http://www.decatour.de/javascript/dew/resources/its90formulas.pdf>

Monteith, J., Unsworth, M. (2008) Principles of Environmental Physics. Academic Press, Amsterdam.

[Equations describing the physical properties of moist air](<http://www.conservaionphysics.org/atmcalc/atmoclc2.pdf>)

Examples

```
water_vp_sat(20) # C -> Pa
water_vp_sat(temperature = c(0, 10, 20, 30, 40)) # C -> Pa
water_vp_sat(temperature = -10) # over water!!
water_vp_sat(temperature = -10, over.ice = TRUE)
water_vp_sat(temperature = 20) / 100 # C -> mbar

water_vp_sat(temperature = 20, method = "magnus") # C -> Pa
water_vp_sat(temperature = 20, method = "tetens") # C -> Pa
water_vp_sat(temperature = 20, method = "wexler") # C -> Pa
water_vp_sat(temperature = 20, method = "goff.gratch") # C -> Pa
```

```
water_vp_sat(temperature = -20, over.ice = TRUE, method = "magnus") # C -> Pa
water_vp_sat(temperature = -20, over.ice = TRUE, method = "tetens") # C -> Pa
water_vp_sat(temperature = -20, over.ice = TRUE, method = "wexler") # C -> Pa
water_vp_sat(temperature = -20, over.ice = TRUE, method = "goff.gratch") # C -> Pa
```

```

water_dp(water.vp = 1000) # Pa -> C
water_dp(water.vp = 1000, method = "magnus") # Pa -> C
water_dp(water.vp = 1000, method = "wexler") # Pa -> C
water_dp(water.vp = 500, over.ice = TRUE) # Pa -> C
water_dp(water.vp = 500, method = "wexler", over.ice = TRUE) # Pa -> C

water_fp(water.vp = 300) # Pa -> C
water_dp(water.vp = 300, over.ice = TRUE) # Pa -> C

water_vp2RH(water.vp = 1500, temperature = 20) # Pa, C -> RH %
water_vp2RH(water.vp = 1500, temperature = c(20, 30)) # Pa, C -> RH %
water_vp2RH(water.vp = c(600, 1500), temperature = 20) # Pa, C -> RH %

water_vp2mvc(water.vp = 1000, temperature = 20) # Pa -> g m-3

water_mvc2vp(water.mvc = 30, temperature = 40) # g m-3 -> Pa

water_dp(water.vp = water_mvc2vp(water.mvc = 10, temperature = 30)) # g m-3 -> C

```

waveband

Waveband constructor method

Description

Constructor for "waveband" objects that can be used as input when calculating irradiances.

Usage

```

waveband(
  x = NULL,
  weight = NULL,
  SWF.e.fun = NULL,
  SWF.q.fun = NULL,
  norm = NULL,
  SWF.norm = NULL,
  hinges = NULL,
  wb.name = NULL,
  wb.label = wb.name
)

```

```

new_waveband(
  w.low,
  w.high,
  weight = NULL,
  SWF.e.fun = NULL,
  SWF.q.fun = NULL,
  norm = NULL,

```



```

    SWF.norm = NULL,
    hinges = NULL,
    wb.name = NULL,
    wb.label = wb.name
  )

```

Arguments

<code>x</code>	any R object on which applying the function <code>range</code> yields an vector of two numeric values, describing a range of wavelengths (nm)
<code>weight</code>	a character string "SWF" or "BSWF", use NULL (the default) to indicate no weighting used when calculating irradiance
<code>SWF.e.fun</code>	a function giving multipliers for a spectral weighting function (energy) as a function of wavelength (nm)
<code>SWF.q.fun</code>	a function giving multipliers for a spectral weighting function (quantum) as a function of wavelength (nm)
<code>norm</code>	a single numeric value indicating the wavelength at which the SWF should be normalized to 1.0, in nm. "NULL" means no normalization.
<code>SWF.norm</code>	a numeric value giving the native normalization wavelength (nm) used by <code>SWF.e.fun</code> and <code>SWF.q.fun</code>
<code>hinges</code>	a numeric vector giving the wavelengths at which the <code>s.irrad</code> should be inserted by interpolation, no interpolation is indicated by an empty vector (<code>numeric(0)</code>), if NULL then interpolation will take place at both ends of the band.
<code>wb.name</code>	character string giving the name for the waveband defined, default is NULL
<code>wb.label</code>	character string giving the label of the waveband to be used for plotting, default is <code>wb.name</code>
<code>w.low</code>	numeric value, wavelength at the short end of the band (nm)
<code>w.high</code>	numeric value, wavelength at the long end of the band (nm)

Value

a waveband object

Functions

- `new_waveband`: A less flexible variant

See Also

Other waveband constructors: [split_bands\(\)](#)

Examples

```

waveband(c(400, 700))

new_waveband(400, 700)

```

waveband_ratio	<i>Photon or energy ratio</i>
----------------	-------------------------------

Description

This function gives the (energy or photon) irradiance ratio between two given wavebands of a radiation spectrum.

Usage

```

waveband_ratio(
  w.length,
  s.irrad,
  w.band.num = NULL,
  w.band.denom = NULL,
  unit.out.num = NULL,
  unit.out.denom = unit.out.num,
  unit.in = "energy",
  check.spectrum = TRUE,
  use.cached.mult = FALSE,
  use.hinges = getOption("photobiology.use.hinges", default = NULL)
)

```

Arguments

w.length	numeric Vector of wavelengths (nm)
s.irrad	numeric vector of spectral (energy or photon) irradiances ($\text{W m}^{-2} \text{nm}^{-1}$) or ($\text{mol s}^{-1} \text{m}^{-2} \text{nm}^{-1}$).
w.band.num	waveband object used to compute the numerator of the ratio.
w.band.denom	waveband object used to compute the denominator of the ratio.
unit.out.num	character Allowed values "energy", and "photon", or its alias "quantum".
unit.out.denom	character Allowed values "energy", and "photon", or its alias "quantum".
unit.in	character Allowed values "energy", and "photon", or its alias "quantum".
check.spectrum	logical Flag indicating whether to sanity check input data, default is TRUE.
use.cached.mult	logical Flag indicating whether multiplier values should be cached between calls.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.

Value

a single numeric value giving the ratio

Note

The default for both w.band parameters is a waveband covering the whole range of w.length. From version 9.19 onwards use of this default does not trigger a warning, but instead is used silently.

Examples

```
# photon:photon ratio
with(sun.data,
     waveband_ratio(w.length, s.e.irrad,
                   new_waveband(400,500),
                   new_waveband(400,700), "photon"))
# energy:energy ratio
with(sun.data,
     waveband_ratio(w.length, s.e.irrad,
                   new_waveband(400,500),
                   new_waveband(400,700), "energy"))
# energy:photon ratio
with(sun.data,
     waveband_ratio(w.length, s.e.irrad,
                   new_waveband(400,700),
                   new_waveband(400,700),
                   "energy", "photon"))
# photon:photon ratio waveband : whole spectrum
with(sun.data,
     waveband_ratio(w.length, s.e.irrad,
                   new_waveband(400,500),
                   unit.out.num="photon"))
# photon:photon ratio of whole spectrum should be equal to 1.0
with(sun.data,
     waveband_ratio(w.length, s.e.irrad,
                   unit.out.num="photon"))
```

wb2rect_spct

Create tagged spectrum from wavebands

Description

Create a generic_spct object with wavelengths from the range of wavebands in a list. The spectrum is suitable for plotting labels, symbols, rectangles or similar, as the midpoint of each waveband is added to the spectrum.

Usage

```
wb2rect_spct(w.band, short.names = TRUE, chroma.type = "CMF")
```

```
fast_wb2rect_spct(w.band, chroma.type = "CMF", simplify = TRUE)
```

Arguments

w.band	waveband or list of waveband objects The waveband(s) determine the wavelengths in variable w.length of the returned spectrum
short.names	logical Flag indicating whether to use short or long names for wavebands
chroma.type	character telling whether "CMF", "CC", or "both" should be returned for human vision, or an object of class chroma_spct for any other trichromatic visual system.
simplify	logical Flag indicating whether to merge neighboring rectangles of equal color. Simplification is done only for narrow wavebands.

Value

A generic.spct object, with columns w.length, wl.low, wl.hi, wl.color, wb.color and wb.name. The w.length values are the midpoint of the wavebands, wl.low and wl.high give the boundaries of the wavebands, wl.color the color definition corresponding to the wavelength at the center of the waveband and wb.color the color of the waveband as a whole (assuming a flat energy irradiance spectrum). Different spectral data variables are set to zero and added making the returned value compatible with classes derived from generic_spct.

Note

Function fast_wb2rect_spct() differs from wb2rect_spct() in that it computes colors for narrow wavebands based on the midpoint wavelength and uses vectorization when possible. It always returns color definitions with short names, which are also used as waveband names for narrow wavebands and merged wavebands. The purpose of merging of rectangles is to speed up rendering and to reduce the size of vector graphics output. This function should be used with care as the color definitions returned are only approximate and original waveband names can be lost.

See Also

Other tagging and related functions: [is_tagged\(\)](#), [tag\(\)](#), [untag\(\)](#), [wb2spct\(\)](#), [wb2tagged_spct\(\)](#)

 wb2spct

Create spectrum from wavebands

Description

Create a generic_spct object with wavelengths from wavebands in a list.

Usage

```
wb2spct(w.band)
```

Arguments

w.band	waveband or list of waveband objects The waveband(s) determine the wavelengths in variable w.length of the returned spectrum
--------	--

Value

A generic.spectrum object, with columns w.length set to the *union* of all boundaries and hinges defined in the waveband(s). Different spectral data variables are set to zero and added making the returned value compatible with classes derived from generic_spct.

See Also

Other tagging and related functions: [is_tagged\(\)](#), [tag\(\)](#), [untag\(\)](#), [wb2rect_spct\(\)](#), [wb2tagged_spct\(\)](#)

wb2tagged_spct	<i>Create tagged spectrum from wavebands</i>
----------------	--

Description

Create a tagged generic_spct object with wavelengths from the range of wavebands in a list, and names of the same bands as factor levels, and corresponding color definitions. The spectrum is not suitable for plotting labels, symbols, rectangles or similar, as the midpoint of each waveband is not added to the spectrum.

Usage

```
wb2tagged_spct(
  w.band,
  use.hinges = TRUE,
  short.names = TRUE,
  chroma.type = "CMF",
  ...
)
```

Arguments

w.band	waveband or list of waveband objects The waveband(s) determine the region(s) of the spectrum that are tagged and the wavelengths returned in variable w.length.
use.hinges	logical Flag indicating whether to insert "hinges" into the spectral data before integration so as to reduce interpolation errors at the boundaries of the wavebands.
short.names	logical Flag indicating whether to use short or long names for wavebands.
chroma.type	character telling whether "CMF", "CC", or "both" should be returned for human vision, or an object of class chroma_spct for any other trichromatic visual system.
...	ignored (possibly used by derived methods).

Value

A spectrum as returned by [wb2spct](#) but additionally tagged using function [tag](#)

See Also

Other tagging and related functions: [is_tagged\(\)](#), [tag\(\)](#), [untag\(\)](#), [wb2rect_spct\(\)](#), [wb2spct\(\)](#)

wb_trim_as_default *Set computation options*

Description

Set computation related options easily.

Usage

```
wb_trim_as_default(flag = TRUE)
```

```
use_cached_mult_as_default(flag = TRUE)
```

Arguments

flag logical.

Value

Previous value of the modified option.

white_body.spct *Theoretical white body*

Description

A dataset for a hypothetical object with transmittance 0/1 (0%), reflectance 1/1 (100%)

Format

A object_spct object with 4 rows and 3 variables

Details

- w.length (nm)
- Tfr (0..1)
- Rfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

white_led.cps_spct	<i>White led bulb spectrum</i>
--------------------	--------------------------------

Description

A dataset containing wavelengths and the corresponding spectral data as counts per second for an Osram warm white led lamp:

Usage

```
white_led.cps_spct
```

Format

A data.frame object with 2068 rows and 2 variables

Details

- w.length (nm), range 188 to 1117 nm.
- cps

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.raw_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
white_led.cps_spct
```

white_led.raw_spct	<i>White led bulb spectrum</i>
--------------------	--------------------------------

Description

A dataset containing wavelengths and the corresponding spectral data as raw instrument counts for an Osram warm white led lamp, for three different integration times:

Usage

```
white_led.raw_spct
```

Format

An object of class `raw_spct` (inherits from `generic_spct`, `tbl_df`, `tbl`, `data.frame`) with 2068 rows and 4 columns.

Details

- `w.length` (nm), range 188 to 1117 nm.
- `counts_1`
- `counts_2`
- `counts_3`
- `w.length` (nm), range 188 to 1117 nm.
- `cps`

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.source_spct](#), [yellow_gel.spct](#)

Examples

```
white_led.raw_spct
```

```
white_led.source_spct
```

White led bulb spectrum

Description

A dataset containing wavelengths and the corresponding spectral irradiance data for an Osram warm white led lamp:

Usage

```
white_led.source_spct
```

Format

A `source_spct` object with 1421 rows and 2 variables

Details

- `w.length` (nm), range 250 to 900 nm.
- `s.e.irrad` ($W\ m^{-2}\ nm^{-1}$)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspect](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [yellow_gel.spct](#)

Examples

```
white_led.source_spct
```

```
wls_at_target
```

Find wavelengths values corresponding to a target spectral value

Description

Find wavelength values corresponding to a target spectral value in a spectrum. The name of the column of the spectral data to be used is inferred from the class of `x` and the argument passed to `unit.out` or `filter.qty` or their defaults that depend on R options set.

Usage

```
wls_at_target(
  x,
  target = NULL,
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  ...
)

## Default S3 method:
wls_at_target(
  x,
  target = NULL,
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  ...
)

## S3 method for class 'data.frame'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
```

```
    idfactor = FALSE,
    na.rm = FALSE,
    x.var.name = NULL,
    y.var.name = NULL,
    ...
  )

## S3 method for class 'generic_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  col.name = NULL,
  y.var.name = col.name,
  ...
)

## S3 method for class 'source_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'response_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  unit.out = getOption("photobiology.radiation.unit", default = "energy"),
  ...
)

## S3 method for class 'filter_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
```

```

    filter.qty = getOption("photobiology.filter.qty", default = "transmittance"),
    ...
)

## S3 method for class 'reflector_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  ...
)

## S3 method for class 'cps_spct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  ...
)

## S3 method for class 'generic_mspct'
wls_at_target(
  x,
  target = "half.maximum",
  interpolate = FALSE,
  idfactor = FALSE,
  na.rm = FALSE,
  ...,
  .parallel = FALSE,
  .paropts = NULL
)

```

Arguments

x	data.frame or spectrum object.
target	numeric value indicating the spectral quantity value for which wavelengths are to be searched and interpolated if need. The character string "half.maximum" is also accepted as argument.
interpolate	logical Indicating whether the nearest wavelength value in x should be returned or a value calculated by linear interpolation between wavelength values straddling the target.
idfactor	logical or character Generates an index column of factor type. If idfactor = TRUE then the column is auto named spct.idx. Alternatively the column name can be directly passed as argument to idfactor as a character string.

<code>na.rm</code>	logical indicating whether NA values should be stripped before searching for the target.
<code>...</code>	currently ignored.
<code>x.var.name, y.var.name, col.name</code>	character The name of the columns in which to search for the target value. Use of <code>col.name</code> is deprecated, and is a synonym for <code>y.var.name</code> .
<code>unit.out</code>	character One of "energy" or "photon"
<code>filter.qty</code>	character One of "transmittance" or "absorbance"
<code>.parallel</code>	if TRUE, apply function in parallel, using parallel backend provided by foreach
<code>.paropts</code>	a list of additional options passed into the foreach function when parallel computation is enabled. This is important if (for example) your code relies on external data or packages: use the <code>.export</code> and <code>.packages</code> arguments to supply them so that all cluster nodes have the correct environment set up for computing.

Value

A `data.frame` or a spectrum object of the same class as `x` with fewer rows, possibly even no rows. If FALSE is passed to `interpolate` a subset of `x` is returned, otherwise a new object of the same class containing interpolated wavelengths for the target value is returned.

Methods (by class)

- `default`: Default returning always an empty object of the same class as `x`.
- `data.frame`: Method for "data.frame" objects.
- `generic_spct`: Method for "generic_spct" objects.
- `source_spct`: Method for "source_spct" objects.
- `response_spct`: Method for "response_spct" objects.
- `filter_spct`: Method for "filter_spct" objects.
- `reflector_spct`: Method for "reflector_spct" objects.
- `cps_spct`: Method for "cps_spct" objects.
- `generic_mspct`: Method for "generic_mspct" objects.

Note

When interpolation is used, only column `w.length` and the column against which the target value was compared are included in the returned object, otherwise, all columns in `x` are returned. We implement support for `data.frame` to simplify the coding of 'ggplot2' stats using this function.

See Also

Other peaks and valleys functions: [find_peaks\(\)](#), [find_spikes\(\)](#), [get_peaks\(\)](#), [peaks\(\)](#), [replace_bad_pixs\(\)](#), [spikes\(\)](#), [valleys\(\)](#)

Examples

```
wls_at_target(sun.spct, target = 0.1)
wls_at_target(sun.spct, target = 2e-6, unit.out = "photon")
wls_at_target(polyester.spct, target = "HM")
wls_at_target(polyester.spct, target = "HM", interpolate = TRUE)
wls_at_target(polyester.spct, target = "HM", idfactor = "target")
wls_at_target(polyester.spct, target = "HM", filter.qty = "absorbance")
```

wl_colors.spct	<i>Precomputed rgb colors</i>
----------------	-------------------------------

Description

A dataset containing wavelengths at a 1 nm interval (100 nm to 4000 nm) and the corresponding CMF and CC colors for human vision.

Usage

```
wl_colors.spct
```

Format

A generic_spct object with 3901 rows and 3 variables.

Details

- w.length (nm), numeric vector
- CMF, named character vector
- CC, named character vector

Note

Data computed with function `color_of()` and used by function `fast_color_of_wl()`

A `chroma_spct` object with variables as follows:

Examples

```
wl_colors.spct
```

wl_max	<i>Wavelength maximum</i>
--------	---------------------------

Description

A method specialization that returns the wavelength maximum from objects of classes "waveband" or of class "generic_spct" or derived.

Usage

```

wl_max(x, na.rm = FALSE)

## S3 method for class 'waveband'
max(..., na.rm = FALSE)

## S3 method for class 'generic_spct'
max(..., na.rm = FALSE)

## S3 method for class 'generic_mspct'
max(..., na.rm = FALSE, idx = "spct.idx")

```

Arguments

x	generic_spct, generic_mspct or waveband object.
na.rm	ignored
...	not used in current version
idx	character Name of the column with the names of the members of the collection of spectra.

Methods (by class)

- generic_spct:
- generic_mspct:

Examples

```

max(sun.spct)
wl_max(sun.spct)

```

wl_midpoint	<i>Midpoint</i>
-------------	-----------------

Description

A function that returns the wavelength (or value) at the center of the of the wavelength range of a waveband or spectrum object (or numeric vector).

Usage

```
wl_midpoint(x, ...)

midpoint(x, ...)

## Default S3 method:
midpoint(x, ...)

## S3 method for class 'numeric'
midpoint(x, ...)

## S3 method for class 'waveband'
midpoint(x, ...)

## S3 method for class 'generic_spct'
midpoint(x, ...)

## S3 method for class 'generic_mspct'
midpoint(x, ..., idx = "spct.idx")
```

Arguments

x	an R object
...	not used in current version
idx	character Name of the column with the names of the members of the collection of spectra.

Value

A numeric value equal to $(\max(x) - \min(x)) / 2$. In the case of spectral objects a wavelength in nm. For any other R object, according to available definitions of [min](#) and [max](#).

Methods (by class)

- default: Default method for generic function
- numeric: Default method for generic function
- waveband: Wavelength at center of a "waveband".

- `generic_spct`: Method for "generic_spct".
- `generic_mspct`: Method for "generic_mspct" objects.

See Also

Other wavelength summaries: [wl_min\(\)](#), [wl_range\(\)](#), [wl_stepsize\(\)](#)

Other wavelength summaries: [wl_min\(\)](#), [wl_range\(\)](#), [wl_stepsize\(\)](#)

Other wavelength summaries: [wl_min\(\)](#), [wl_range\(\)](#), [wl_stepsize\(\)](#)

Examples

```
midpoint(10:20)
midpoint(sun.spct)
wl_midpoint(sun.spct)
```

```
midpoint(sun.spct)
```

wl_min	<i>Wavelength minimum</i>
--------	---------------------------

Description

A method specialization that returns the wavelength minimum from objects of classes "waveband" or of class "generic_spct" or derived.

Usage

```
wl_min(x, na.rm = FALSE)

## S3 method for class 'waveband'
min(..., na.rm = FALSE)

## S3 method for class 'generic_spct'
min(..., na.rm = FALSE)

## S3 method for class 'generic_mspct'
min(..., na.rm = FALSE, idx = "spct.idx")
```

Arguments

<code>x</code>	generic_spct, generic_mspct or waveband object.
<code>na.rm</code>	ignored
<code>...</code>	not used in current version
<code>idx</code>	character Name of the column with the names of the members of the collection of spectra.

Methods (by class)

- generic_spct:
- generic_mspct:

See Also

Other wavelength summaries: [wl_midpoint\(\)](#), [wl_range\(\)](#), [wl_stepsize\(\)](#)

Examples

```
min(sun.spct)
wl_min(sun.spct)
```

wl_range	<i>Wavelength range</i>
----------	-------------------------

Description

A method specialization that returns the wavelength range from objects of classes "waveband" or of class "generic_spct" or derived.

Usage

```
wl_range(x, na.rm = FALSE)

## S3 method for class 'waveband'
range(..., na.rm = FALSE)

## S3 method for class 'generic_spct'
range(..., na.rm = FALSE)

## S3 method for class 'generic_mspct'
range(..., na.rm = FALSE, idx = "spct.idx")
```

Arguments

x	generic_spct, generic_mspct or waveband object.
na.rm	ignored
...	a single R object
idx	character Name of the column with the names of the members of the collection of spectra.

Methods (by class)

- generic_spct:
- generic_mspct:

See Also

Other wavelength summaries: [wl_midpoint\(\)](#), [wl_min\(\)](#), [wl_stepsize\(\)](#)

Examples

```
range(sun.spct)
wl_range(sun.spct)

range(sun.spct)
```

wl_stepsize	<i>Stepsize</i>
-------------	-----------------

Description

Function that returns the range of step sizes in an object. Range of differences between successive sorted values.

Usage

```
wl_stepsize(x, ...)

stepsize(x, ...)

## Default S3 method:
stepsize(x, ...)

## S3 method for class 'numeric'
stepsize(x, ...)

## S3 method for class 'generic_spct'
stepsize(x, ...)

## S3 method for class 'generic_mspct'
stepsize(x, ..., idx = "spct.idx")
```

Arguments

x	an R object
...	not used in current version
idx	character Name of the column with the names of the members of the collection of spectra.

Value

A numeric vector of length 2 with min and maximum stepsize values.

Methods (by class)

- `default`: Default function usable on numeric vectors.
- `numeric`: Method for numeric vectors.
- `generic_spct`: Method for "generic_spct" objects.
- `generic_mspct`: Method for "generic_mspct" objects.

See Also

Other wavelength summaries: [wl_midpoint\(\)](#), [wl_min\(\)](#), [wl_range\(\)](#)

Examples

```
stepsize(sun.spct)
wl_stepsize(sun.spct)

stepsize(sun.spct)
```

w_length2rgb

Wavelength to rgb color conversion

Description

Calculates rgb values from spectra based on human color matching functions

Usage

```
w_length2rgb(w.length, sens = photobiology::ciexyzCMF2.spct, color.name = NULL)
```

Arguments

w.length	numeric Vector of wavelengths (nm)
sens	chroma_spct Used as chromaticity definition
color.name	character Used for naming the rgb color definition

Value

A vector of colors defined using `rgb()`. The numeric values of the RGB components can be obtained using function `col2rgb()`.

See Also

Other color functions: [rgb_spct\(\)](#), [w_length_range2rgb\(\)](#)

Examples

```
col2rgb(w_length2rgb(580))
col2rgb(w_length2rgb(c(400, 500, 600, 700)))
col2rgb(w_length2rgb(c(400, 500, 600, 700), color.name=c("a", "b", "c", "d")))
col2rgb(w_length2rgb(c(400, 500, 600, 700), color.name="a"))
```

w_length_range2rgb	<i>Wavelength range to rgb color conversion</i>
--------------------	---

Description

Calculates rgb values from spectra based on human color matching functions

Usage

```
w_length_range2rgb(  
  w.length,  
  sens = photobiology::ciexyzCMF2.spct,  
  color.name = NULL  
)
```

Arguments

w.length	numeric vector of wavelengths (nm) of length 2. If longer, its range is used.
sens	chroma_spct Used as the chromaticity definition.
color.name	character Used for naming the rgb color definition(s) returned.

Value

A vector of colors defined using `rgb()`. The numeric values of the RGB components can be obtained by calling function `col2rgb`.

See Also

Other color functions: `rgb_spct()`, `w_length2rgb()`

Examples

```
col2rgb(w_length_range2rgb(c(500, 600)))
col2rgb(w_length_range2rgb(550))
col2rgb(w_length_range2rgb(500:600))
```

yellow_gel.spct	<i>Transmittance spectrum of yellow theatrical gel.</i>
-----------------	---

Description

A dataset containing the wavelengths at a 1 nm interval and fractional total transmittance for polyester film.

Usage

```
yellow_gel.spct
```

Format

A filter_spct object with 611 rows and 2 variables

Details

- w.length (nm).
- Tfr (0..1)

See Also

Other Spectral data examples: [A.illuminant.spct](#), [D65.illuminant.spct](#), [Ler_leaf.spct](#), [Ler_leaf_rflt.spct](#), [Ler_leaf_trns.spct](#), [Ler_leaf_trns_i.spct](#), [black_body.spct](#), [ccd.spct](#), [clear.spct](#), [clear_body.spct](#), [filter_cps.mspct](#), [green_leaf.spct](#), [opaque.spct](#), [photodiode.spct](#), [polyester.spct](#), [sun.daily.data](#), [sun.daily.spct](#), [sun.data](#), [sun.spct](#), [white_body.spct](#), [white_led.cps_spct](#), [white_led.raw_spct](#), [white_led.source_spct](#)

Examples

```
yellow_gel.spct
```

<code>^.generic_spct</code>	<i>Arithmetic Operators</i>
-----------------------------	-----------------------------

Description

Power operator for spectra.

Usage

```
## S3 method for class 'generic_spct'  
e1 ^ e2
```

Arguments

- e1 an object of class "generic_spct"
e2 a numeric vector. possibly of length one.

See Also

Other math operators and functions: [MathFun](#), [convolve_each\(\)](#), [div-.generic_spct](#), [log\(\)](#), [minus-.generic_spct](#), [mod-.generic_spct](#), [plus-.generic_spct](#), [round\(\)](#), [sign\(\)](#), [slash-.generic_spct](#), [times-.generic_spct](#)

Index

*Topic **datasets**

- A.illuminant.spct, 10
 - beesxyzCMF.spct, 52
 - black_body.spct, 53
 - ccd.spct, 56
 - ciev10.spct, 62
 - ciev2.spct, 63
 - cixyzCC10.spct, 64
 - cixyzCC2.spct, 65
 - cixyzCMF10.spct, 66
 - cixyzCMF2.spct, 67
 - clear.spct, 73
 - clear_body.spct, 74
 - cone_fundamentals10.spct, 79
 - D2.UV586, 86
 - D2.UV653, 86
 - D2.UV654, 87
 - D65.illuminant.spct, 88
 - FEL.BN.9101.165, 126
 - green_leaf.spct, 166
 - Ler_leaf.spct, 194
 - Ler_leaf_rflt.spct, 195
 - Ler_leaf_trns.spct, 196
 - Ler_leaf_trns_i.spct, 197
 - opaque.spct, 214
 - photodiode.spct, 222
 - polyester.spct, 228
 - sun.daily.data, 310
 - sun.daily.spct, 311
 - sun.data, 312
 - sun.spct, 313
 - white_body.spct, 374
 - white_led.cps_spct, 375
 - white_led.raw_spct, 375
 - white_led.source_spct, 376
 - wl_colors.spct, 381
 - yellow_gel.spct, 389
- *Topic **internal**.
- v_insert_hinges, 363
 - v_replace_hinges, 364
 - *.generic_spct (times-.generic_spct), 338
 - +.generic_spct (plus-.generic_spct), 227
 - .generic_spct (minus-.generic_spct), 201
 - /.generic_spct (slash-.generic_spct), 281
 - [.chroma_spct (Extract), 111
 - [.cps_spct (Extract), 111
 - [.filter_spct (Extract), 111
 - [.generic_mspct (Extract_mspct), 113
 - [.generic_spct (Extract), 111
 - [.object_spct (Extract), 111
 - [.raw_spct (Extract), 111
 - [.reflector_spct (Extract), 111
 - [.response_spct (Extract), 111
 - [.source_spct (Extract), 111
 - [<-.generic_mspct (Extract_mspct), 113
 - [<-.generic_spct (Extract), 111
 - [[<-.generic_mspct (Extract_mspct), 113
 - \$<-.generic_mspct (Extract_mspct), 113
 - \$<-.generic_spct (Extract), 111
 - %/.generic_spct (div-.generic_spct), 101
 - %/.generic_spct (mod-.generic_spct), 202
 - ^.generic_spct, 84, 101, 198, 199, 201, 202, 227, 261, 280, 281, 338, 389
 - A.illuminant.spct, 10, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389
 - A2T, 11, 21, 22, 50, 104, 105, 234, 331, 333
 - A_as_default (energy_as_default), 106
 - abs.generic_spct (MathFun), 199
 - absorbance, 12, 212
 - absorptance, 15
 - acos.generic_spct (Trig), 341
 - add_attr2tb, 14, 17, 18, 110, 116, 119, 122, 124, 135, 177, 235, 238, 241, 244,

- 247, 251, 256, 340
 Afr2T, 12, 19, 22, 50, 104, 105, 234, 331, 333
 Afr_as_default (energy_as_default), 106
 any2A (any2T), 21
 any2Afr (any2T), 21
 any2T, 12, 21, 21, 50, 104, 105, 234, 331, 333
 as.calibration_mspct, 22, 26, 28, 31, 33, 36, 39, 42, 44, 47, 297, 306
 as.calibration_spct, 24, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as.chroma_mspct, 24, 25, 28, 31, 33, 36, 39, 42, 44, 47, 297, 306
 as.chroma_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as.cps_mspct, 24, 26, 27, 31, 33, 36, 39, 42, 44, 47, 297, 306
 as.cps_spct, 25, 26, 28, 31, 34, 37, 40, 43, 45, 48, 288
 as.filter_mspct, 24, 26, 28, 29, 33, 36, 39, 42, 44, 47, 297, 306
 as.filter_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as.generic_mspct, 24, 26, 28, 31, 32, 36, 39, 42, 44, 47, 297, 306
 as.generic_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as.matrix_mspct, 34
 as.matrix.generic_mspct (as.matrix_mspct), 34
 as.object_mspct, 24, 26, 28, 31, 33, 35, 39, 42, 44, 47, 297, 306
 as.object_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as.raw_mspct, 24, 26, 28, 31, 33, 36, 38, 42, 44, 47, 297, 306
 as.raw_spct, 25, 26, 29, 31, 34, 37, 39, 43, 45, 48, 288
 as.reflector_mspct, 24, 26, 28, 31, 33, 36, 39, 40, 44, 47, 297, 306
 as.reflector_spct, 25, 26, 29, 31, 34, 37, 40, 42, 45, 48, 288
 as.response_mspct, 24, 26, 28, 31, 33, 36, 39, 42, 43, 47, 297, 306
 as.response_spct, 25, 26, 29, 31, 34, 37, 40, 43, 44, 48, 288
 as.solar_date, 45
 as.source_mspct, 24, 26, 28, 31, 33, 36, 39, 42, 44, 46, 297, 306
 as.source_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 288
 as_energy, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365
 as_quantum, 12, 21, 22, 49, 104, 105, 234, 331, 333
 as_quantum_mol, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365
 as_tod, 51
 asin.generic_spct (Trig), 341
 astrocalc4r, 91, 315
 atan.generic_spct (Trig), 341
 average_spct, 52
 beesxyzCMF.spct, 52, 63–67, 80
 black_body.spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389
 c, 54
 calc_filter_multipliers (defunct), 92
 calc_multipliers, 49, 50, 54, 102, 107, 108, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365
 calc_source_output, 55
 calibration_mspct (generic_mspct), 146
 calibration_spct (source_spct), 284
 ccd.spct, 11, 53, 56, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389
 ceiling.generic_spct (round), 261
 check_spct, 58, 61, 62, 105
 check_spectrum, 61, 61, 62, 105, 299, 300, 302
 check_w.length, 61, 62, 105
 checkTimeUnit, 57, 81–83, 158, 275
 chroma_mspct (generic_mspct), 146
 chroma_spct (source_spct), 284
 ciev10.spct, 53, 62, 64–67, 80
 ciev2.spct, 53, 63, 63, 64–67, 80
 cixyzCC10.spct, 53, 63, 64, 64, 65–67, 80
 cixyzCC2.spct, 53, 63, 64, 65, 66, 67, 80
 cixyzCMF10.spct, 53, 63–65, 66, 67, 80
 cixyzCMF2.spct, 53, 63–66, 67, 80

- class_spct, 68
- clean, 68
- clear.spct, *11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389*
- clear_body.spct, *11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389*
- clip_wl, *74, 345, 348, 350*
- col2rgb, *316, 388*
- color (color_of), 76
- color_of, 76
- colour_of (color_of), 76
- compare_spct, 78
- cone_fundamentals10.mspect
 - (cone_fundamentals10.spct), 79
- cone_fundamentals10.spct, *53, 63–67, 79*
- convertTfrType, *58, 80, 82, 83, 158, 275*
- convertThickness, *58, 81, 81, 83, 158, 275*
- convertTimeUnit, *58, 81, 82, 82, 158, 275*
- convolve_each, *83, 101, 198, 199, 201, 202, 227, 261, 280, 281, 338, 390*
- copy_attributes, 84
- cor, 329
- cos.generic_spct (Trig), 341
- cps2irrad, 85
- cps2Rfr (cps2irrad), 85
- cps2Tfr (cps2irrad), 85
- cps_mspect (generic_mspect), 146
- cps_spct (source_spct), 284

- D2.UV586, 86
- D2.UV653, 86
- D2.UV654, 87
- D2_spectrum, 87
- D65.illuminant.spct, *11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389*
- day_length (day_night), 89
- day_night, *89, 136, 183, 230, 231, 283, 315*
- day_night_fast (day_night), 89
- defunct, 92
- despike, 93
- diffraction_double_slit
 - (diffraction_single_slit), 99
- diffraction_single_slit, 99
- dim.generic_mspect, 100
- dim<- .generic_mspect
 - (dim.generic_mspect), 100
- disable_check_spct (enable_check_spct), 105
- div-.generic_spct, 101
- div_spectra, *49, 50, 55, 101, 107, 108, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365*

- e2q, *12, 21, 22, 50, 103, 104, 105, 234, 331, 333*
- e2qmol_multipliers, *12, 21, 22, 50, 104, 104, 105, 234, 331, 333*
- e2quantum_multipliers, *12, 21, 22, 50, 104, 104, 234, 331, 333*
- e_fluence, *114, 119, 135, 178, 239, 242*
- e_irrad, *116, 117, 135, 178, 239, 242*
- e_ratio, *111, 120, 236, 245*
- e_response, *123, 248, 257*
- enable_check_spct, *61, 62, 105*
- energy_as_default, 106
- energy_irradiance, *49, 50, 55, 102, 106, 108, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365*
- energy_ratio, *49, 50, 55, 102, 107, 107, 169, 171, 173, 180, 215, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 365*
- eq_ratio, *109, 123, 236, 245*
- exp.generic_spct (log), 198
- expanse (spread), 302
- extend2extremes (trim_spct), 343
- Extract, *111, 112, 113*
- Extract_mspect, 113
- Extremes, 324

- f_mspect (defunct), 92
- fast_color_of_wb (color_of), 76
- fast_color_of_wl (color_of), 76
- fast_wb2rect_spct (wb2rect_spct), 371
- FEL.BN.9101.165, 126
- FEL_spectrum, 126
- filter_cps.mspect, *11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–377, 389*
- filter_mspect (generic_mspect), 146
- filter_properties
 - (getFilterProperties), 148

- filter_properties<-
 (setFilterProperties), 263
- filter_spct (source_spct), 284
- find_peaks, 127, 129, 165, 222, 254, 294,
 363, 380
- find_spikes, 99, 128, 128, 165, 222, 254,
 294, 363, 380
- find_wls, 130
- findMultipleWl, 127
- fit_peaks, 131
- fit_valleys (fit_peaks), 131
- floor.generic_spct (round), 261
- fluence, 116, 119, 133, 178, 239, 242
- format, 137, 307
- format.solar_time, 91, 136, 136, 183, 230,
 231, 283, 315
- format.tod_time, 91, 136, 136, 183, 230,
 231, 283, 315
- formatted_range, 137
- fscale, 137, 146, 155, 156, 189, 190, 211,
 272, 274
- fshift, 142, 142, 155, 156, 189, 190, 211,
 272, 274

- generic_mspct, 146
- generic_spct (source_spct), 284
- geocode2tb (add_attr2tb), 18
- get_attributes, 149, 151–153, 160–162,
 163, 185, 186, 262, 264, 268, 270,
 276, 278, 279, 289, 342, 343
- get_peaks, 128, 129, 164, 222, 254, 294, 363,
 380
- get_valleys (get_peaks), 164
- getAfrType (defunct), 92
- getBSWFUsed, 148, 263
- getFilterProperties, 148, 151–153,
 160–162, 164, 185, 186, 262, 264,
 268, 270, 276, 278, 279, 289, 342,
 343
- getHowMeasured, 149, 150, 152, 153,
 160–162, 164, 185, 186, 262, 264,
 268, 270, 276, 278, 279, 289, 342,
 343
- getIdFactor, 151, 269
- getInstrDesc, 149, 151, 152, 153, 160–162,
 164, 185, 186, 262, 264, 268, 270,
 276, 278, 279, 289, 342, 343
- getInstrSettings, 149, 151, 152, 153,
 160–162, 164, 185, 186, 262, 264,
 268, 270, 276, 278, 279, 289, 342,
 343
- getMspctVersion, 153
- getMultipleWl, 154, 271
- getNormalised (getNormalized), 155
- getNormalized, 142, 146, 155, 156, 189, 190,
 211, 272, 274
- getRfrType, 155, 272
- getScaled, 142, 146, 155, 156, 189, 190, 211,
 272, 274
- getSpctVersion, 157
- getTfrType, 157, 274
- getTimeUnit, 58, 81–83, 158, 275
- getWhatMeasured, 149, 151–153, 159, 161,
 162, 164, 185, 186, 262, 264, 268,
 270, 276, 278, 279, 289, 342, 343
- getWhenMeasured, 149, 151–153, 160, 160,
 162, 164, 185, 186, 262, 264, 268,
 270, 276, 278, 279, 289, 342, 343
- getWhereMeasured, 149, 151–153, 160, 161,
 161, 164, 185, 186, 262, 264, 268,
 270, 276, 278, 279, 289, 342, 343
- green_leaf.spct, 11, 53, 57, 73, 74, 88, 166,
 194–197, 214, 223, 228, 310–313,
 374–377, 389

- head, 168
- head_tail, 167
- how_measured (getHowMeasured), 150
- how_measured<- (setHowMeasured), 268

- insert_hinges, 49, 50, 55, 102, 107, 108,
 168, 171, 173, 180, 215, 224, 225,
 227, 233, 299, 302, 307, 309, 317,
 347, 364, 365
- insert_spct_hinges, 169
- integrate_spct, 170
- integrate_xy, 49, 50, 55, 102, 107, 108, 169,
 171, 173, 180, 215, 224, 225, 227,
 233, 299, 302, 307, 309, 317, 347,
 364, 365
- interpolate_mspct (interpolate_spct),
 171
- interpolate_spct, 171
- interpolate_spectrum, 49, 50, 55, 102, 107,
 108, 169, 171, 173, 180, 215, 224,
 225, 227, 233, 299, 302, 307, 309,
 317, 347, 364, 365
- interpolate_wl, 174

- irrad, [116](#), [119](#), [135](#), [175](#), [239](#), [242](#)
- irradiance, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#), [171](#), [173](#), [179](#), [212](#), [215](#), [224](#), [225](#), [227](#), [233](#), [299](#), [302](#), [307](#), [309](#), [317](#), [347](#), [364](#), [365](#)
- is.any_mspct (is.generic_mspct), [180](#)
- is.any_spct (is.generic_spct), [181](#)
- is.any_summary_spct
(is.summary_generic_spct), [183](#)
- is.calibration_mspct
(is.generic_mspct), [180](#)
- is.calibration_spct (is.generic_spct), [181](#)
- is.chroma_mspct (is.generic_mspct), [180](#)
- is.chroma_spct (is.generic_spct), [181](#)
- is.cps_mspct (is.generic_mspct), [180](#)
- is.cps_spct (is.generic_spct), [181](#)
- is.filter_mspct (is.generic_mspct), [180](#)
- is.filter_spct (is.generic_spct), [181](#)
- is.generic_mspct, [180](#)
- is.generic_spct, [181](#)
- is.object_mspct (is.generic_mspct), [180](#)
- is.object_spct (is.generic_spct), [181](#)
- is.old_spct, [182](#), [354](#), [355](#)
- is.raw_mspct (is.generic_mspct), [180](#)
- is.raw_spct (is.generic_spct), [181](#)
- is.reflector_mspct (is.generic_mspct), [180](#)
- is.reflector_spct (is.generic_spct), [181](#)
- is.response_mspct (is.generic_mspct), [180](#)
- is.response_spct (is.generic_spct), [181](#)
- is.solar_date (is.solar_time), [183](#)
- is.solar_time, [91](#), [136](#), [183](#), [230](#), [231](#), [283](#), [315](#)
- is.source_mspct (is.generic_mspct), [180](#)
- is.source_spct (is.generic_spct), [181](#)
- is.summary_chroma_spct
(is.summary_generic_spct), [183](#)
- is.summary_cps_spct
(is.summary_generic_spct), [183](#)
- is.summary_filter_spct
(is.summary_generic_spct), [183](#)
- is.summary_generic_spct, [183](#)
- is.summary_object_spct
(is.summary_generic_spct), [183](#)
- is.summary_raw_spct
(is.summary_generic_spct), [183](#)
- is.summary_reflector_spct
(is.summary_generic_spct), [183](#)
- is.summary_response_spct
(is.summary_generic_spct), [183](#)
- is.summary_source_spct
(is.summary_generic_spct), [183](#)
- is.waveband, [184](#)
- is_absorbance_based, [186](#), [190](#)
- is_absorptance_based
(is_absorbance_based), [186](#)
- is_effective, [187](#), [193](#), [207](#)
- is_energy_based (is_photon_based), [189](#)
- is_normalised (is_normalized), [188](#)
- is_normalized, [142](#), [146](#), [155](#), [156](#), [188](#), [190](#), [211](#), [272](#), [274](#)
- is_photon_based, [187](#), [189](#)
- is_scaled, [142](#), [146](#), [155](#), [156](#), [189](#), [190](#), [211](#), [272](#), [274](#)
- is_tagged, [191](#), [334](#), [353](#), [372](#), [373](#)
- is_transmittance_based
(is_absorbance_based), [186](#)
- is_valid_geocode (validate_geocode), [356](#)
- isValidInstrDesc, [149](#), [151–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- isValidInstrSettings, [149](#), [151–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- join, [200](#)
- join_mspct, [191](#)
- l_insert_hinges, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#), [171](#), [173](#), [180](#), [215](#), [224](#), [225](#), [227](#), [233](#), [299](#), [302](#), [307](#), [309](#), [317](#), [347](#), [364](#), [365](#)
- labels, [188](#), [193](#), [207](#)
- lat2tb (add_attr2tb), [18](#)
- length_geocode (validate_geocode), [356](#)
- Ler_leaf.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#), [194](#), [195–197](#), [214](#), [223](#), [228](#), [310–313](#), [374–377](#), [389](#)
- Ler_leaf_rflt.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#), [194](#), [195](#), [196](#), [197](#), [214](#), [223](#), [228](#), [310–313](#), [374–377](#), [389](#)
- Ler_leaf_trns.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#), [194](#), [195](#), [196](#), [197](#), [214](#), [223](#), [228](#), [310–313](#), [374–377](#), [389](#)

- Ler_leaf_trns_i.spct, [11](#), [53](#), [57](#), [73](#), [74](#),
[88](#), [166](#), [194–196](#), [197](#), [214](#), [223](#),
[228](#), [310–313](#), [374–377](#), [389](#)
 log, [84](#), [101](#), [198](#), [199](#), [201](#), [202](#), [227](#), [261](#),
[280](#), [281](#), [338](#), [390](#)
 log10.generic_spct (log), [198](#)
 log2.generic_spct (log), [198](#)
 lon2tb (add_attr2tb), [18](#)
 lonlat2tb (add_attr2tb), [18](#)

 mat2mspct (as.generic_mspct), [32](#)
 MathFun, [84](#), [101](#), [198](#), [199](#), [201](#), [202](#), [227](#),
[261](#), [280](#), [281](#), [338](#), [390](#)
 max, [303](#), [383](#)
 max (wl_max), [382](#)
 mean, [318](#), [320](#)
 median, [321](#)
 merge2object_spct, [199](#)
 merge_attributes, [200](#)
 midpoint (wl_midpoint), [383](#)
 min, [303](#), [383](#)
 min (wl_min), [384](#)
 minus-.generic_spct, [201](#)
 mod-.generic_spct, [202](#)
 msaply (msmsply), [202](#)
 msdply (msmsply), [202](#)
 mslply (msmsply), [202](#)
 msmsply, [202](#)
 mspct2mat (as.matrix_mspct), [34](#)
 mspct_classes, [203](#)
 mutate_mspct (defunct), [92](#)

 NA, [137](#)
 na.action, [206](#)
 na.exclude.chroma_spct (na.omit), [204](#)
 na.exclude.cps_spct (na.omit), [204](#)
 na.exclude.filter_spct (na.omit), [204](#)
 na.exclude.generic_mspct (na.omit), [204](#)
 na.exclude.generic_spct (na.omit), [204](#)
 na.exclude.object_spct (na.omit), [204](#)
 na.exclude.raw_spct (na.omit), [204](#)
 na.exclude.reflector_spct (na.omit), [204](#)
 na.exclude.response_spct (na.omit), [204](#)
 na.exclude.source_spct (na.omit), [204](#)
 na.fail, [206](#)
 na.omit, [204](#)
 na_geocode (validate_geocode), [356](#)
 NDxI (normalized_diff_ind), [211](#)
 new_waveband (waveband), [368](#)

 night_length (day_night), [89](#)
 noon_time (day_night), [89](#)
 normalise (normalize), [207](#)
 normalised_diff_ind
 (normalized_diff_ind), [211](#)
 normalization, [188](#), [193](#), [206](#)
 normalize, [142](#), [146](#), [155](#), [156](#), [189](#), [190](#), [207](#),
[272](#), [274](#)
 normalize_range_arg, [213](#)
 normalized_diff_ind, [211](#)

 object_mspct (generic_mspct), [146](#)
 object_spct (source_spct), [284](#)
 opaque.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#),
[194–197](#), [214](#), [223](#), [228](#), [310–313](#),
[374–377](#), [389](#)
 oper_spectra, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#),
[171](#), [173](#), [180](#), [214](#), [224](#), [225](#), [227](#),
[233](#), [299](#), [302](#), [307](#), [309](#), [317](#), [347](#),
[364](#), [365](#)

 paste, [137](#)
 peaks, [128](#), [129](#), [165](#), [216](#), [254](#), [294](#), [363](#), [380](#)
 photobiology (photobiology-package), [8](#)
 photobiology-package, [8](#)
 photobiologyWavebands, [212](#)
 photodiode.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#),
[194–197](#), [214](#), [222](#), [228](#), [310–313](#),
[374–377](#), [389](#)
 photon_as_default (energy_as_default),
[106](#)
 photon_irradiance, [49](#), [50](#), [55](#), [102](#), [107](#),
[108](#), [169](#), [171](#), [173](#), [180](#), [215](#), [224](#),
[224](#), [227](#), [233](#), [299](#), [302](#), [307](#), [309](#),
[317](#), [347](#), [364](#), [365](#)
 photon_ratio, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#),
[171](#), [173](#), [180](#), [215](#), [224](#), [225](#), [226](#),
[233](#), [299](#), [302](#), [307](#), [309](#), [317](#), [347](#),
[364](#), [365](#)
 photons_energy_ratio, [49](#), [50](#), [55](#), [102](#), [107](#),
[108](#), [169](#), [171](#), [173](#), [180](#), [216](#), [223](#),
[225](#), [227](#), [233](#), [299](#), [302](#), [307](#), [309](#),
[317](#), [347](#), [364](#), [365](#)
 plus-.generic_spct, [227](#)
 polyester.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#),
[194–197](#), [214](#), [223](#), [228](#), [310–313](#),
[374–377](#), [389](#)
 print, [228](#)
 print.solar_date (print.solar_time), [229](#)

- print.solar_time, [91](#), [136](#), [183](#), [229](#), [231](#), [283](#), [315](#)
- print.summary_generic_spct, [230](#)
- print.tod_time, [91](#), [136](#), [183](#), [230](#), [231](#), [283](#), [315](#)
- print.waveband, [231](#)
- prod, [323](#)
- prod_spectra, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#), [171](#), [173](#), [180](#), [216](#), [224](#), [225](#), [227](#), [232](#), [299](#), [302](#), [307](#), [309](#), [317](#), [347](#), [364](#), [365](#)
- q2e, [12](#), [21](#), [22](#), [50](#), [104](#), [105](#), [233](#), [331](#), [333](#)
- q_fluence, [116](#), [119](#), [135](#), [178](#), [237](#), [242](#)
- q_irrad, [116](#), [119](#), [135](#), [178](#), [239](#), [239](#)
- q_ratio, [111](#), [123](#), [236](#), [242](#)
- q_response, [125](#), [245](#), [257](#)
- qe_ratio, [111](#), [123](#), [234](#), [245](#)
- quantum_as_default (energy_as_default), [106](#)
- range, [137](#)
- range (wl_range), [385](#)
- raw_mspct (generic_mspct), [146](#)
- raw_spct (source_spct), [284](#)
- rbindspect, [248](#)
- reflectance, [212](#), [250](#)
- reflector_mspct (generic_mspct), [146](#)
- reflector_spct (source_spct), [284](#)
- relative_AM, [252](#)
- replace_bad_pixs, [99](#), [128](#), [129](#), [165](#), [222](#), [253](#), [294](#), [363](#), [380](#)
- response, [125](#), [212](#), [248](#), [255](#)
- response_mspct (generic_mspct), [146](#)
- response_spct (source_spct), [284](#)
- Rfr_from_n, [257](#)
- Rfr_p_from_n (Rfr_from_n), [257](#)
- Rfr_s_from_n (Rfr_from_n), [257](#)
- rgb, [316](#)
- rgb_spct, [258](#), [387](#), [388](#)
- rmDerivedMspct, [259](#), [280](#)
- rmDerivedSpct, [260](#), [267](#)
- round, [84](#), [101](#), [198](#), [199](#), [201](#), [202](#), [227](#), [261](#), [280](#), [281](#), [338](#), [390](#)
- s_e_irrad2rgb, [49](#), [50](#), [55](#), [102](#), [107](#), [108](#), [169](#), [171](#), [173](#), [180](#), [216](#), [224](#), [225](#), [227](#), [233](#), [299](#), [302](#), [307](#), [309](#), [316](#), [347](#), [364](#), [365](#)
- s_mean, [317](#)
- s_mean_se, [319](#)
- s_median, [320](#)
- s_prod, [321](#)
- s_range, [323](#)
- s_sd, [324](#)
- s_se, [325](#)
- s_sum, [327](#)
- s_var, [328](#)
- sd, [325](#)
- select_spct_attributes, [149](#), [151–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- set_check_spct (enable_check_spct), [105](#)
- setAfrType (defunct), [92](#)
- setBSWFUsed, [148](#), [263](#)
- setCalibrationSpct (setGenericSpct), [265](#)
- setChromaSpct (setGenericSpct), [265](#)
- setCpsSpct (setGenericSpct), [265](#)
- setFilterProperties, [149](#), [151–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [263](#), [268](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- setFilterSpct (setGenericSpct), [265](#)
- setGenericSpct, [25](#), [26](#), [29](#), [31](#), [34](#), [37](#), [40](#), [43](#), [45](#), [48](#), [260](#), [265](#)
- setHowMeasured, [149](#), [151–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- setIdFactor, [152](#), [269](#)
- setInstrDesc, [150–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [269](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- setInstrSettings, [150–153](#), [160–162](#), [164](#), [185](#), [186](#), [262](#), [264](#), [268](#), [270](#), [270](#), [276](#), [278](#), [279](#), [289](#), [342](#), [343](#)
- setMultipleWL, [154](#), [271](#)
- setNormalised (setNormalized), [271](#)
- setNormalized, [142](#), [146](#), [155](#), [156](#), [189](#), [190](#), [211](#), [271](#), [274](#)
- setObjectSpct (setGenericSpct), [265](#)
- setRawSpct (setGenericSpct), [265](#)
- setReflectorSpct (setGenericSpct), [265](#)
- setResponseSpct (setGenericSpct), [265](#)
- setRfrType, [156](#), [272](#)
- setScaled, [142](#), [146](#), [155](#), [156](#), [189](#), [190](#), [211](#), [272](#), [273](#)

- setSourceSpct (setGenericSpct), 265
- setTfrType, 158, 274
- setTimeUnit, 58, 81–83, 158, 275
- setWhatMeasured, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 278, 279, 289, 342, 343
- setWhenMeasured, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 277, 279, 289, 342, 343
- setWhereMeasured, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 278, 278, 289, 342, 343
- shared_member_class, 260, 280
- sign, 84, 101, 198, 199, 201, 202, 227, 261, 280, 281, 338, 390
- signif.generic_spct (round), 261
- sin.generic_spct (Trig), 341
- slash-.generic_spct, 281
- smooth_spct, 281
- solar_time, 91, 136, 183, 230, 231, 283, 315
- source_mspct (generic_mspct), 146
- source_spct, 25, 26, 29, 31, 34, 37, 40, 43, 45, 48, 284
- spct_attr2tb, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 278, 279, 288, 342, 343
- spct_attributes
 - (select_spct_attributes), 262
- spct_classes, 289
- spikes, 128, 129, 165, 222, 254, 289, 363, 380
- splinefun, 173
- split2calibration_mspct (split2mspct), 294
- split2cps_mspct (split2mspct), 294
- split2filter_mspct (split2mspct), 294
- split2mspct, 24, 26, 28, 31, 33, 36, 39, 42, 44, 47, 294, 306
- split2raw_mspct (split2mspct), 294
- split2reflector_mspct (split2mspct), 294
- split2response_mspct (split2mspct), 294
- split2source_mspct (split2mspct), 294
- split_bands, 297, 369
- split_energy_irradiance, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 298, 302, 307, 309, 317, 347, 364, 365
- split_irradiance, 299
- split_photon_irradiance, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 301, 307, 309, 317, 347, 364, 365
- spread, 302
- sqrt.generic_spct (MathFun), 199
- stepsize (wl_stepsize), 386
- strict_range_as_default
 - (verbose_as_default), 363
- Subset, 304
- subset, 113
- subset.generic_spct (Subset), 304
- subset2mspct, 24, 26, 28, 31, 33, 36, 39, 42, 44, 47, 297, 305
- subt_spectra, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 302, 306, 309, 317, 347, 364, 365
- sum, 328
- sum_spectra, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 302, 307, 308, 317, 347, 364, 365
- summary, 307
- summary_spct_classes, 308
- sun.daily.data, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310, 311–313, 374–377, 389
- sun.daily.spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310, 311, 312, 313, 374–377, 389
- sun.data, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310, 311, 312, 313, 374–377, 389
- sun.spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–312, 313, 374–377, 389
- sun_angles, 91, 136, 183, 230, 231, 283, 314
- sun_angles_fast (sun_angles), 314
- sun_azimuth (sun_angles), 314
- sun_elevation (sun_angles), 314
- sun_zenith_angle (sun_angles), 314
- sunrise_time (day_night), 89
- sunset_time (day_night), 89
- T2A, 12, 21, 22, 50, 104, 105, 234, 330, 333
- T2Afr, 12, 21, 22, 50, 104, 105, 234, 331, 331
- T2T (defunct), 92
- tag, 78, 191, 333, 353, 372, 373
- tan.generic_spct (Trig), 341

- Tfr_as_default (energy_as_default), 106
 thin_wl, 335, 352
 times-.generic_spct, 338
 transmittance, 212, 338
 Trig, 341
 trim2overlap (trim_spct), 343
 trim_mspect (trim_spct), 343
 trim_spct, 75, 113, 343, 348, 350
 trim_tails, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 302, 307, 309, 317, 346, 364, 365
 trim_waveband, 75, 345, 347, 350
 trim_wl, 75, 345, 348, 349
 trimInstrDesc, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 278, 279, 289, 342, 343
 trimInstrSettings, 150–153, 160–162, 164, 185, 186, 262, 264, 268, 270, 276, 278, 279, 289, 342, 343
 trunc.generic_spct (round), 261
 tz_time_diff, 351

 uncollect, 337, 351
 unset_filter_qty_default (energy_as_default), 106
 unset_radiation_unit_default (energy_as_default), 106
 unset_user_defaults (energy_as_default), 106
 untag, 191, 334, 353, 372, 373
 upgrade_spct, 183, 354, 355
 upgrade_spectra, 183, 354, 354
 use_cached_mult_as_default (wb_trim_as_default), 374
 using_A (using_Tfr), 355
 using_Afr (using_Tfr), 355
 using_energy (using_Tfr), 355
 using_photon (using_Tfr), 355
 using_quantum (using_Tfr), 355
 using_Tfr, 355

 v_insert_hinges, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 363, 365
 v_replace_hinges, 49, 50, 55, 102, 107, 108, 169, 171, 173, 180, 216, 224, 225, 227, 233, 299, 302, 307, 309, 317, 347, 364, 364
 validate_geocode, 356
 valleys, 128, 129, 165, 222, 254, 294, 357, 380
 verbose_as_default, 363

 w_length2rgb, 259, 387, 388
 w_length_range2rgb, 259, 387, 388
 water_dp (water_vp_sat), 365
 water_fp (water_vp_sat), 365
 water_mvc2vp (water_vp_sat), 365
 water_RH2vp (water_vp_sat), 365
 water_vp2mvc (water_vp_sat), 365
 water_vp2RH (water_vp_sat), 365
 water_vp_sat, 365
 waveband, 77, 207, 297, 368
 waveband_ratio, 370
 wb2rect_spct, 191, 334, 353, 371, 373
 wb2spct, 191, 334, 353, 372, 372, 373
 wb2tagged_spct, 191, 334, 353, 372, 373, 373
 wb_trim_as_default, 374
 what_measured (getWhatMeasured), 159
 what_measured2tb (add_attr2tb), 18
 what_measured<- (setWhatMeasured), 276
 when_measured (getWhenMeasured), 160
 when_measured2tb (add_attr2tb), 18
 when_measured<- (setWhenMeasured), 277
 where_measured (getWhereMeasured), 161
 where_measured<- (setWhereMeasured), 278
 white_body.spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374, 375–377, 389
 white_led.cps_spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374, 375, 376, 377, 389
 white_led.raw_spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374, 375, 375, 377, 389
 white_led.source_spct, 11, 53, 57, 73, 74, 88, 166, 194–197, 214, 223, 228, 310–313, 374–376, 376, 389
 wl_colors.spct, 381
 wl_expance (spread), 302
 wl_max, 382
 wl_midpoint, 383, 385–387
 wl_min, 384, 384, 386, 387
 wl_range, 384, 385, 385, 387
 wl_stepsize, 384–386, 386

wls_at_target, [128](#), [129](#), [165](#), [222](#), [254](#), [294](#),
[363](#), [377](#)

yellow_gel.spct, [11](#), [53](#), [57](#), [73](#), [74](#), [88](#), [166](#),
[194–197](#), [214](#), [223](#), [228](#), [310–313](#),
[374–377](#), [389](#)