

Package ‘pollster’

May 26, 2020

Type Package

Title Calculate Crosstab and Topline Tables of Weighted Survey Data

Version 0.1.2

Author John D. Johnson [aut, cre]

Maintainer John D. Johnson <john.d.johnson@marquette.edu>

Description Calculate common types of tables for weighted survey data. Options include topline and (2-way and 3-way) crosstab tables of categorical or ordinal data as well as summary tables of weighted numeric variables. Optionally, include the margin of error at selected confidence intervals including the design effect. The design effect is calculated as described by Kish (1965) <doi:10.1002/bimj.19680100122> beginning on page 257. Output takes the form of tibbles (simple data frames). This package conveniently handles labelled data, such as that commonly used by 'Stata' and 'SPSS.' Complex survey design is not supported at this time.

Depends R (>= 2.10)

Imports dplyr (>= 0.8.0), stringr (>= 1.0.0), tidyr (>= 1.1.0), labelled (>= 2.0.0), forcats, rlang (>= 0.4.5)

Suggests ggplot2 (>= 3.3.0), knitr, rmarkdown

License CC0

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-05-26 20:00:03 UTC

R topics documented:

crosstab	2
crosstab_3way	3
deff_calc	4
illinois	5
moedeff_calc	6
moe_crosstab	6
moe_crosstab_3way	8
moe_topline	9
moe_wave_crosstab	10
moe_wave_crosstab_3way	11
summary_table	12
topline	13
wtd_mean	14

Index	15
--------------	-----------

crosstab	<i>weighted crosstabs</i>
----------	---------------------------

Description

crosstab returns a tibble containing a weighted crosstab of two variables

Usage

```
crosstab(
  df,
  x,
  y,
  weight,
  remove = "",
  n = TRUE,
  pct_type = "row",
  format = "wide"
)
```

Arguments

df	The data source
x	The independent variable
y	The dependent variable
weight	The weighting variable
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.

n	logical, if TRUE numeric totals are included. They are included in a separate column for row and cell percentages, but in a separate row for wide format column percentages.
pct_type	Controls the kind of percentage values returned. One of "row," "cell," or "column."
format	one of "long" or "wide"

Details

Options include row, column, or cell percentages. The tibble can be in long or wide format.

Value

a tibble

Examples

```
crosstab(df = illinois, x = voter, y = raceethnic, weight = weight)
crosstab(df = illinois, x = voter, y = raceethnic, weight = weight, n = FALSE)
```

crosstab_3way	<i>weighted 3-way crosstabs</i>
---------------	---------------------------------

Description

crosstab_3way returns a tibble containing a weighted crosstab of two variables by a third variable

Usage

```
crosstab_3way(
  df,
  x,
  y,
  z,
  weight,
  remove = c(""),
  n = TRUE,
  pct_type = "row",
  format = "wide"
)
```

Arguments

df	The data source
x	The independent variable
y	The dependent variable

z	The second control variable
weight	The weighting variable
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE numeric totals are included.
pct_type	Controls the kind of percentage values returned. One of "row" or "cell."
format	one of "long" or "wide"

Details

Options include row or cell percentages. The tibble can be in long or wide format. These tables are ideal for use with small multiples created with `ggplot2::facet_wrap`.

Value

a tibble

Examples

```
crosstab_3way(df = illinois, x = sex, y = educ6, z = maritalstatus, weight = weight)
crosstab_3way(df = illinois, x = sex, y = educ6, z = maritalstatus, weight = weight,
format = "wide")
```

deff_calc

Calculate the design effect of a sample

Description

deff_calc returns a single number

Usage

```
deff_calc(w)
```

Arguments

w a vector of weights

Details

This function returns the design effect of a given sample using the formula $\text{length}(w) * \text{sum}(w^2) / (\text{sum}(w)^2)$. It is designed for use in the moe family of functions.

Value

A number

Examples

```
deff_calc(illinois$weight)
```

illinois	<i>Illinois respondents to the Voting and Registration Supplement for the Current Population Survey</i>
----------	---

Description

A dataset containing the responses of 36,207 Illinois respondents to the Current Population Survey's biennial Voting and Registration Supplement for the Current Population Survey, 1996-2018.

Usage

```
illinois
```

Format

A data frame with 36207 rows and 9 variables:

year year of survey

fips the state fips code

sex sex of the respondent, labelled value

educ6 highest level of education for respondent, labelled values

raceethnic one of white, black, Hispanic, or other, labelled values

maritalstatus one of Married, Widowed/divorced/Sep, or Never Married, labelled values

rv indicates if the respondent is registered to vote, labelled values

voter indicates if the respondent voted, labelled values

age the age of the respondent, numeric values

weight the number of people each respondent is calculated to represent

Source

<https://www.census.gov/topics/public-sector/voting.html>

moedeff_calc	<i>Calculate the margin of error (including design effect) of a sample</i>
--------------	--

Description

moedeff_calc returns a single number. It is designed for use in the moe family of functions.

Usage

```
moedeff_calc(pct, deff, n, zscore = 1.96)
```

Arguments

pct	a proportion
deff	a design effect
n	the sample size
zscore	defaults to 1.96, consistent with a 95% confidence interval.

Details

This function returns the margin of error including design effect of a given sample of weighted data using the formula $\text{sqrt}(\text{deff}) * \text{zscore} * \text{sqrt}(\text{pct} * (1 - \text{pct}) / (n - 1)) * 100$

Value

A percentage

Examples

```
moedeff_calc(pct = 0.515, deff = 1.6, n = 214)
```

moe_crosstab	<i>weighted crosstabs with margin of error</i>
--------------	--

Description

moe_crosstab returns a tibble containing a weighted crosstab of two variables with margin of error

Usage

```
moe_crosstab(  
  df,  
  x,  
  y,  
  weight,  
  remove = c(""),  
  n = TRUE,  
  pct_type = "row",  
  format = "long",  
  zscore = 1.96  
)
```

Arguments

df	The data source
x	The independent variable
y	The dependent variable
weight	The weighting variable, defaults to zwave_weight
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE numeric totals are included.
pct_type	Controls the kind of percentage values returned. One of "row" or "cell." Column percents are not supported.
format	one of "long" or "wide"
zscore	defaults to 1.96, consistent with a 95% confidence interval

Details

Options include row or cell percentages. The tibble can be in long or wide format. The margin of error includes the design effect of the weights.

Value

a tibble

Examples

```
moe_crosstab(df = illinois, x = voter, y = raceethnic, weight = weight)  
moe_crosstab(df = illinois, x = voter, y = raceethnic, weight = weight, n = FALSE)
```

moe_crosstab_3way	<i>weighted 3-way crosstabs with margin of error</i>
-------------------	--

Description

moe_crosstab_3way returns a tibble containing a weighted crosstab of two variables by a third variable with margin of error

Usage

```
moe_crosstab_3way(  
  df,  
  x,  
  y,  
  z,  
  weight,  
  remove = c(""),  
  n = TRUE,  
  pct_type = "row",  
  format = "long",  
  zscore = 1.96  
)
```

Arguments

df	The data source
x	The independent variable
y	The dependent variable
z	The second control variable
weight	The weighting variable
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE numeric totals are included.
pct_type	Controls the kind of percentage values returned. One of "row" or "cell."
format	one of "long" or "wide"
zscore	defaults to 1.96, consistent with a 95% confidence interval

Details

Options include row or cell percentages. The tibble can be in long or wide format. These tables are ideal for use with small multiples created with `ggplot2::facet_wrap`.

Value

a tibble

Examples

```
moe_crosstab_3way(df = illinois, x = sex, y = educ6, z = maritalstatus, weight = weight)
moe_crosstab_3way(df = illinois, x = sex, y = educ6, z = maritalstatus, weight = weight,
format = "wide")
```

moe_topline	<i>weighted topline with margin of error</i>
-------------	--

Description

moe_topline returns a tibble containing a weighted topline of one variable with margin of error

Usage

```
moe_topline(
  df,
  variable,
  weight,
  remove = c(""),
  n = TRUE,
  pct = TRUE,
  valid_pct = TRUE,
  cum_pct = TRUE,
  zscore = 1.96
)
```

Arguments

df	The data source
variable	the variable name
weight	The weighting variable, defaults to zwave_weight
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE a frequency column is included percentages, but in a separate row for column percentages.
pct	logical, if TRUE a column of percents is included
valid_pct	logical, if TRUE a column of valid percents is included
cum_pct	logical, if TRUE a column of cumulative percents is included
zscore	defaults to 1.96, consistent with a 95% confidence interval

Details

By default the table includes a column for frequency count, percent, valid percent, and cumulative percent.

Value

a tibble

Examples

```
moe_topleft(df = illinois, variable = educ6, weight = weight)
moe_topleft(df = illinois, variable = educ6, weight = weight, remove = c("LT HS"))
```

moe_wave_crosstab	<i>weighted crosstabs with margin of error, where the x-variable identifies different survey waves</i>
-------------------	--

Description

moe_wave_crosstab returns a tibble containing a weighted crosstab of two variables with margin of error. Use this function when the x-variable indicates different survey waves for which weights were calculated independently.

Usage

```
moe_wave_crosstab(
  df,
  x,
  y,
  weight,
  remove = c(""),
  n = TRUE,
  pct_type = "row",
  format = "long",
  zscore = 1.96
)
```

Arguments

df	The data source
x	The independent variable, which uniquely identifies survey waves
y	The dependent variable
weight	The weighting variable, defaults to zwave_weight
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.

n	logical, if TRUE numeric totals are included.
pct_type	Controls the kind of percentage values returned. One of "row" or "cell." Column percents are not supported.
format	one of "long" or "wide"
zscore	defaults to 1.96, consistent with a 95% confidence interval

Details

Options include row or cell percentages. The tibble can be in long or wide format. The margin of error includes the design effect of the weights, calculated separately for each survey wave.

Value

a tibble

Examples

```
moe_wave_crosstab(df = illinois, x = year, y = maritalstatus, weight = weight)
moe_wave_crosstab(df = illinois, x = year, y = maritalstatus, weight = weight, format = "wide")
```

moe_wave_crosstab_3way

weighted 3-way crosstabs with margin of error, where the z-variable identifies different survey waves

Description

moe_wave_crosstab_3way returns a tibble containing a weighted crosstab of two variables by a third variable with margin of error. Use this function when the z-variable indicates different survey waves for which weights were calculated independently.

Usage

```
moe_wave_crosstab_3way(
  df,
  x,
  y,
  z,
  weight,
  remove = c(""),
  n = TRUE,
  pct_type = "row",
  format = "long",
  zscore = 1.96
)
```

Arguments

df	The data source
x	The independent variable
y	The dependent variable
z	The second control variable, uniquely identifies survey waves
weight	The weighting variable
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE numeric totals are included.
pct_type	Controls the kind of percentage values returned. One of "row" or "cell."
format	one of "long" or "wide"
zscore	defaults to 1.96, consistent with a 95% confidence interval

Details

Options include row or cell percentages. The tibble can be in long or wide format. These tables are ideal for use with small multiples created with `ggplot2::facet_wrap`.

Value

a tibble

Examples

```
moe_crosstab_3way(df = illinois, x = sex, y = educ6, z = year, weight = weight)
moe_crosstab_3way(df = illinois, x = sex, y = educ6, z = year, weight = weight, format = "wide")
```

summary_table	<i>weighted summary table</i>
---------------	-------------------------------

Description

`summary_table` returns a tibble containing a weighted summary table of a single variable.

Usage

```
summary_table(df, variable, weight, name_style = "clean")
```

Arguments

df	The data source
variable	the variable to summarize, it should be numeric
weight	The weighting variable
name_style	the style of the column names—one of "clean" or "pretty." Clean names are all lower case and words are separated by an underscore. Pretty names begin with a capital letter are words a separated by a space.

Details

The resulting tibble includes columns for the variable name, unweighted observations, weighted observations, weighted mean, minimum value, maximum value, unweighted missing values, and weighted missing values

Value

a tibble

Examples

```
summary_table(illinois, age, weight)
summary_table(illinois, age, weight, name_style = "pretty")
```

topline	<i>weighted topline</i>
---------	-------------------------

Description

topline returns a tibble containing a weighted topline of one variable

Usage

```
topline(
  df,
  variable,
  weight,
  remove = c(""),
  n = TRUE,
  pct = TRUE,
  valid_pct = TRUE,
  cum_pct = TRUE
)
```

Arguments

df	The data source
variable	the variable name
weight	The weighting variable, defaults to <code>zwave_weight</code>
remove	An optional character vector of values to remove from final table (e.g. "refused"). This will not affect any calculations made. The vector is not case-sensitive.
n	logical, if TRUE a frequency column is included percentages, but in a separate row for column percentages.
pct	logical, if TRUE a column of percents is included
valid_pct	logical, if TRUE a column of valid percents is included
cum_pct	logical, if TRUE a column of cumulative percents is included

Details

By default the table includes a column for frequency count, percent, valid percent, and cumulative percent.

Value

a tibble

Examples

```
topline(illinois, sex, weight)
topline(illinois, sex, weight, pct = FALSE)
```

wtd_mean	<i>weighted mean</i>
----------	----------------------

Description

wtd_mean returns the weighted mean of a variable. It's a tidy-compatible wrapper around stats::weighted.mean().

Usage

```
wtd_mean(df, variable, weight)
```

Arguments

df	The data source
variable	the variable, it should be numeric
weight	The weighting variable

Value

a numeric value

Examples

```
wtd_mean(illinois, age, weight)

library(dplyr)
illinois %>% wtd_mean(age, weight)
```

Index

*Topic **datasets**

illinois, [5](#)

crosstab, [2](#)

crosstab_3way, [3](#)

deff_calc, [4](#)

illinois, [5](#)

moe_crosstab, [6](#)

moe_crosstab_3way, [8](#)

moe_topline, [9](#)

moe_wave_crosstab, [10](#)

moe_wave_crosstab_3way, [11](#)

moedeff_calc, [6](#)

summary_table, [12](#)

topline, [13](#)

wtd_mean, [14](#)