

Package ‘prediction’

June 17, 2019

Type Package

Title Tidy, Type-Safe ‘prediction()’ Methods

Description A one-function package containing ‘prediction()’, a type-safe alternative to ‘predict()’ that always returns a data frame. The ‘summary()’ method provides a data frame with average predictions, possibly over counterfactual versions of the data (a la the ‘margins’ command in ‘Stata’). Marginal effect estimation is provided by the related package, ‘margins’ <<https://cran.r-project.org/package=margins>>. The package currently supports common model types (e.g., ‘`lm`’, ‘`glm`’) from the ‘stats’ package, as well as numerous other model classes from other add-on packages. See the README or main package documentation page for a complete listing.

License MIT + file LICENSE

Version 0.3.14

Date 2019-06-16

URL <https://github.com/leeper/prediction>

BugReports <https://github.com/leeper/prediction/issues>

Depends R (>= 3.5.0)

Imports utils, stats, data.table

Suggests datasets, methods, testthat

Enhances AER, aod, betareg, biglm, brglm, caret, crch, e1071, earth, ff, ffbase, gam (>= 1.15), gee, glmnet, glmx, kernlab, lme4, MASS, mcllogit, mda, mlogit, MNP, nlme, nnet, ordinal, plm, pscl, quantreg, rpart, sampleSelection, speedglm, survey (>= 3.31-5), survival, truncreg, VGAM

ByteCompile true

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author Thomas J. Leeper [aut, cre] (<<https://orcid.org/0000-0003-4097-6326>>),
Carl Ganz [ctb],
Vincent Arel-Bundock [ctb] (<<https://orcid.org/0000-0003-2042-7063>>)

Maintainer Thomas J. Leeper <thosjleeper@gmail.com>

Repository CRAN

Date/Publication 2019-06-17 19:40:03 UTC

R topics documented:

prediction-package	2
build_datalist	11
find_data	12
margex	14
mean_or_mode	15
seq_range	17

Index

[18](#)

prediction-package	<i>Extract Predictions from a Model Object</i>
------------------------------------	--

Description

Extract predicted values via [predict](#) from a model object, conditional on data, and return a data frame.

Usage

```

prediction(model, ...)

## Default S3 method:
prediction(model, data = find\_data(model,
  parent.frame()), at = NULL, type = "response",
  vcov = stats::vcov(model), calculate_se = TRUE, ...)

## S3 method for class 'Arima'
prediction(model, calculate_se = TRUE, ...)

## S3 method for class 'ar'
prediction(model, data, at = NULL, calculate_se = TRUE,
  ...)

## S3 method for class 'arima0'
prediction(model, data, at = NULL,
  calculate_se = TRUE, ...)

## S3 method for class 'betareg'
prediction(model, data = find\_data(model,
  parent.frame()), at = NULL, type = c("response", "link", "precision",
  ...

```

```
"variance", "quantile"), calculate_se = FALSE, ...)

## S3 method for class 'biglm'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = "response", calculate_se = TRUE,
...)

## S3 method for class 'bruto'
prediction(model, data = NULL, at = NULL,
  type = "fitted", calculate_se = FALSE, ...)

## S3 method for class 'clm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = TRUE, category, ...)

## S3 method for class 'coxph'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("risk", "expected", "lp"),
  calculate_se = TRUE, ...)

## S3 method for class 'crch'
prediction(model, data = find_data(model), at = NULL,
  type = c("response", "location", "scale", "quantile"),
  calculate_se = FALSE, ...)

## S3 method for class 'earth'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("response", "link"),
  calculate_se = TRUE, category, ...)

## S3 method for class 'fda'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'Gam'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link", "terms"),
  calculate_se = TRUE, ...)

## S3 method for class 'gausspr'
prediction(model, data, at = NULL, type = NULL,
  calculate_se = TRUE, category, ...)

## S3 method for class 'gee'
prediction(model, calculate_se = FALSE, ...)

## S3 method for class 'glimML'
prediction(model, data = find_data(model,
```

```
parent.frame()), at = NULL, type = c("response", "link"),
calculate_se = TRUE, ...)

## S3 method for class 'glimQL'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, type = c("response", "link"),
calculate_se = TRUE, ...)

## S3 method for class 'glm'
prediction(model, data = find_data(model, parent.frame()),
at = NULL, type = c("response", "link"), vcov = stats::vcov(model),
calculate_se = TRUE, ...)

## S3 method for class 'glmnet'
prediction(model, data, lambda = model[["lambda"]][1L],
at = NULL, type = c("response", "link"), calculate_se = FALSE, ...)

## S3 method for class 'glmx'
prediction(model, data = find_data(model, parent.frame()),
at = NULL, type = c("response", "link"), calculate_se = FALSE, ...)

## S3 method for class 'gls'
prediction(model, data = find_data(model), at = NULL,
calculate_se = FALSE, ...)

## S3 method for class 'hetglm'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, type = c("response", "link", "scale"),
calculate_se = FALSE, ...)

## S3 method for class 'hurdle'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, type = c("response", "count", "prob",
"zero"), calculate_se = FALSE, ...)

## S3 method for class 'hxlr'
prediction(model, data = find_data(model), at = NULL,
type = c("class", "probability", "cumprob", "location", "scale"),
calculate_se = FALSE, ...)

## S3 method for class 'ivreg'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'knnreg'
prediction(model, data, at = NULL,
calculate_se = FALSE, ...)
```

```
## S3 method for class 'kqr'
prediction(model, data, at = NULL, calculate_se = FALSE,
...)

## S3 method for class 'ksvm'
prediction(model, data, at = NULL, type = NULL,
calculate_se = TRUE, category, ...)

## S3 method for class 'lm'
prediction(model, data = find_data(model, parent.frame()),
at = NULL, type = "response", vcov = stats::vcov(model),
calculate_se = TRUE, ...)

## S3 method for class 'lme'
prediction(model, data = find_data(model), at = NULL,
calculate_se = FALSE, ...)

## S3 method for class 'loess'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, type = "response", calculate_se = TRUE,
...)

## S3 method for class 'lqs'
prediction(model, data = find_data(model), at = NULL,
calculate_se = FALSE, ...)

## S3 method for class 'mars'
prediction(model, data = NULL, at = NULL,
type = "fitted", calculate_se = FALSE, ...)

## S3 method for class 'mca'
prediction(model, data = find_data(model), at = NULL,
calculate_se = FALSE, ...)

## S3 method for class 'mclogit'
prediction(model, data = find_data(model,
parent.frame()), at = NULL, type = "response",
vcov = stats::vcov(model), calculate_se = TRUE, ...)

## S3 method for class 'merMod'
prediction(model, data = find_data(model), at = NULL,
type = c("response", "link"), re.form = NULL, calculate_se = FALSE,
...)

## S3 method for class 'mnp'
prediction(model, data = find_data(model, parent.frame()),
at = NULL, type = NULL, calculate_se = FALSE, category, ...)
```

```
## S3 method for class 'multinom'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = NULL, calculate_se = FALSE,
  category, ...)

## S3 method for class 'nls'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'nnet'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'plm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'polr'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'polyreg'
prediction(model, data = NULL, at = NULL,
  type = "fitted", calculate_se = FALSE, ...)

## S3 method for class 'ppr'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'princomp'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'rlm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", vcov = stats::vcov(model),
  calculate_se = TRUE, ...)

## S3 method for class 'rpart'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = NULL, calculate_se = FALSE,
  category, ...)

## S3 method for class 'rq'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = TRUE, ...)

## S3 method for class 'selection'
```

```
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = "response",
  calculate_se = FALSE, ...)

## S3 method for class 'speedglm'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("response", "link"),
  calculate_se = FALSE, ...)

## S3 method for class 'speedlm'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'survreg'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("response", "lp", "quantile",
  "uquantile"), calculate_se = TRUE, ...)

## S3 method for class 'svm'
prediction(model, data = NULL, at = NULL,
  calculate_se = TRUE, category, ...)

## S3 method for class 'svyglm'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("response", "link"),
  calculate_se = TRUE, ...)

## S3 method for class 'train'
prediction(model, data = find_data(model), at = NULL,
  type = c("raw", "prob"), ...)

## S3 method for class 'truncreg'
prediction(model, data, at = NULL,
  calculate_se = FALSE, ...)

## S3 method for class 'zeroinfl'
prediction(model, data = find_data(model,
  parent.frame()), at = NULL, type = c("response", "count", "prob",
  "zero"), calculate_se = FALSE, ...)

prediction_summary(model, ..., level = 0.95)
```

Arguments

model	A model object, perhaps returned by lm or glm .
...	Additional arguments passed to predict methods.
data	A data.frame over which to calculate marginal effects. If missing, find_data is used to specify the data frame.

at	A list of one or more named vectors, specifically values at which to calculate the predictions. These are used to modify the value of <code>data</code> (see <code>build_datalist</code> for details on use).
type	A character string indicating the type of marginal effects to estimate. Mostly relevant for non-linear models, where the reasonable options are “response” (the default) or “link” (i.e., on the scale of the linear predictor in a GLM). For models of class “polr” (from <code>polr</code>), possible values are “class” or “probs”; both are returned.
vcov	A matrix containing the variance-covariance matrix for estimated model coefficients, or a function to perform the estimation with <code>model</code> as its only argument.
calculate_se	A logical indicating whether to calculate standard errors for observation-specific predictions and average predictions (if possible). The output will always contain a “calculate_se” column regardless of this value; this only controls the calculation of standard errors. Setting it to FALSE may improve speed.
category	For multi-level or multi-category outcome models (e.g., ordered probit, multinomial logit, etc.), a value specifying which of the outcome levels should be used for the “fitted” column. If missing, some default is chosen automatically.
lambda	For models of class “glmnet”, a value of the penalty parameter at which predictions are required.
re.form	An argument passed forward to <code>predict.merMod</code> .
level	A numeric value specifying the confidence level for calculating p-values and confidence intervals.

Details

This function is simply a wrapper around `predict` that returns a data frame containing the value of `data` and the predicted values with respect to all variables specified in `data`.

Methods are currently implemented for the following object classes:

- “lm”, see `lm`
- “glm”, see `glm`, `glm.nb`, `glmx`, `hetglm`, `brglm`
- “ar”, see `ar`
- “Arima”, see `arima`
- “arima0”, see `arima0`
- “bigglm”, see `bigglm` (including “ffdf”-backed models provided by `bigglm.ffdf`)
- “betareg”, see `betareg`
- “bruto”, see `bruto`
- “clm”, see `clm`
- “coxph”, see `coxph`
- “crch”, see `crch`
- “earth”, see `earth`
- “fda”, see `fda`
- “Gam”, see `gam`

- “gausspr”, see [gausspr](#)
- “gee”, see [gee](#)
- “glmnet”, see [glmnet](#)
- “gls”, see [gls](#)
- “glimML”, see [betabin](#), [negbin](#)
- “glimQL”, see [quasibin](#), [quasipois](#)
- “hurdle”, see [hurdle](#)
- “hxlr”, see [hxlr](#)
- “ivreg”, see [ivreg](#)
- “knnreg”, see [knnreg](#)
- “kqr”, see [kqr](#)
- “ksvm”, see [ksvm](#)
- “lda”, see [lda](#)
- “lme”, see [lme](#)
- “loess”, see [loess](#)
- “lqs”, see [lqs](#)
- “mars”, see [mars](#)
- “mca”, see [mca](#)
- “mclogit”, see [mclogit](#)
- “mda”, see [mda](#)
- “merMod”, see [lmer](#), [glmer](#)
- “mnp”, see [mnp](#)
- “naiveBayes”, see [naiveBayes](#)
- “nlme”, see [nlme](#)
- “nls”, see [nls](#)
- “nnet”, see [nnet](#)
- “plm”, see [plm](#)
- “polr”, see [polr](#)
- “polyreg”, see [polyreg](#)
- “ppr”, see [ppr](#)
- “princomp”, see [princomp](#)
- “qda”, see [qda](#)
- “rlm”, see [rlm](#)
- “rpart”, see [rpart](#)
- “rq”, see [rq](#)
- “selection”, see [selection](#)
- “speedglm”, see [speedglm](#)

- “speedlm”, see [speedlm](#)
- “survreg”, see [survreg](#)
- “svm”, see [svm](#)
- “svyglm”, see [svyglm](#)
- “tobit”, see [tobit](#)
- “train”, see [train](#)
- “truncreg”, see [truncreg](#)
- “zeroinfl”, see [zeroinfl](#)

Where implemented, `prediction` also returns average predictions (and the variances thereof). Variances are implemented using the delta method, as described in http://indiana.edu/~jlsoc/stata/ci_computations/spost_deltaci.pdf.

Value

A data frame with class “`prediction`” that has a number of rows equal to number of rows in `data`, or a multiple thereof, if `!is.null(at)`. The return value contains `data` (possibly modified by `at` using [build_datalist](#)), plus a column containing fitted/predicted values (“`fitted`”) and a column containing the standard errors thereof (“`calculate_se`”). Additional columns may be reported depending on the object class. The data frame also carries attributes used by `print` and `summary`, which will be lost during subsetting.

See Also

[find_data](#), [build_datalist](#), [mean_or_mode](#), [seq_range](#)

Examples

```
require("datasets")
x <- lm(Petal.Width ~ Sepal.Length * Sepal.Width * Species, data = iris)
# prediction for every case
prediction(x)

# prediction for first case
prediction(x, iris[1,])

# basic use of 'at' argument
summary(prediction(x, at = list(Species = c("setosa", "virginica"))))

# basic use of 'at' argument
prediction(x, at = list(Sepal.Length = seq_range(iris$Sepal.Length, 5)))

# prediction at means/modes of input variables
prediction(x, at = lapply(iris, mean_or_mode))

# prediction with multi-category outcome
## Not run:
library("mlogit")
data("Fishing", package = "mlogit")
```

```
Fish <- mlogit.data(Fishing, varying = c(2:9), shape = "wide", choice = "mode")
mod <- mlogit(mode ~ price + catch, data = Fish)
prediction(mod)
prediction(mod, category = 3)

## End(Not run)
```

build_datalist *Build list of data.frames*

Description

Construct a list of data.frames based upon an input data.frame and a list of one or more at values

Usage

```
build_datalist(data, at = NULL, as.data.frame = FALSE, ...)
```

Arguments

- | | |
|---------------|--|
| data | A data.frame containing the original data. |
| at | A list of one or more named vectors of values, which will be used to specify values of variables in data. All possible combinations are generated. Alternatively, this can be a data frame of combination levels if only a subset of combinations are desired. See examples. |
| as.data.frame | A logical indicating whether to return a single stacked data frame rather than a list of data frames |
| ... | Ignored. |

Value

A list of data.frames, unless as.data.frame = TRUE in which case a single, stacked data frame is returned.

Author(s)

Thomas J. Leeper

See Also

[find_data](#), [mean_or_mode](#), [seq_range](#)

Examples

```
# basic examples
require("datasets")
build_datalist(head(mtcars), at = list(cyl = c(4, 6)))

str(build_datalist(head(mtcars), at = list(cyl = c(4,6), wt = c(2.75,3,3.25))), 1)

str(build_datalist(head(mtcars), at = data.frame(cyl = c(4,4), wt = c(2.75,3))))
```

find_data

Extract data from a model object

Description

Attempt to reconstruct the data used to create a model object

Usage

```
find_data(model, ...)

## Default S3 method:
find_data(model, env = parent.frame(), ...)

## S3 method for class 'data.frame'
find_data(model, ...)

## S3 method for class 'crch'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'glimML'
find_data(model, ...)

## S3 method for class 'glm'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'hxlr'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'lm'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'mca'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'merMod'
find_data(model, env = parent.frame(), ...)
```

```
## S3 method for class 'svyglm'  
find_data(model, ...)  
  
## S3 method for class 'train'  
find_data(model, ...)  
  
## S3 method for class 'vgam'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'vglm'  
find_data(model, env = parent.frame(), ...)
```

Arguments

- | | |
|-------|--|
| model | The model object. |
| ... | Additional arguments passed to methods. |
| env | An environment in which to look for the data argument to the modelling call. |

Details

This is a convenience function and, as such, carries no guarantees. To behave well, it typically requires that a model object be specified using a formula interface and an explicit data argument. Models that can be specified using variables from the `.GlobalEnv` or with a non-formula interface (e.g., a matrix of data) will tend to generate errors. `find_data` is an S3 generic so it is possible to expand it with new methods.

Value

A data frame containing the original data used in a modelling call, modified according to the original model's 'subset' and 'na.action' arguments, if appropriate.

See Also

[prediction](#), [build_datalist](#), [mean_or_mode](#), [seq_range](#)

Examples

```
require("datasets")  
x <- lm(mpg ~ cyl * hp + wt, data = head(mtcars))  
find_data(x)
```

margex*Artificial data for margins, copied from Stata***Description**

The dataset is identical to the one provided by Stata and available from `webuse::webuse("margex")` with categorical variables explicitly encoded as factors.

Usage`margex`**Format**

A data frame with 3000 observations on the following 11 variables.

- ‘y’ A numeric vector
- ‘outcome’ A binary numeric vector with values (0,1)
- ‘sex’ A factor with two levels
- ‘group’ A factor with three levels
- ‘age’ A numeric vector
- ‘distance’ A numeric vector
- ‘ycn’ A numeric vector
- ‘yc’ A numeric vector
- ‘treatment’ A factor with two levels
- ‘agegroup’ A factor with three levels
- ‘arm’ A factor with three levels

Source

<http://www.stata-press.com/data/r14/margex.dta>

See Also

[prediction](#)

Examples

```
# Examples from Stata's help files
# Also available from: webuse::webuse("margex")
data("margex")

# A simple case after regress
```

```

# . regress y i.sex i.group
# . margins sex
m1 <- lm(y ~ factor(sex) + factor(group), data = margex)
prediction(m1, at = list(sex = c("male", "female")))

# A simple case after logistic
# . logistic outcome i.sex i.group
# . margins sex
m2 <- glm(outcome ~ sex + group, binomial(), data = margex)
prediction(m2, at = list(sex = c("male", "female")))

# Average response versus response at average
# . margins sex
prediction(m2, at = list(sex = c("male", "female")))
# . margins sex, atmeans
## TODO

# Multiple margins from one margins command
# . margins sex group
prediction(m2, at = list(sex = c("male", "female")))
prediction(m2, at = list(group = c("1", "2", "3")))

# Margins with interaction terms
# . logistic outcome i.sex i.group sex#group
# . margins sex group
m3 <- glm(outcome ~ sex * group, binomial(), data = margex)
prediction(m3, at = list(sex = c("male", "female")))
prediction(m3, at = list(group = c("1", "2", "3")))

# Margins with continuous variables
# . logistic outcome i.sex i.group sex#group age
# . margins sex group
m4 <- glm(outcome ~ sex * group + age, binomial(), data = margex)
prediction(m4, at = list(sex = c("male", "female")))
prediction(m4, at = list(group = c("1", "2", "3")))

# Margins of continuous variables
# . margins, at(age=40)
prediction(m4, at = list(age = 40))
# . margins, at(age=(30 35 40 45 50))
prediction(m4, at = list(age = c(30, 35, 40, 45, 50)))

# Margins of interactions
# . margins sex#group
prediction(m4, at = list(sex = c("male", "female"), group = c("1", "2", "3")))

```

Description

Summarize a vector/variable into a single number, either a mean (median) for numeric vectors or the mode for categorical (character, factor, ordered, or logical) vectors. Useful for aggregation.

Usage

```
mean_or_mode(x)

## Default S3 method:
mean_or_mode(x)

## S3 method for class 'numeric'
mean_or_mode(x)

## S3 method for class 'data.frame'
mean_or_mode(x)

median_or_mode(x)

## Default S3 method:
median_or_mode(x)

## S3 method for class 'numeric'
median_or_mode(x)

## S3 method for class 'data.frame'
median_or_mode(x)
```

Arguments

x A vector.

Value

A numeric or factor vector of length 1.

See Also

[prediction](#), [build_datalist](#), [seq_range](#)

Examples

```
require("datasets")
# mean for numerics
mean_or_mode(iris)
mean_or_mode(iris[["Sepal.Length"]])
mean_or_mode(iris[["Species"]])

# median for numerics
median_or_mode(iris)
```

seq_range	<i>Create a sequence over the range of a vector</i>
-----------	---

Description

Define a sequence of evenly spaced values from the minimum to the maximum of a vector

Usage

```
seq_range(x, n = 2)
```

Arguments

- | | |
|---|---|
| x | A numeric vector |
| n | An integer specifying the length of sequence (i.e., number of points across the range of x) |

Value

A vector of length n.

See Also

[mean_or_mode](#), [build_datalist](#)

Examples

```
identical(range(1:5), seq_range(1:5, n = 2))
seq_range(1:5, n = 3)
```

Index

*Topic **datasets**
 margex, 14
*Topic **data**
 build_datalist, 11
*Topic **manip**
 build_datalist, 11
*Topic **models**
 prediction-package, 2

ar, 8
arima, 8
arima0, 8

betabin, 9
betareg, 8
bigglm, 8
bigglm.ffdf, 8
brglm, 8
bruto, 8
build_datalist, 8, 10, 11, 13, 16, 17

clm, 8
coxph, 8
crch, 8

earth, 8

fda, 8
find_data, 7, 10, 11, 12

gam, 8
gausspr, 9
gee, 9
glm, 7, 8
glm.nb, 8
glmer, 9
glmnet, 9
glmx, 8
gls, 9

hetglm, 8

hurdle, 9
hxlr, 9

ivreg, 9

knnreg, 9
kqr, 9
ksvm, 9

lda, 9
lm, 7, 8
lme, 9
lmer, 9
loess, 9
lqs, 9

margex, 14
mars, 9
mca, 9
mclogit, 9
mda, 9
mean_or_mode, 10, 11, 13, 15, 17
median_or_mode (mean_or_mode), 15
mnp, 9

naiveBayes, 9
negbin, 9
nlme, 9
nls, 9
nnet, 9

plm, 9
polr, 8, 9
polyreg, 9
ppr, 9
predict, 2, 7, 8
predict.merMod, 8
prediction, 13, 14, 16
prediction(prediction-package), 2
prediction-package, 2
prediction.ar (prediction-package), 2

`prediction.Arima` (prediction-package), 2
`prediction.arima0` (prediction-package), 2
`prediction.betareg` (prediction-package), 2
`prediction.biglm` (prediction-package), 2
`prediction.bruto` (prediction-package), 2
`prediction.clm` (prediction-package), 2
`prediction.coxph` (prediction-package), 2
`prediction.crch` (prediction-package), 2
`prediction.default` (prediction-package), 2
`prediction.earth` (prediction-package), 2
`prediction.fda` (prediction-package), 2
`prediction.Gam` (prediction-package), 2
`prediction.gausspr` (prediction-package), 2
`prediction.gee` (prediction-package), 2
`prediction.glimML` (prediction-package), 2
`prediction.glimQL` (prediction-package), 2
`prediction.glm` (prediction-package), 2
`prediction.glmnet` (prediction-package), 2
`prediction.glmx` (prediction-package), 2
`prediction.gls` (prediction-package), 2
`prediction.hetglm` (prediction-package), 2
`prediction.hurdle` (prediction-package), 2
`prediction.hxlr` (prediction-package), 2
`prediction.ivreg` (prediction-package), 2
`prediction.knnreg` (prediction-package), 2
`prediction.kqr` (prediction-package), 2
`prediction.ksvm` (prediction-package), 2
`prediction.lm` (prediction-package), 2
`prediction.lme` (prediction-package), 2
`prediction.loess` (prediction-package), 2
`prediction.lqs` (prediction-package), 2
`prediction.mars` (prediction-package), 2
`prediction.mca` (prediction-package), 2
`prediction.mclogit` (prediction-package), 2
`prediction.merMod` (prediction-package), 2
`prediction.mnp` (prediction-package), 2
`prediction.multinom` (prediction-package), 2
`prediction.nls` (prediction-package), 2
`prediction.nnet` (prediction-package), 2
`prediction.plm` (prediction-package), 2
`prediction.polr` (prediction-package), 2
`prediction.polyreg` (prediction-package), 2
`prediction.ppr` (prediction-package), 2
`prediction.princomp` (prediction-package), 2
`prediction.rlm` (prediction-package), 2
`prediction.rpart` (prediction-package), 2
`prediction.rq` (prediction-package), 2
`prediction.selection` (prediction-package), 2
`prediction.speedglm` (prediction-package), 2
`prediction.speedlm` (prediction-package), 2
`prediction.survreg` (prediction-package), 2
`prediction.svm` (prediction-package), 2
`prediction.svyglm` (prediction-package), 2
`prediction.train` (prediction-package), 2
`prediction.truncreg` (prediction-package), 2
`prediction.zeroinfl` (prediction-package), 2
`prediction_summary` (prediction-package), 2
`princomp`, 9
`qda`, 9
`quasibin`, 9
`quasipois`, 9
`rlm`, 9
`rpart`, 9
`rq`, 9
`selection`, 9
`seq_range`, 10, 11, 13, 15, 16, 17
`speedglm`, 9
`speedlm`, 10
`survreg`, 10
`svm`, 10
`svyglm`, 10

tobit, *10*
train, *10*
truncreg, *10*
zeroinfl, *10*