

Package ‘primes’

July 29, 2020

Type Package

Title Generate and Test for Prime Numbers

Version 1.0.0

Date 2020-07-27

Description Functions for dealing with prime numbers, such as testing whether a number is prime and generating a sequence prime numbers. Additional functions include finding prime factors and Ruth-Aaron pairs, finding next and previous prime numbers in the series, finding or estimating the nth prime, estimating the number of primes less than or equal to an arbitrary number, computing primorials, and prime k-tuples (e.g., twin primes).

License MIT + file LICENSE

Depends R (>= 2.10)

Imports Rcpp

LinkingTo Rcpp

Suggests testthat

SystemRequirements C++11

URL <http://github.com/ironholds/primes>

BugReports <http://github.com/ironholds/primes/issues>

RoxygenNote 7.1.1

Encoding UTF-8

LazyData true

NeedsCompilation yes

Author Os Keyes [aut, cre],
Paul Egeler [aut] (<<https://orcid.org/0000-0001-6948-9498>>)

Maintainer Os Keyes <ironholds@gmail.com>

Repository CRAN

Date/Publication 2020-07-28 23:00:02 UTC

R topics documented:

| | |
|-----------------------------|---|
| generate_n_primes | 2 |
| is_prime | 3 |
| k_tuple | 3 |
| next_prime | 5 |
| nth_prime | 6 |
| primes | 6 |
| prime_count | 7 |
| prime_factors | 8 |
| primorial | 9 |
| ruth_aaron_pairs | 9 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

| | |
|-------------------|---|
| generate_n_primes | <i>Generate a Sequence of Prime Numbers</i> |
|-------------------|---|

Description

Generate a sequence of prime numbers from min to max or generate a vector of the first n primes. Both functions use a fast implementation of the Sieve of Eratosthenes.

Usage

```
generate_n_primes(n)

generate_primes(min = 2L, max)
```

Arguments

| | |
|-----|-----------------------------------|
| n | the number of primes to generate. |
| min | the lower bound of the sequence. |
| max | the upper bound of the sequence. |

Value

An integer vector of prime numbers.

Author(s)

Paul Egeler, MS

Examples

```
generate_primes(max = 12)
## [1] 2 3 5 7 11

generate_n_primes(5)
## [1] 2 3 5 7 11
```

`is_prime`*Test for Prime Numbers*

Description

Test whether a vector of numbers is prime or composite.

Usage

```
is_prime(x)
```

Arguments

`x` an integer vector containing elements to be tested for primality.

Value

A logical vector.

Author(s)

Os Keyes and Paul Egeler, MS

Examples

```
is_prime(4:7)
## [1] FALSE TRUE FALSE TRUE
```

```
is_prime(1299827)
## [1] TRUE
```

`k_tuple`*Prime k-tuples*

Description

Use prime k -tuples to create lists of twin primes, cousin primes, prime triplets, and so forth.

Usage

```

k_tuple(min, max, tuple)

twin_primes(min, max)

cousin_primes(min, max)

sexy_primes(min, max)

sexy_prime_triplets(min, max)

third_cousin_primes(min, max)

```

Arguments

| | |
|--------------------|--|
| <code>min</code> | the lower bound of the sequence. |
| <code>max</code> | the upper bound of the sequence. |
| <code>tuple</code> | an integer vector representing the target <i>k</i> -tuple pattern. |

Details

You can construct your own tuples and generate series of primes using `k_tuple`; however, there are functions that exist for some of the named relationships. They are listed below.

- `twin_primes`: represents $c(0, 2)$.
- `cousin_primes`: represents $c(0, 4)$.
- `third_cousin_primes`: represents $c(0, 8)$.
- `sexy_primes`: represents $c(0, 6)$.
- `sexy_prime_triplets`: represents $c(0, 6, 12)$.

The term "third cousin primes" is of the author's coinage. There is no canonical name for that relationship to the author's knowledge.

Value

A list of vectors of prime numbers satisfying the condition of `tuple`.

Author(s)

Paul Egeler, MS

Examples

```

# All twin primes up to 13
twin_primes(2, 13) # Identical to `k_tuple(2, 13, c(0,2))`
## [[1]]
## [1] 3 5
##

```

```
## [[2]]
## [1] 5 7
##
## [[3]]
## [1] 11 13

# Some prime triplets
k_tuple(2, 19, c(0,4,6))
## [[1]]
## [1] 7 11 13
##
## [[2]]
## [1] 13 17 19
```

next_prime

Find the Next and Previous Prime Numbers

Description

Find the next prime numbers or previous prime numbers over a vector.

Usage

```
next_prime(x)
```

```
prev_prime(x)
```

Arguments

x a vector of integers from which to start the search.

Details

For prev_prime, if a value is less than or equal to 2, the function will return NA.

Value

An integer vector of prime numbers.

Author(s)

Paul Egeler, MS

Examples

```
next_prime(5)
## [1] 7

prev_prime(5:7)
## [1] 3 5 5
```

`nth_prime` *Get the n-th Prime from the Sequence of Primes.*

Description

Get the n-th prime, p_n , in the sequence of primes.

Usage

```
nth_prime(x)
```

Arguments

`x` an integer vector.

Value

An integer vector.

Author(s)

Paul Egeler, MS

Examples

```
nth_prime(5)
## [1] 11

nth_prime(c(1:3, 7))
## [1] 2 3 5 17
```

`primes` *Pre-computed Prime Numbers*

Description

The first one thousand prime numbers.

Usage

```
primes
```

Format

An integer vector containing the first one thousand prime numbers.

See Also

[generate_primes](#), [generate_n_primes](#)

prime_count

Prime-counting Functions and Estimating the Value of the n-th Prime

Description

Functions for estimating $\pi(n)$ —the number of primes less than or equal to n —and for estimating the value of p_n , the n -th prime number.

Usage

```
prime_count(n, upper_bound)
```

```
nth_prime_estimate(n, upper_bound)
```

Arguments

`n` an integer. See *Details* for more information.

`upper_bound` a logical indicating whether to estimate the lower- or upper bound.

Details

The `prime_count` function estimates the number of primes $\leq n$. When `upper_bound = FALSE`, it is guaranteed to under-estimate for all $n \geq 17$. When `upper_bound = TRUE`, it holds for all positive n .

The `nth_prime_estimate` function brackets upper and lower bound values of the n th prime. It is valid for $n \geq 6$.

The methods of estimation used here are a few of many alternatives. For further information, the reader is directed to the *References* section.

Author(s)

Paul Egeler, MS

References

"Prime-counting function" (2020) *Wikipedia*. https://en.wikipedia.org/wiki/Prime-counting_function#Inequalities (Accessed 26 Jul 2020).

`prime_factors`*Perform Prime Factorization on a Vector*

Description

Compute the prime factors of elements of an integer vector.

Usage

```
prime_factors(x)
```

Arguments

`x` an integer vector.

Value

A list of integer vectors reflecting the prime factorizations of each element of the input vector.

Author(s)

Paul Egeler, MS

Examples

```
prime_factors(c(1, 5:7, 99))
## [[1]]
## integer(0)
##
## [[2]]
## [1] 5
##
## [[3]]
## [1] 2 3
##
## [[4]]
## [1] 7
##
## [[5]]
## [1] 3 3 11
```

| | |
|-----------|------------------------------|
| primorial | <i>Compute the Primorial</i> |
|-----------|------------------------------|

Description

Computes the primorial for prime numbers and natural numbers.

Usage

```
primorial_n(n)
```

```
primorial_p(n)
```

Arguments

| | |
|---|---|
| n | an integer indicating the numbers to be used in the computation. See <i>Details</i> for more information. |
|---|---|

Details

The `primorial_p` function computes the primorial with respect to the first n *prime* numbers; while the `primorial_n` function computes the primorial with respect to the first n *natural* numbers.

Author(s)

Paul Egeler, MS

| | |
|------------------|--|
| ruth_aaron_pairs | <i>Find Ruth-Aaron Pairs of Integers</i> |
|------------------|--|

Description

Find pairs of consecutive integers where the prime factors sum to the same value. For example, (5, 6) are Ruth-Aaron pairs because the prime factors $5 = 2 + 3$.

Usage

```
ruth_aaron_pairs(min, max, distinct = FALSE)
```

Arguments

| | |
|----------|---|
| min | an integer representing the minimum number to check. |
| max | an integer representing the maximum number to check. |
| distinct | a logical indicating whether to consider repeating prime factors or only distinct prime number factors. |

Value

A List of integer pairs.

Author(s)

Paul Egeler, MS

Index

* datasets

- primes, 6
- cousin_primes (k_tuple), 3
- generate_n_primes, 2, 6
- generate_primes, 6
- generate_primes (generate_n_primes), 2
- is_prime, 3
- k_tuple, 3
- next_prime, 5
- nth_prime, 6
- nth_prime_estimate (prime_count), 7
- prev_prime (next_prime), 5
- prime_count, 7
- prime_factors, 8
- primes, 6
- primorial, 9
- primorial_n (primorial), 9
- primorial_p (primorial), 9
- ruth_aaron_pairs, 9
- sexy_prime_triplets (k_tuple), 3
- sexy_primes (k_tuple), 3
- third_cousin_primes (k_tuple), 3
- twin_primes (k_tuple), 3