

Package ‘qrng’

September 9, 2019

Version 0.0-7

Encoding UTF-8

Title (Randomized) Quasi-Random Number Generators

Description Functionality for generating (randomized) quasi-random numbers in high dimensions.

Author Marius Hofert [aut, cre],
Christiane Lemieux [aut]

Maintainer Marius Hofert <marius.hofert@uwaterloo.ca>

Depends R (>= 3.0.0)

Imports methods, randtoolbox, utils, copula

Suggests

Enhances

License GPL-2 | GPL-3

NeedsCompilation yes

Repository CRAN

Date/Publication 2019-09-09 12:40:02 UTC

R topics documented:

qrng	2
test_functions	4
Index	7

Description

Computing Korobov, generalize Halton and Sobol' quasi-random sequences.

Usage

```
korobov(n, d = 1, generator, randomize = c("none", "shift"))
ghalton(n, d = 1, method = c("generalized", "halton"))
sobol (n, d = 1, randomize = c("none", "digital.shift", "Owen", "Faure.Tezuka",
                              "Owen.Faure.Tezuka"), seed, skip = 0, ...)
```

Arguments

n	Number n of points to be generated ≥ 2 .
d	Dimension d .
generator	A numeric of length d or length 1 (in which case it is appropriately extended to length d). All numbers must be in $\{1, \dots, n\}$ and must be (coercible to) integers.
randomize	A character string indicating the type of randomization for the point set. korobov() one of the following: "none" no randomization. "shift" a uniform random variate modulo 1. sobol() one of the following: "none" no randomization. "digital.shift" a digital shift. "Owen", "Faure.Tezuka", "Owen.Faure.Tezuka" calls <code>sobol()</code> from package randtoolbox with scrambling being 1, 2 and 3, respectively. If <code>randomize</code> is a logical , then it is interpreted as "none" if FALSE and "digital.shift" if TRUE.
method	A character string indicating which sequence is generated, generalized Halton or (plain) Halton.
seed	if provided, an integer used within <code>set.seed()</code> for the non-scrambling randomize methods (so "none" or "digital.shift") or passed to the underlying <code>sobol()</code> from package randtoolbox for the scrambling methods. If not provided, the non-scrambling methods respect a global <code>set.seed()</code> but scrambling methods do not (they then use 4711 as default); see <code>sobol()</code> from package randtoolbox .
skip	number of initial points in the sequence to be skipped (<code>skip = 0</code> means the sequence starts with at the origin). Note that for the scrambling methods this simply computes $n + \text{skip}$ points and omits the first <code>skip</code> -many.
...	additional arguments passed to <code>sobol()</code> from package randtoolbox .

Details

For `sobol()` examples see `demo(sobol_examples)`. In particular, be careful when using `skip > 0` and `randomize = TRUE`; in this case, choosing a wrong seed (or no seed) might lead to a bad sequence.

Note that these procedures call fast C code. The following restrictions apply:

korobov() n, d must be $\leq 2^{31} - 1$.

ghalton() n must be $\leq 2^{32} - 1$ and d must be ≤ 360 .

sobol() if `randomize = "none"` or `randomize = "digital.shift"`, n must be $\leq 2^{31} - 1$ and d must be ≤ 16510 .

The choice of parameters for `korobov()` is crucial for the quality of this quasi-random sequence (only basic sanity checks are conducted). For more details, see l'Ecuyer and Lemieux (2000).

The generalized Halton sequence uses the scrambling factors of Faure and Lemieux (2009).

Value

`korobov()` and `ghalton()` return an (n, d) -matrix; for $d = 1$ an n -vector is returned.

Author(s)

Marius Hofert and Christiane Lemieux

References

Faure, H., Lemieux, C. (2009). Generalized Halton Sequences in 2008: A Comparative Study. *ACM-TOMACS* **19**(4), Article 15.

l'Ecuyer, P., Lemieux, C. (2000). Variance Reduction via Lattice Rules. *Stochastic Models and Simulation*, 1214–1235.

Lemieux, C., Cieslak, M., Luttmer, K. (2004). RandQMC User's guide. See <https://www.math.uwaterloo.ca/~clemieux/randq>

Examples

```
n <- 1021 # prime
d <- 4 # dimension

## Korobov's sequence
generator <- 76 # see l'Ecuyer and Lemieux
u <- korobov(n, d = d, generator = generator)
pairs(u, gap = 0, pch = ".", labels = as.expression(
  sapply(1:d, function(j) bquote(italic(u[.(j)]))))))

## Randomized Korobov's sequence
set.seed(271)
u <- korobov(n, d = d, generator = generator, randomize = "shift")
pairs(u, gap = 0, pch = ".", labels = as.expression(
  sapply(1:d, function(j) bquote(italic(u[.(j)]))))))

## Generalized Halton sequence (randomized by definition)
```

```

set.seed(271)
u <- ghalton(n, d)
pairs(u, gap = 0, pch = ".", labels = as.expression(
  sapply(1:d, function(j) bquote(italic(u[.(j)]))))))

## For sobol() examples, see demo(sobol_examples)

```

test_functions

Test Functions

Description

Functions for testing low-discrepancy sequences.

Usage

```

sum_of_squares(u)
sobol_g(u, copula = indepCopula(dim = ncol(u), alpha = 1:ncol(u), ...))
exceedance(x, q, p = 0.99, method = c("indicator", "individual.given.sum.exceeds",
  "sum.given.sum.exceeds"))

```

Arguments

u	(n, d)-matrix containing n d -dimensional realizations (of a potential quasi-random number generator). For <code>sum_of_squares()</code> these need to be marginally standard uniform and for <code>sobol_g()</code> they need to follow the copula specified by <code>copula</code> .
copula	Copula object for which the inverse Rosenblatt transformation exists.
alpha	vector of parameters of Sobol's g test function.
...	additional arguments passed to the underlying <code>cCopula()</code> .
x	(n, d)-matrix containing n d -dimensional realizations.
q	"indicator" d -vector containing the componentwise thresholds; if a number it is recycled to a d -vector. "individual.given.sum.exceeds" , "sum.given.sum.exceeds" threshold for the sum (row sums of x).
p	If q is not provided, the probability p is used to determine q . "indicator" d -vector containing the probabilities determining componentwise thresholds via empirical quantiles; if a number, it is recycled to a d -vector. "individual.given.sum.exceeds" , "sum.given.sum.exceeds" probability determining the threshold for the sum (row sums of x) via the corresponding empirical quantile.
method	character string indicating the type of exceedance computed (see Section Value below).

Details

For examples see the demo `man_test_functions`.

See `ES_np(<matrix>)` from **qrmtools** for another test function.

Value

`sum_of_squares()` returns an n -vector (`numeric(n)`) with the rowwise computed scaled sum of squares (theoretically integrating to 1).

`sobol_g()` returns an n -vector (`numeric(n)`) with the rowwise computed Sobol' g functions.

`exceedance()`'s return value depends on method:

"indicator" returns indicators whether, componentwise, x exceeds the threshold determined by q .

"individual.given.sum.exceeds" returns all rows of x whose sum exceeds the threshold determined by q .

"sum.given.sum.exceeds" returns the row sums of those rows of x whose sum exceeds the threshold determined by q .

Author(s)

Marius Hofert and Christiane Lemieux

References

Radovic, I., Sobol', I. M. and Tichy, R. F. (1996). Quasi-Monte Carlo methods for numerical integration: Comparison of different low discrepancy sequences. *Monte Carlo Methods and Applications* **2**(1), 1–14.

Faure, H., Lemieux, C. (2009). Generalized Halton Sequences in 2008: A Comparative Study. *ACM-TOMACS* **19**(4), Article 15.

Owen, A. B. (2003). The dimension distribution and quadrature test functions. *Stat. Sinica* **13**, 1–17.

Sobol', I. M. and Asotsky, D. I. (2003). One more experiment on estimating high-dimensional integrals by quasi-Monte Carlo methods. *Math. Comput. Simul.* **62**, 255–263.

Examples

```
## Generate some (here: copula, pseudo-random) data
library(copula)
set.seed(271)
cop <- claytonCopula(iTau(claytonCopula(), tau = 0.5)) # Clayton copula
U <- rCopula(1000, copula = cop)

## Compute sum of squares test function
mean(sum_of_squares(U)) # estimate of  $E(3(\sum_{j=1}^d U_j^2)/d)$ 

## Compute the Sobol' g test function
if(packageVersion("copula") >= "0.999-20")
  mean(sobol_g(U)) # estimate of  $E(\langle \text{Sobol's } g \text{ function} \rangle)$ 
```

```
## Compute an exceedance probability
X <- qnorm(U)
mean(exceedance(X, q = qnorm(0.99))) # fixed threshold q
mean(exceedance(X, p = 0.99)) # empirically estimated marginal p-quantiles as thresholds

## Compute 99% expected shortfall for the sum
mean(exceedance(X, p = 0.99, method = "sum.given.sum.exceeds"))
## Or use ES_np(X, level = 0.99) from 'qrmtools'
```

Index

*Topic **distribution**

qrng, 2

*Topic **utilities**

test_functions, 4

cCopula, 4

character, 2, 4

Copula, 4

exceedance (test_functions), 4

ghalton (qrng), 2

korobov (qrng), 2

logical, 2

matrix, 3

numeric, 2, 5

qrng, 2

set.seed, 2

sobol, 2

sobol (qrng), 2

sobol_g (test_functions), 4

sum_of_squares (test_functions), 4

test_functions, 4