

Package ‘qtlcharts’

February 5, 2019

Version 0.11-6

Date 2019-02-04

Title Interactive Graphics for QTL Experiments

Author Karl W Broman [aut, cre],

Michael Bostock [ctb, cph] (d3.js library in htmlwidgets/lib,
<https://d3js.org>),

Justin Palmer [ctb, cph] (d3.tip library in htmlwidgets/lib,
<https://github.com/caged/d3-tip>),

Cynthia Brewer [cph] (ColorBrewer library in htmlwidgets/lib,
<http://colorbrewer2.org>),

Mark Harrower [cph] (ColorBrewer library in htmlwidgets/lib,
<http://colorbrewer2.org>),

The Pennsylvania State University [cph] (ColorBrewer library in
htmlwidgets/lib, <http://colorbrewer2.org>),

jQuery Foundation [cph] (jQuery library in htmlwidgets/lib,
<https://jquery.com>),

jQuery contributors [ctb] (jQuery library in htmlwidgets/lib; see
<https://github.com/jquery/jquery/blob/master/AUTHORS.txt>),

jQuery UI contributors [ctb] (jQuery UI library in htmlwidgets/lib; see
<https://jqueryui.com/about>)

Maintainer Karl W Broman <broman@wisc.edu>

Description Web-based interactive charts (using D3.js) for the analysis of
experimental crosses to identify genetic loci (quantitative trait
loci, QTL) contributing to variation in quantitative traits.

Depends R (>= 2.15)

Imports qtl (>= 1.30-4), htmlwidgets, graphics, stats, utils

Suggests htmltools, jsonlite, knitr, devtools, roxygen2, rmarkdown,
testthat

License GPL-3 | file LICENSE

URL <https://kbroman.org/qtlcharts>,

<https://github.com/kbroman/qtlcharts>

BugReports <https://github.com/kbroman/qtlcharts/issues>

LazyData true
Encoding UTF-8
ByteCompile true
RoxygenNote 6.1.1
NeedsCompilation no
Repository CRAN
Date/Publication 2019-02-05 16:20:03 UTC

R topics documented:

| | |
|-----------------------------|-----------|
| qtlcharts-package | 2 |
| cbindQTLeffects | 3 |
| estQTLeffects | 4 |
| geneExpr | 5 |
| grav | 5 |
| iboxplot | 6 |
| iboxplot_output | 7 |
| idotplot | 9 |
| iheatmap | 10 |
| ipleiotropy | 11 |
| iplot | 12 |
| iplotCorr | 13 |
| iplotCurves | 14 |
| iplotMap | 16 |
| iplotMScanone | 17 |
| iplotPXG | 18 |
| iplotRF | 20 |
| iplotScanone | 21 |
| iplotScantwo | 22 |
| itriplot | 24 |
| qtlchartsversion | 25 |
| scat2scat | 25 |
| setScreenSize | 26 |
| Index | 28 |

qtlcharts-package *R/qtlcharts: Interactive charts for QTL data*

Description

A QTL is a *quantitative trait locus*: a genetic locus that contributes to variation in a quantitative trait. The goal of **R/qtlcharts** is to provide interactive data visualizations for QTL analyses, and to make these visualizations available from R. It is a companion to the **R/qtl** package.

Details

Vignettes online at the [R/qlcharts website](#):

- [User guide](#)
- [Developer guide](#)
- [Use with R Markdown \[Rmd source\]](#)
- [List of chart customization options](#)

| | |
|-----------------|---|
| cbindQTLeffects | <i>Combine multiple runs of estQTLeffects</i> |
|-----------------|---|

Description

Combine multiple runs of estQTLeffects by applying cbind to each component

Usage

```
cbindQTLeffects(..., labels)
```

Arguments

| | |
|--------|---|
| ... | Results of estQTLeffects |
| labels | Vector of labels to use in the combination. |

Value

list of matrices; each component corresponds to a position in the genome and is a matrix with phenotypes x effects

See Also

[estQTLeffects](#)

Examples

```
library(ql)
data(fake.f2)
fake.f2 <- calc.genoprob(fake.f2)
sex <- fake.f2$pheno$sex
eff.fem <- estQTLeffects(fake.f2[,sex==0], pheno.col=1)
eff.mal <- estQTLeffects(fake.f2[,sex==1], pheno.col=1)
eff <- cbindQTLeffects(eff.fem, eff.mal, labels=c("female", "male"))
```

`estQTLeffects`*Calculate QTL effects at each position across the genome*

Description

Calculates the effects of QTL at each position across the genome using Haley-Knott regression, much like [effectscan](#), but considering multiple phenotypes and not plotting the results

Usage

```
estQTLeffects(cross, pheno.col = 1, what = c("means", "effects"))
```

Arguments

| | |
|------------------------|---|
| <code>cross</code> | (Optional) Object of class "cross", see read.cross . |
| <code>pheno.col</code> | Phenotype columns in cross object. |
| <code>what</code> | Indicates whether to calculate phenotype averages for each genotype group or to turn these into additive and dominance effects. |

Details

One should first run [calc.genoprob](#); if not, it is run with the default arguments.

The estimated effects will be poorly estimated in the case of selective genotyping, as Haley-Knott regression performs poorly in this case.

Value

list of matrices; each component corresponds to a position in the genome and is a matrix with phenotypes x effects

See Also

[iplotMScanone](#), [effectscan](#) [cbindQTLeffects](#)

Examples

```
data(grav)
library(qtl)
grav <- reduce2grid(calc.genoprob(grav, step=1))
out <- estQTLeffects(grav, phe=seq(1, nphe(grav), by=5))
```

`geneExpr`*Anonymized gene expression data*

Description

An anonymized set of gene expression values, for 100 genes all influenced by a common locus, plus a vector of genotypes for the 491 individuals.

Usage

```
data(geneExpr)
```

Format

A list containing a matrix `expr` with the gene expression data plus a vector `genotype` with the genotypes.

Author(s)

Karl W Broman, 2013-05-16

Examples

```
data(geneExpr)

# heat map of correlation matrix, linked to scatterplots
iplotCorr(geneExpr$expr, geneExpr$genotype, reorder=TRUE)
```

`grav`*Arabidopsis QTL data on gravitropism*

Description

Data from a QTL experiment on gravitropism in Arabidopsis, with data on 162 recombinant inbred lines (Ler x Cvi). The outcome is the root tip angle (in degrees) at two-minute increments over eight hours.

Usage

```
data(grav)
```

Format

An object of class "cross"; see [read.cross](#).

Source

[Mouse Phenome Database](#)

References

Moore CR, Johnson LS, Kwak I-Y, Livny M, Broman KW, Spalding EP (2013) High-throughput computer vision introduces the time axis to a quantitative trait map of a plant growth response. *Genetics* 195:1077-1086 ([PubMed](#))

Examples

```
data(grav)
times <- attr(grav, "time")
phe <- grav$pheno

iplotCurves(phe, times, phe[,c(61,121)], phe[,c(121,181)],
             chartOpts=list(curves_xlab="Time (hours)", curves_ylab="Root tip angle (degrees)",
                             scat1_xlab="Angle at 2 hrs", scat1_ylab="Angle at 4 hrs",
                             scat2_xlab="Angle at 4 hrs", scat2_ylab="Angle at 6 hrs"))
```

iboxplot

Modern boxplot linked to underlying histograms

Description

Creates an interactive graph for a large set of box plots (rendered as lines connecting the quantiles), linked to underlying histograms.

Usage

```
iboxplot(dat, qu = c(0.001, 0.01, 0.1, 0.25), orderByMedian = TRUE,
         breaks = 251, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|----------------------------|---|
| <code>dat</code> | Data matrix (individuals x variables) |
| <code>qu</code> | Quantiles to plot (All with $0 < qu < 0.5$) |
| <code>orderByMedian</code> | If TRUE, reorder individuals by their median |
| <code>breaks</code> | Number of bins in the histograms, or a vector of locations of the breakpoints between bins (as in hist) |
| <code>chartOpts</code> | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotCorr](#), [scat2scat](#)

Examples

```
n.ind <- 500
n.gene <- 10000
expr <- matrix(rnorm(n.ind * n.gene, (1:n.ind)/n.ind*3), ncol=n.gene)
dimnames(expr) <- list(paste0("ind", 1:n.ind),
                      paste0("gene", 1:n.gene))

iboxplot(expr, chartOpts=list(xlab="Mice", ylab="Gene expression"))
```

iboxplot_output

Shiny bindings for R/qlcharts widgets

Description

Output and render functions for using R/qlcharts widgets within Shiny applications and interactive Rmd documents.

Usage

```
iboxplot_output(outputId, width = "100%", height = "900")
iboxplot_render(expr, env = parent.frame(), quoted = FALSE)
idotplot_output(outputId, width = "100%", height = "530")
idotplot_render(expr, env = parent.frame(), quoted = FALSE)
iheatmap_output(outputId, width = "100%", height = "1000")
iheatmap_render(expr, env = parent.frame(), quoted = FALSE)
ipleiotropy_output(outputId, width = "100%", height = "580")
ipleiotropy_render(expr, env = parent.frame(), quoted = FALSE)
iplot_output(outputId, width = "100%", height = "580")
```

```

iplot_render(expr, env = parent.frame(), quoted = FALSE)
iplotCorr_output(outputId, width = "100%", height = "1000")
iplotCorr_render(expr, env = parent.frame(), quoted = FALSE)
iplotCurves_output(outputId, width = "100%", height = "1000")
iplotCurves_render(expr, env = parent.frame(), quoted = FALSE)
iplotMScanone_output(outputId, width = "100%", height = "580")
iplotMScanone_render(expr, env = parent.frame(), quoted = FALSE)
iplotMap_output(outputId, width = "100%", height = "680")
iplotMap_render(expr, env = parent.frame(), quoted = FALSE)
iplotRF_output(outputId, width = "100%", height = "1000")
iplotRF_render(expr, env = parent.frame(), quoted = FALSE)
iplotScanone_output(outputId, width = "100%", height = "580")
iplotScanone_render(expr, env = parent.frame(), quoted = FALSE)
iplotScantwo_output(outputId, width = "100%", height = "1000")
iplotScantwo_render(expr, env = parent.frame(), quoted = FALSE)
itriplot_output(outputId, width = "100%", height = "530")
itriplot_render(expr, env = parent.frame(), quoted = FALSE)
scat2scat_output(outputId, width = "100%", height = "530")
scat2scat_render(expr, env = parent.frame(), quoted = FALSE)

```

Arguments

| | |
|---------------|--|
| outputId | output variable to read from |
| width, height | Must be a valid CSS unit (like "100%", "400px", "auto") or a number, which will be coerced to a string and have "px" appended. |
| expr | An expression that generates a networkD3 graph |
| env | The environment in which to evaluate expr. |
| quoted | Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable. |

`idotplot`*Interactive phenotype x genotype plot*

Description

Creates an interactive graph of phenotypes vs genotypes at a marker.

Usage

```
idotplot(x, y, indID = NULL, group = NULL, chartOpts = NULL,  
         digits = 5)
```

Arguments

| | |
|------------------------|--|
| <code>x</code> | Vector of groups of individuals (e.g., a genotype) |
| <code>y</code> | Numeric vector (e.g., a phenotype) |
| <code>indID</code> | Optional vector of character strings, shown with tool tips |
| <code>group</code> | Optional vector of categories for coloring points |
| <code>chartOpts</code> | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplot](#), [iplotPXG](#)

Examples

```
n <- 100  
g <- sample(LETTERS[1:3], n, replace=TRUE)  
y <- rnorm(n, match(g, LETTERS[1:3])*10, 5)  
  
idotplot(g, y)
```

`iheatmap`*Interactive heat map*

Description

Creates an interactive heatmap, with each cell linked to plots of horizontal and vertical slices

Usage

```
iheatmap(z, x = NULL, y = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|------------------------|---|
| <code>z</code> | Numeric matrix of dim <code>length(x) x length(y)</code> |
| <code>x</code> | Vector of numeric values for the x-axis |
| <code>y</code> | Vector of numeric values for the y-axis |
| <code>chartOpts</code> | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use <code>NULL</code> to not round.) |

Details

By default, the z-axis limits are from $-\max(\text{abs}(z))$ to $\max(\text{abs}(z))$, and negative cells are colored blue to white which positive cells are colored white to red.

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotCorr](#)

Examples

```
n <- 101
x <- y <- seq(-2, 2, len=n)
z <- matrix(ncol=n, nrow=n)
for(i in seq(along=x))
  for(j in seq(along=y))
    z[i,j] <- x[i]*y[j]*exp(-x[i]^2 - y[j]^2)

iheatmap(z, x, y)
```

`ipleiotropy`*Tool to explore pleiotropy*

Description

Creates an interactive graph of a scatterplot of two phenotypes, plus optionally the LOD curves for the two traits along one chromosome, with a slider for selecting the locations of two QTL which are then indicated on the LOD curves and the corresponding genotypes used to color the points in the scatterplot.

Usage

```
ipleiotropy(cross, scanoneOutput = NULL, pheno.col = 1:2,  
            lodcolumn = 1:2, chr = NULL, interval = NULL,  
            fillgenoArgs = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|----------------------------|--|
| <code>cross</code> | (Optional) Object of class "cross", see read.cross . |
| <code>scanoneOutput</code> | (Optional) object of class "scanone", as output from scanone . |
| <code>pheno.col</code> | Vector indicating two phenotype column in cross object; either numeric or character strings (the latter being the phenotype column names). |
| <code>lodcolumn</code> | Vector of two numeric values indicating LOD score columns to plot. |
| <code>chr</code> | A single chromosome ID, as a character string. |
| <code>interval</code> | A numeric vector of length 2, defining an interval that indicates what portion of the chromosome should be included. |
| <code>fillgenoArgs</code> | List of named arguments to pass to fill.geno , if needed. |
| <code>chartOpts</code> | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

[fill.geno](#) is used to impute missing genotypes. In this case, arguments to [fill.geno](#) are passed as a list, for example `fillgenoArgs=list(method="argmax", error.prob=0.002, map.function="c-f")`.

Individual IDs (viewable when hovering over a point in the scatterplot of the two phenotypes) are taken from the input cross object, using the [getid](#) function in R/ql.

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotScanone](#), [iplotMScanone](#), [iplotPXG](#)

Examples

```
library(qt1)
data(fake.bc)
fake.bc <- calc.genoprob(fake.bc[5,], step=1) # select chr 5
out <- scanone(fake.bc, method="hk", pheno.col=1:2)

ipleiotropy(fake.bc, out)

# omit the LOD curves
ipleiotropy(fake.bc)
```

iplot

Interactive scatterplot

Description

Creates an interactive scatterplot.

Usage

```
iplot(x, y, group = NULL, indID = NULL, chartOpts = NULL,
      digits = 5)
```

Arguments

| | |
|-----------|--|
| x | Numeric vector of x values |
| y | Numeric vector of y values |
| group | Optional vector of categories for coloring the points |
| indID | Optional vector of character strings, shown with tool tips |
| chartOpts | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotCorr](#), [iplotCurves](#), [itriplot](#), [idotplot](#), [iplotPXG](#)

Examples

```
x <- rnorm(100)
grp <- sample(1:3, 100, replace=TRUE)
y <- x*grp + rnorm(100)

iplot(x, y, grp)
```

iplotCorr

Image of correlation matrix with linked scatterplot

Description

Creates an interactive graph with an image of a correlation matrix linked to underlying scatterplots.

Usage

```
iplotCorr(mat, group = NULL, rows = NULL, cols = NULL,
  reorder = FALSE, corr = NULL, scatterplots = TRUE,
  chartOpts = NULL, digits = 5)
```

Arguments

| | |
|--------------|---|
| mat | Data matrix (individuals x variables) |
| group | Optional vector of groups of individuals (e.g., a genotype) |
| rows | Selected rows of the correlation matrix to include in the image. Ignored if corr is provided. |
| cols | Selected columns of the correlation matrix to include in the image. Ignored if corr is provided. |
| reorder | If TRUE, reorder the variables by clustering. Ignored if corr is provided as a subset of the overall correlation matrix |
| corr | Correlation matrix (optional). |
| scatterplots | If FALSE, don't have the heat map be linked to scatterplots. |
| chartOpts | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

corr may be provided as a subset of the overall correlation matrix for the columns of mat. In this case, the reorder, rows and cols arguments are ignored. The row and column names of corr must match the names of some subset of columns of mat.

Individual IDs are taken from rownames(mat); they must match names(group).

Value

An object of class htmlwidget that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iheatmap](#), [scat2scat](#), [iplotCurves](#)

Examples

```
data(geneExpr)

iplotCorr(geneExpr$expr, geneExpr$genotype, reorder=TRUE,
          chartOpts=list(cortitle="Correlation matrix",
                        scattitle="Scatterplot"))

# use Spearman's correlation
corr <- cor(geneExpr$expr, method="spearman", use="pairwise.complete.obs")
# order by hierarchical clustering
o <- hclust(as.dist(1-corr))$order

iplotCorr(geneExpr$expr[,o], geneExpr$genotype, corr=corr[o,o],
          chartOpts=list(cortitle="Spearman correlation",
                        scattitle="Scatterplot"))
```

iplotCurves

Plot of a bunch of curves, linked to points in scatterplots

Description

Creates an interactive graph with a panel having a number of curves (say, a phenotype measured over time) linked to one or two (or no) scatter plots (say, of the first vs middle and middle vs last times).

Usage

```
iplotCurves(curveMatrix, times = NULL, scatter1 = NULL,
             scatter2 = NULL, group = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|-------------|---|
| curveMatrix | Matrix (dim n_ind x n_times) with outcomes |
| times | Vector (length n_times) with time points for the columns of curveMatrix |
| scatter1 | Matrix (dim n_ind x 2) with data for the first scatterplot |
| scatter2 | Matrix (dim n_ind x 2) with data for the second scatterplot |
| group | Optional vector of groups of individuals (e.g., a genotype) |
| chartOpts | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotCorr](#), [iplot](#), [scat2scat](#)

Examples

```
# random growth curves, based on some data
times <- 1:16
n <- 100
start <- rnorm(n, 5.2, 0.8)
slope1to5 <- rnorm(n, 2.6, 0.5)
slope5to16 <- rnorm(n, 0.24 + 0.09*slope1to5, 0.195)
y <- matrix(ncol=16, nrow=n)
y[,1] <- start
for(j in 2:5)
  y[,j] <- y[,j-1] + slope1to5
for(j in 6:16)
  y[,j] <- y[,j-1] + slope5to16
y <- y + rnorm(prod(dim(y)), 0, 0.35)

iplotCurves(y, times, y[,c(1,5)], y[,c(5,16)],
             chartOpts=list(
               curves_xlab="Time", curves_ylab="Size",
               scat1_xlab="Size at T=1", scat1_ylab="Size at T=5",
               scat2_xlab="Size at T=5", scat2_ylab="Size at T=16"))
```

`iplotMap`*Interactive genetic map plot*

Description

Creates an interactive graph of a genetic marker map.

Usage

```
iplotMap(map, chr = NULL, shift = FALSE, chartOpts = NULL,  
         digits = 5)
```

Arguments

| | |
|------------------------|---|
| <code>map</code> | Object of class "map", a list with each component being a vector of marker positions. You can also provide an object of class "cross", in which case the map is extracted with pull.map . |
| <code>chr</code> | (Optional) Vector indicating the chromosomes to plot. |
| <code>shift</code> | If TRUE, shift each chromosome so that the initial marker is at position 0. |
| <code>chartOpts</code> | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotScanone](#), [iplotPXG](#)

Examples

```
library(qt1)  
data(hyper)  
map <- pull.map(hyper)  
  
iplotMap(map, shift=TRUE)
```

| | |
|---------------|------------------------------|
| iplotMScanone | <i>Interactive LOD curve</i> |
|---------------|------------------------------|

Description

Creates an interactive graph of a set of single-QTL genome scans, as calculated by [scanone](#). If cross or effects are provide, LOD curves will be linked to a panel with estimated QTL effects.

Usage

```
iplotMScanone(scanoneOutput, cross = NULL, lodcolumn = NULL,  
  pheno.col = NULL, times = NULL, effects = NULL, chr = NULL,  
  chartOpts = NULL, digits = 5)
```

Arguments

| | |
|---------------|--|
| scanoneOutput | Object of class "scanone", as output from scanone . |
| cross | (Optional) Object of class "cross", see read.cross . |
| lodcolumn | Numeric value indicating LOD score column to plot. |
| pheno.col | (Optional) Phenotype column in cross object. |
| times | (Optional) Vector (length equal to the number of LOD score columns) with quantitative values to which the different LOD score columns correspond (times of measurements, or something like age or dose). These need to be ordered and equally-spaced. If omitted, the names of the columns in scanoneOutput are used and treated as qualitative. |
| effects | (Optional) |
| chr | (Optional) Optional vector indicating the chromosomes for which LOD scores should be calculated. This should be a vector of character strings referring to chromosomes by name; numeric values are converted to strings. Refer to chromosomes with a preceding - to have all chromosomes but those considered. A logical (TRUE/FALSE) vector may also be used. |
| chartOpts | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

If cross is provided, Haley-Knott regression is used to estimate QTL effects at each pseudomarker.

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also[iplotScanone](#)**Examples**

```

data(grav)
library(qtl)
grav <- calc.genoprob(grav, step=1)
grav <- reduce2grid(grav)

# we're going to subset the phenotypes
phecol <- seq(1, nphe(grav), by=5)

# the times were saved as an attributed
times <- attr(grav, "time")[phecol]

# genome scan
out <- scanone(grav, phe=phecol, method="hk")

# plot with qualitative labels on y-axis
iplotMScanone(out)

# plot with quantitative y-axis
iplotMScanone(out, times=times)

# estimate QTL effect for each time point at each genomic position
eff <- estQTLeffects(grav, phe=seq(1, nphe(grav), by=5), what="effects")

# plot with QTL effects included (and with quantitative y-axis)
iplotMScanone(out, effects=eff, times=times,
              chartOpts=list(eff_ylab="QTL effect", eff_xlab="Time (hrs)"))

```

iplotPXG*Interactive phenotype x genotype plot*

Description

Creates an interactive graph of phenotypes vs genotypes at a marker.

Usage

```

iplotPXG(cross, marker, pheno.col = 1, chartOpts = NULL,
         fillgenoArgs = NULL, digits = 5)

```

Arguments

| | |
|--------------|--|
| cross | Object of class "cross", see read.cross . |
| marker | Character string with marker name. |
| pheno.col | Phenotype column in cross object. |
| chartOpts | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| fillgenoArgs | List of named arguments to pass to fill.geno , if needed. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

The function [fill.geno](#) is used to impute missing genotypes, with arguments passed as a list, for example `fillgenoArgs=list(method="argmax", error.prob=0.002, map.function="c-f")`.

Individual IDs (viewable when hovering over a point) are taken from the input cross object, using the [getid](#) function in R/qt1.

By default, points are colored blue and pink according to whether the marker genotype is observed or inferred, respectively.

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[idotplot](#), [iplot](#), [iplotScanone](#), [iplotMap](#)

Examples

```
library(qt1)
data(hyper)
marker <- sample(markernames(hyper), 1)

iplotPXG(hyper, marker)

# different colors
iplotPXG(hyper, marker, chartOpts=list(pointcolor=c("black", "gray")))
```

`iplotRF`*Interactive plot of recombination fractions*

Description

Creates an interactive graph of estimated recombination fractions and LOD scores for all pairs of markers.

Usage

```
iplotRF(cross, chr = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|------------------------|--|
| <code>cross</code> | Object of class "cross", see read.cross . |
| <code>chr</code> | Optional vector indicating chromosomes to include. This should be a vector of character strings referring to chromosomes by name; numeric values are converted to strings. Refer to chromosomes with a preceding - to have all chromosomes but those considered. A logical (TRUE/FALSE) vector may also be used. |
| <code>chartOpts</code> | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

The usual `height` and `width` options in `chartOpts` are ignored in this plot. Instead, you may provide `pixelPerCell` (number of pixels per cell in the heat map), `chrGap` (gap in pixels between chromosomes in the heat map), `cellHeight` (height in pixels of each cell in the cross-tabulation), `cellWidth` (width in pixels of each cell in the cross-tabulation), and `hbot` (height in pixels of the lower panels showing cross-sections of the heat map)

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[est.rf](#), [plotRF](#)

Examples

```
library(qt1)
data(fake.f2)

fake.f2 <- est.rf(fake.f2)

iplotRF(fake.f2)
```

iplotScanone

Interactive LOD curve

Description

Creates an interactive graph of a single-QTL genome scan, as calculated by [scanone](#). If cross is provided, the LOD curves are linked to a phenotype x genotype plot for a marker: Click on a marker on the LOD curve and see the corresponding phenotype x genotype plot.

Usage

```
iplotScanone(scanoneOutput, cross = NULL, lodcolumn = 1,
  pheno.col = 1, chr = NULL, pxgtype = c("ci", "raw"),
  fillgenoArgs = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|---------------|---|
| scanoneOutput | Object of class "scanone", as output from scanone . |
| cross | (Optional) Object of class "cross", see read.cross . |
| lodcolumn | Numeric value indicating LOD score column to plot. |
| pheno.col | (Optional) Phenotype column in cross object. |
| chr | (Optional) Vector indicating the chromosomes for which LOD scores should be calculated. This should be a vector of character strings referring to chromosomes by name; numeric values are converted to strings. Refer to chromosomes with a preceding - to have all chromosomes but those considered. A logical (TRUE/FALSE) vector may also be used. |
| pxgtype | If phenotype x genotype plot is to be shown, should it be with means ± 2 SE ("ci"), or raw phenotypes ("raw")? |
| fillgenoArgs | List of named arguments to pass to fill.geno , if needed. |
| chartOpts | A list of options for configuring the chart (see the coffeescript code). Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

If cross is provided, `fill.geno` is used to impute missing genotypes. In this case, arguments to `fill.geno` are passed as a list, for example `fillgenoArgs=list(method="argmax", error.prob=0.002, map.function=`

With `pxgtype="raw"`, individual IDs (viewable when hovering over a point in the phenotype-by-genotype plot) are taken from the input cross object, using the `getid` function in R/ctl.

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotMScanone](#), [iplotPXG](#), [iplotMap](#)

Examples

```
library(qt1)
data(hyper)
hyper <- calc.genoprob(hyper, step=1)
out <- scanone(hyper)

# iplotScanone with no effects
iplotScanone(out, chr=c(1, 4, 6, 7, 15))

# iplotScanone with CIs
iplotScanone(out, hyper, chr=c(1, 4, 6, 7, 15))

# iplotScanone with raw phe x gen
iplotScanone(out, hyper, chr=c(1, 4, 6, 7, 15),
             pxgtype='raw')
```

iplotScantwo

Interactive plot of 2d genome scan

Description

Creates an interactive plot of the results of `scantwo`, for a two-dimensional, two-QTL genome scan.

Usage

```
iplotScantwo(scantwoOutput, cross = NULL, lodcolumn = 1,
             pheno.col = 1, chr = NULL, chartOpts = NULL, digits = 5)
```

Arguments

| | |
|---------------|--|
| scantwoOutput | Output of scantwo |
| cross | (Optional) Object of class "cross", see read.cross . |
| lodcolumn | Numeric value indicating LOD score column to plot. |
| pheno.col | (Optional) Phenotype column in cross object. |
| chr | (Optional) Optional vector indicating the chromosomes for which LOD scores should be calculated. This should be a vector of character strings referring to chromosomes by name; numeric values are converted to strings. Refer to chromosomes with a preceding - to have all chromosomes but those considered. A logical (TRUE/FALSE) vector may also be used. |
| chartOpts | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Details

The estimated QTL effects, and the genotypes in the phenotype x genotype plot, in the right-hand panels, are derived following a single imputation to fill in missing data, and so are a bit crude.

Note that the usual height and width options in chartOpts are ignored here. Instead, you may provide pixelPerCell (number of pixels per cell in the heat map), chrGap (gaps between chr in heat map), wright (width in pixels of right panels), and hbot (height in pixels of each of the lower panels)

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotScanone](#)

Examples

```
library(qt1)
data(fake.f2)

fake.f2 <- calc.genoprob(fake.f2, step=5)
out <- scantwo(fake.f2, method="hk", verbose=FALSE)

iplotScantwo(out, fake.f2)
```

`itriplot`*Interactive plot of trinomial probabilities*

Description

Creates an interactive graph of trinomial probabilities, represented as points within an equilateral triangle.

Usage

```
itriplot(p, indID = NULL, group = NULL, chartOpts = NULL,  
         digits = 5)
```

Arguments

| | |
|------------------------|--|
| <code>p</code> | Matrix of trinomial probabilities (n x 3); each row should sum to 1. |
| <code>indID</code> | Optional vector of character strings, shown with tool tips |
| <code>group</code> | Optional vector of categories for coloring the points |
| <code>chartOpts</code> | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| <code>digits</code> | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplot](#), [iplotPXG](#), [idotplot](#)

Examples

```
n <- 100  
p <- matrix(runif(3*n), ncol=3)  
p <- p / colSums(p)  
g <- sample(1:3, n, replace=TRUE)  
  
itriplot(p, group=g)
```


qtlchartsversion *print the installed version of R/qtlcharts*

Description

print the installed version of R/qtlcharts

Usage

qtlchartsversion()

Value

Character string with version number

Examples

qtlchartsversion()

scat2scat *Scatterplot driving another scatterplot*

Description

A pair of linked scatterplots, where each point the first scatterplot corresponds to a scatter of points in the second scatterplot. The first scatterplot corresponds to a pair of summary measures for a larger dataset.

Usage

```
scat2scat(scat1data, scat2data, group = NULL, chartOpts = NULL,
          digits = 5)
```

Arguments

- scat1data Matrix with two columns; rownames are used as identifiers. Can have an optional third column with categories for coloring points in the first scatterplot (to be used if group is not provided).
- scat2data List of matrices each with at least two columns, to be shown in the second scatterplot. The components of the list correspond to the rows in scat1dat. An option third column can contain categories. Row names identify individual points.
- group Categories for coloring points in the first scatterplot; length should be the number of rows in scat1data.

| | |
|-----------|--|
| chartOpts | A list of options for configuring the chart. Each element must be named using the corresponding option. |
| digits | Round data to this number of significant digits before passing to the chart function. (Use NULL to not round.) |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

See Also

[iplotCorr](#)

Examples

```
# simulate some data
p <- 500
n <- 300
SD <- runif(p, 1, 5)
r <- runif(p, -1, 1)
scat2 <- vector("list", p)
for(i in 1:p)
  scat2[[i]] <- matrix(rnorm(2*n), ncol=2) %*% chol(SD[i]^2*matrix(c(1, r[i], r[i], 1), ncol=2))
scat1 <- cbind(SD=SD, r=r)
# plot it
scat2scat(scat1, scat2)
```

| | |
|---------------|--|
| setScreenSize | <i>Set default maximum screen size</i> |
|---------------|--|

Description

Set the default screen size as a global option.

Usage

```
setScreenSize(size = c("normal", "small", "large"), height, width)
```

Arguments

| | |
|--------|---|
| size | Character vector representing screen size (normal, small, large). Ignored if height and width are provided. |
| height | (Optional) Height in pixels |
| width | (Optional) Width in pixels |

Details

Used to set a global option, `qtChartsScreenSize`, that contains the maximum height and maximum width for a chart in the browser.

"small", "normal", and "large" correspond to 600x900, 700x1000, and 1200x1600, for height x width, respectively.

Value

None.

Examples

```
setSize("large")
```

Index

- *Topic **datasets**
 - geneExpr, 5
 - grav, 5
- *Topic **hplot**
 - iboxplot, 6
 - idotplot, 9
 - iheatmap, 10
 - ipleiotropy, 11
 - iplot, 12
 - iplotCorr, 13
 - iplotCurves, 14
 - iplotMap, 16
 - iplotMScanone, 17
 - iplotPXG, 18
 - iplotRF, 20
 - iplotScanone, 21
 - iplotScantwo, 22
 - itriplot, 24
 - scat2scat, 25
- *Topic **regression**
 - estQTLeffects, 4
- *Topic **utilities**
 - cbindQTLeffects, 3
 - setScreenSize, 26
- calc.genoprob, 4
- cbindQTLeffects, 3, 4
- effectscan, 4
- est.rf, 20
- estQTLeffects, 3, 4
- fill.geno, 11, 19, 21, 22
- geneExpr, 5
- getid, 11, 19, 22
- grav, 5
- hist, 6
- iboxplot, 6
- iboxplot_output, 7
- iboxplot_render (iboxplot_output), 7
- idotplot, 9, 13, 19, 24
- idotplot_output (iboxplot_output), 7
- idotplot_render (iboxplot_output), 7
- iheatmap, 10, 14
- iheatmap_output (iboxplot_output), 7
- iheatmap_render (iboxplot_output), 7
- ipleiotropy, 11
- ipleiotropy_output (iboxplot_output), 7
- ipleiotropy_render (iboxplot_output), 7
- iplot, 9, 12, 15, 19, 24
- iplot_output (iboxplot_output), 7
- iplot_render (iboxplot_output), 7
- iplotCorr, 7, 10, 13, 13, 15, 26
- iplotCorr_output (iboxplot_output), 7
- iplotCorr_render (iboxplot_output), 7
- iplotCurves, 13, 14, 14
- iplotCurves_output (iboxplot_output), 7
- iplotCurves_render (iboxplot_output), 7
- iplotMap, 16, 19, 22
- iplotMap_output (iboxplot_output), 7
- iplotMap_render (iboxplot_output), 7
- iplotMScanone, 4, 12, 17, 22
- iplotMScanone_output (iboxplot_output), 7
- iplotMScanone_render (iboxplot_output), 7
- iplotPXG, 9, 12, 13, 16, 18, 22, 24
- iplotRF, 20
- iplotRF_output (iboxplot_output), 7
- iplotRF_render (iboxplot_output), 7
- iplotScanone, 12, 16, 18, 19, 21, 23
- iplotScanone_output (iboxplot_output), 7
- iplotScanone_render (iboxplot_output), 7
- iplotScantwo, 22
- iplotScantwo_output (iboxplot_output), 7
- iplotScantwo_render (iboxplot_output), 7
- itriplot, 13, 24

itriplot_output (iboxplot_output), 7
itriplot_render (iboxplot_output), 7

plotRF, 20
pull.map, 16

qtlcharts (qtlcharts-package), 2
qtlcharts-package, 2
qtlcharts-shiny (iboxplot_output), 7
qtlchartsversion, 25

read.cross, 4, 5, 11, 17, 19–21, 23

scanone, 11, 17, 21
scantwo, 22, 23
scat2scat, 7, 14, 15, 25
scat2scat_output (iboxplot_output), 7
scat2scat_render (iboxplot_output), 7
setScreenSize, 26