

# Package ‘readr’

December 21, 2018

**Version** 1.3.1

**Title** Read Rectangular Text Data

**Description** The goal of 'readr' is to provide a fast and friendly way to read rectangular data (like 'csv', 'tsv', and 'fwf'). It is designed to flexibly parse many types of data found in the wild, while still cleanly failing when data unexpectedly changes.

**Encoding** UTF-8

**Depends** R (>= 3.1)

**LinkingTo** Rcpp, BH

**Imports** Rcpp (>= 0.12.0.5), tibble, hms (>= 0.4.1), R6, clipr, crayon, methods

**Suggests** curl, testthat, knitr, rmarkdown, stringi, covr, spelling

**License** GPL (>= 2) | file LICENSE

**BugReports** <https://github.com/tidyverse/readr/issues>

**URL** <http://readr.tidyverse.org>, <https://github.com/tidyverse/readr>

**VignetteBuilder** knitr

**RoxygenNote** 6.1.1

**SystemRequirements** GNU make

**Language** en-US

**NeedsCompilation** yes

**Author** Hadley Wickham [aut],  
Jim Hester [aut, cre],  
Romain Francois [aut],  
R Core Team [ctb] (Date time code adapted from R),  
RStudio [cph, fnd],  
Jukka Jylänki [ctb, cph] (grisu3 implementation),  
Mikkel Jørgensen [ctb, cph] (grisu3 implementation)

**Maintainer** Jim Hester <james.hester@rstudio.com>

**Repository** CRAN

**Date/Publication** 2018-12-21 09:40:02 UTC

**R topics documented:**

clipboard	2
cols	3
cols_condense	4
col_skip	5
count_fields	5
date_names	6
format_delim	7
guess_encoding	8
locale	9
melt_delim	10
melt_fwf	13
melt_table	14
parse_atomic	16
parse_datetime	17
parse_factor	20
parse_guess	22
parse_number	23
problems	24
readr_example	25
read_delim	25
read_file	28
read_fwf	29
read_lines	32
read_log	33
read_table	35
show_progress	37
spec_delim	37
type_convert	40
write_delim	41
<b>Index</b>	<b>44</b>

---

clipboard	<i>Returns values from the clipboard</i>
-----------	--

---

**Description**

This is useful in the `read_delim()` functions to read from the clipboard.

**Usage**

```
clipboard()
```

**See Also**

`read_delim`

---

**cols** *Create column specification*

---

**Description**

`cols()` includes all columns in the input data, guessing the column types as the default. `cols_only()` includes only the columns you explicitly specify, skipping the rest.

**Usage**

```
cols(..., .default = col_guess())
```

```
cols_only(...)
```

**Arguments**

`...` Either column objects created by `col_*()`, or their abbreviated character names (as described in the `col_types` argument of `read_delim()`). If you're only overriding a few columns, it's best to refer to columns by name. If not named, the column types must match the column names exactly.

`.default` Any named columns not explicitly overridden in `...` will be read with this column type.

**Details**

The available specifications are: (with string abbreviations in brackets)

- `col_logical()` [l], containing only T, F, TRUE or FALSE.
- `col_integer()` [i], integers.
- `col_double()` [d], doubles.
- `col_character()` [c], everything else.
- `col_factor(levels, ordered)` [f], a fixed set of values.
- `col_date(format = "")` [D]: with the locale's `date_format`.
- `col_time(format = "")` [t]: with the locale's `time_format`.
- `col_datetime(format = "")` [T]: ISO8601 date times
- `col_number()` [n], numbers containing the `grouping_mark`
- `col_skip()` [\_, -], don't import this column.
- `col_guess()` [?], parse using the "best" type based on the input.

**See Also**

Other parsers: [col\\_skip](#), [cols\\_condense](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

## Examples

```
cols(a = col_integer())
cols_only(a = col_integer())

# You can also use the standard abbreviations
cols(a = "i")
cols(a = "i", b = "d", c = "_")

# You can also use multiple sets of column definitions by combining
# them like so:

t1 <- cols(
  column_one = col_integer(),
  column_two = col_number())

t2 <- cols(
  column_three = col_character())

t3 <- t1
t3$cols <- c(t1$cols, t2$cols)
t3
```

---

cols\_condense

*Examine the column specifications for a data frame*

---

## Description

cols\_condense() takes a spec object and condenses its definition by setting the default column type to the most frequent type and only listing columns with a different type.

spec() extracts the full column specification from a tibble created by readr.

## Usage

```
cols_condense(x)
```

```
spec(x)
```

## Arguments

x                    The data frame object to extract from

## Value

A col\_spec object.

## See Also

Other parsers: [col\\_skip](#), [cols](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

**Examples**

```
df <- read_csv(readr_example("mtcars.csv"))
s <- spec(df)
s

cols_condense(s)
```

---

col_skip	<i>Skip a column</i>
----------	----------------------

---

**Description**

Use this function to ignore a column when reading in a file. To skip all columns not otherwise specified, use [cols\\_only\(\)](#).

**Usage**

```
col_skip()
```

**See Also**

Other parsers: [cols\\_condense](#), [cols](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

---

count_fields	<i>Count the number of fields in each line of a file</i>
--------------	--

---

**Description**

This is useful for diagnosing problems with functions that fail to parse correctly.

**Usage**

```
count_fields(file, tokenizer, skip = 0, n_max = -1L)
```

**Arguments**

**file** Either a path to a file, a connection, or literal data (either a single string or a raw vector). Files ending in `.gz`, `.bz2`, `.xz`, or `.zip` will be automatically uncompressed. Files starting with `http://`, `https://`, `ftp://`, or `ftps://` will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed. Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1. Using a value of `clipboard()` will read from the system clipboard.

tokenizer	A tokenizer that specifies how to break the file up into fields, e.g., <code>tokenizer_csv()</code> , <code>tokenizer_fwf()</code>
skip	Number of lines to skip before reading data.
n_max	Optionally, maximum number of rows to count fields for.

### Examples

```
count_fields(readr_example("mtcars.csv"), tokenizer_csv())
```

---

date_names	<i>Create or retrieve date names</i>
------------	--------------------------------------

---

### Description

When parsing dates, you often need to know how weekdays of the week and months are represented as text. This pair of functions allows you to either create your own, or retrieve from a standard list. The standard list is derived from ICU (<http://site.icu-project.org>) via the stringi package.

### Usage

```
date_names(mon, mon_ab = mon, day, day_ab = day, am_pm = c("AM",
  "PM"))

date_names_lang(language)

date_names_langs()
```

### Arguments

mon, mon_ab	Full and abbreviated month names.
day, day_ab	Full and abbreviated week day names. Starts with Sunday.
am_pm	Names used for AM and PM.
language	A BCP 47 locale, made up of a language and a region, e.g. "en_US" for American English. See <code>date_names_langs()</code> for a complete list of available locales.

### Examples

```
date_names_lang("en")
date_names_lang("ko")
date_names_lang("fr")
```

---

format_delim	Convert a data frame to a delimited string
--------------	--

---

### Description

These functions are equivalent to `write_csv()` etc., but instead of writing to disk, they return a string.

### Usage

```
format_delim(x, delim, na = "NA", append = FALSE,  
            col_names = !append, quote_escape = "double")
```

```
format_csv(x, na = "NA", append = FALSE, col_names = !append,  
          quote_escape = "double")
```

```
format_csv2(x, na = "NA", append = FALSE, col_names = !append,  
           quote_escape = "double")
```

```
format_tsv(x, na = "NA", append = FALSE, col_names = !append,  
          quote_escape = "double")
```

### Arguments

x	A data frame to write to disk
delim	Delimiter used to separate values. Defaults to " " for <code>write_delim()</code> , ",", for <code>write_excel_csv()</code> and ";" for <code>write_excel_csv2()</code> . Must be a single character.
na	String used for missing values. Defaults to NA. Missing values will never be quoted; strings with the same value as na will always be quoted.
append	If FALSE, will overwrite existing file. If TRUE, will append to existing file. In both cases, if file does not exist a new file is created.
col_names	Write columns names at the top of the file? Must be either TRUE or FALSE.
quote_escape	The type of escaping to use for quoted values, one of "double", "backslash" or "none". You can also use FALSE, which is equivalent to "none". The default is to double the quotes, which is the format excel expects.

### Value

A string.

### Output

Factors are coerced to character. Doubles are formatted using the `grisu3` algorithm. POSIXct's are formatted as ISO8601 with a UTC timezone *Note: POSIXct objects in local or non-UTC timezones will be converted to UTC time before writing.*

All columns are encoded as UTF-8. `write_excel_csv()` and `write_excel_csv2()` also include a **UTF-8 Byte order mark** which indicates to Excel the csv is UTF-8 encoded.

`write_excel_csv2()` and `write_csv2` were created to allow users with different locale settings save csv files with their default settings ; as column separator and , as decimal separator. This is common in some European countries.

Values are only quoted if needed: if they contain a comma, quote or newline.

The `write_*`() functions will automatically compress outputs if an appropriate extension is given. At present, three extensions are supported, `.gz` for gzip compression, `.bz2` for bzip2 compression and `.xz` for lzma compression. See the examples for more information.

## References

Florian Loitsch, Printing Floating-Point Numbers Quickly and Accurately with Integers, PLDI '10, <http://www.cs.tufts.edu/~nr/cs257/archive/florian-loitsch/printf.pdf>

## Examples

```
tmp <- tempfile()
write_csv(mtcars, tmp)
head(read_csv(tmp))

# format_* is useful for testing and reprepexes
cat(format_csv(head(mtcars)))
cat(format_tsv(head(mtcars)))
cat(format_delim(head(mtcars), ";"))

df <- data.frame(x = c(1, 2, NA))
format_csv(df, na = ".")

# Quotes are automatically as needed
df <- data.frame(x = c("a", "'", ",,", "\n"))
cat(format_csv(df))

# A output connection will be automatically created for output filenames
# with appropriate extensions.
dir <- tempdir()
write_tsv(mtcars, file.path(dir, "mtcars.tsv.gz"))
write_tsv(mtcars, file.path(dir, "mtcars.tsv.bz2"))
write_tsv(mtcars, file.path(dir, "mtcars.tsv.xz"))
```

---

guess\_encoding

*Guess encoding of file*

---

## Description

Uses `stringi::stri_enc_detect()`: see the documentation there for caveats.



**Usage**

```
guess_encoding(file, n_max = 10000, threshold = 0.2)
```

**Arguments**

file	A character string specifying an input as specified in <a href="#">datasource()</a> , a raw vector, or a list of raw vectors.
n_max	Number of lines to read. If n_max is -1, all lines in file will be read.
threshold	Only report guesses above this threshold of certainty.

**Value**

A tibble

**Examples**

```
guess_encoding(readr_example("mtcars.csv"))
guess_encoding(read_lines_raw(readr_example("mtcars.csv")))
guess_encoding(read_file_raw(readr_example("mtcars.csv")))

guess_encoding("a\n\u00b5\u00b5")
```

---

locale	<i>Create locales</i>
--------	-----------------------

---

**Description**

A locale object tries to capture all the defaults that can vary between countries. You set the locale in once, and the details are automatically passed on down to the columns parsers. The defaults have been chosen to match R (i.e. US English) as closely as possible. See [vignette\("locales"\)](#) for more details.

**Usage**

```
locale(date_names = "en", date_format = "%AD", time_format = "%AT",
       decimal_mark = ".", grouping_mark = ", ", tz = "UTC",
       encoding = "UTF-8", asciify = FALSE)

default_locale()
```

**Arguments**

date_names	Character representations of day and month names. Either the language code as string (passed on to <a href="#">date_names_lang()</a> ) or an object created by <a href="#">date_names()</a> .
date_format, time_format	Default date and time formats.

decimal_mark, grouping_mark	Symbols used to indicate the decimal place, and to chunk larger numbers. Decimal mark can only be , or ..
tz	Default tz. This is used both for input (if the time zone isn't present in individual strings), and for output (to control the default display). The default is to use "UTC", a time zone that does not use daylight savings time (DST) and hence is typically most useful for data. The absence of time zones makes it approximately 50x faster to generate UTC times than any other time zone. Use "" to use the system default time zone, but beware that this will not be reproducible across systems. For a complete list of possible time zones, see <a href="#">OlsonNames()</a> . Americans, note that "EST" is a Canadian time zone that does not have DST. It is <i>not</i> Eastern Standard Time. It's better to use "US/Eastern", "US/Central" etc.
encoding	Default encoding. This only affects how the file is read - readr always converts the output to UTF-8.
asciify	Should diacritics be stripped from date names and converted to ASCII? This is useful if you're dealing with ASCII data where the correct spellings have been lost. Requires the <b>stringi</b> package.

### Examples

```
locale()
locale("fr")

# South American locale
locale("es", decimal_mark = ",")
```

---

melt_delim	<i>Return melted data for each token in a delimited file (including csv &amp; tsv)</i>
------------	--

---

### Description

For certain non-rectangular data formats, it can be useful to parse the data into a melted format where each row represents a single token.

### Usage

```
melt_delim(file, delim, quote = "\"", escape_backslash = FALSE,
  escape_double = TRUE, locale = default_locale(), na = c("", "NA"),
  quoted_na = TRUE, comment = "", trim_ws = FALSE, skip = 0,
  n_max = Inf, progress = show_progress(), skip_empty_rows = FALSE)

melt_csv(file, locale = default_locale(), na = c("", "NA"),
  quoted_na = TRUE, quote = "\"", comment = "", trim_ws = TRUE,
  skip = 0, n_max = Inf, progress = show_progress(),
  skip_empty_rows = FALSE)
```

```
melt_csv2(file, locale = default_locale(), na = c("", "NA"),
  quoted_na = TRUE, quote = "\"", comment = "#", trim_ws = TRUE,
  skip = 0, n_max = Inf, progress = show_progress(),
  skip_empty_rows = FALSE)
```

```
melt_tsv(file, locale = default_locale(), na = c("", "NA"),
  quoted_na = TRUE, quote = "\t", comment = "#", trim_ws = TRUE,
  skip = 0, n_max = Inf, progress = show_progress(),
  skip_empty_rows = FALSE)
```

## Arguments

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
delim	Single character used to separate fields within a record.
quote	Single character used to quote strings.
escape_backslash	Does the file use backslashes to escape special characters? This is more general than <code>escape_double</code> as backslashes can be used to escape the delimiter character, the quote character, or to add special characters like <code>\n</code> .
escape_double	Does the file escape quotes by doubling them? i.e. If this option is TRUE, the value <code>""""</code> represents a single quote, <code>\</code> .
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
quoted_na	Should missing values inside quotes be treated as missing values (the default) or strings.
comment	A string used to identify comments. Any text after the comment characters will be silently ignored.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?
skip	Number of lines to skip before reading data.
n_max	Maximum number of records to read.

progress	Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code> .
skip_empty_rows	Should blank rows be ignored altogether? i.e. If this option is <code>TRUE</code> then blank rows will not be represented at all. If it is <code>FALSE</code> then they will be represented by <code>NA</code> values in all the columns.

## Details

`melt_csv()` and `melt_tsv()` are special cases of the general `melt_delim()`. They're useful for reading the most common types of flat file data, comma separated values and tab separated values, respectively. `melt_csv2()` uses `;` for the field separator and `,` for the decimal point. This is common in some European countries.

## Value

A `tibble()` of four columns:

- `row`, the row that the token comes from in the original file
- `col`, the column that the token comes from in the original file
- `data_type`, the data type of the token, e.g. "integer", "character", "date", guessed in a similar way to the `guess_parser()` function.
- `value`, the token itself as a character string, unchanged from its representation in the original file.

If there are parsing problems, a warning tells you how many, and you can retrieve the details with [problems\(\)](#).

## See Also

[read\\_delim\(\)](#) for the conventional way to read rectangular data from delimited files.

## Examples

```
# Input sources -----
# Read from a path
melt_csv(readr_example("mtcars.csv"))
melt_csv(readr_example("mtcars.csv.zip"))
melt_csv(readr_example("mtcars.csv.bz2"))
## Not run:
melt_csv("https://github.com/tidyverse/readr/raw/master/inst/extdata/mtcars.csv")

## End(Not run)

# Or directly from a string (must contain a newline)
melt_csv("x,y\n1,2\n3,4")
```

```
# To import empty cells as 'empty' rather than `NA`
melt_csv("x,y\n,NA,\"\",'', na = "NA")

# File types -----
melt_csv("a,b\n1.0,2.0")
melt_csv2("a;b\n1,0;2,0")
melt_tsv("a\tb\n1.0\t2.0")
melt_delim("a|b\n1.0|2.0", delim = "|")
```

---

melt\_fwf

*Return melted data for each token in a fixed width file*


---

## Description

For certain non-rectangular data formats, it can be useful to parse the data into a melted format where each row represents a single token.

## Usage

```
melt_fwf(file, col_positions, locale = default_locale(), na = c("",
  "NA"), comment = "", trim_ws = TRUE, skip = 0, n_max = Inf,
  progress = show_progress(), skip_empty_rows = FALSE)
```

## Arguments

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
col_positions	<p>Column positions, as created by <code>fwf_empty()</code>, <code>fwf_widths()</code> or <code>fwf_positions()</code>. To read in only selected fields, use <code>fwf_positions()</code>. If the width of the last column is variable (a ragged fwf file), supply the last end position as NA.</p>
locale	<p>The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.</p>
na	<p>Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.</p>
comment	<p>A string used to identify comments. Any text after the comment characters will be silently ignored.</p>

trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?
skip	Number of lines to skip before reading data.
n_max	Maximum number of records to read.
progress	Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code> .
skip_empty_rows	Should blank rows be ignored altogether? i.e. If this option is <code>TRUE</code> then blank rows will not be represented at all. If it is <code>FALSE</code> then they will be represented by <code>NA</code> values in all the columns.

### Details

`melt_fwf()` parses each token of a fixed width file into a single row, but it still requires that each field is in the same in every row of the source file.

### See Also

[melt\\_table\(\)](#) to melt fixed width files where each column is separated by whitespace, and [read\\_fwf\(\)](#) for the conventional way to read rectangular data from fixed width files.

### Examples

```
fwf_sample <- readr_example("fwf-sample.txt")
cat(read_lines(fwf_sample))

# You can specify column positions in several ways:
# 1. Guess based on position of empty columns
melt_fwf(fwf_sample, fwf_empty(fwf_sample, col_names = c("first", "last", "state", "ssn")))
# 2. A vector of field widths
melt_fwf(fwf_sample, fwf_widths(c(20, 10, 12), c("name", "state", "ssn")))
# 3. Paired vectors of start and end positions
melt_fwf(fwf_sample, fwf_positions(c(1, 30), c(10, 42), c("name", "ssn")))
# 4. Named arguments with start and end positions
melt_fwf(fwf_sample, fwf_cols(name = c(1, 10), ssn = c(30, 42)))
# 5. Named arguments with column widths
melt_fwf(fwf_sample, fwf_cols(name = 20, state = 10, ssn = 12))
```

---

melt\_table

*Return melted data for each token in a whitespace-separated file*

---

## Description

For certain non-rectangular data formats, it can be useful to parse the data into a melted format where each row represents a single token.

`melt_table()` and `melt_table2()` are designed to read the type of textual data where each column is separated by one (or more) columns of space.

`melt_table2()` allows any number of whitespace characters between columns, and the lines can be of different lengths.

`melt_table()` is more strict, each line must be the same length, and each field is in the same position in every line. It first finds empty columns and then parses like a fixed width file.

## Usage

```
melt_table(file, locale = default_locale(), na = "NA", skip = 0,
           n_max = Inf, guess_max = min(n_max, 1000),
           progress = show_progress(), comment = "", skip_empty_rows = FALSE)
```

```
melt_table2(file, locale = default_locale(), na = "NA", skip = 0,
            n_max = Inf, progress = show_progress(), comment = "",
            skip_empty_rows = FALSE)
```

## Arguments

<code>file</code>	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in <code>.gz</code>, <code>.bz2</code>, <code>.xz</code>, or <code>.zip</code> will be automatically uncompressed. Files starting with <code>http://</code>, <code>https://</code>, <code>ftp://</code>, or <code>ftps://</code> will be automatically downloaded. Remote <code>gz</code> files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
<code>locale</code>	<p>The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.</p>
<code>na</code>	<p>Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.</p>
<code>skip</code>	<p>Number of lines to skip before reading data.</p>
<code>n_max</code>	<p>Maximum number of records to read.</p>
<code>guess_max</code>	<p>Maximum number of records to use for guessing column types.</p>
<code>progress</code>	<p>Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code>.</p>

comment	A string used to identify comments. Any text after the comment characters will be silently ignored.
skip_empty_rows	Should blank rows be ignored altogether? i.e. If this option is TRUE then blank rows will not be represented at all. If it is FALSE then they will be represented by NA values in all the columns.

**See Also**

[melt\\_fwf\(\)](#) to melt fixed width files where each column is not separated by whitespace. [melt\\_fwf\(\)](#) is also useful for reading tabular data with non-standard formatting. [read\\_table\(\)](#) is the conventional way to read tabular data from whitespace-separated files.

**Examples**

```
# One corner from http://www.masseyratings.com/cf/compare.htm
massey <- readr_example("massey-rating.txt")
cat(read_file(massey))
melt_table(massey)

# Sample of 1978 fuel economy data from
# http://www.fueleconomy.gov/feg/epadata/78data.zip
epa <- readr_example("epa78.txt")
cat(read_file(epa))
melt_table(epa)
```

---

 parse\_atomic

*Parse logicals, integers, and reals*


---

**Description**

Use `parse_*`() if you have a character vector you want to parse. Use `col_*`() in conjunction with a `read_*`() function to parse the values as they're read in.

**Usage**

```
parse_logical(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE)
```

```
parse_integer(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE)
```

```
parse_double(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE)
```

```
parse_character(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE)
```



```
col_logical()
col_integer()
col_double()
col_character()
```

### Arguments

x	Character vector of values to parse.
na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?

### See Also

Other parsers: [col\\_skip](#), [cols\\_condense](#), [cols](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_number](#), [parse\\_vector](#)

### Examples

```
parse_integer(c("1", "2", "3"))
parse_double(c("1", "2", "3.123"))
parse_number("$1,123,456.00")

# Use locale to override default decimal and grouping marks
es_MX <- locale("es", decimal_mark = ",")
parse_number("$1.123.456,00", locale = es_MX)

# Invalid values are replaced with missing values with a warning.
x <- c("1", "2", "3", "-")
parse_double(x)
# Or flag values as missing
parse_double(x, na = "-")
```

---

parse\_datetime

*Parse date/times*

---

### Description

Parse date/times

**Usage**

```
parse_datetime(x, format = "", na = c("", "NA"),
              locale = default_locale(), trim_ws = TRUE)
```

```
parse_date(x, format = "", na = c("", "NA"),
           locale = default_locale(), trim_ws = TRUE)
```

```
parse_time(x, format = "", na = c("", "NA"),
           locale = default_locale(), trim_ws = TRUE)
```

```
col_datetime(format = "")
```

```
col_date(format = "")
```

```
col_time(format = "")
```

**Arguments**

x	A character vector of dates to parse.
format	A format specification, as described below. If set to "", date times are parsed as ISO8601, dates and times used the date and time formats specified in the <a href="#">locale()</a> . Unlike <a href="#">strptime()</a> , the format specification must match the complete string.
na	Character vector of strings to interpret as missing values. Set this option to <a href="#">character()</a> to indicate no missing values.
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <a href="#">locale()</a> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?

**Value**

A [POSIXct\(\)](#) vector with `tz` attribute set to `tz`. Elements that could not be parsed (or did not generate valid dates) will be set to `NA`, and a warning message will inform you of the total number of failures.

**Format specification**

`readr` uses a format specification similar to [strptime\(\)](#). There are three types of element:

1. Date components are specified with "%" followed by a letter. For example "%Y" matches a 4 digit year, "%m", matches a 2 digit month and "%d" matches a 2 digit day. Month and day default to 1, (i.e. Jan 1st) if not present, for example if only a year is given.
2. Whitespace is any sequence of zero or more whitespace characters.
3. Any other character is matched exactly.

parse\_datetime() recognises the following format specifications:

- Year: "%Y" (4 digits), "%y" (2 digits); 00-69 -> 2000-2069, 70-99 -> 1970-1999.
- Month: "%m" (2 digits), "%b" (abbreviated name in current locale), "%B" (full name in current locale).
- Day: "%d" (2 digits), "%e" (optional leading space), "
- Hour: "%H" or "%I", use I (and not H) with AM/PM.
- Minutes: "%M"
- Seconds: "%S" (integer seconds), "%OS" (partial seconds)
- Time zone: "%Z" (as name, e.g. "America/Chicago"), "%z" (as offset from UTC, e.g. "+0800")
- AM/PM indicator: "%p".
- Non-digits: "%." skips one non-digit character, "%+" skips one or more non-digit characters, "%\*" skips any number of non-digits characters.
- Automatic parsers: "%AD" parses with a flexible YMD parser, "%AT" parses with a flexible HMS parser.
- Shortcuts: "%D" = "%m/%d/%y", "%F" = "%Y-%m-%d", "%R" = "%H:%M", "%T" = "%H:%M:%S", "%x" = "%y/%m/%d".

### ISO8601 support

Currently, readr does not support all of ISO8601. Missing features:

- Week & weekday specifications, e.g. "2013-W05", "2013-W05-10"
- Ordinal dates, e.g. "2013-095".
- Using commas instead of a period for decimal separator

The parser is also a little laxer than ISO8601:

- Dates and times can be separated with a space, not just T.
- Mostly correct specifications like "2009-05-19 14:" and "200912-01" work.

### See Also

Other parsers: [col\\_skip](#), [cols\\_condense](#), [cols](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

### Examples

```
# Format strings -----
parse_datetime("01/02/2010", "%d/%m/%Y")
parse_datetime("01/02/2010", "%m/%d/%Y")
# Handle any separator
parse_datetime("01/02/2010", "%m%.%d%.%Y")

# Dates look the same, but internally they use the number of days since
# 1970-01-01 instead of the number of seconds. This avoids a whole lot
# of troubles related to time zones, so use if you can.
```

```

parse_date("01/02/2010", "%d/%m/%Y")
parse_date("01/02/2010", "%m/%d/%Y")

# You can parse timezones from strings (as listed in OlsonNames())
parse_datetime("2010/01/01 12:00 US/Central", "%Y/%m/%d %H:%M %Z")
# Or from offsets
parse_datetime("2010/01/01 12:00 -0600", "%Y/%m/%d %H:%M %z")

# Use the locale parameter to control the default time zone
# (but note UTC is considerably faster than other options)
parse_datetime("2010/01/01 12:00", "%Y/%m/%d %H:%M",
  locale = locale(tz = "US/Central"))
parse_datetime("2010/01/01 12:00", "%Y/%m/%d %H:%M",
  locale = locale(tz = "US/Eastern"))

# Unlike strptime, the format specification must match the complete
# string (ignoring leading and trailing whitespace). This avoids common
# errors:
strptime("01/02/2010", "%d/%m/%y")
parse_datetime("01/02/2010", "%d/%m/%y")

# Failures -----
parse_datetime("01/01/2010", "%d/%m/%Y")
parse_datetime(c("01/ab/2010", "32/01/2010"), "%d/%m/%Y")

# Locales -----
# By default, readr expects English date/times, but that's easy to change'
parse_datetime("1 janvier 2015", "%d %B %Y", locale = locale("fr"))
parse_datetime("1 enero 2015", "%d %B %Y", locale = locale("es"))

# ISO8601 -----
# With separators
parse_datetime("1979-10-14")
parse_datetime("1979-10-14T10")
parse_datetime("1979-10-14T10:11")
parse_datetime("1979-10-14T10:11:12")
parse_datetime("1979-10-14T10:11:12.12345")

# Without separators
parse_datetime("19791014")
parse_datetime("19791014T101112")

# Time zones
us_central <- locale(tz = "US/Central")
parse_datetime("1979-10-14T1010", locale = us_central)
parse_datetime("1979-10-14T1010-0500", locale = us_central)
parse_datetime("1979-10-14T1010Z", locale = us_central)
# Your current time zone
parse_datetime("1979-10-14T1010", locale = locale(tz = ""))

```

---

parse\_factor *Parse factors*

---

### Description

parse\_factor is similar to [factor\(\)](#), but will generate warnings if elements of x are not found in levels.

### Usage

```
parse_factor(x, levels = NULL, ordered = FALSE, na = c("", "NA"),
  locale = default_locale(), include_na = TRUE, trim_ws = TRUE)

col_factor(levels = NULL, ordered = FALSE, include_na = FALSE)
```

### Arguments

x	Character vector of values to parse.
levels	Character vector providing set of allowed levels. if NULL, will generate levels based on the unique values of x, ordered by order of appearance in x.
ordered	Is it an ordered factor?
na	Character vector of strings to interpret as missing values. Set this option to character() to indicate no missing values.
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <a href="#">locale()</a> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
include_na	If NA are present, include as an explicit factor to level?
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?

### See Also

Other parsers: [col\\_skip](#), [cols\\_condense](#), [cols](#), [parse\\_datetime](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

### Examples

```
parse_factor(c("a", "b"), letters)

x <- c("cat", "dog", "caw")
levels <- c("cat", "dog", "cow")

# Base R factor() silently converts unknown levels to NA
x1 <- factor(x, levels)

# parse_factor generates a warning & problems
x2 <- parse_factor(x, levels)
```

```
# Using an argument of `NULL` will generate levels based on values of `x`
x2 <- parse_factor(x, levels = NULL)
```

---

parse_guess	<i>Parse using the "best" type</i>
-------------	------------------------------------

---

### Description

parse\_guess() returns the parser vector; guess\_parser() returns the name of the parser. These functions use a number of heuristics to determine which type of vector is "best". Generally they try to err of the side of safety, as it's straightforward to override the parsing choice if needed.

### Usage

```
parse_guess(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE, guess_integer = FALSE)
```

```
col_guess()
```

```
guess_parser(x, locale = default_locale(), guess_integer = FALSE)
```

### Arguments

x	Character vector of values to parse.
na	Character vector of strings to interpret as missing values. Set this option to character() to indicate no missing values.
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <a href="#">locale()</a> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?
guess_integer	If TRUE, guess integer types for whole numbers, if FALSE guess numeric type for all numbers.

### See Also

Other parsers: [col\\_skip](#), [cols\\_condense](#), [cols](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_logical](#), [parse\\_number](#), [parse\\_vector](#)

**Examples**

```
# Logical vectors
parse_guess(c("FALSE", "TRUE", "F", "T"))

# Integers and doubles
parse_guess(c("1", "2", "3"))
parse_guess(c("1.6", "2.6", "3.4"))

# Numbers containing grouping mark
guess_parser("1,234,566")
parse_guess("1,234,566")

# ISO 8601 date times
guess_parser(c("2010-10-10"))
parse_guess(c("2010-10-10"))
```

---

parse_number	<i>Parse numbers, flexibly</i>
--------------	--------------------------------

---

**Description**

This drops any non-numeric characters before or after the first number. The grouping mark specified by the locale is ignored inside the number.

**Usage**

```
parse_number(x, na = c("", "NA"), locale = default_locale(),
  trim_ws = TRUE)

col_number()
```

**Arguments**

x	Character vector of values to parse.
na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?

**Value**

A numeric vector (double) of parsed numbers.

**See Also**

Other parsers: [col\\_skip](#), [cols\\_condense](#), [cols](#), [parse\\_datetime](#), [parse\\_factor](#), [parse\\_guess](#), [parse\\_logical](#), [parse\\_vector](#)

**Examples**

```
parse_number("$1000")
parse_number("1,234,567.78")
```

---

problems

*Retrieve parsing problems*

---

**Description**

Readr functions will only throw an error if parsing fails in an unrecoverable way. However, there are lots of potential problems that you might want to know about - these are stored in the `problems` attribute of the output, which you can easily access with this function. `stop_for_problems()` will throw an error if there are any parsing problems: this is useful for automated scripts where you want to throw an error as soon as you encounter a problem.

**Usage**

```
problems(x)

stop_for_problems(x)
```

**Arguments**

`x` An data frame (from `read_*()`) or a vector (from `parse_*()`).

**Value**

A data frame with one row for each problem and four columns:

<code>row, col</code>	Row and column of problem
<code>expected</code>	What readr expected to find
<code>actual</code>	What it actually got

**Examples**

```
x <- parse_integer(c("1X", "blah", "3"))
problems(x)

y <- parse_integer(c("1", "2", "3"))
problems(y)
```



---

readr_example	<i>Get path to readr example</i>
---------------	----------------------------------

---

**Description**

readr comes bundled with a number of sample files in its `inst/extdata` directory. This function make them easy to access

**Usage**

```
readr_example(path = NULL)
```

**Arguments**

`path` Name of file. If `NULL`, the example files will be listed.

**Examples**

```
readr_example()
readr_example("challenge.csv")
```

---

read_delim	<i>Read a delimited file (including csv &amp; tsv) into a tibble</i>
------------	--

---

**Description**

`read_csv()` and `read_tsv()` are special cases of the general `read_delim()`. They're useful for reading the most common types of flat file data, comma separated values and tab separated values, respectively. `read_csv2()` uses `;` for the field separator and `,` for the decimal point. This is common in some European countries.

**Usage**

```
read_delim(file, delim, quote = "\"", escape_backslash = FALSE,
  escape_double = TRUE, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  comment = "", trim_ws = FALSE, skip = 0, n_max = Inf,
  guess_max = min(1000, n_max), progress = show_progress(),
  skip_empty_rows = TRUE)
```

```
read_csv(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"", comment = "", trim_ws = TRUE, skip = 0,
  n_max = Inf, guess_max = min(1000, n_max),
  progress = show_progress(), skip_empty_rows = TRUE)
```

```
read_csv2(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"", comment = "", trim_ws = TRUE, skip = 0,
  n_max = Inf, guess_max = min(1000, n_max),
  progress = show_progress(), skip_empty_rows = TRUE)
```

```
read_tsv(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"", comment = "", trim_ws = TRUE, skip = 0,
  n_max = Inf, guess_max = min(1000, n_max),
  progress = show_progress(), skip_empty_rows = TRUE)
```

## Arguments

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
delim	Single character used to separate fields within a record.
quote	Single character used to quote strings.
escape_backslash	Does the file use backslashes to escape special characters? This is more general than <code>escape_double</code> as backslashes can be used to escape the delimiter character, the quote character, or to add special characters like <code>\n</code> .
escape_double	Does the file escape quotes by doubling them? i.e. If this option is TRUE, the value <code>""</code> represents a single quote, <code>\</code> .
col_names	<p>Either TRUE, FALSE or a character vector of column names.</p> <p>If TRUE, the first row of the input will be used as the column names, and will not be included in the data frame. If FALSE, column names will be generated automatically: X1, X2, X3 etc.</p> <p>If <code>col_names</code> is a character vector, the values will be used as the names of the columns, and the first row of the input will be read into the first row of the output data frame.</p> <p>Missing (NA) column names will generate a warning, and be filled in with dummy names X1, X2 etc. Duplicate column names will generate a warning and be made unique with a numeric prefix.</p>
col_types	<p>One of NULL, a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details.</p> <p>If NULL, all column types will be imputed from the first 1000 rows on the input. This is convenient (and fast), but not robust. If the imputation fails, you'll need to supply the correct types yourself.</p>

If a column specification created by `cols()`, it must contain one column specification for each column. If you only want to read a subset of the columns, use `cols_only()`.

Alternatively, you can use a compact string representation where each character represents one column: c = character, i = integer, n = number, d = double, l = logical, f = factor, D = date, T = date time, t = time, ? = guess, or `_/-` to skip the column.

locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
quoted_na	Should missing values inside quotes be treated as missing values (the default) or strings.
comment	A string used to identify comments. Any text after the comment characters will be silently ignored.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?
skip	Number of lines to skip before reading data.
n_max	Maximum number of records to read.
guess_max	Maximum number of records to use for guessing column types.
progress	Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code> .
skip_empty_rows	Should blank rows be ignored altogether? i.e. If this option is <code>TRUE</code> then blank rows will not be represented at all. If it is <code>FALSE</code> then they will be represented by NA values in all the columns.

## Value

A `tibble()`. If there are parsing problems, a warning tells you how many, and you can retrieve the details with `problems()`.

## Examples

```
# Input sources -----
# Read from a path
read_csv(readr_example("mtcars.csv"))
read_csv(readr_example("mtcars.csv.zip"))
read_csv(readr_example("mtcars.csv.bz2"))

## Not run:
# Including remote paths
```

```

read_csv("https://github.com/tidyverse/readr/raw/master/inst/extdata/mtcars.csv")

## End(Not run)

# Or directly from a string (must contain a newline)
read_csv("x,y\n1,2\n3,4")

# Column types -----
# By default, readr guesses the columns types, looking at the first 1000 rows.
# You can override with a compact specification:
read_csv("x,y\n1,2\n3,4", col_types = "dc")

# Or with a list of column types:
read_csv("x,y\n1,2\n3,4", col_types = list(col_double(), col_character()))

# If there are parsing problems, you get a warning, and can extract
# more details with problems()
y <- read_csv("x\n1\n2\nb", col_types = list(col_double()))
y
problems(y)

# File types -----
read_csv("a,b\n1.0,2.0")
read_csv2("a;b\n1,0;2,0")
read_tsv("a\tb\n1.0\t2.0")
read_delim("a|b\n1.0|2.0", delim = "|")

```

---

read\_file

*Read/write a complete file*


---

## Description

`read_file()` reads a complete file into a single object: either a character vector of length one, or a raw vector. `write_file()` takes a single string, or a raw vector, and writes it exactly as is. Raw vectors are useful when dealing with binary data, or if you have text data with unknown encoding.

## Usage

```
read_file(file, locale = default_locale())
```

```
read_file_raw(file)
```

```
write_file(x, path, append = FALSE)
```

## Arguments

`file` Either a path to a file, a connection, or literal data (either a single string or a raw vector).

Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.

Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.

Using a value of `clipboard()` will read from the system clipboard.

locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
x	A data frame to write to disk
path	Path or connection to write to.
append	If FALSE, will overwrite existing file. If TRUE, will append to existing file. In both cases, if file does not exist a new file is created.

### Value

`read_file`: A length 1 character vector. `read_lines_raw`: A raw vector.

### Examples

```
read_file(file.path(R.home("doc"), "AUTHORS"))
read_file_raw(file.path(R.home("doc"), "AUTHORS"))

tmp <- tempfile()

x <- format_csv(mtcars[1:6, ])
write_file(x, tmp)
identical(x, read_file(tmp))

read_lines(x)
```

---

read\_fwf

*Read a fixed width file into a tibble*

---

### Description

A fixed width file can be a very compact representation of numeric data. It's also very fast to parse, because every field is in the same place in every line. Unfortunately, it's painful to parse because you need to describe the length of every field. Readr aims to make it as easy as possible by providing a number of different ways to describe the field structure.

**Usage**

```
read_fwf(file, col_positions, col_types = NULL,
         locale = default_locale(), na = c("", "NA"), comment = "",
         trim_ws = TRUE, skip = 0, n_max = Inf, guess_max = min(n_max,
         1000), progress = show_progress(), skip_empty_rows = TRUE)

fwf_empty(file, skip = 0, skip_empty_rows = FALSE, col_names = NULL,
         comment = "", n = 100L)

fwf_widths(widths, col_names = NULL)

fwf_positions(start, end = NULL, col_names = NULL)

fwf_cols(...)
```

**Arguments**

- |               |  |
|---------------|--|
| file          | <p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in <code>.gz</code>, <code>.bz2</code>, <code>.xz</code>, or <code>.zip</code> will be automatically uncompressed. Files starting with <code>http://</code>, <code>https://</code>, <code>ftp://</code>, or <code>ftps://</code> will be automatically downloaded. Remote <code>gz</code> files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>  |
| col_positions | <p>Column positions, as created by <code>fwf_empty()</code>, <code>fwf_widths()</code> or <code>fwf_positions()</code>. To read in only selected fields, use <code>fwf_positions()</code>. If the width of the last column is variable (a ragged fwf file), supply the last end position as <code>NA</code>.</p>   |
| col_types     | <p>One of <code>NULL</code>, a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details.</p> <p>If <code>NULL</code>, all column types will be imputed from the first 1000 rows on the input. This is convenient (and fast), but not robust. If the imputation fails, you'll need to supply the correct types yourself.</p> <p>If a column specification created by <code>cols()</code>, it must contain one column specification for each column. If you only want to read a subset of the columns, use <code>cols_only()</code>.</p> <p>Alternatively, you can use a compact string representation where each character represents one column: <code>c</code> = character, <code>i</code> = integer, <code>n</code> = number, <code>d</code> = double, <code>l</code> = logical, <code>f</code> = factor, <code>D</code> = date, <code>T</code> = date time, <code>t</code> = time, <code>?</code> = guess, or <code>_/-</code> to skip the column.</p> |
| locale        | <p>The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.</p>  |

na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
comment	A string used to identify comments. Any text after the comment characters will be silently ignored.
trim_ws	Should leading and trailing whitespace be trimmed from each field before parsing it?
skip	Number of lines to skip before reading data.
n_max	Maximum number of records to read.
guess_max	Maximum number of records to use for guessing column types.
progress	Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code> .
skip_empty_rows	Should blank rows be ignored altogether? i.e. If this option is <code>TRUE</code> then blank rows will not be represented at all. If it is <code>FALSE</code> then they will be represented by <code>NA</code> values in all the columns.
col_names	Either <code>NULL</code> , or a character vector column names.
n	Number of lines the tokenizer will read to determine file structure. By default it is set to 100.
widths	Width of each field. Use <code>NA</code> as width of last field when reading a ragged fwf file.
start, end	Starting and ending (inclusive) positions of each field. Use <code>NA</code> as last end field when reading a ragged fwf file.
...	If the first element is a data frame, then it must have all numeric columns and either one or two rows. The column names are the variable names. The column values are the variable widths if a length one vector, and if length two, variable start and end positions. The elements of ... are used to construct a data frame with one or two rows as above.

### See Also

[read\\_table\(\)](#) to read fixed width files where each column is separated by whitespace.

### Examples

```
fwf_sample <- readr_example("fwf-sample.txt")
cat(read_lines(fwf_sample))

# You can specify column positions in several ways:
# 1. Guess based on position of empty columns
read_fwf(fwf_sample, fwf_empty(fwf_sample, col_names = c("first", "last", "state", "ssn")))
# 2. A vector of field widths
read_fwf(fwf_sample, fwf_widths(c(20, 10, 12), c("name", "state", "ssn")))
# 3. Paired vectors of start and end positions
```

```

read_fwf(fwf_sample, fwf_positions(c(1, 30), c(20, 42), c("name", "ssn")))
# 4. Named arguments with start and end positions
read_fwf(fwf_sample, fwf_cols(name = c(1, 20), ssn = c(30, 42)))
# 5. Named arguments with column widths
read_fwf(fwf_sample, fwf_cols(name = 20, state = 10, ssn = 12))

```

---

read\_lines

*Read/write lines to/from a file*


---

## Description

`read_lines()` reads up to `n_max` lines from a file. New lines are not included in the output. `read_lines_raw()` produces a list of raw vectors, and is useful for handling data with unknown encoding. `write_lines()` takes a character vector or list of raw vectors, appending a new line after each entry.

## Usage

```

read_lines(file, skip = 0, skip_empty_rows = FALSE, n_max = -1L,
  locale = default_locale(), na = character(),
  progress = show_progress())

```

```

read_lines_raw(file, skip = 0, n_max = -1L,
  progress = show_progress())

```

```

write_lines(x, path, sep = "\n", na = "NA", append = FALSE)

```

## Arguments

<code>file</code>	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in <code>.gz</code>, <code>.bz2</code>, <code>.xz</code>, or <code>.zip</code> will be automatically uncompressed. Files starting with <code>http://</code>, <code>https://</code>, <code>ftp://</code>, or <code>ftps://</code> will be automatically downloaded. Remote <code>gz</code> files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
<code>skip</code>	Number of lines to skip before reading data.
<code>skip_empty_rows</code>	Should blank rows be ignored altogether? i.e. If this option is <code>TRUE</code> then blank rows will not be represented at all. If it is <code>FALSE</code> then they will be represented by <code>NA</code> values in all the columns.
<code>n_max</code>	Number of lines to read. If <code>n_max</code> is <code>-1</code> , all lines in file will be read.



locale	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.
na	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
progress	Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to <code>FALSE</code> .
x	A data frame to write to disk
path	Path or connection to write to.
sep	The line separator. Defaults to <code>\n</code> , commonly used on POSIX systems like macOS and linux. For native windows (CRLF) separators use <code>\r\n</code> .
append	If <code>FALSE</code> , will overwrite existing file. If <code>TRUE</code> , will append to existing file. In both cases, if file does not exist a new file is created.

**Value**

`read_lines()`: A character vector with one element for each line. `read_lines_raw()`: A list containing a raw vector for each line.

`write_lines()` returns `x`, invisibly.

**Examples**

```
read_lines(file.path(R.home("doc"), "AUTHORS"), n_max = 10)
read_lines_raw(file.path(R.home("doc"), "AUTHORS"), n_max = 10)

tmp <- tempfile()

write_lines(rownames(mtcars), tmp)
read_lines(tmp)
read_file(tmp) # note trailing \n

write_lines(airquality$Ozone, tmp, na = "-1")
read_lines(tmp)
```

---

read\_log

*Read common/combined log file into a tibble*


---

**Description**

This is a fairly standard format for log files - it uses both quotes and square brackets for quoting, and there may be literal quotes embedded in a quoted string. The dash, "-", is used for missing values.

**Usage**

```
read_log(file, col_names = FALSE, col_types = NULL, skip = 0,
         n_max = Inf, progress = show_progress())
```

**Arguments**

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
col_names	<p>Either TRUE, FALSE or a character vector of column names.</p> <p>If TRUE, the first row of the input will be used as the column names, and will not be included in the data frame. If FALSE, column names will be generated automatically: X1, X2, X3 etc.</p> <p>If col_names is a character vector, the values will be used as the names of the columns, and the first row of the input will be read into the first row of the output data frame.</p> <p>Missing (NA) column names will generate a warning, and be filled in with dummy names X1, X2 etc. Duplicate column names will generate a warning and be made unique with a numeric prefix.</p>
col_types	<p>One of NULL, a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details.</p> <p>If NULL, all column types will be imputed from the first 1000 rows on the input. This is convenient (and fast), but not robust. If the imputation fails, you'll need to supply the correct types yourself.</p> <p>If a column specification created by <code>cols()</code>, it must contain one column specification for each column. If you only want to read a subset of the columns, use <code>cols_only()</code>.</p> <p>Alternatively, you can use a compact string representation where each character represents one column: c = character, i = integer, n = number, d = double, l = logical, f = factor, D = date, T = date time, t = time, ? = guess, or _/- to skip the column.</p>
skip	Number of lines to skip before reading data.
n_max	Maximum number of records to read.
progress	<p>Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to FALSE.</p>

**Examples**

```
read_log(readr_example("example.log"))
```

---

read_table	<i>Read whitespace-separated columns into a tibble</i>
------------	--

---

**Description**

`read_table()` and `read_table2()` are designed to read the type of textual data where each column is separated by one (or more) columns of space.

`read_table2()` is like `read.table()`, it allows any number of whitespace characters between columns, and the lines can be of different lengths.

`read_table()` is more strict, each line must be the same length, and each field is in the same position in every line. It first finds empty columns and then parses like a fixed width file.

`spec_table()` and `spec_table2()` return the column specifications rather than a data frame.

**Usage**

```
read_table(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = "NA", skip = 0, n_max = Inf,
  guess_max = min(n_max, 1000), progress = show_progress(),
  comment = "", skip_empty_rows = TRUE)
```

```
read_table2(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = "NA", skip = 0, n_max = Inf,
  guess_max = min(n_max, 1000), progress = show_progress(),
  comment = "", skip_empty_rows = TRUE)
```

**Arguments**

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in <code>.gz</code>, <code>.bz2</code>, <code>.xz</code>, or <code>.zip</code> will be automatically uncompressed. Files starting with <code>http://</code>, <code>https://</code>, <code>ftp://</code>, or <code>ftps://</code> will be automatically downloaded. Remote <code>gz</code> files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
col_names	<p>Either <code>TRUE</code>, <code>FALSE</code> or a character vector of column names.</p> <p>If <code>TRUE</code>, the first row of the input will be used as the column names, and will not be included in the data frame. If <code>FALSE</code>, column names will be generated automatically: <code>X1</code>, <code>X2</code>, <code>X3</code> etc.</p>

	<p>If <code>col_names</code> is a character vector, the values will be used as the names of the columns, and the first row of the input will be read into the first row of the output data frame.</p> <p>Missing (NA) column names will generate a warning, and be filled in with dummy names X1, X2 etc. Duplicate column names will generate a warning and be made unique with a numeric prefix.</p>
<code>col_types</code>	<p>One of NULL, a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details.</p> <p>If NULL, all column types will be imputed from the first 1000 rows on the input. This is convenient (and fast), but not robust. If the imputation fails, you'll need to supply the correct types yourself.</p> <p>If a column specification created by <code>cols()</code>, it must contain one column specification for each column. If you only want to read a subset of the columns, use <code>cols_only()</code>.</p> <p>Alternatively, you can use a compact string representation where each character represents one column: c = character, i = integer, n = number, d = double, l = logical, f = factor, D = date, T = date time, t = time, ? = guess, or <code>_/-</code> to skip the column.</p>
<code>locale</code>	<p>The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.</p>
<code>na</code>	<p>Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.</p>
<code>skip</code>	<p>Number of lines to skip before reading data.</p>
<code>n_max</code>	<p>Maximum number of records to read.</p>
<code>guess_max</code>	<p>Maximum number of records to use for guessing column types.</p>
<code>progress</code>	<p>Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to FALSE.</p>
<code>comment</code>	<p>A string used to identify comments. Any text after the comment characters will be silently ignored.</p>
<code>skip_empty_rows</code>	<p>Should blank rows be ignored altogether? i.e. If this option is TRUE then blank rows will not be represented at all. If it is FALSE then they will be represented by NA values in all the columns.</p>

### See Also

`read_fwf()` to read fixed width files where each column is not separated by whitespace. `read_fwf()` is also useful for reading tabular data with non-standard formatting.

**Examples**

```
# One corner from http://www.masseyratings.com/cf/compare.htm
massey <- readr_example("massey-rating.txt")
cat(read_file(massey))
read_table(massey)

# Sample of 1978 fuel economy data from
# http://www.fueleconomy.gov/feg/epadata/78data.zip
epa <- readr_example("epa78.txt")
cat(read_file(epa))
read_table(epa, col_names = FALSE)
```

---

show_progress	<i>Determine progress bars should be shown</i>
---------------	--

---

**Description**

Progress bars are shown *unless* one of the following is TRUE

- The bar is explicitly disabled by setting `options(readr.show_progress = FALSE)`
- The code is run in a non-interactive session (`interactive()` is FALSE).
- The code is run in an RStudio notebook chunk.
- The code is run by knitr / rmarkdown.

**Usage**

```
show_progress()
```

---

spec_delim	<i>Generate a column specification</i>
------------	--

---

**Description**

When printed, only the first 20 columns are printed by default. To override, set `options(readr.num_columns)` can be used to modify this (a value of 0 turns off printing).

**Usage**

```
spec_delim(file, delim, quote = "\"", escape_backslash = FALSE,
  escape_double = TRUE, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  comment = "", trim_ws = FALSE, skip = 0, n_max = 0,
  guess_max = 1000, progress = show_progress(),
  skip_empty_rows = TRUE)
```

```
spec_csv(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"" , comment = "", trim_ws = TRUE, skip = 0,
  n_max = 0, guess_max = 1000, progress = show_progress(),
  skip_empty_rows = TRUE)
```

```
spec_csv2(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"" , comment = "", trim_ws = TRUE, skip = 0,
  n_max = 0, guess_max = 1000, progress = show_progress(),
  skip_empty_rows = TRUE)
```

```
spec_tsv(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = c("", "NA"), quoted_na = TRUE,
  quote = "\"" , comment = "", trim_ws = TRUE, skip = 0,
  n_max = 0, guess_max = 1000, progress = show_progress(),
  skip_empty_rows = TRUE)
```

```
spec_table(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = "NA", skip = 0, n_max = 0,
  guess_max = 1000, progress = show_progress(), comment = "",
  skip_empty_rows = TRUE)
```

```
spec_table2(file, col_names = TRUE, col_types = NULL,
  locale = default_locale(), na = "NA", skip = 0, n_max = 0,
  guess_max = 1000, progress = show_progress(), comment = "",
  skip_empty_rows = TRUE)
```

## Arguments

file	<p>Either a path to a file, a connection, or literal data (either a single string or a raw vector).</p> <p>Files ending in .gz, .bz2, .xz, or .zip will be automatically uncompressed. Files starting with http://, https://, ftp://, or ftps:// will be automatically downloaded. Remote gz files can also be automatically downloaded and decompressed.</p> <p>Literal data is most useful for examples and tests. It must contain at least one new line to be recognised as data (instead of a path) or be a vector of greater than length 1.</p> <p>Using a value of <code>clipboard()</code> will read from the system clipboard.</p>
delim	Single character used to separate fields within a record.
quote	Single character used to quote strings.
escape_backslash	Does the file use backslashes to escape special characters? This is more general than <code>escape_double</code> as backslashes can be used to escape the delimiter character, the quote character, or to add special characters like <code>\n</code> .
escape_double	Does the file escape quotes by doubling them? i.e. If this option is TRUE, the value <code>""""</code> represents a single quote, <code>\</code> .

col_names	<p>Either TRUE, FALSE or a character vector of column names.</p> <p>If TRUE, the first row of the input will be used as the column names, and will not be included in the data frame. If FALSE, column names will be generated automatically: X1, X2, X3 etc.</p> <p>If col_names is a character vector, the values will be used as the names of the columns, and the first row of the input will be read into the first row of the output data frame.</p> <p>Missing (NA) column names will generate a warning, and be filled in with dummy names X1, X2 etc. Duplicate column names will generate a warning and be made unique with a numeric prefix.</p>
col_types	<p>One of NULL, a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details.</p> <p>If NULL, all column types will be imputed from the first 1000 rows on the input. This is convenient (and fast), but not robust. If the imputation fails, you'll need to supply the correct types yourself.</p> <p>If a column specification created by <code>cols()</code>, it must contain one column specification for each column. If you only want to read a subset of the columns, use <code>cols_only()</code>.</p> <p>Alternatively, you can use a compact string representation where each character represents one column: c = character, i = integer, n = number, d = double, l = logical, f = factor, D = date, T = date time, t = time, ? = guess, or <code>_/-</code> to skip the column.</p>
locale	<p>The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.</p>
na	<p>Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.</p>
quoted_na	<p>Should missing values inside quotes be treated as missing values (the default) or strings.</p>
comment	<p>A string used to identify comments. Any text after the comment characters will be silently ignored.</p>
trim_ws	<p>Should leading and trailing whitespace be trimmed from each field before parsing it?</p>
skip	<p>Number of lines to skip before reading data.</p>
n_max	<p>Maximum number of records to read.</p>
guess_max	<p>Maximum number of records to use for guessing column types.</p>
progress	<p>Display a progress bar? By default it will only display in an interactive session and not while knitting a document. The display is updated every 50,000 values and will only display if estimated reading time is 5 seconds or more. The automatic progress bar can be disabled by setting option <code>readr.show_progress</code> to FALSE.</p>
skip_empty_rows	<p>Should blank rows be ignored altogether? i.e. If this option is TRUE then blank rows will not be represented at all. If it is FALSE then they will be represented by NA values in all the columns.</p>

**Value**

The `col_spec` generated for the file.

**Examples**

```
# Input sources -----
# Retrieve specs from a path
spec_csv(system.file("extdata/mtcars.csv", package = "readr"))
spec_csv(system.file("extdata/mtcars.csv.zip", package = "readr"))

# Or directly from a string (must contain a newline)
spec_csv("x,y\n1,2\n3,4")

# Column types -----
# By default, readr guesses the columns types, looking at the first 1000 rows.
# You can specify the number of rows used with guess_max.
spec_csv(system.file("extdata/mtcars.csv", package = "readr"), guess_max = 20)
```

---

type\_convert

*Re-convert character columns in existing data frame*

---

**Description**

This is useful if you need to do some manual munging - you can read the columns in as character, clean it up with (e.g.) regular expressions and then let readr take another stab at parsing it. The name is a homage to the base `utils::type.convert()`.

**Usage**

```
type_convert(df, col_types = NULL, na = c("", "NA"), trim_ws = TRUE,
             locale = default_locale())
```

**Arguments**

<code>df</code>	A data frame.
<code>col_types</code>	One of <code>NULL</code> , a <code>cols()</code> specification, or a string. See <code>vignette("readr")</code> for more details. If <code>NULL</code> , column types will be imputed using all rows.
<code>na</code>	Character vector of strings to interpret as missing values. Set this option to <code>character()</code> to indicate no missing values.
<code>trim_ws</code>	Should leading and trailing whitespace be trimmed from each field before parsing it?
<code>locale</code>	The locale controls defaults that vary from place to place. The default locale is US-centric (like R), but you can use <code>locale()</code> to create your own locale that controls things like the default time zone, encoding, decimal mark, big mark, and day/month names.



**Examples**

```
df <- data.frame(
  x = as.character(runif(10)),
  y = as.character(sample(10)),
  stringsAsFactors = FALSE
)
str(df)
str(type_convert(df))

df <- data.frame(x = c("NA", "10"), stringsAsFactors = FALSE)
str(type_convert(df))

# Type convert can be used to infer types from an entire dataset

# first read the data as character
data <- read_csv(readr_example("mtcars.csv"),
  col_types = cols(.default = col_character()))
str(data)
# Then convert it with type_convert
type_convert(data)
```

---

write\_delim

*Write a data frame to a delimited file*


---

**Description**

This is about twice as fast as `write.csv()`, and never writes row names. `output_column()` is a generic method used to coerce columns to suitable output.

**Usage**

```
write_delim(x, path, delim = " ", na = "NA", append = FALSE,
  col_names = !append, quote_escape = "double")

write_csv(x, path, na = "NA", append = FALSE, col_names = !append,
  quote_escape = "double")

write_csv2(x, path, na = "NA", append = FALSE, col_names = !append,
  quote_escape = "double")

write_excel_csv(x, path, na = "NA", append = FALSE,
  col_names = !append, delim = ",", quote_escape = "double")

write_excel_csv2(x, path, na = "NA", append = FALSE,
  col_names = !append, delim = ";", quote_escape = "double")

write_tsv(x, path, na = "NA", append = FALSE, col_names = !append,
  quote_escape = "double")
```

**Arguments**

x	A data frame to write to disk
path	Path or connection to write to.
delim	Delimiter used to separate values. Defaults to " " for write_delim(), ", " for write_excel_csv() and ";" for write_excel_csv2(). Must be a single character.
na	String used for missing values. Defaults to NA. Missing values will never be quoted; strings with the same value as na will always be quoted.
append	If FALSE, will overwrite existing file. If TRUE, will append to existing file. In both cases, if file does not exist a new file is created.
col_names	Write columns names at the top of the file? Must be either TRUE or FALSE.
quote_escape	The type of escaping to use for quoted values, one of "double", "backslash" or "none". You can also use FALSE, which is equivalent to "none". The default is to double the quotes, which is the format excel expects.

**Value**

write\_\*() returns the input x invisibly.

**Output**

Factors are coerced to character. Doubles are formatted using the grisu3 algorithm. POSIXct's are formatted as ISO8601 with a UTC timezone *Note: POSIXct objects in local or non-UTC timezones will be converted to UTC time before writing.*

All columns are encoded as UTF-8. write\_excel\_csv() and write\_excel\_csv2() also include a **UTF-8 Byte order mark** which indicates to Excel the csv is UTF-8 encoded.

write\_excel\_csv2() and write\_csv2 were created to allow users with different locale settings save csv files with their default settings ; as column separator and , as decimal separator. This is common in some European countries.

Values are only quoted if needed: if they contain a comma, quote or newline.

The write\_\*() functions will automatically compress outputs if an appropriate extension is given. At present, three extensions are supported, .gz for gzip compression, .bz2 for bzip2 compression and .xz for lzma compression. See the examples for more information.

**References**

Florian Loitsch, Printing Floating-Point Numbers Quickly and Accurately with Integers, PLDI '10, <http://www.cs.tufts.edu/~nr/cs257/archive/florian-loitsch/printf.pdf>

**Examples**

```
tmp <- tempfile()
write_csv(mtcars, tmp)
head(read_csv(tmp))

# format_* is useful for testing and represses
```

```
cat(format_csv(head(mtcars)))
cat(format_tsv(head(mtcars)))
cat(format_delim(head(mtcars), ";"))

df <- data.frame(x = c(1, 2, NA))
format_csv(df, na = ".")

# Quotes are automatically as needed
df <- data.frame(x = c("a", "'", ",,", "\n"))
cat(format_csv(df))

# A output connection will be automatically created for output filenames
# with appropriate extensions.
dir <- tempdir()
write_tsv(mtcars, file.path(dir, "mtcars.tsv.gz"))
write_tsv(mtcars, file.path(dir, "mtcars.tsv.bz2"))
write_tsv(mtcars, file.path(dir, "mtcars.tsv.xz"))
```

# Index

clipboard, 2  
clipboard(), 5, 11, 13, 15, 26, 29, 30, 32, 34, 35, 38  
col\_character (parse\_atomic), 16  
col\_date (parse\_datetime), 17  
col\_datetime (parse\_datetime), 17  
col\_double (parse\_atomic), 16  
col\_factor (parse\_factor), 21  
col\_guess (parse\_guess), 22  
col\_integer (parse\_atomic), 16  
col\_logical (parse\_atomic), 16  
col\_number (parse\_number), 23  
col\_skip, 3, 4, 5, 17, 19, 21, 22, 24  
col\_time (parse\_datetime), 17  
cols, 3, 4, 5, 17, 19, 21, 22, 24  
cols(), 26, 27, 30, 34, 36, 39, 40  
cols\_condense, 3, 4, 5, 17, 19, 21, 22, 24  
cols\_only (cols), 3  
cols\_only(), 5, 27, 30, 34, 36, 39  
count\_fields, 5  
  
datasource(), 9  
date\_names, 6  
date\_names(), 9  
date\_names\_lang (date\_names), 6  
date\_names\_lang(), 9  
date\_names\_langs (date\_names), 6  
default\_locale (locale), 9  
  
factor(), 21  
format\_csv (format\_delim), 7  
format\_csv2 (format\_delim), 7  
format\_delim, 7  
format\_tsv (format\_delim), 7  
fwf\_cols (read\_fwf), 29  
fwf\_empty (read\_fwf), 29  
fwf\_empty(), 13, 30  
fwf\_positions (read\_fwf), 29  
fwf\_positions(), 13, 30  
fwf\_widths (read\_fwf), 29  
  
fwf\_widths(), 13, 30  
  
guess\_encoding, 8  
guess\_parser (parse\_guess), 22  
  
locale, 9  
locale(), 11, 13, 15, 17, 18, 21–23, 27, 29, 30, 33, 36, 39, 40  
  
melt\_csv (melt\_delim), 10  
melt\_csv2 (melt\_delim), 10  
melt\_delim, 10  
melt\_fwf, 13  
melt\_fwf(), 16  
melt\_table, 14  
melt\_table(), 14  
melt\_table2 (melt\_table), 14  
melt\_tsv (melt\_delim), 10  
  
OlsonNames(), 10  
  
parse\_atomic, 16  
parse\_character (parse\_atomic), 16  
parse\_date (parse\_datetime), 17  
parse\_datetime, 3–5, 17, 17, 21, 22, 24  
parse\_double (parse\_atomic), 16  
parse\_factor, 3–5, 17, 19, 20, 22, 24  
parse\_guess, 3–5, 17, 19, 21, 22, 24  
parse\_integer (parse\_atomic), 16  
parse\_logical, 3–5, 19, 21, 22, 24  
parse\_logical (parse\_atomic), 16  
parse\_number, 3–5, 17, 19, 21, 22, 23  
parse\_time (parse\_datetime), 17  
parse\_vector, 3–5, 17, 19, 21, 22, 24  
POSIXct(), 18  
problems, 24  
problems(), 12, 27  
  
read.table(), 35  
read\_csv (read\_delim), 25  
read\_csv2 (read\_delim), 25

read\_delim, 25  
read\_delim(), 2, 3, 12  
read\_file, 28  
read\_file\_raw(read\_file), 28  
read\_fwf, 29  
read\_fwf(), 14, 36  
read\_lines, 32  
read\_lines\_raw(read\_lines), 32  
read\_log, 33  
read\_table, 35  
read\_table(), 16, 31  
read\_table2(read\_table), 35  
read\_tsv(read\_delim), 25  
readr\_example, 25

show\_progress, 37  
spec(cols\_condense), 4  
spec\_csv(spec\_delim), 37  
spec\_csv2(spec\_delim), 37  
spec\_delim, 37  
spec\_table(spec\_delim), 37  
spec\_table2(spec\_delim), 37  
spec\_tsv(spec\_delim), 37  
stop\_for\_problems(problems), 24  
stringi::stri\_enc\_detect(), 8  
strptime(), 18

tibble(), 12, 27  
tokenizer\_csv(), 6  
tokenizer\_fwf(), 6  
type\_convert, 40

utils::type.convert(), 40

write.csv(), 41  
write\_csv(write\_delim), 41  
write\_csv(), 7  
write\_csv2(write\_delim), 41  
write\_delim, 41  
write\_excel\_csv(write\_delim), 41  
write\_excel\_csv2(write\_delim), 41  
write\_file(read\_file), 28  
write\_lines(read\_lines), 32  
write\_tsv(write\_delim), 41