

Package ‘solvebio’

June 24, 2020

Type Package

Title The Official SolveBio API Client

Version 2.8.0

Date 2020-06-24

Author David Caplan

Maintainer David Caplan <dcaplan@solvebio.com>

Description R language bindings for SolveBio's API.

SolveBio is a biomedical knowledge hub that enables life science organizations to collect and harmonize the complex, disparate “multi-omic” data essential for today's R&D and BI needs.

For more information, visit <<https://www.solvebio.com>>.

URL <https://github.com/solvebio/solvebio-r>

Imports httr, jsonlite, dplyr (>= 0.5.0), mime

License MIT + file LICENSE

Collate solvebio.R annotation.R application.R beacon.R beacon_set.R dataset.R dataset_commit.R dataset_export.R dataset_field.R dataset_import.R dataset_migration.R dataset_template.R object.R saved_query.R shiny.R task.R user.R utils.R vault.R zzz.R

RoxygenNote 7.0.2

Suggests testthat, shiny, shinyjs, openssl

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-24 14:30:02 UTC

R topics documented:

Annotator.annotate	4
Application.all	5
Application.create	5

Application.delete	6
Application.retrieve	7
Application.update	7
Beacon.all	8
Beacon.create	9
Beacon.delete	10
Beacon.query	10
Beacon.retrieve	11
Beacon.update	12
BeaconSet.all	12
BeaconSet.create	13
BeaconSet.delete	14
BeaconSet.query	15
BeaconSet.retrieve	15
BeaconSet.update	16
createEnv	17
Dataset.activity	17
Dataset.all	18
Dataset.count	19
Dataset.create	19
Dataset.data	20
Dataset.delete	21
Dataset.facets	21
Dataset.fields	22
Dataset.get_by_full_path	23
Dataset.get_or_create_by_full_path	23
Dataset.query	24
Dataset.retrieve	25
Dataset.template	25
Dataset.update	26
DatasetCommit.all	27
DatasetCommit.delete	27
DatasetCommit.retrieve	28
DatasetExport.all	29
DatasetExport.create	29
DatasetExport.delete	30
DatasetExport.get_download_url	31
DatasetExport.retrieve	31
DatasetField.all	32
DatasetField.create	33
DatasetField.facets	34
DatasetField.retrieve	34
DatasetField.update	35
DatasetImport.all	36
DatasetImport.create	36
DatasetImport.delete	37
DatasetImport.retrieve	38
DatasetMigration.all	38

DatasetMigration.create	39
DatasetMigration.delete	40
DatasetMigration.retrieve	41
DatasetTemplate.all	41
DatasetTemplate.create	42
DatasetTemplate.delete	43
DatasetTemplate.retrieve	43
DatasetTemplate.update	44
Expression.evaluate	45
login	46
Object.all	46
Object.create	47
Object.delete	48
Object.get_by_full_path	49
Object.get_by_path	49
Object.get_download_url	50
Object.get_or_upload_file	51
Object.retrieve	52
Object.update	52
Object.upload_file	53
protectedServer	54
protectedServerJS	55
SavedQuery.all	55
SavedQuery.create	56
SavedQuery.delete	57
SavedQuery.retrieve	57
SavedQuery.update	58
Task.all	59
Task.follow	59
Task.retrieve	60
User.retrieve	60
Vault.all	61
Vault.create	62
Vault.create_dataset	62
Vault.create_folder	63
Vault.datasets	64
Vault.delete	64
Vault.files	65
Vault.folders	66
Vault.get_by_full_path	66
Vault.get_or_create_by_full_path	67
Vault.get_personal_vault	68
Vault.objects	68
Vault.retrieve	69
Vault.search	70
Vault.update	70

Annotator.annotate *Annotator.annotate*

Description

Annotate a data table/frame with additional fields.

Usage

```
Annotator.annotate(  
  records,  
  fields,  
  include_errors = FALSE,  
  raw = FALSE,  
  env = solvebio::.solveEnv  
)
```

Arguments

records	The data table or data frame to annotate.
fields	The fields to add.
include_errors	Set to TRUE to include errors in the output (default: FALSE).
raw	Set to TRUE to return the raw response (default: FALSE).
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Annotator.annotate(records=tbl, fields=fields)  
  
## End(Not run)
```

Application.all *Application.all*

Description

Retrieves the metadata about all application on SolveBio available to the current user.

Usage

```
Application.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Application.all()  
  
## End(Not run)
```

Application.create *Application.create*

Description

Create a new SolveBio application.

Usage

```
Application.create(name, redirect_uris, env = solvebio:::.solveEnv, ...)
```

Arguments

name	The name of the application.
redirect_uris	A list of space-separated OAuth2 redirect URIs.
env	(optional) Custom client environment.
...	(optional) Additional application attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Application.create(
  name="My new application",
  redirect_uris="http://localhost:3838/"
)

## End(Not run)
```

Application.delete *Application.delete*

Description

Delete a specific application from SolveBio.

Usage

```
Application.delete(client_id, env = solvebio:::solveEnv)
```

Arguments

<code>client_id</code>	The client ID for the application.
<code>env</code>	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Application.delete("abcd1234")

## End(Not run)
```

Application.retrieve *Application.retrieve*

Description

Retrieves the metadata about a specific application SolveBio.

Usage

```
Application.retrieve(client_id, env = solvebio:::.solveEnv)
```

Arguments

client_id	The client ID for the application.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Application.retrieve("abcd1234")  
  
## End(Not run)
```

Application.update *Application.update*

Description

Updates the attributes of an existing application.

Usage

```
Application.update(client_id, env = solvebio:::.solveEnv, ...)
```

Arguments

client_id	The client ID for the application.
env	(optional) Custom client environment.
...	Application attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Application.update(
  "abcd1234",
  name="New app name"
)

## End(Not run)
```

Beacon.all

Beacon.all

Description

Retrieves the metadata about all beacons on SolveBio accessible to the current user.

Usage

```
Beacon.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Beacon.all()

## End(Not run)
```

Beacon.create	<i>Beacon.create</i>
---------------	----------------------

Description

Add a new beacon to an existing beacon set. The beacon set must already exist in order to add beacons.

Usage

```
Beacon.create(  
  beacon_set_id,  
  vault_object_id,  
  title,  
  env = solvebio:::solveEnv,  
  ...  
)
```

Arguments

<code>beacon_set_id</code>	The ID of the parent beacon set.
<code>vault_object_id</code>	The ID of the vault object (i.e. dataset) queried by the beacon.
<code>title</code>	The title displayed for the beacon.
<code>env</code>	(optional) Custom client environment.
<code>...</code>	(optional) Additional beacon attributes (such as description and params).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Beacon.create(  
  beacon_set_id="1234",  
  vault_object_id="1234567890",  
  title="My new beacon"  
)  
  
## End(Not run)
```

Beacon.delete	<i>Beacon.delete</i>
---------------	----------------------

Description

Delete a specific beacon from SolveBio.

Usage

```
Beacon.delete(id, env = solvebio:::solveEnv)
```

Arguments

id	The ID of the beacon.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Beacon.delete("1234567890")

## End(Not run)
```

Beacon.query	<i>Beacon.query</i>
--------------	---------------------

Description

Query an individual beacon.

Usage

```
Beacon.query(id, query, entity_type, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the beacon.
query	The entity ID or query string.
entity_type	(optional) A valid SolveBio entity type.
env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Beacon.query(
  id="1234",
  query="BRCA2",
  entity_type="gene"
)

## End(Not run)
```

Beacon.retrieve	<i>Beacon.retrieve</i>
-----------------	------------------------

Description

Retrieves the metadata about a specific beacon on SolveBio.

Usage

```
Beacon.retrieve(id, env = solvebio:::solveEnv)
```

Arguments

id	The ID of the beacon.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Beacon.retrieve("1234")

## End(Not run)
```

Beacon.update	<i>Beacon.update</i>
---------------	----------------------

Description

Updates the attributes of an existing beacon.

Usage

```
Beacon.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the beacon to update.
env	(optional) Custom client environment.
...	Beacon attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Beacon.update(  
  id="1234",  
  title="New Beacon Title"  
)  
  
## End(Not run)
```

BeaconSet.all	<i>BeaconSet.all</i>
---------------	----------------------

Description

Retrieves the metadata about all beacon sets on SolveBio accessible to the current user.

Usage

```
BeaconSet.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
BeaconSet.all()

## End(Not run)
```

BeaconSet.create	<i>BeaconSet.create</i>
------------------	-------------------------

Description

Create a new beacon set.

Usage

```
BeaconSet.create(
  title,
  description,
  is_shared = FALSE,
  env = solvebio:::.solveEnv,
  ...
)
```

Arguments

title	The title displayed for the beacon set.
description	(optional) An optional description for the new beacon set.
is_shared	If TRUE, everyone else in your account will be able to see and query the beacon set, but will not be able to edit it. (Default: FALSE)
env	(optional) Custom client environment.
...	(optional) Additional beacon set attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
BeaconSet.create(
  title="My new beacon set",
)

## End(Not run)
```

BeaconSet.delete	<i>BeaconSet.delete</i>
------------------	-------------------------

Description

Delete a specific beacon set (including all its beacons) from SolveBio.

Usage

```
BeaconSet.delete(id, env = solvebio:::.solveEnv)
```

Arguments

<code>id</code>	The ID of the beacon set.
<code>env</code>	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
BeaconSet.delete("1234")

## End(Not run)
```

BeaconSet.query	<i>BeaconSet.query</i>
-----------------	------------------------

Description

Query a beacon set (i.e. all the beacons within a beacon set).

Usage

```
BeaconSet.query(id, query, entity_type, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the beacon set.
query	The entity ID or query string.
entity_type	(optional) A valid SolveBio entity type.
env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
BeaconSet.query(
  id="1234",
  query="BRCA2",
  entity_type="gene"
)

## End(Not run)
```

BeaconSet.retrieve	<i>BeaconSet.retrieve</i>
--------------------	---------------------------

Description

Retrieves the metadata about a specific beacon set on SolveBio.

Usage

```
BeaconSet.retrieve(id, env = solvebio:::solveEnv)
```

Arguments

`id` The ID of the beacon set.
`env` (optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
BeaconSet.retrieve("1234")  
  
## End(Not run)
```

<code>BeaconSet.update</code>	<i>BeaconSet.update</i>
-------------------------------	-------------------------

Description

Updates the attributes of an existing beacon set.

Usage

```
BeaconSet.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

`id` The ID of the beacon set to update.
`env` (optional) Custom client environment.
`...` Beacon set attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
BeaconSet.update(  
  id="1234",  
  title="New Beacon Set Title"  
)  
  
## End(Not run)
```

createEnv	<i>createEnv</i>
-----------	------------------

Description

Create a new SolveBio environment.

Usage

```
createEnv(token, token_type = "Token", host = .solveEnv$host)
```

Arguments

token	A SolveBio API key or OAuth2 token
token_type	SolveBio token type (default: Token)
host	(optional) The SolveBio API host (default: https://api.solvebio.com)

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
env <- createEnv("MyAPIkey")  
User.retrieve(env = myEnv)  
  
## End(Not run)
```

Dataset.activity	<i>Dataset.activity</i>
------------------	-------------------------

Description

A helper function to get or follow the current activity on a dataset.

Usage

```
Dataset.activity(id, follow = TRUE, env = solvebio::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset
follow	Follow active tasks until they complete.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.activity("1234567890")  
  
## End(Not run)
```

Dataset.all

Dataset.all

Description

Retrieves the metadata about datasets on SolveBio.

Usage

```
Dataset.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.all()  
  
## End(Not run)
```

Dataset.count	<i>Dataset.count</i>
---------------	----------------------

Description

Returns the total number of records for a given SolveBio dataset.

Usage

```
Dataset.count(id, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of a SolveBio dataset, or a Dataset object.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. filters, limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
dataset <- Dataset.get_by_full_path("solvebio:public:/ClinVar/3.7.4-2017-01-30/Variants-GRCh37")  
Dataset.count(dataset)  
Dataset.count(dataset, filters='[["gene_symbol", "BRCA2"]]' )  
  
## End(Not run)
```

Dataset.create	<i>Dataset.create</i>
----------------	-----------------------

Description

Create an empty SolveBio dataset.

Usage

```
Dataset.create(  
  vault_id,  
  vault_parent_object_id,  
  name,  
  env = solvebio:::solveEnv,  
  ...  
)
```

Arguments

vault_id The ID of the vault.
 vault_parent_object_id
 The parent object (folder) ID in the vault.
 name The name of the dataset in the parent folder.
 env (optional) Custom client environment.
 ... (optional) Additional dataset attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Dataset.create(vault_id=vault$id, vault_parent_object_id=NULL, name="My Dataset")

## End(Not run)
```

Dataset.data

Dataset.data

Description

Returns one page of documents from a SolveBio dataset and processes the response.

Usage

```
Dataset.data(id, filters, env = solvebio:::.solveEnv, ...)
```

Arguments

id The ID of a SolveBio dataset, or a Dataset object.
 filters (optional) Query filters.
 env (optional) Custom client environment.
 ... (optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Dataset.data("1234567890")

## End(Not run)
```

Dataset.delete	<i>Dataset.delete</i>
----------------	-----------------------

Description

Delete a specific dataset from SolveBio.

Usage

```
Dataset.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.delete("1234567890")  
  
## End(Not run)
```

Dataset.facets	<i>Dataset.facets</i>
----------------	-----------------------

Description

Retrieves aggregated statistics or term counts for one or more fields in a SolveBio dataset. Returns a list of data frames, one for each requested facet.

Usage

```
Dataset.facets(id, facets, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of a SolveBio dataset, or a Dataset object.
facets	A list of one or more field facets.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. filters, limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.facets("1234567890", list("clinical_significance", "gene_symbol"))  
  
## End(Not run)
```

Dataset.fields	<i>Dataset.fields</i>
----------------	-----------------------

Description

Retrieves the list of fields and field metadata for a dataset.

Usage

```
Dataset.fields(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of a SolveBio dataset, or a Dataset object.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.fields("1234567890")  
  
## End(Not run)
```

Dataset.get_by_full_path
Dataset.get_by_full_path

Description

A helper function to get a dataset by its full path.

Usage

```
Dataset.get_by_full_path(full_path, env = solvebio:::.solveEnv)
```

Arguments

full_path	A valid full path to a dataset.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.get_by_full_path("solvebio:public:/ClinVar/3.7.4-2017-01-30/Variants-GRCh37")  
  
## End(Not run)
```

Dataset.get_or_create_by_full_path
Dataset.get_or_create_by_full_path

Description

A helper function to get or create a dataset by its full path.

Usage

```
Dataset.get_or_create_by_full_path(full_path, env = solvebio:::.solveEnv, ...)
```

Arguments

full_path	A valid full path to a dataset.
env	(optional) Custom client environment.
...	Additional dataset creation parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.get_or_create_by_full_path("MyVault:/folder/sub-folder/dataset")  
  
## End(Not run)
```

Dataset.query

Dataset.query

Description

Queries a SolveBio dataset and returns an R data frame containing all records (up to 500,000). Returns a single page of results otherwise (default).

Usage

```
Dataset.query(id, paginate = FALSE, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of a SolveBio dataset, or a Dataset object.
paginate	When set to TRUE, retrieves up to 500,000 records.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. filters, limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.query("12345678790", paginate=TRUE)  
  
## End(Not run)
```

Dataset.retrieve	<i>Dataset.retrieve</i>
------------------	-------------------------

Description

Retrieves the metadata about a specific dataset from SolveBio.

Usage

```
Dataset.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.retrieve("1234567890")  
  
## End(Not run)
```

Dataset.template	<i>Dataset.template</i>
------------------	-------------------------

Description

Retrieves the template for a dataset.

Usage

```
Dataset.template(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.template("1234567890")  
  
## End(Not run)
```

Dataset.update

Dataset.update

Description

Updates the attributes of an existing dataset.

Usage

```
Dataset.update(id, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the dataset to update.
env	(optional) Custom client environment.
...	Dataset attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Dataset.update(  
  id="1234",  
  name="New Dataset Name",  
)  
  
## End(Not run)
```

DatasetCommit.all *DatasetCommit.all*

Description

Retrieves the metadata about all dataset commits on SolveBio.

Usage

```
DatasetCommit.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetCommit.all()  
  
## End(Not run)
```

DatasetCommit.delete *DatasetCommit.delete*

Description

Deletes a specific dataset commit on SolveBio.

Usage

```
DatasetCommit.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id String The ID or full name of a SolveBio dataset commit.
env (optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetCommit.delete(<ID>)  
  
## End(Not run)
```

DatasetCommit.retrieve

DatasetCommit.retrieve

Description

Retrieves the metadata about a specific dataset commit on SolveBio.

Usage

```
DatasetCommit.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset commit.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetCommit.retrieve(<ID>)  
  
## End(Not run)
```

DatasetExport.all *DatasetExport.all*

Description

Retrieves the metadata about all dataset exports on SolveBio.

Usage

```
DatasetExport.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetExport.all()  
  
## End(Not run)
```

DatasetExport.create *DatasetExport.create*

Description

Create a new dataset export.

Usage

```
DatasetExport.create(  
  dataset_id,  
  format = "json",  
  params = list(),  
  follow = FALSE,  
  env = solvebio:::.solveEnv,  
  ...  
)
```

Arguments

dataset_id	The target dataset ID.
format	(optional) The export format (default: json).
params	(optional) Query parameters for the export.
follow	(default: FALSE) Follow the export task until it completes.
env	(optional) Custom client environment.
...	(optional) Additional dataset export parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetExport.create(dataset_id=<ID>, format='json', params=list(fields=c("field_1"), limit=100))  
  
## End(Not run)
```

DatasetExport.delete *DatasetExport.delete*

Description

Deletes a specific dataset export on SolveBio.

Usage

```
DatasetExport.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset export.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetExport.delete(<ID>)  
  
## End(Not run)
```

```
DatasetExport.get_download_url  
    DatasetExport.get_download_url
```

Description

Helper method to get the download URL for a dataset export.

Usage

```
DatasetExport.get_download_url(id, env = solvebio:::.solveEnv)
```

Arguments

id	The ID of the dataset export.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetExport.get_download_url("1234567890")  
  
## End(Not run)
```

```
DatasetExport.retrieve  
    DatasetExport.retrieve
```

Description

Retrieves the metadata about a specific dataset export on SolveBio.

Usage

```
DatasetExport.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset export.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetExport.retrieve(<ID>)  
  
## End(Not run)
```

DatasetField.all	<i>DatasetField.all</i>
------------------	-------------------------

Description

Retrieves the metadata about all dataset fields on SolveBio.

Usage

```
DatasetField.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetField.all()  
  
## End(Not run)
```

DatasetField.create *DatasetField.create*

Description

Create a new dataset field.

Usage

```
DatasetField.create(  
    dataset_id,  
    name,  
    data_type = "auto",  
    env = solvebio:::solveEnv,  
    ...  
)
```

Arguments

dataset_id	The dataset ID.
name	The name of the dataset field.
data_type	(optional) The data type for the field (default: auto).
env	(optional) Custom client environment.
...	(optional) Additional dataset import attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetField.create(dataset_id=<ID>, name="my_field", title="My Field", data_type="string")  
  
## End(Not run)
```

DatasetField.facets *DatasetField.facets*

Description

Returns the facets for a given dataset field.

Usage

```
DatasetField.facets(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	String The ID of a dataset field.
env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetField.facets(691)  
  
## End(Not run)
```

DatasetField.retrieve *DatasetField.retrieve*

Description

Retrieves the metadata about a specific dataset field.

Usage

```
DatasetField.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a dataset field.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetField.retrieve(691)  
  
## End(Not run)
```

DatasetField.update *DatasetField.update*

Description

Updates the attributes of an existing dataset field. NOTE: The data_type of a field cannot be changed.

Usage

```
DatasetField.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the dataset field to update.
env	(optional) Custom client environment.
...	Dataset field attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetField.update(  
  id="1234",  
  title="New Field Title"  
)  
  
## End(Not run)
```

DatasetImport.all *DatasetImport.all*

Description

Retrieves the metadata about all dataset imports on SolveBio.

Usage

```
DatasetImport.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetImport.all()  
  
## End(Not run)
```

DatasetImport.create *DatasetImport.create*

Description

Create a new dataset import. Either an `object_id`, `manifest`, or `data_records` is required.

Usage

```
DatasetImport.create(  
  dataset_id,  
  commit_mode = "append",  
  env = solvebio:::.solveEnv,  
  ...  
)
```

Arguments

dataset_id	The target dataset ID.
commit_mode	(optional) The commit mode (default: append).
env	(optional) Custom client environment.
...	(optional) Additional dataset import attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetImport.create(dataset_id=<ID>, upload_id=<ID>)  
  
## End(Not run)
```

DatasetImport.delete *DatasetImport.delete*

Description

Deletes a specific dataset import on SolveBio.

Usage

```
DatasetImport.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset import.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetImport.delete(<ID>)  
  
## End(Not run)
```

`DatasetImport.retrieve`*DatasetImport.retrieve*

Description

Retrieves the metadata about a specific dataset import on SolveBio.

Usage

```
DatasetImport.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

<code>id</code>	String The ID of a SolveBio dataset import.
<code>env</code>	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetImport.retrieve(<ID>)  
  
## End(Not run)
```

`DatasetMigration.all` *DatasetMigration.all*

Description

Retrieves the metadata about all dataset migrations on SolveBio.

Usage

```
DatasetMigration.all(env = solvebio:::.solveEnv, ...)
```

Arguments

<code>env</code>	(optional) Custom client environment.
<code>...</code>	(optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
DatasetMigration.all()

## End(Not run)
```

```
DatasetMigration.create
      DatasetMigration.create
```

Description

Create a new dataset migration.

Usage

```
DatasetMigration.create(
  source_id,
  target_id,
  commit_mode = "append",
  source_params = NULL,
  target_fields = NULL,
  include_errors = FALSE,
  env = solvebio:::solveEnv,
  ...
)
```

Arguments

<code>source_id</code>	The source dataset ID.
<code>target_id</code>	The target dataset ID.
<code>commit_mode</code>	(optional) The commit mode (default: <code>append</code>).
<code>source_params</code>	(optional) The query parameters used on the source dataset.
<code>target_fields</code>	(optional) A list of valid dataset fields to add or override in the target dataset.
<code>include_errors</code>	(optional) If TRUE, a new field (<code>_errors</code>) will be added to each record containing expression evaluation errors (default: <code>FALSE</code>).
<code>env</code>	(optional) Custom client environment.
<code>...</code>	(optional) Additional dataset migration attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetMigration.create(dataset_id=<ID>, upload_id=<ID>)  
  
## End(Not run)
```

```
DatasetMigration.delete  
    DatasetMigration.delete
```

Description

Deletes specific dataset migration on SolveBio.

Usage

```
DatasetMigration.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset migration.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetMigration.delete(<ID>)  
  
## End(Not run)
```

```
DatasetMigration.retrieve  
    DatasetMigration.retrieve
```

Description

Retrieves the metadata about a specific dataset migration on SolveBio.

Usage

```
DatasetMigration.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset migration.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetMigration.retrieve(<ID>)  
  
## End(Not run)
```

```
DatasetTemplate.all    DatasetTemplate.all
```

Description

Retrieves the metadata about all dataset templates on SolveBio.

Usage

```
DatasetTemplate.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetTemplate.all()  
  
## End(Not run)
```

DatasetTemplate.create

DatasetTemplate.create

Description

Create a SolveBio dataset template.

Usage

```
DatasetTemplate.create(env = solvebio:::solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Dataset template attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetTemplate.create(name="My Dataset Template")  
  
## End(Not run)
```

DatasetTemplate.delete
DatasetTemplate.delete

Description

Deletes a specific dataset template on SolveBio.

Usage

```
DatasetTemplate.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID or full name of a SolveBio dataset template.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetTemplate.delete(<ID>)  
  
## End(Not run)
```

DatasetTemplate.retrieve
DatasetTemplate.retrieve

Description

Retrieves the metadata about a specific dataset template on SolveBio.

Usage

```
DatasetTemplate.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio dataset template.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetTemplate.retrieve(<ID>)  
  
## End(Not run)
```

DatasetTemplate.update
DatasetTemplate.update

Description

Updates the attributes of an existing dataset template.

Usage

```
DatasetTemplate.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the dataset template to update.
env	(optional) Custom client environment.
...	Dataset template attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
DatasetTemplate.update(  
  id="1234",  
  name="New Template Name",  
)  
  
## End(Not run)
```

Expression.evaluate *Expression.evaluate*

Description

Evaluate a SolveBio expression.

Usage

```
Expression.evaluate(  
  expression,  
  data_type = "string",  
  is_list = FALSE,  
  data = NULL,  
  raw = FALSE,  
  env = solvebio:::solveEnv  
)
```

Arguments

expression	The SolveBio expression string.
data_type	The data type to cast the expression result (default: string).
is_list	Set to TRUE if the result is expected to be a list (default: FALSE).
data	Variables used in the expression (default: NULL).
raw	Set to TRUE to return the raw response (default: FALSE).
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Expression.evaluate("1 + 1", data_type="integer", is_list=FALSE)  
  
## End(Not run)
```

login *login*

Description

Store and verify your SolveBio credentials.

Usage

```
login(api_key, api_host, env = solvebio:::solveEnv)
```

Arguments

api_key	Your SolveBio API key
api_host	SolveBio API host (default: https://api.solvebio.com)
env	(optional) The R environment used to store API credentials.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
login()  
  
## End(Not run)
```

Object.all *Object.all*

Description

Retrieves the metadata about all objects on SolveBio accessible to the current user.

Usage

```
Object.all(env = solvebio:::solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.all()  
  
## End(Not run)
```

Object.create	<i>Object.create</i>
---------------	----------------------

Description

Create a SolveBio object.

Usage

```
Object.create(  
  vault_id,  
  parent_object_id,  
  object_type,  
  filename,  
  env = solvebio:::.solveEnv,  
  ...  
)
```

Arguments

vault_id	The target vault ID.
parent_object_id	The ID of the parent object (folder) or NULL for the vault root.
object_type	The type of object (i.e. "folder").
filename	The filename (i.e. the name) of the object.
env	(optional) Custom client environment.
...	(optional) Additional object attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Object.create(
  vault_id="1234567890",
  parent_object_id=NULL,
  object_type="folder",
  filename="My Folder"
)

## End(Not run)
```

Object.delete

Object.delete

Description

Delete a specific object from SolveBio.

Usage

```
Object.delete(id, env = solvebio::.solveEnv)
```

Arguments

id	The ID of the object.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Object.delete("1234567890")

## End(Not run)
```

Object.get_by_full_path
Object.get_by_full_path

Description

A helper function to get an object on SolveBio by its full path.

Usage

```
Object.get_by_full_path(full_path, env = solvebio:::solveEnv, ...)
```

Arguments

full_path	The full path to the object.
env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.get_by_full_path("solvebio:public:/ClinVar")  
  
## End(Not run)
```

Object.get_by_path *Object.get_by_path*

Description

A helper function to get an object on SolveBio by its path. Used as a pass-through function from some Vault methods.

Usage

```
Object.get_by_path(path, env = solvebio:::solveEnv, ...)
```

Arguments

path	The path to the object, relative to a vault.
env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.get_by_path("/ClinVar")  
  
## End(Not run)
```

```
Object.get_download_url  
Object.get_download_url
```

Description

Helper method to get the download URL for a file object.

Usage

```
Object.get_download_url(id, env = solvebio:::.solveEnv)
```

Arguments

id	The ID of the object.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.get_download_url("1234567890")  
  
## End(Not run)
```

```
Object.get_or_upload_file  
    Object.get_or_upload_file
```

Description

Upload a local file to a vault on SolveBio only if it does not yet exist (by name, at the provided path). The vault path provided is the parent directory for uploaded file. Accepts the same arguments as 'Object.upload_file'.

Usage

```
Object.get_or_upload_file(  
  local_path,  
  vault_id,  
  vault_path,  
  filename,  
  env = solvebio:::.solveEnv  
)
```

Arguments

local_path	The path to the local file
vault_id	The SolveBio vault ID
vault_path	The remote path in the vault
filename	(optional) The filename for the uploaded file in the vault (default: the basename of the local_path)
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.get_or_upload_file("my_file.json.gz", vault$id, "/parent/directory/")  
  
## End(Not run)
```

Object.retrieve *Object.retrieve*

Description

Retrieves the metadata about a specific object on SolveBio.

Usage

```
Object.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	The ID of the object.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Object.retrieve("1234567890")  
  
## End(Not run)
```

Object.update *Object.update*

Description

Updates the attributes of an existing vault object.

Usage

```
Object.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the vault to update.
env	(optional) Custom client environment.
...	Object attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Object.update(
  id="1234",
  filename="New Name",
)

## End(Not run)
```

Object.upload_file *Object.upload_file*

Description

Upload a local file to a vault on SolveBio. The vault path provided is the parent directory for uploaded file.

Usage

```
Object.upload_file(
  local_path,
  vault_id,
  vault_path,
  filename,
  env = solvebio:::solveEnv
)
```

Arguments

local_path	The path to the local file
vault_id	The SolveBio vault ID
vault_path	The remote path in the vault
filename	(optional) The filename for the uploaded file in the vault (default: the basename of the local_path)
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Object.upload_file("my_file.json.gz", vault$id, "/parent/directory/")

## End(Not run)
```

protectedServer	<i>protectedServer</i>
-----------------	------------------------

Description

Wraps an existing Shiny server in an OAuth2 flow.

Usage

```
protectedServer(
  server,
  client_id,
  client_secret = NULL,
  base_url = "https://my.solvebio.com"
)
```

Arguments

<code>server</code>	Your original Shiny server function.
<code>client_id</code>	Your application's client ID.
<code>client_secret</code>	(optional) Your application's client secret.
<code>base_url</code>	(optional) Override the default login host (default: https://my.solvebio.com).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
protectedServer(
  server=server,
  client_id="abcd1234"
)

## End(Not run)
```

protectedServerJS	<i>protectedServerUI</i>
-------------------	--------------------------

Description

Returns ShinyJS-compatible JS code to support cookie-based token storage.

Usage

```
protectedServerJS()
```

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
jscookie_src <- "https://cdnjs.cloudflare.com/ajax/libs/js-cookie/2.2.0/js.cookie.js"
ui <- fluidPage(
  shiny::tags$head(
    shiny::tags$script(src = jscookie_src)
  ),
  useShinyjs(),
  extendShinyjs(text = solvebio::protectedServerJS(),
               functions = c("enableCookieAuth", "getCookie", "setCookie", "rmCookie"))
)
## End(Not run)
```

SavedQuery.all	<i>SavedQuery.all</i>
----------------	-----------------------

Description

Retrieves the all saved queries on SolveBio.

Usage

```
SavedQuery.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. page).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
SavedQuery.all()  
  
## End(Not run)
```

SavedQuery.create	<i>SavedQuery.create</i>
-------------------	--------------------------

Description

Create a SolveBio saved query.

Usage

```
SavedQuery.create(env = solvebio:::solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Saved query attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
SavedQuery.create(name="My Dataset Template")  
  
## End(Not run)
```

SavedQuery.delete *SavedQuery.delete*

Description

Deletes a specific saved query on SolveBio.

Usage

```
SavedQuery.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of the SolveBio saved query.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
SavedQuery.delete(<ID>)  
  
## End(Not run)
```

SavedQuery.retrieve *SavedQuery.retrieve*

Description

Retrieves a specific saved query on SolveBio by ID.

Usage

```
SavedQuery.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio saved query.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
SavedQuery.retrieve(<ID>)  
  
## End(Not run)
```

SavedQuery.update	<i>SavedQuery.update</i>
-------------------	--------------------------

Description

Updates the attributes of an existing saved query.

Usage

```
SavedQuery.update(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the saved query to update.
env	(optional) Custom client environment.
...	Saved query attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
SavedQuery.update(  
  id="1234",  
  name="New query Name",  
)  
  
## End(Not run)
```

Task.all	<i>Task.all</i>
----------	-----------------

Description

Retrieves the metadata about all tasks on SolveBio accessible to the current user.

Usage

```
Task.all(env = solvebio:::.solveEnv, ...)
```

Arguments

env	(optional) Custom client environment.
...	(optional) Additional query parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Task.all()  
  
## End(Not run)
```

Task.follow	<i>Task.follow</i>
-------------	--------------------

Description

A helper function to follow a specific tasks.

Usage

```
Task.follow(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a task.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Task.follow("1234567890")  
  
## End(Not run)
```

Task.retrieve	<i>Task.retrieve</i>
---------------	----------------------

Description

Retrieves the metadata about a specific task on SolveBio.

Usage

```
Task.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	The ID of a task.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Task.retrieve("1234567890")  
  
## End(Not run)
```

User.retrieve	<i>User.retrieve</i>
---------------	----------------------

Description

Retrieves information about the current user.

Usage

```
User.retrieve(env = solvebio:::.solveEnv)
```

Arguments

env (optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
User.retrieve()  
  
## End(Not run)
```

Vault.all

Vault.all

Description

Retrieves the metadata about all accessible vaults.

Usage

```
Vault.all(..., env = solvebio:::.solveEnv)
```

Arguments

... (optional) Additional query parameters (e.g. limit, offset).
env (optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Vault.all()  
  
## End(Not run)
```

Vault.create	<i>Vault.create</i>
--------------	---------------------

Description

Create a new SolveBio vault.

Usage

```
Vault.create(name, env = solvebio:::solveEnv, ...)
```

Arguments

name	The unique name of the vault.
env	(optional) Custom client environment.
...	(optional) Additional vault attributes.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Vault.create(name="my-domain:MyVault")

## End(Not run)
```

Vault.create_dataset	<i>Vault.create_dataset</i>
----------------------	-----------------------------

Description

Create a new dataset in a vault.

Usage

```
Vault.create_dataset(id, path, name, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the vault.
path	The path to the dataset, within the vault.
name	The name (filename) for the dataset.
env	(optional) Custom client environment.
...	(optional) Additional dataset creation parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.create_dataset(vault$id, path="/", name="My Dataset")  
  
## End(Not run)
```

Vault.create_folder *Vault.create_folder*

Description

Create a new folder in a vault.

Usage

```
Vault.create_folder(  
  id,  
  path,  
  recursive = FALSE,  
  env = solvebio:::solveEnv,  
  ...  
)
```

Arguments

id	The ID of the vault.
path	The path to the folder, within the vault.
recursive	Create all parent directories that do not yet exist (default: FALSE).
env	(optional) Custom client environment.
...	(optional) Additional folder creation parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.create_folder(vault$id, "/My Folder")  
  
## End(Not run)
```

Vault.datasets *Vault.datasets*

Description

Retrieves all datasets in a specific vault.

Usage

```
Vault.datasets(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the vault.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.datasets(vault$id)  
  
## End(Not run)
```

Vault.delete *Vault.delete*

Description

Delete a specific vault from SolveBio. This operation cannot be undone.

Usage

```
Vault.delete(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio vault.
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Vault.delete("1")  
  
## End(Not run)
```

Vault.files

Vault.files

Description

Retrieves all files in a specific vault.

Usage

```
Vault.files(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the vault.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.files(vault$id)  
  
## End(Not run)
```

Vault.folders	<i>Vault.folders</i>
---------------	----------------------

Description

Retrieves all folders in a specific vault.

Usage

```
Vault.folders(id, env = solvebio:::.solveEnv, ...)
```

Arguments

id	The ID of the vault.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
vault = Vault.get_personal_vault()
Vault.folders(vault$id)

## End(Not run)
```

Vault.get_by_full_path	<i>Vault.get_by_full_path</i>
------------------------	-------------------------------

Description

Retrieves a specific vault by its full path (domain:vault).

Usage

```
Vault.get_by_full_path(full_path, verbose = TRUE, env = solvebio:::.solveEnv)
```

Arguments

full_path	The full path of a SolveBio vault.
verbose	Print warning/error messages (default: TRUE).
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Vault.get_by_full_path("SolveBio:Public")

## End(Not run)
```

```
Vault.get_or_create_by_full_path
      Vault.get_or_create_by_full_path
```

Description

Retrieves or creates a specific vault by its full path (domain:vault).

Usage

```
Vault.get_or_create_by_full_path(full_path, env = solvebio::.solveEnv, ...)
```

Arguments

full_path	The full path of a SolveBio vault.
env	(optional) Custom client environment.
...	(optional) Additional parameters.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:
Vault.get_or_create_by_full_path("My New Vault")

## End(Not run)
```

```
Vault.get_personal_vault  
    Vault.get_personal_vault
```

Description

Retrieves the current users"s personal, private vault.

Usage

```
Vault.get_personal_vault(env = solvebio:::solveEnv)
```

Arguments

env (optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Vault.get_personal_vault()  
  
## End(Not run)
```

```
Vault.objects    Vault.objects
```

Description

Retrieves all objects in a specific vault.

Usage

```
Vault.objects(id, env = solvebio:::solveEnv, ...)
```

Arguments

id The ID of the vault.
env (optional) Custom client environment.
... (optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.objects(vault$id)  
  
## End(Not run)
```

Vault.retrieve

Vault.retrieve

Description

Retrieves the metadata about a specific SolveBio vault.

Usage

```
Vault.retrieve(id, env = solvebio:::.solveEnv)
```

Arguments

id	String The ID of a SolveBio vault
env	(optional) Custom client environment.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Vault.retrieve("1234567890")  
  
## End(Not run)
```

Vault.search *Vault.search*

Description

Search for objects in a specific vault.

Usage

```
Vault.search(id, query, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the vault.
query	The search query.
env	(optional) Custom client environment.
...	(optional) Additional query parameters (e.g. limit, offset).

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
vault = Vault.get_personal_vault()  
Vault.search('test')  
  
## End(Not run)
```

Vault.update *Vault.update*

Description

Updates the attributes of an existing vault.

Usage

```
Vault.update(id, env = solvebio:::solveEnv, ...)
```

Arguments

id	The ID of the vault to update.
env	(optional) Custom client environment.
...	Vault attributes to change.

References

<https://docs.solvebio.com/>

Examples

```
## Not run:  
Vault.update(  
  id="1234",  
  name="New Vault Name",  
)  
  
## End(Not run)
```

Index

Annotator.annotate, 4
Application.all, 5
Application.create, 5
Application.delete, 6
Application.retrieve, 7
Application.update, 7

Beacon.all, 8
Beacon.create, 9
Beacon.delete, 10
Beacon.query, 10
Beacon.retrieve, 11
Beacon.update, 12
BeaconSet.all, 12
BeaconSet.create, 13
BeaconSet.delete, 14
BeaconSet.query, 15
BeaconSet.retrieve, 15
BeaconSet.update, 16

createEnv, 17

Dataset.activity, 17
Dataset.all, 18
Dataset.count, 19
Dataset.create, 19
Dataset.data, 20
Dataset.delete, 21
Dataset.facets, 21
Dataset.fields, 22
Dataset.get_by_full_path, 23
Dataset.get_or_create_by_full_path, 23
Dataset.query, 24
Dataset.retrieve, 25
Dataset.template, 25
Dataset.update, 26
DatasetCommit.all, 27
DatasetCommit.delete, 27
DatasetCommit.retrieve, 28
DatasetExport.all, 29
DatasetExport.create, 29
DatasetExport.delete, 30
DatasetExport.get_download_url, 31
DatasetExport.retrieve, 31
DatasetField.all, 32
DatasetField.create, 33
DatasetField.facets, 34
DatasetField.retrieve, 34
DatasetField.update, 35
DatasetImport.all, 36
DatasetImport.create, 36
DatasetImport.delete, 37
DatasetImport.retrieve, 38
DatasetMigration.all, 38
DatasetMigration.create, 39
DatasetMigration.delete, 40
DatasetMigration.retrieve, 41
DatasetTemplate.all, 41
DatasetTemplate.create, 42
DatasetTemplate.delete, 43
DatasetTemplate.retrieve, 43
DatasetTemplate.update, 44

Expression.evaluate, 45

login, 46

Object.all, 46
Object.create, 47
Object.delete, 48
Object.get_by_full_path, 49
Object.get_by_path, 49
Object.get_download_url, 50
Object.get_or_upload_file, 51
Object.retrieve, 52
Object.update, 52
Object.upload_file, 53

protectedServer, 54
protectedServerJS, 55

SavedQuery.all, [55](#)
SavedQuery.create, [56](#)
SavedQuery.delete, [57](#)
SavedQuery.retrieve, [57](#)
SavedQuery.update, [58](#)

Task.all, [59](#)
Task.follow, [59](#)
Task.retrieve, [60](#)

User.retrieve, [60](#)

Vault.all, [61](#)
Vault.create, [62](#)
Vault.create_dataset, [62](#)
Vault.create_folder, [63](#)
Vault.datasets, [64](#)
Vault.delete, [64](#)
Vault.files, [65](#)
Vault.folders, [66](#)
Vault.get_by_full_path, [66](#)
Vault.get_or_create_by_full_path, [67](#)
Vault.get_personal_vault, [68](#)
Vault.objects, [68](#)
Vault.retrieve, [69](#)
Vault.search, [70](#)
Vault.update, [70](#)