

Package ‘summarytools’

March 2, 2020

Type Package

Title Tools to Quickly and Neatly Summarize Data

Version 0.9.6

Description Data frame summaries, cross-tabulations, weight-enabled frequency tables and common descriptive (univariate) statistics in concise tables available in a variety of formats (plain ASCII, Markdown and HTML). A good point-of-entry for exploring data, both for experienced and new R users.

Imports base64enc, checkmate, dplyr, grDevices, htmltools, lubridate, magick, matrixStats, methods, pander, pryr, reporttools, stats, tcltk, tibble, tidyverse, utils

Suggestsforcats, kableExtra, knitr, magrittr, rmarkdown, rstudioapi

Depends R (>= 2.10)

VignetteBuilder knitr

LazyData true

License GPL-2

URL <https://github.com/dcomtois/summarytools>

BugReports <https://github.com/dcomtois/summarytools/issues>

Encoding UTF-8

RoxygenNote 7.0.2

NeedsCompilation no

Author Dominic Comtois [aut, cre]

Maintainer Dominic Comtois <dominic.comtois@gmail.com>

Repository CRAN

Date/Publication 2020-03-02 07:20:02 UTC

R topics documented:

summarytools-package	2
cleartmp	3
ctable	4
define_keywords	6
descr	9
dfSummary	11
examens	15
exams	16
freq	16
label	19
print.list	20
print.stby	21
print.summarytools	22
stby	25
st_css	26
st_options	27
tabagisme	30
tb	31
tobacco	32
unlabel	32
use_custom_lang	33
view	33
what.is	35

Index

37

summarytools-package *Tools to Quickly and Neatly Summarize Data*

Description

summarytools provides users with functions to neatly and quickly summarize numerical and categorical data. Data frame summaries, frequency tables and cross-tabulations, as well as common descriptive (univariate) statistics can be produced in a straightforward manner. Users with little to no prior R programming experience but who are familiar with popular commercial statistical software such as SAS, SPSS and Stata should feel right at home.

Details

These are the four core functions:

dfSummary Extensive yet legible data frame summaries.

freq Frequency tables supporting weights and displaying proportions of valid and of total data, including cumulative proportions.

descr All common univariate descriptive stats for single vectors or for all numerical vectors in a data frame.

ctable Cross-tabulations for two categorical vectors or factors. Choose between *Total*, *Columns* or *Rows* proportions.

Output formats are:

plain ascii Ideal when looking at results in the console.

rmarkdown Ideal when writing short papers or presentations.

html This format is well integrated in RStudio (but will work with any browser). Use the `view()` function to see results appear directly in RStudio's Viewer or in your default Web Browser.

Author(s)

Maintainer: Dominic Comtois <dominic.comtois@gmail.com>

See Also

Useful links:

- <https://github.com/dcomtois/summarytools>
- Report bugs at <https://github.com/dcomtois/summarytools/issues>

cleartmp

Delete Temporary Html Files

Description

Delete temporary files created when using generic print method with `method='browser'` or `method='viewer'`, or when calling `view()` function.

Usage

```
cleartmp(all = TRUE, silent = FALSE, verbose = FALSE)
```

Arguments

<code>all</code>	Logical. When TRUE (default), all temporary summarytools files are deleted. When FALSE, only the latest file is.
<code>silent</code>	Logical. Hide confirmation messages (FALSE by default).
<code>verbose</code>	Logical. Display a message for every file that is deleted. FALSE by default.

Details

All temporary files are deleted automatically when R session is ended. This function is thus an overkill in most circumstances.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>>

ctable*Cross-Tabulation*

Description

Cross-tabulation for a pair of categorical variables (or factors) with either row, column, or total proportions, as well as marginal sums.

Usage

```
ctable(
  x,
  y,
  prop = st_options("ctable.prop"),
  useNA = "ifany",
  totals = st_options("ctable.totals"),
  style = st_options("style"),
  round.digits = 1,
  justify = "right",
  plain.ascii = st_options("plain.ascii"),
  headings = st_options("headings"),
  display.labels = st_options("display.labels"),
  split.tables = Inf,
  dnn = c(substitute(x), substitute(y)),
  chisq = FALSE,
  OR = FALSE,
  RR = FALSE,
  weights = NA,
  rescale.weights = FALSE,
  ...
)
```

Arguments

<code>x</code>	First categorical variable - values will appear as row names.
<code>y</code>	Second categorical variable - values will appear in as column names.
<code>prop</code>	Proportions to display; “r” for <i>rows</i> (default), “c” for <i>columns</i> , “t” for <i>total</i> , or “n” for <i>none</i> . This option can be set globally; see st_options .
<code>useNA</code>	Argument passed on to table ; One of “ifany” (default), “no”, or “always”.
<code>totals</code>	Logical. Should row and column totals be displayed? Defaults to TRUE. To change this default value globally, see st_options .
<code>style</code>	Style to be used by pander when rendering output table; One of “simple” (default), “grid”, or “rmarkdown”. This option can be set globally; see st_options .
<code>round.digits</code>	Number of significant digits to display. Defaults to 1. To change this default value globally, see st_options .

<code>justify</code>	String indicating alignment of columns; one of “l” (left) “c” (center), or “r” (right). Defaults to “r”.
<code>plain.ascii</code>	Logical. <code>pander</code> argument; when TRUE, no markup characters will be used (useful when printing to console). Defaults to TRUE unless <code>style = 'rmarkdown'</code> , in which case it will be set to FALSE automatically. To change the default value globally, use <code>st_options</code> .
<code>headings</code>	Logical. Set to FALSE to omit heading section. Can be set globally via <code>st_options</code> .
<code>display.labels</code>	Logical. Should variable / data frame label be displayed in the title section? Default is TRUE. To change this default value globally, use <code>st_options</code> .
<code>split.tables</code>	Pander argument that specifies how many characters wide a table can be. Inf by default.
<code>dnn</code>	Names to be used in output table. Vector of two strings; By default, the character values for arguments <code>x</code> and <code>y</code> are used.
<code>chisq</code>	Logical. Display chisq statistic along with p-value.
<code>OR</code>	Logical or numeric. Display odds ratio with the specified confidence level (typically .95). Can be set to TRUE, in which case 95 interval is given. Confidence intervals are calculated using Wald’s method (normal approximation).
<code>RR</code>	Logical or numeric. Display risk ratio (also called relative risk) with the specified confidence level (typically .95). Can be set to TRUE, in which case 95 calculated using Wald’s method (normal approximation).
<code>weights</code>	Vector of weights; must be of the same length as <code>x</code> .
<code>rescale.weights</code>	Logical parameter. When set to TRUE, the total count will be the same as the unweighted <code>x</code> . FALSE by default.
<code>...</code>	Additional arguments passed to <code>pander</code> .

Details

Rmarkdown does not, to this day, support multi-header tables. Therefore, until such support is available, the recommended way to display cross-tables in .Rmd documents is to use ‘method=render’ with the ‘print()’ or ‘view()’ functions. See package vignettes for examples.

Value

A frequency table of classes `matrix` and `summarytools` with added attributes used by `print` method.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

See Also

`table`, `xtabs`

Examples

```

data("tobacco")
ctable(tobacco$gender, tobacco$smoker)

# Use with() to simplify syntax
with(tobacco, ctable(smoker, diseased))

# Show column proportions, without totals
with(tobacco, ctable(smoker, diseased, prop = "c", totals = FALSE))

# Simple 2 x 2 table with odds ratio and risk ratio
with(tobacco, ctable(gender, smoker, totals = FALSE, headings = FALSE, prop = "n",
                     OR = TRUE, RR = TRUE))

# Grouped cross-tabulations
with(tobacco, stby(list(x = smoker, y = diseased), gender, ctable))

## Not run:
ct <- ctable(tobacco$gender, tobacco$smoker)

# Show html results in browser
print(ct, method = "browser")

# Save results to html file
print(ct, file = "ct_gender_smoker.html")

# Save results to text file
print(ct, file = "ct_gender_smoker.txt")

## End(Not run)

```

define_keywords

Modify Keywords Used In Outputs

Description

As an alternative to [use_custom_lang](#), this allows temporarily modifying the keywords used in the outputs.

Usage

```
define_keywords(...)
```

Arguments

...	one or more pairs of keywords and their new values see <i>Details</i> .
-----	---

Details

On systems with GUI capabilities, a window will pop-up, allowing the modification of the *custom* column. The changes will be active as long as the package is loaded. A dialog will show up prompting the user to save the modified set of keywords in a custom csv language file.

Here is the full list of modifiable keywords. Check out the *language_template.csv* file in the package's *includes* directory.

title.freq main heading for freq()
title.freq.weighted main heading for freq() (weighted)
title.ctable main heading for ctable()
title.ctable.weighted main heading ctable() (weighted)
title.ctable.row indicates what proportions are displayed
title.ctable.col indicates what proportions are displayed
title.ctable.tot indicates what proportions are displayed
title.descr main heading for descr()
title.descr.weighted main heading for descr() (weighted)
title.dfSummary main heading for dfSummary()
n heading item used in descr()
dimensions heading item used in dfSummary()
duplicates heading item used in dfSummary()
data.frame heading item (all functions)
label heading item (all functions) & column name in dfSummary()
variable heading item (all functions) & column name in dfSummary()
group heading item (all functions when used with stby())
by heading item for descr() when used with stby()
weights heading item - descr() & freq()
type heading item for freq()
logical heading item - type in freq()
character heading item - type in freq()
numeric heading item - type in freq()
factor heading item - type in freq()
factor.ordered heading item - type in freq()
date heading item - type in freq()
datetime heading item - type in freq()
freq column name in freq()
pct column name in freq() when report.nas=FALSE
pct.valid.f column name in freq()
pct.valid.cum column name in freq()

pct.total column name in freq()
pct.total.cum column name in freq()
pct.cum column name in freq()
valid column name in freq() and dfSummary() & column content in dfSummary()
invalid column content in dfSummary() (emails)
total column grouping in freq(), html version
mean row name in descr()
sd.long row name in descr()
sd cell content (dfSummary)
min row name in descr()
q1 row name in descr() - 1st quartile
med row name in descr()
q3 row name in descr() - 3rd quartile
max row name in descr()
mad row name in descr() - Median Absolute Deviation
iqr row name in descr() - Inter-Quartile Range
cv row name in descr() - Coefficient of Variation
skewness row name in descr()
se.skewness row name in descr() - Std. Error for Skewness
kurtosis row name in descr()
n.valid row name in descr() - Count of non-missing values
pct.valid row name in descr() - pct. of non-missing values
no column name in dfSummary() - position of column in the data frame
stats.values column name in dfSummary()
freqs.pct.valid column name in dfSummary()
graph column name in dfSummary()
missing column name in dfSummary()
distinct.value cell content in dfSummary() - singular form
distinct.values cell content in dfSummary() - plural form
all.nas cell content in dfSummary() - column has only NAs
all.empty.str cell content in dfSummary() - column has only empty strings
all.empty.str.nas cell content in dfSummary() - col. has only NAs and empty strings
no.levels.defined cell content in dfSummary() - factor has no levels defined
int.sequence cell content in dfSummary()
rounded cell content in dfSummary() - note appearing in Stats/Values
others cell content in dfSummary() - nbr of values not displayed
codes cell content in dfSummary() - When UPC codes are detected

mode cell content in dfSummary() - mode = most frequent value
med.short cell content in dfSummary() - median (shortened term)
start cell content in dfSummary() - earliest date for date-type cols
end cell content in dfSummary() - latest date for data-type cols
emails cell content in dfSummary()
generated.by footnote content
version footnote content
date.fmt footnote - date format (see [strptime](#))

Examples

```
## Not run:
define_keywords(n = "Nb. Obs.")

## End(Not run)
```

descr

Univariate Statistics for Numerical Data

Description

Calculates mean, sd, min, Q1*, median, Q3*, max, MAD, IQR*, CV, skewness*, SE.skewness*, and kurtosis* on numerical vectors. (*) Not available when using sampling weights.

Usage

```
descr(
  x,
  var = NULL,
  stats = st_options("descr.stats"),
  na.rm = TRUE,
  round.digits = st_options("round.digits"),
  transpose = st_options("descr.transpose"),
  style = st_options("style"),
  plain.ascii = st_options("plain.ascii"),
  justify = "r",
  headings = st_options("headings"),
  display.labels = st_options("display.labels"),
  split.tables = 100,
  weights = NA,
  rescale.weights = FALSE,
  ...
)
```

Arguments

x	A numerical vector or a data frame.
var	Unquoted expression referring to a specific column in x. Provides support for piped function calls (e.g. df %>% descr(some_var)).
stats	Which stats to produce. Either "all" (default), "fivenum", "common" (see Details), or a selection of : "mean", "sd", "min", "q1", "med", "q3", "max", "mad", "iqr", "cv", "skewness", "se.skewness", "kurtosis", "n.valid", and "pct.valid". This can be set globally via st_options ("descr.stats").
na.rm	Argument to be passed to statistical functions. Defaults to TRUE. Can be set globally; see st_options .
round.digits	Number of significant digits to display. Defaults to 2, and can be set globally (see st_options).
transpose	Logical. Makes variables appears as columns, and stats as rows. Defaults to FALSE. To change this default value, see st_options (option "descr.transpose").
style	Style to be used by pander when rendering output table; One of "simple" (default), "grid", or "rmarkdown" This option can be set globally; see st_options .
plain.ascii	Logical. pander argument; when TRUE, no markup characters will be used (useful when printing to console). Defaults to TRUE unless style = 'rmarkdown', in which case it will be set to FALSE automatically. To change the default value globally, see st_options .
justify	Alignment of numbers in cells; "l" for left, "c" for center, or "r" for right (default). Has no effect on <i>html</i> tables.
headings	Logical. Set to FALSE to omit heading section. Can be set globally via st_options . TRUE by default.
display.labels	Logical. Should variable / data frame labels be displayed in the title section? Default is TRUE. To change this default value globally, see st_options .
split.tables	Pander argument that specifies how many characters wide a table can be. 100 by default.
weights	Vector of weights having same length as x. NA (default) indicates that no weights are used.
rescale.weights	Logical. When set to TRUE, the total count will be the same as the unweighted x. FALSE by default.
...	Additional arguments passed to pander .

Value

An object having classes `matrix` and `summarytools` containing the statistics, with extra attributes used by `print` method.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

Examples

```
data("exams")

# All stats for all numerical variables
descr(exams)

# Only common statistics
descr(exams, stats = "common")

# Arbitrary selection of statistics, transposed
descr(exams, stats = c("mean", "sd", "min", "max"), transpose = TRUE)

# Rmarkdown-ready
descr(exams, plain.ascii = FALSE, style = "rmarkdown")

# Grouped statistics
data("tobacco")
with(tobacco, stby(BMI, gender, descr))

# Grouped statistics, transposed
with(tobacco, stby(BMI, age.gr, descr, stats = "common", transpose = TRUE))

## Not run:
# Show in Viewer (or browser if not in RStudio)
view(descr(exams))

# Save to html file with title
print(descr(exams),
      file = "descr_exams.html",
      report.title = "BMI by Age Group",
      footnote = "<b>Schoolyear:</b> 2018-2019<br/><b>Semester:</b> Fall")

## End(Not run)
```

Description

Summary of a data frame consisting of: variable names, labels if any, factor levels, frequencies and/or numerical summary statistics, and valid/missing observation counts.

Usage

```
dfSummary(
  x,
  round.digits = st_options("round.digits"),
```

```

varnumbers = st_options("dfSummary.varnumbers"),
labels.col = st_options("dfSummary.labels.col"),
valid.col = st_options("dfSummary.valid.col"),
na.col = st_options("dfSummary.na.col"),
graph.col = st_options("dfSummary.graph.col"),
graph.magnif = st_options("dfSummary.graph.magnif"),
style = st_options("dfSummary.style"),
plain.ascii = st_options("plain.ascii"),
justify = "l",
col.widths = NA,
headings = st_options("headings"),
display.labels = st_options("display.labels"),
max.distinct.values = 10,
trim.strings = FALSE,
max.string.width = 25,
split.cells = 40,
split.tables = Inf,
tmp.img.dir = st_options("tmp.img.dir"),
silent = st_options("dfSummary.silent"),
...
)

```

Arguments

x	A data frame.
round.digits	Number of significant digits to display. Defaults to 2 and can be set globally; see st_options .
varnumbers	Logical. Should the first column contain variable number? Defaults to TRUE. Can be set globally; see st_options , option “dfSummary.varnumbers”.
labels.col	Logical. If TRUE, variable labels (as defined with rapporootools , Hmisc or summarytools ’ label functions) will be displayed. TRUE by default, but the <i>labels</i> column is only shown if at least one column has a defined label. This option can also be set globally; see st_options , option “dfSummary.labels.col”.
valid.col	Logical. Include column indicating count and proportion of valid (non-missing) values. TRUE by default, but can be set globally; see st_options , option “dfSummary.valid.col”.
na.col	Logical. Include column indicating count and proportion of missing (NA) values. TRUE by default, but can be set globally; see st_options , option “dfSummary.na.col”.
graph.col	Logical. Display barplots / histograms column in <i>html</i> reports. TRUE by default, but can be set globally; see st_options , option “dfSummary.graph.col”.
graph.magnif	Numeric. Magnification factor, useful if the graphs show up too large (then use a value < 1) or too small (use a value > 1). Must be positive. Default to 1. Can be set globally; see st_options , option “dfSummary.graph.magnif”.
style	Style to be used by pander when rendering output table. Defaults to “multiline”. The only other valid option is “grid”. Style “simple” is not supported for this particular function, and “rmarkdown” will fallback to “multiline”.

plain.ascii	Logical. pander argument; when TRUE, no markup characters will be used (useful when printing to console). Defaults to TRUE. Set to FALSE when in context of markdown rendering. To change the default value globally, see st_options .
justify	String indicating alignment of columns; one of “l” (left) “c” (center), or “r” (right). Defaults to “l”.
col.widths	Numeric or character. Vector of column widths. If numeric, values are assumed to be numbers of pixels. Otherwise, any CSS-supported units can be used. NA by default, meaning widths are calculated automatically.
headings	Logical. Set to FALSE to omit headings. To change this default value globally, see st_options .
display.labels	Logical. Should data frame label be displayed in the title section? Default is TRUE. To change this default value globally, see st_options .
max.distinct.values	The maximum number of values to display frequencies for. If variable has more distinct values than this number, the remaining frequencies will be reported as a whole, along with the number of additional distinct values. Defaults to 10.
trim.strings	Logical; for character variables, should leading and trailing white space be removed? Defaults to FALSE. See <i>details</i> section.
max.string.width	Limits the number of characters to display in the frequency tables. Defaults to 25.
split.cells	A numeric argument passed to pander . It is the number of characters allowed on a line before splitting the cell. Defaults to 40.
split.tables	pander argument which determines the maximum width of a table. Keeping the default value (Inf) is recommended.
tmp.img.dir	Character. Directory used to store temporary images when rendering dfSummary() with ‘method = “pander”’, ‘plain.ascii = TRUE’ and ‘style = “grid”’. See <i>Details</i> .
silent	Logical. Hide console messages. FALSE by default. To change this value globally, see st_options .
...	Additional arguments passed to pander .

Details

The default plain.ascii = TRUE option is there to make results appear cleaner in the console. When used in a context of *rmarkdown* rendering, set this option to FALSE.

When the trim.strings is set to TRUE, trimming is done *before* calculating frequencies, so those will be impacted accordingly.

Specifying tmp.img.dir allows producing results consistent with pandoc styling while also showing *png* graphs. Due to the fact that in Pandoc, column widths are determined by the length of cell contents **even if said content is merely a link to an image**, we cannot use the standard R temporary directory to store the images. We need a shorter path; on Mac OS and Linux, using “/tmp” is a sensible choice, since this directory is cleaned up automatically on a regular basis. On Windows however, there is no such convenient directory and the user will have to choose a directory and cleanup the temporary images manually after the document has been rendered. Providing a relative path such as “img” is recommended. The maximum length for this parameter is set to 5 characters. It can be set globally using [st_options](#); for example: st_options(tmp.img.dir = “.”).

Value

A data frame with additional class `summarytools` containing as many rows as there are columns in `x`, with attributes to inform `print` method. Columns in the output data frame are:

No Number indicating the order in which column appears in the data frame.

Variable Name of the variable, along with its class(es).

Label Label of the variable (if applicable).

Stats / Values For factors, a list of their values, limited by the `max.distinct.values` parameter.

For character variables, the most common values (in descending frequency order), also limited by `max.distinct.values`. For numerical variables, common univariate statistics (mean, std. deviation, min, med, max, IQR and CV).

Freqs (% of Valid) For factors and character variables, the frequencies and proportions of the values listed in the previous column. For numerical vectors, number of distinct values, or frequency of distinct values if their number is not greater than `max.distinct.values`.

Text Graph An ascii histogram for numerical variables, and ascii barplot for factors and character variables.

Valid Number and proportion of valid values.

Missing Number and proportion of missing (NA and NAN) values.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

Examples

```
data("tobacco")
saved_x11_option <- st_options("use.x11")
st_options(use.x11 = FALSE)
dfSummary(tobacco)

# Exclude some columns
dfSummary(tobacco, varnumbers = FALSE, valid.col = FALSE)

# Limit number of categories to be displayed for factors / categorical data
dfSummary(tobacco, max.distinct.values = 5, style = "grid")

# Using stby()
stby(tobacco, tobacco$gender, dfSummary)

st_options(use.x11 = saved_x11_option)

## Not run:

# Show in Viewer or browser (view: no capital V!)
view(dfSummary(iris))

# Rmarkdown-ready
dfSummary(tobacco, style = "rmarkdown", plain.ascii = TRUE,
```

```
varnumbers = FALSE, valid.col = FALSE, tmp.img.dir = "./img")  
  
# Using group_by()  
tobacco %>% group_by(gender) %>% dfSummary()  
  
## End(Not run)
```

examens*Bulletin de Notes (Donne simulees)*

Description

Jeu de donnees simulees contenant les notes de 30 etudiants, avec les colonnes suivantes:

- etudiant Nom de l'étudiant.
- sexe Variable categorielle (facteur). Deux niveaux: "Fille", "Garcon".
- francais Note en francais (numerique).
- math Note en maths (numerique).
- geographie Note en geographie (numerique).
- histoire Note en histoire (numerique).
- economie Note en economie (numerique).
- anglais Note en anglais (numerique).

Usage

```
data(examens)
```

Format

Un data frame de 30 rangees et 8 colonnes

Details

Donnees simulees. Les notes de chaque etudiant sont centreses autour d'une moyenne personnelle et ecart-type randomises.

A copy of this dataset is **available in English** under the name "exams".

exams*Report Cards - Simulated Data*

Description

A simulated dataset with grades for hypothetical 30 students, with the following variables:

- student Student's name.
- gender Factor with 2 levels: "Girl", "Boy".
- french French Grade (numerical).
- math Math Grade (numerical).
- geography Geography Grade (numerical).
- history History Grade (numerical).
- economics Economics Grade (numerical).
- english English Grade (numerical).

Usage

```
data(exams)
```

Format

A data frame with 30 rows and 8 variables

Details

All names and grades are simulated. Grades for each student are centered around a personal randomized average and standard deviation.

A copy of this dataset is also **available in French** under the name "examens".

freq*Frequency Tables for Factors and Other Discrete Data*

Description

Displays weighted or unweighted frequencies, including <NA> counts and proportions.

Usage

```
freq(
  x,
  var = NULL,
  round.digits = st_options("round.digits"),
  order = "default",
  style = st_options("style"),
  plain.ascii = st_options("plain.ascii"),
  justify = "default",
  cumul = st_options("freq.cumul"),
  totals = st_options("freq.totals"),
  report.nas = st_options("freq.report.nas"),
  rows = numeric(),
  missing = "",
  display.type = TRUE,
  display.labels = st_options("display.labels"),
  headings = st_options("headings"),
  weights = NA,
  rescale.weights = FALSE,
  ...
)
```

Arguments

<code>x</code>	Factor or vector, or data frame when <code>y</code> is also provided, usually in a piped call.
<code>var</code>	Unquoted expression referring to a specific column in <code>x</code> . Provides support for piped function calls (e.g. <code>df %>% freq(some_var)</code>).
<code>round.digits</code>	Number of significant digits to display. Defaults to 2 and can be set globally; see st_options .
<code>order</code>	Ordering of rows in frequency table; “names” (default for non-factors), “levels” (default for factors), or “freq” (from most frequent to less frequent). To invert the order, place a minus sign before or after the word. “-freq” will thus display the items starting from the lowest in frequency to the highest, and so forth.
<code>style</code>	Style to be used by pander when rendering output table; One of “simple” (default), “grid”, or “rmarkdown”. This option can be set globally; see st_options .
<code>plain.ascii</code>	Logical. pander argument; when TRUE, no markup characters will be used (useful when printing to console). Defaults to TRUE unless <code>style = 'rmarkdown'</code> , in which case it will be set to FALSE automatically. To change the default value globally, see st_options .
<code>justify</code>	String indicating alignment of columns. By default (“default”), “right” is used for text tables and “center” is used for <i>html</i> tables. You can force it to one of “left”, “center”, or “right”.
<code>cumul</code>	Logical. Set to FALSE to hide cumulative proportions from results. TRUE by default. To change this value globally, see st_options .
<code>totals</code>	Logical. Set to FALSE to hide totals from results. TRUE by default. To change this value globally, see st_options .

report.nas	Logical. Set to FALSE to turn off reporting of missing values. To change this default value globally, see st_options .
rows	Character or numeric vector allowing subsetting of the results. The order given here will be reflected in the resulting table. If a single string is used, it will be used as a regular expression to filter row names.
missing	Characters to display in NA cells. Defaults to “”.
display.type	Logical. Should variable type be displayed? Default is TRUE.
display.labels	Logical. Should variable / data frame labels be displayed? Default is TRUE. To change this default value globally, see st_options .
headings	Logical. Set to FALSE to omit heading section. Can be set globally via st_options .
weights	Vector of weights; must be of the same length as x.
rescale.weights	Logical parameter. When set to TRUE, the total count will be the same as the unweighted x. FALSE by default.
...	Additional arguments passed to pander .

Details

The default `plain.ascii = TRUE` option is there to make results appear cleaner in the console. To avoid rmarkdown rendering problems, this option is automatically set to FALSE whenever `style = "rmarkdown"` (unless `plain.ascii = TRUE` is made explicit in the function call).

Value

A frequency table of class `matrix` and `summarytools` with added attributes used by `print` method.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

See Also

[table](#)

Examples

```
data(tobacco)
freq(tobacco$gender)
freq(tobacco$gender, totals = FALSE)

# Ignore NA's, don't show totals, omit headings
freq(tobacco$gender, report.nas = FALSE, totals = FALSE, headings = FALSE)

# In .Rmd documents, use the two following arguments, minimally
freq(tobacco$gender, style="rmarkdown", plain.ascii = FALSE)

# Grouped Frequencies
with(tobacco, stby(diseased, smoker, freq))
```

```
(fr_smoker_by_gender <- with(tobacco, stby(smoker, gender, freq)))

# Print html Source
print(fr_smoker_by_gender, method = "render", footnote = NA)

# Order by frequency (+ to -)
freq(tobacco$age.gr, order = "freq")

# Order by frequency (- to +)
freq(tobacco$age.gr, order = "-freq")

# Use the 'rows' argument to display only the 10 most common items
freq(tobacco$age.gr, order = "freq", rows = 1:10)

## Not run:
# Display rendered html results in RStudio's Viewer
# notice 'view()' is NOT written with capital V
# If working outside RStudio, Web browser is used instead
# A temporary file is stored in temp dir
view(fr_smoker_by_gender)

# Display rendered html results in default Web browser
# A temporary file is stored in temp dir here too
print(fr_smoker_by_gender, method = "browser")

# Write results to text file (.txt, .md, .Rmd) or html file (.html)
print(fr_smoker_by_gender, method = "render", file = "fr_smoker_by_gender.md")
print(fr_smoker_by_gender, method = "render", file = "fr_smoker_by_gender.html")

## End(Not run)
```

label*Get or Set Variable or Data Frame Labels*

Description

Assigns a label to a vector or data frame, or returns value stored in the object's `label` attribute (or `NA` if none exists).

Usage

```
label(x, all = FALSE, fallback = FALSE, simplify = FALSE)
label(x) <- value
```

Arguments

`x` An R object to extract labels from.

all	Logical. When x is a data frame, setting this argument to TRUE will make the function return all variable labels. By default, its value is FALSE, so that if x is a data frame, it is the data frame's label that will be returned.
fallback	a logical value indicating if labels should fallback to object name(s). Defaults to FALSE.
simplify	When x is a data frame and all = TRUE, coerce results to a vector and remove NA's. Default is FALSE.
value	String to be used as label. To clear existing labels, use NA or NULL.

Note

Loosely based on Gergely Daróczsi's [label](#) function.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>,

print.list

Print Method for Objects of Class “list”

Description

Displays a list comprised of summarytools objects created with `lapply`.

Usage

```
## S3 method for class 'list'
print(x, method = "pander", file = "",
      append = FALSE, report.title = NA, table.classes = NA,
      bootstrap.css = st_options('bootstrap.css'),
      custom.css = st_options('custom.css'), silent = FALSE,
      footnote = st_options('footnote'), collapse = 0,
      escape.pipe = st_options('escape.pipe'), ...)
```

Arguments

x	A summarytools object that was generated with freq , descr , ctable or dfSummary .
method	One of “pander”, “viewer”, “browser”, or “render”. For <code>print()</code> , default is “pander”; for <code>view()</code> , default is “viewer”. If “viewer” is used outside <i>RStudio</i> , “browser” will be used instead. Use “render” if function is called from an Rmd document.
file	File name to write output to. Defaults to “”.
append	Logical. When file argument is supplied, this indicates whether to append output to existing file. FALSE by default.
report.title	For <i>html</i> reports, this goes into the <code><title></code> tag. Defaults to NA, in which case <code><title></code> will be generic.

table.classes	Character. Additional classes to assign to output tables. All <i>Bootstrap css</i> classes can be used. It also allows user-defined classes (see <code>custom.css</code> parameter). See <i>details</i> section. NA by default.
bootstrap.css	Logical. Set to FALSE to omit <i>Bootstrap css</i> . TRUE by default. To change this default value globally, see st_options .
custom.css	Path to a user-defined .css file. Classes defined in this file can be used in the <code>table.classes</code> parameter. NA by default. To change this default value globally, see st_options .
silent	Hide console messages (such as ignored variables or NaN to NA transformations).
footnote	footnote in <i>html</i> output. When set to “default”, this is the package name and version, R version, and current date). Has no effect when <code>method</code> is “pander”. Set to “default”, provide your own text, or set to NA to omit. To change this default value globally, see st_options .
collapse	Numeric. 0 by default. Set to 1 to make <code>freq()</code> sections collapsible (when clicking on the variable name). Future versions might provide alternate collapsing options.
escape.pipe	Logical. Set to TRUE when using <code>style='grid'</code> and <code>file</code> argument is supplied if the intent is to generate a text file that can be converted to other formats using <i>Pandoc</i> . To change this default value globally, see st_options .
...	Additional arguments can be used to override parameters stored as attributes in the object being printed. See <i>Details</i> section.

print.stby*Print Method for Objects of Class “stby”*

Description

Displays a list comprised of `summarytools` objects created with `stby`.

Usage

```
## S3 method for class 'stby'
print(x, method = "pander", file = "",
      append = FALSE, report.title = NA, table.classes = NA,
      bootstrap.css = st_options('bootstrap.css'),
      custom.css = st_options('custom.css'), silent = FALSE,
      footnote = st_options('footnote'),
      escape.pipe = st_options('escape.pipe'), ...)
```

Arguments

x	A <code>summarytools</code> object that was generated with <code>freq</code> , <code>descr</code> , <code>ctable</code> or <code>dfSummary</code> .
method	One of “pander”, “viewer”, “browser”, or “render”. For <code>print()</code> , default is “pander”; for <code>view()</code> , default is “viewer”. If “viewer” is used outside <i>RStudio</i> , “browser” will be used instead. Use “render” if function is called from an Rmd document.

<code>file</code>	File name to write output to. Defaults to “”.
<code>append</code>	Logical. When <code>file</code> argument is supplied, this indicates whether to append output to existing file. FALSE by default.
<code>report.title</code>	For <i>html</i> reports, this goes into the <code><title></code> tag. Defaults to NA, in which case <code><title></code> will be generic.
<code>table.classes</code>	Character. Additional classes to assign to output tables. All <i>Bootstrap css</i> classes can be used. It also allows user-defined classes (see <code>custom.css</code> parameter). See <i>Details</i> section. NA by default.
<code>bootstrap.css</code>	Logical. Set to FALSE to omit <i>Bootstrap css</i> . TRUE by default. To change this default value globally, see st_options .
<code>custom.css</code>	Path to a user-defined <code>.css</code> file. Classes defined in this file can be used in the <code>table.classes</code> parameter. NA by default. To change this default value globally, see st_options .
<code>silent</code>	Hide console messages (such as ignored variables or NaN to NA transformations).
<code>footnote</code>	footnote in <i>html</i> output. When set to “default”, this is the package name and version, R version, and current date). Has no effect when <code>method</code> is “pander”. Set to “default”, provide your own text, or set to NA to omit. To change this default value globally, see st_options .
<code>escape.pipe</code>	Logical. Set to TRUE when using <code>style='grid'</code> and <code>file</code> argument is supplied if the intent is to generate a text file that can be converted to other formats using <i>Pandoc</i> . To change this default value globally, see st_options .
...	Additional arguments can be used to override parameters stored as attributes in the object being printed. See <i>Details</i> section.

`print.summarytools` *print.summarytools*

Description

Display `summarytools` objects in the console, in Web Browser or in *RStudio*’s Viewer, or write content to file.

Usage

```
## S3 method for class 'summarytools'
print(x, method = "pander", file = "",
      append = FALSE, report.title = NA, table.classes = NA,
      bootstrap.css = st_options('bootstrap.css'),
      custom.css = st_options('custom.css'), silent = FALSE,
      footnote = st_options('footnote'), max.tbl.height = Inf,
      collapse = 0, escape.pipe = st_options("escape.pipe"), ...)
```

Arguments

x	A summarytools object that was generated with freq , descr , ctable or dfSummary .
method	One of “pander”, “viewer”, “browser”, or “render”. For <code>print()</code> , default is “pander”; for <code>view()</code> , default is “viewer”. If “viewer” is used outside <i>RStudio</i> , “browser” will be used instead. Use “render” if function is called from an Rmd document.
file	File name to write output to. Defaults to “”.
append	Logical. When <code>file</code> argument is supplied, this indicates whether to append output to existing file. FALSE by default.
report.title	For <i>html</i> reports, this goes into the <code><title></code> tag. Defaults to NA, in which case <code><title></code> will be generic.
table.classes	Character. Additional classes to assign to output tables. All <i>Bootstrap css</i> classes can be used. It also allows user-defined classes (see <code>custom.css</code> parameter). See <i>Details</i> section. NA by default.
bootstrap.css	Logical. Set to FALSE to omit <i>Bootstrap css</i> . TRUE by default. To change this default value globally, see st_options .
custom.css	Path to a user-defined .css file. Classes defined in this file can be used in the <code>table.classes</code> parameter. NA by default. To change this default value globally, see st_options .
silent	Hide console messages (such as ignored variables or NaN to NA transformations).
footnote	footnote in <i>html</i> output. When set to “default”, this is the package name and version, R version, and current date). Has no effect when <code>method</code> is “pander”. Set to “default”, provide your own text, or set to NA to omit. To change this default value globally, see st_options .
max.tbl.height	Maximum table height (in pixels) allowed in rendered <code>dfSummary()</code> tables. When this argument is used, results will show up in a <code><div></code> with the specified height and a scroll bar. Intended to be used in <i>Rmd</i> documents. Has no effect when <code>method</code> is “pander”. Inf by default.
collapse	Numeric. 0 by default. Set to 1 to make <code>freq()</code> sections collapsible (when clicking on the variable name). Future versions might provide alternate collapsing options.
escape.pipe	Logical. Set to TRUE when using <code>style='grid'</code> and <code>file</code> argument is supplied if the intent is to generate a text file that can be converted to other formats using <i>Pandoc</i> . To change this default value globally, see st_options .
...	Additional arguments can be used to override parameters stored as attributes in the object being printed. See <i>Details</i> section.

Details

Plain ascii and *rmarkdown* tables are generated via [pander](#). See *References* section for a list of all available `pander` options.

The following additional arguments can be used to override formatting attributes stored in the object to be printed. Refer to the function’s documentation for details on these arguments.

- `style`
- `round.digits` (except for `dfSummary` objects)
- `plain.ascii`
- `justify`
- `headings`
- `display.labels`
- `varnumbers` (`dfSummary` objects)
- `labels.col` (`dfSummary` objects)
- `graph.col` (`dfSummary` objects)
- `valid.col` (`dfSummary` objects)
- `na.col` (`dfSummary` objects)
- `col.widths` (`dfSummary` objects)
- `split.tables`
- `report.nas` (`freq` objects)
- `display.type` (`freq` objects)
- `missing` (`freq` objects)
- `totals` (`freq` and `ctable` objects)
- `caption` (`freq` and `ctable` objects)

The following additional arguments can be used to override heading elements to be printed:

- `Data.frame`
- `Data.frame.label`
- `Variable`
- `Variable.label`
- `Group`
- `date`
- `Weights` (`freq` & `descr` objects)
- `Data.type` (`freq` objects)
- `Row.variable` (`ctable` objects)
- `Col.variable` (`ctable` objects)

Value

NULL when `method="pander"`; a file path (returned invisibly) when `method="viewer"` or `method="browser"`. In the latter case, the file path is also passed to `shell.exec` so the document is opened in default Web Browser.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

References

[RStudio Summarytools on GitHub](#) [List of pander options on GitHub](#) [Bootstrap Cascading Stylesheets](#)

See Also

[pander](#)

Examples

```
## Not run:  
data(tobacco)  
view(dfSummary(tobacco), footnote = NA)  
  
## End(Not run)  
data(exams)  
print(freq(exams$gender), style = 'rmarkdown')  
print(descr(exams), headings = FALSE)
```

stby

Obtain Grouped Statistics With summarytools

Description

This is essentially the base [by](#) function, except for the class of the returned object.

Usage

```
stby(data, INDICES, FUN, ..., simplify = TRUE)
```

Arguments

data	an R object, normally a data frame, possibly a matrix.
INDICES	a grouping variable or a list of grouping variables, each of length nrow(data).
FUN	a function to be applied to (usually data-frame) subsets of data.
...	Further arguments to FUN.
simplify	Logical. Essentially a placeholder to maintain full compatibility with base by. For more details, see tapply .

Value

An object having classes “list” and “summarytools”.

See Also

[by](#), [tapply](#)

Examples

```
data("tobacco")
with(tobacco, stby(BMI, gender, descr))
```

st_css

*Include **summarytools**' css Into Active Document*

Description

Generates the *css* needed by **summarytools** in *Rmarkdown* documents.

Usage

```
st_css(main = TRUE, global = FALSE, bootstrap = FALSE, style.tag = TRUE, ...)
```

Arguments

main	Logical. Include <i>summarytools.css</i> file. TRUE by default. Affects only summarytools objects.
global	Logical. Include the additional <i>summarytools-global.css</i> file, which affects all content in the document. Provides control over objects that were not <i>html-rendered</i> ; in particular, table widths and vertical alignment are modified to improve layout. FALSE by default.
bootstrap	Logical. Include <i>bootstrap.min.css</i> . FALSE by default.
style.tag	Logical. Includes the opening and closing <style> tags. TRUE by default.
...	Character. Path to additional <i>css</i> file(s) to include.

Details

Typically the function is called right after the initial setup chunk of an *Rmarkdown* document, in a chunk having options `echo=FALSE` and `results="asis"`.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

st_options*Query and set summarytools global options*

Description

To list all `summarytools` global options, call without arguments. To display the value of one or several options, enter the name(s) of the option(s) in a character vector as sole argument. To **reset** all options, use single unnamed argument ‘`reset`’ or `0`.

Usage

```
st_options(  
  option = NULL,  
  value = NULL,  
  style = "simple",  
  plain.ascii = TRUE,  
  round.digits = 2,  
  headings = TRUE,  
  footnote = "default",  
  display.labels = TRUE,  
  bootstrap.css = TRUE,  
  custom.css = NA,  
  escape.pipe = FALSE,  
  freq.cumul = TRUE,  
  freq.totals = TRUE,  
  freq.report.nas = TRUE,  
  freq.ignore.threshold = 25,  
  freq.silent = FALSE,  
  ctable.prop = "r",  
  ctable.totals = TRUE,  
  descr.stats = "all",  
  descr.transpose = FALSE,  
  descr.silent = FALSE,  
  dfSummary.style = "multiline",  
  dfSummary.varnumbers = TRUE,  
  dfSummary.labels.col = TRUE,  
  dfSummary.valid.col = TRUE,  
  dfSummary.na.col = TRUE,  
  dfSummary.graph.col = TRUE,  
  dfSummary.graph.magnif = 1,  
  dfSummary.silent = FALSE,  
  tmp.img.dir = NA,  
  subtitle.emphasis = TRUE,  
  lang = "en",  
  use.x11 = TRUE  
)
```

Arguments

<code>option</code>	option(s) name(s) to query (optional). Can be a single string or a vector of strings to query multiple values.
<code>value</code>	The value you wish to assign to the option specified in the first argument. This is for backward-compatibility, as all options can now be set via their own parameter. That is, instead of <code>st_options('plain.ascii', FALSE)</code> , use <code>st_options(plain.ascii = FALSE)</code> .
<code>style</code>	Character. One of “simple” (default), “rmarkdown”, or “grid”. Does not apply to <code>dfSummary</code> .
<code>plain.ascii</code>	Logical. TRUE by default. Set to FALSE when using summarytools with a rendering tool such as knitr or when creating rmarkdown output files to be converted with Pandoc. Note however that its value will automatically be set to FALSE whenever <code>style</code> is set to “rmarkdown”).
<code>round.digits</code>	Numeric. Defaults to 2.
<code>headings</code>	Logical. Set to FALSE to remove all headings from outputs. Only the tables will be printed out, except when <code>by</code> or <code>lapply</code> are used. In that case, the variable or the group will still appear before the tables. FALSE by default.
<code>footnote</code>	Character. When the default value “default” is used, the package name & version, as well as the R version number are displayed below <i>html</i> outputs. Set no NA to omit the footnote, or provide a custom string. Applies only to <i>html</i> outputs.
<code>display.labels</code>	Logical. TRUE by default. Set to FALSE to omit data frame and variable labels in the headings section.
<code>bootstrap.css</code>	Logical. Specifies whether to Include <i>Bootstrap css</i> in <i>html</i> reports <i>head</i> section outputs. Defaults to TRUE. Set to FALSE when using the “render” method inside a shiny app to avoid interacting with the app’s layout.
<code>custom.css</code>	Character. Path to an additional, user-provided, CSS file. NA by default.
<code>escape.pipe</code>	Logical. Set to TRUE if Pandoc conversion is your goal and you have unsatisfying results with grid or multiline tables. FALSE by default.
<code>freq.cumul</code>	Logical. Corresponds to the <code>cumul</code> parameter of <code>freq</code> . TRUE by default.
<code>freq.totals</code>	Logical. Corresponds to the <code>totals</code> parameter of <code>freq</code> . TRUE by default.
<code>freq.report.nas</code>	Logical. Corresponds to the <code>display.nas</code> parameter of <code>freq</code> . TRUE by default.
<code>freq.ignore.threshold</code>	Numeric. Number of distinct values above which numerical variables are ignored when calling <code>freq</code> with a whole data frame as main argument. Defaults to 25.
<code>freq.silent</code>	Logical. Hide console messages. FALSE by default.
<code>ctable.prop</code>	Character. Corresponds to the <code>prop</code> parameter of <code>ctable</code> . Defaults to “r” (row).
<code>ctable.totals</code>	Logical. Corresponds to the <code>totals</code> parameter of <code>ctable</code> . TRUE by default.
<code>descr.stats</code>	Character. Corresponds to the <code>stats</code> parameter of <code>descr</code> . Defaults to “all”.
<code>descr.transpose</code>	Logical. Corresponds to the <code>transpose</code> parameter of <code>descr</code> . FALSE by default.

descr.silent Logical. Hide console messages. FALSE by default.

dfSummary.style Character. “multiline” by default. Set to “grid” for *Rmarkdown* documents.

dfSummary.varnumbers Logical. In `dfSummary`, display variable numbers in the first column. Defaults to TRUE.

dfSummary.labels.col Logical. In `dfSummary`, display variable labels Defaults to TRUE.

dfSummary.valid.col Logical. In `dfSummary`, include column indicating count and proportion of valid (non-missing). TRUE by default.

dfSummary.na.col Logical. In `dfSummary`, include column indicating count and proportion of missing (NA) values. TRUE by default.

dfSummary.graph.col Logical. Display barplots / histograms column in `dfSummary` *html* reports. TRUE by default.

dfSummary.graph.magnif Numeric. Magnification factor, useful if `dfSummary` graphs show up too large (then use a value between 0 and 1) or too small (use a value > 1). Must be positive. Default to 1.

dfSummary.silent Logical. Hide console messages. FALSE by default.

tmp.img.dir Character. Directory used to store temporary images. See *Details* section of `dfSummary`. NA by default.

subtitle.emphasis Logical. Controls the formatting of the “subtitle” (the *data frame* or *variable* name, depending on context. When TRUE (default), “h4” is used, while with FALSE, “bold” / “strong” is used. Hence the default value gives it stronger emphasis.

lang Character. A 2-letter code for the language to use in the produced outputs. Currently available languages are: ‘en’, ‘es’, ‘fr’, ‘pt’, ‘ru’, and ‘tr’.

use.x11 Logical. TRUE by default. In console-only environments, setting this to FALSE will prevent errors occurring when `dfSummary` tries to generate *html* “Base64-encoded” graphs.

Details

To learn more about summarytools options, see the [project’s GitHub page](#).

Examples

```
## Not run:
# show all summarytools global options
st_options()

# show a specific option
```

```

st_options("round.digits")

# show two (or more) options
st_options(c("plain.ascii", "style", "footnote"))

# set one option
st_options(plain.ascii = FALSE)

# set one options, legacy way
st_options("plain.ascii", FALSE)

# set several options
st_options(plain.ascii = FALSE,
           style      = "rmarkdown",
           footnote   = NA)

# reset all
st_options('reset')
# ... or
st_options(0)

## End(Not run)

```

tabagisme*Usage du Tabac et etat de Sante (Donnees simulees)***Description**

Jeu de donnees simulees de 1000 sujets, avec les colonnes suivantes:

- sexe Variable categorielle (facteur), 2 niveaux: “F” et “M”. Environ 500 chacun.
- age Numerique.
- age.gr Groupe d’age - variable categorielle, 4 niveaux.
- IMC Indice de masse corporelle (numerique).
- fumeur Variable categorielle, 2 niveaux (“Oui” / “Non”).
- cigs.par.jour Nombre de cigarettes fumees par jour (numerique).
- malade Variable categorielle, 2 niveaux (“Oui” / “Non”).
- maladie Champs texte.
- ponderation Poids echantillonnal (numerique).

Usage

```
data(tabagisme)
```

Format

Un data frame de 1000 rangees et 9 colonnes

Details

Note sur la simulation des donnees: la probabilite pour un sujet de tomber dans la categorie “malade” est basee sur une fonction arbitraire faisant intervenir l’age, l’IMC et le nombre de cigarettes fumees par jour.

A copy of this dataset is **available in English** under the name “tobacco”.

tb	<i>Convert Summarytools Objects into Tibbles</i>
----	--

Description

Make a tidy dataset out of freq() or descr() outputs

Usage

```
tb(x, order = 1, na.rm = FALSE, drop.var.col = FALSE)
```

Arguments

x	a freq() or descr() output object.
order	Integer. Useful for grouped results produced with <code>stby</code> or <code>dplyr::group_by</code> . When set to 1 (default), the ordering is done using the grouping variables first. When set to 2, the ordering is first determined by the variable column for <code>descr</code> or the column displaying the variable values for <code>freq</code> . When set to 3, the same ordering as with 2 is used, but columns are rearranged to reflect this sort order.
na.rm	Logical. For <code>freq</code> objects, remove <NA> rows (or (Missing) rows if NA values were made explicit with <code>forcats::fct_explicit_na()</code>). Has no effect on <code>descr</code> objects.
drop.var.col	Logical. For <code>descr</code> objects, drop the variable column. This is possible only when statistics are produced for a single variable; for multiple variables, this argument is ignored. FALSE by default.

Value

A `tibble` which is constructed following the *tidy* principles.

Examples

```
tb(freq(iris$Species))
tb(descr(iris))

data("tobacco")
tb(stby(tobacco, tobacco$gender, descr))
```

tobacco

*Tobacco Use and Health - Simulated Dataset***Description**

A simulated datasets of 1,000 subjects, with the following variables:

Usage

```
data(tobacco)
```

Format

A data frame with 1000 rows and 9 variables

Details

- gender Factor with 2 levels: “F” and “M”, having roughly 500 of each.
- age Numerical.
- age.gr Factor with 4 age categories.
- BMI Body Mass Index (numerical).
- smoker Factor (“Yes” / “No”).
- cigs.per.day Number of cigarettes smoked per day (numerical).
- diseased Factor (“Yes” / “No”).
- disease Character.
- samp.wgts Sampling weights (numerical).

A note on simulation: probability for an individual to fall into category “diseased” is based on an arbitrary function involving age, BMI and number of cigarettes per day.

A copy of this dataset is also **available in French** under the name “tabagisme”.

unlabel

*Clear Variable and Data Frame Label(s)***Description**

Returns the object with all labels removed. Both the “label” attribute and **Hmisc**’s “labelled” class are removed.

Usage

```
unlabel(x)
```

Arguments

- x An R object to remove labels from.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>,

See Also

[label](#)

use_custom_lang *Import and use a custom language*

Description

If your language is not available or if you wish to customize the outputs' language to suit your preference, you can set up a translations file (see details) and import it with this function.

Usage

`use_custom_lang(file)`

Arguments

- file Character. The path to the translations file.

Details

To build the translations file, copy the `language_template.csv` file located in the installed package's `includes` directory and fill out the 'custom' column using a text editor, leaving column titles unchanged. The file must also retain its `UTF-8` encoding.

view *view*

Description

Visualize results in RStudio's Viewer or in Web Browser

Usage

```
view(x, method = "viewer", file = "", append = FALSE,
  report.title = NA, table.classes = NA,
  bootstrap.css = st_options("bootstrap.css"),
  custom.css = st_options("custom.css"), silent = FALSE,
  footnote = st_options("footnote"),
  max.tbl.height = Inf,
  collapse = 0,
  escape.pipe = st_options("escape.pipe"), ...)
```

Arguments

x	A summarytools object that was generated with freq , descr , ctable or dfSummary .
method	One of “pander”, “viewer”, “browser”, or “render”. For <code>print()</code> , default is “pander”; for <code>view()</code> , default is “viewer”. If “viewer” is used outside <i>RStudio</i> , “browser” will be used instead. Use “render” if function is called from an Rmd document.
file	File name to write output to. Defaults to “”.
append	Logical. When <code>file</code> argument is supplied, this indicates whether to append output to existing file. FALSE by default.
report.title	For <i>html</i> reports, this goes into the <code><title></code> tag. Defaults to NA, in which case <code><title></code> will be generic.
table.classes	Character. Additional classes to assign to output tables. All <i>Bootstrap</i> css classes can be used. It also allows user-defined classes (see <code>custom.css</code> parameter). See <i>details</i> section. NA by default.
bootstrap.css	Logical. Set to FALSE to omit <i>Bootstrap</i> css. TRUE by default. To change this default value globally, see st_options .
custom.css	Path to a user-defined .css file. Classes defined in this file can be used in the <code>table.classes</code> parameter. NA by default. To change this default value globally, see st_options .
silent	Hide console messages (such as ignored variables or NaN to NA transformations).
footnote	footnote in <i>html</i> output. When set to “default”, this is the package name and version, R version, and current date). Has no effect when <code>method</code> is “pander”. Set to “default”, provide your own text, or set to NA to omit. To change this default value globally, see st_options .
max.tbl.height	Maximum table height (in pixels) allowed in rendered <code>dfSummary()</code> tables. When this argument is used, results will show up in a <code><div></code> with the specified height and a scroll bar. Intended to be used in <i>Rmd</i> documents. Has no effect when <code>method</code> is “pander”. Inf by default.
collapse	Numeric. 0 by default. Set to 1 to make <code>freq()</code> sections collapsible (when clicking on the variable name). Future versions might provide alternate collapsing options.
escape.pipe	Logical. Set to TRUE when using <code>style='grid'</code> and <code>file</code> argument is supplied if the intent is to generate a text file that can be converted to other formats using <i>Pandoc</i> . To change this default value globally, see st_options .

... Additional arguments can be used to override parameters stored as attributes in the object being printed. See *Details* section.

Details

Creates *html* outputs and opens them in the Viewer, in a browser or renders the *html* code appropriate for *Rmarkdown* documents.

For objects of class “summarytools”, this function is simply a wrapper around `print.summarytools` with *method* set to “viewer”.

Objects of class “by” or “list” are dispatched to the present function, as it can manage multiple objects, whereas `print.summarytools` can only manage one object at a time.

`what.is`

Obtain Extended Properties of Objects

Description

Combination of most common “macro-level” functions that describe an object.

Usage

```
what.is(x, show.all = FALSE, ignore.size.warn = FALSE)
```

Arguments

<code>x</code>	Any object.
<code>show.all</code>	Logical. When TRUE, all logical results from the “is.” <i>identifier functions</i> will be displayed, with a warning message when the result applies only to the first element in the structure. FALSE by default.
<code>ignore.size.warn</code>	Set to TRUE to force execution of the function for large (> 20 K-bytes) objects. Defaults to FALSE.

Details

An alternative to calling in turn `class`, `typeof`, `dim`, and so on. A call to this function will readily give all this information at once.

Value

A list with following elements:

properties A data frame with the class(es), type, mode and storage mode of the object as well as the dim, length and object.size.

attributes.lengths A named character vector giving all attributes (*c.f.* “names”, “row.names”, “class”, “dim”, and so forth) along with their length.

extensive.is A character vector of all the *identifier functions*. (starting with “is.”) that yield TRUE when used with `x` as argument.

function.type When `x` is a function, results of `ftype` are added.

Author(s)

Dominic Comtois, <dominic.comtois@gmail.com>

See Also

[class](#), [typeof](#), [mode](#), [storage.mode](#), [dim](#), [length](#), [is.object](#), [otype](#), [object.size](#), [ftype](#)

Examples

```
what.is(1)
what.is(NaN)
what.is(iris3)
what.is(print)
what.is(what.is)
```

Index

*Topic **IO**
 cleartmp, 3

*Topic **attribute**
 dfSummary, 11
 what.is, 35

*Topic **category**
 ctable, 4
 dfSummary, 11
 freq, 16

*Topic **classes**
 ctable, 4
 dfSummary, 11
 freq, 16
 what.is, 35

*Topic **datasets**
 examens, 15
 exams, 16
 tabagisme, 30
 tobacco, 32

*Topic **methods**
 print.summarytools, 22

*Topic **print**
 print.summarytools, 22

*Topic **univar**
 descr, 9
 dfSummary, 11
 freq, 16

*Topic **utilities**
 define_keywords, 6
 st_css, 26
 st_options, 27
 stby, 25
 use_custom_lang, 33
 what.is, 35

by, 25, 28

 class, 35, 36
 cleartmp, 3
 ctable, 4, 20, 21, 23, 24, 28, 34

 define_keywords, 6
 descr, 9, 20, 21, 23, 24, 28, 31, 34
 dfSummary, 11, 20, 21, 23, 24, 28, 29, 34
 dim, 35, 36

 examens, 15
 exams, 16

 freq, 16, 20, 21, 23, 24, 28, 31, 34
 ftype, 35, 36

 is.object, 36

 label, 19, 20, 33
 label<- (label), 19
 lapply, 28
 length, 36

 mode, 36

 object.size, 36
 otype, 36

 pander, 4, 5, 10, 12, 13, 17, 18, 23, 25
 print, 5, 10
 print.list, 20
 print.stby, 21
 print.summarytools, 22, 35

 st_css, 26
 st_options, 4, 5, 10, 12, 13, 17, 18, 21–23,
 27, 34
 stby, 25, 31
 storage.mode, 36
 strptime, 9
 summarytools (summarytools-package), 2
 summarytools-package, 2

 tabagisme, 30
 table, 4, 5, 18
 tapply, 25

tb, 31
tibble, 31
tobacco, 32
typeof, 35, 36

unlabel, 32
use_custom_lang, 6, 33

view, 33

what.is, 35

xtabs, 5