

Package ‘textrecipes’

July 8, 2020

Title Extra 'Recipes' for Text Processing

Version 0.3.0

Description Converting text to numerical features requires specifically created procedures, which are implemented as steps according to the 'recipes' package. These steps allows for tokenization, filtering, counting (tf and tfidf) and feature hashing.

License MIT + file LICENSE

URL <https://github.com/tidymodels/textrecipes>,
<https://textrecipes.tidymodels.org>

BugReports <https://github.com/tidymodels/textrecipes/issues>

Depends R (>= 2.10), recipes (>= 0.1.4)

Imports dplyr, generics, magrittr, Matrix, purrr, Rcpp, rlang, SnowballC, stringr, tibble, tidyr, tokenizers, vctrs

Suggests covr, knitr, modeldata, rmarkdown, spacyr, stopwords, testthat (>= 2.1.0), text2vec, textfeatures (>= 0.3.3), stringi

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

SystemRequirements GNU make, C++11

NeedsCompilation yes

Author Emil Hvitfeldt [aut, cre] (<<https://orcid.org/0000-0002-0679-1945>>)

Maintainer Emil Hvitfeldt <emilhhvitfeldt@gmail.com>

Repository CRAN

Date/Publication 2020-07-08 21:50:02 UTC

R topics documented:

rcpp_ngram	2
step_lda	3
step_lemma	5
step_ngram	7
step_pos_filter	9
step_sequence_onehot	10
step_stem	12
step_stopwords	14
step_textfeature	17
step_texthash	19
step_text_normalization	21
step_tf	23
step_tfidf	25
step_tokenfilter	27
step_tokenize	30
step_tokenmerge	32
step_untokenize	34
step_word_embeddings	36
tokenlist	38
Index	40

rcpp_ngram	<i>ngram generator</i>
------------	------------------------

Description

ngram generator

Usage

```
rcpp_ngram(x, n, n_min, delim)
```

Arguments

x	list of character vectors
n	number of grams
n_min	minimum number of grams
delim	delimiter

step_lda	<i>Calculates lda dimension estimates</i>
----------	---

Description

step_lda creates a *specification* of a recipe step that will return the lda dimension estimates of a text variable.

Usage

```
step_lda(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  lda_models = NULL,
  num_topics = 10,
  prefix = "lda",
  skip = FALSE,
  id = rand_id("lda")
)

## S3 method for class 'step_lda'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_lda, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
lda_models	A WarpLDA model object from the text2vec package. If left to NULL, the default, will it train its model based on the training data. Look at the examples for how to fit a WarpLDA model.
num_topics	integer desired number of latent topics.
prefix	A prefix for generated column names, default to "lda".

skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it
x	A <code>step_lda</code> object.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

Source

<https://arxiv.org/abs/1301.3781>

See Also

Other character to numeric steps: `step_sequence_onehot()`, `step_textfeature()`

Examples

```
if (requireNamespace("text2vec", quietly = TRUE)) {

  library(recipes)
  library(modeldata)
  data(okc_text)

  okc_rec <- recipe(~ ., data = okc_text) %>%
    step_lda(essay0)

  okc_obj <- okc_rec %>%
    prep()

  juice(okc_obj) %>%
    slice(1:2)
  tidy(okc_rec, number = 1)
  tidy(okc_obj, number = 1)

  # Changing the number of topics.
  recipe(~ ., data = okc_text) %>%
    step_lda(essay0, essay1, num_topics = 20) %>%
    prep() %>%
    juice() %>%
    slice(1:2)

  # Supplying A pre-trained LDA model trained using text2vec
  library(text2vec)
  tokens <- word_tokenizer(tolower(okc_text$essay5))
  it <- itoken(tokens, ids = seq_along(okc_text$essay5))
  v <- create_vocabulary(it)
```

```

dtm <- create_dtm(it, vocab_vectorizer(v))
lda_model <- LDA$new(n_topics = 15)

recipe(~ ., data = okc_text) %>%
  step_lda(essay0, essay1, lda_models = lda_model) %>%
  prep() %>%
  juice() %>%
  slice(1:2)

}

```

step_lemma

*Lemmatization of [tokenlist](#) variables***Description**

step_lemma creates a *specification* of a recipe step that will extract the lemmatization of a tokenlist.

Usage

```

step_lemma(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  skip = FALSE,
  id = rand_id("lemma")
)

## S3 method for class 'step_lemma'
tidy(x, ...)

```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_lemma, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .

skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_lemma</code> object.

Details

This stem doesn't perform lemmatization by itself, but rather lets you extract the lemma attribute of the tokenlist. To be able to use `step_lemma` you need to use a tokenization method that includes lemmatization. Currently using the "spacyr" engine in `step_tokenize()` provides lemmatization and works well with `step_lemma`.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

`step_tokenize()` to turn character into tokenlist.

Other tokenlist to tokenlist steps: `step_ngram()`, `step_pos_filter()`, `step_stem()`, `step_stopwords()`, `step_tokenfilter()`, `step_tokenmerge()`

Examples

```
## Not run:
library(recipes)

short_data <- data.frame(text = c("This is a short tale,",
                                "With many cats and ladies.))

okc_rec <- recipe(~ text, data = short_data) %>%
  step_tokenize(text, engine = "spacyr") %>%
  step_lemma(text) %>%
  step_tf(text)

okc_obj <- prep(okc_rec)

juice(okc_obj)

## End(Not run)
```

step_ngram	<i>Generate ngrams from tokenlist</i>
------------	---------------------------------------

Description

step_ngram creates a *specification* of a recipe step that will convert a [tokenlist](#) into a list of ngram of tokens.

Usage

```
step_ngram(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  num_tokens = 3L,
  min_num_tokens = 3L,
  delim = "_",
  skip = FALSE,
  id = rand_id("ngram")
)

## S3 method for class 'step_ngram'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_ngram, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
num_tokens	The number of tokens in the n-gram. This must be an integer greater than or equal to 1. Defaults to 3.
min_num_tokens	The minimum number of tokens in the n-gram. This must be an integer greater than or equal to 1 and smaller than n. Defaults to 3.
delim	The separator between words in an n-gram. Defaults to "_".

skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_ngram</code> object.

Details

The use of this step will leave the ordering of the tokens meaningless. If `min_num_tokens < num_tokens` then the tokens order in increasing fashion with respect to the number of tokens in the n-gram. If `min_num_tokens = 1` and `num_tokens = 3` then the output contains all the 1-grams followed by all the 2-grams followed by all the 3-grams.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_pos_filter\(\)](#), [step_stem\(\)](#), [step_stopwords\(\)](#), [step_tokenfilter\(\)](#), [step_tokenmerge\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_ngram(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
```

step_pos_filter	Part of speech filtering of <i>tokenlist</i> variables
-----------------	--

Description

step_pos_filter creates a *specification* of a recipe step that will filter a [tokenlist](#) based on part of speech tags.

Usage

```
step_pos_filter(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  keep_tags = "NOUN",
  skip = FALSE,
  id = rand_id("pos_filter")
)

## S3 method for class 'step_pos_filter'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_pos_filter, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
keep_tags	Character variable of part of speech tags to keep. See details for complete list of tags. Defaults to "NOUN".
skip	A logical. Should the step be skipped when the recipe is baked by recipes::bake.recipe() ? While all operations are baked when recipes::prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A step_pos_filter object.

Details

Possible part of speech tags for spacyr engine are: "ADJ", "ADP", "ADV", "AUX", "CONJ", "CCONJ", "DET", "INTJ", "NOUN", "NUM", "PART", "PRON", "PROPN", "PUNCT", "SCONJ", "SYM", "VERB", "X" and "SPACE". For more information look here <https://spacy.io/api/annotation#pos-tagging>.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_ngram\(\)](#), [step_stem\(\)](#), [step_stopwords\(\)](#), [step_tokenfilter\(\)](#), [step_tokenmerge\(\)](#)

Examples

```
## Not run:
library(recipes)

short_data <- data.frame(text = c("This is a short tale,",
                                "With many cats and ladies.))

okc_rec <- recipe(~ text, data = short_data) %>%
  step_tokenize(text, engine = "spacyr") %>%
  step_pos_filter(text, keep_tags = "NOUN") %>%
  step_tf(text)

okc_obj <- prep(okc_rec)

juice(okc_obj)

## End(Not run)
```

step_sequence_onehot *Generate the basic set of text features*

Description

step_sequence_onehot creates a *specification* of a recipe step that will take a string and do one hot encoding for each character by position.

Usage

```
step_sequence_onehot(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  string_length = 100,
  integer_key = letters,
  prefix = "seq1hot",
  skip = FALSE,
  id = rand_id("sequence_onehot")
)

## S3 method for class 'step_sequence_onehot'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_sequence_onehot</code> , this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the <code>tidy</code> method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is <code>NULL</code> until the step is trained by recipes::prep.recipe() .
string_length	A numeric, number of characters to keep before discarding. Defaults to 100.
integer_key	A character vector, characters to be mapped to integers. Characters not in the <code>integer_key</code> will be encoded as 0. Defaults to <code>letters</code> .
prefix	A prefix for generated column names, default to "seq1hot".
skip	A logical. Should the step be skipped when the recipe is baked by recipes::bake.recipe() ? While all operations are baked when recipes::prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it
x	A <code>step_sequence_onehot</code> object.

Details

The string will be capped by the `string_length` argument, strings shorter than `string_length` will be padded with empty characters. The encoding will assign a integer to each character in the `integer_key`, and will encode accordingly. Characters not in the `integer_key` will be encoded as 0.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

Source

<https://papers.nips.cc/paper/5782-character-level-convolutional-networks-for-text-classification.pdf>

See Also

Other character to numeric steps: [step_lda\(\)](#), [step_textfeature\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_sequence_onehot(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj)

tidy(okc_rec, number = 1)
tidy(okc_obj, number = 1)
```

step_stem

Stemming of [tokenlist](#) variables

Description

step_stem creates a *specification* of a recipe step that will convert a [tokenlist](#) to have its tokens stemmed.

Usage

```
step_stem(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  options = list(),
  custom_stemmer = NULL,
```

```

    skip = FALSE,
    id = rand_id("stem")
  )

## S3 method for class 'step_stem'
tidy(x, ...)

```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_stem</code> , this indicates the variables to be encoded into a tokenlist . See <code>recipes::selections()</code> for more details. For the <code>tidy</code> method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by <code>recipes::prep.recipe()</code> .
options	A list of options passed to the stemmer function.
custom_stemmer	A custom stemming function. If none is provided it will default to "SnowballC".
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_stem</code> object.

Details

Words tend to have different forms depending on context, such as organize, organizes, and organizing. In many situations it is beneficial to have these words condensed into one to allow for a smaller pool of words. Stemming is the act of chopping off the end of words using a set of heuristics.

Note that the stemming will only be done at the end of the word and will therefore not work reliably on ngrams or sentences.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_ngram\(\)](#), [step_pos_filter\(\)](#), [step_stopwords\(\)](#), [step_tokenfilter\(\)](#), [step_tokenmerge\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_stem(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)

# Using custom stemmer. Here a custom stemmer that removes the last letter
# if it is a "s".
remove_s <- function(x) gsub("s$", "", x)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_stem(essay0, custom_stemmer = remove_s)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)
```

step_stopwords

Filtering of stopwords from a [tokenlist](#) variable

Description

step_stopwords creates a *specification* of a recipe step that will filter a [tokenlist](#) for stopwords(keep or remove).

Usage

```

step_stopwords(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  language = "en",
  keep = FALSE,
  stopword_source = "snowball",
  custom_stopword_source = NULL,
  skip = FALSE,
  id = rand_id("stopwords")
)

## S3 method for class 'step_stopwords'
tidy(x, ...)

```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_stopwords</code> , this indicates the variables to be encoded into a tokenlist . See <code>recipes::selections()</code> for more details. For the <code>tidy</code> method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is <code>NULL</code> until the step is trained by <code>recipes::prep.recipe()</code> .
language	A character to indicate the language of stopwords by ISO 639-1 coding scheme.
keep	A logical. Specifies whether to keep the stopwords or discard them.
stopword_source	A character to indicate the stopwords source as listed in <code>stopwords::stopwords_getsources</code> .
custom_stopword_source	A character vector to indicate a custom list of words that cater to the users specific problem.
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_stopwords</code> object.

Details

Stop words are words which sometimes are removed before natural language processing tasks. While stop words usually refers to the most common words in the language there is no universal stop word list.

The argument `custom_stopword_source` allows you to pass a character vector to filter against. With the `keep` argument one can specify to keep the words instead of removing thus allowing you to select words with a combination of these two arguments.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_ngram\(\)](#), [step_pos_filter\(\)](#), [step_stem\(\)](#), [step_tokenfilter\(\)](#), [step_tokenmerge\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

if (requireNamespace("stopwords", quietly = TRUE)) {
  okc_rec <- recipe(~ ., data = okc_text) %>%
    step_tokenize(essay0) %>%
    step_stopwords(essay0)

  okc_obj <- okc_rec %>%
    prep()

  juice(okc_obj, essay0) %>%
    slice(1:2)

  juice(okc_obj) %>%
    slice(2) %>%
    pull(essay0)

  tidy(okc_rec, number = 2)
  tidy(okc_obj, number = 2)
}

# With a custom stopwords list

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_stopwords(essay0, custom_stopword_source = c("twice", "upon"))
okc_obj <- okc_rec %>%
  prep(traimomg = okc_text)
```



```
juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)
```

step_textfeature	<i>Generate the basic set of text features</i>
------------------	--

Description

step_textfeature creates a *specification* of a recipe step that will extract a number of numeric features of a text column.

Usage

```
step_textfeature(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  extract_functions = textfeatures::count_functions,
  prefix = "textfeature",
  skip = FALSE,
  id = rand_id("textfeature")
)

## S3 method for class 'step_textfeature'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_textfeature, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
extract_functions	A named list of feature extracting functions. default to count_functions from the textfeatures package. See details for more information.

prefix	A prefix for generated column names, default to "textfeature".
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it
x	A <code>step_textfeature</code> object.

Details

This step will take a character column and returns a number of numeric columns equal to the number of functions in the list passed to the `extract_functions` argument. The default is a list of functions from the `textfeatures` package.

All the functions passed to `extract_functions` must take a character vector as input and return a numeric vector of the same length, otherwise an error will be thrown.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

Other character to numeric steps: [step_lda\(\)](#), [step_sequence_onehot\(\)](#)

Examples

```
if (requireNamespace("textfeatures", quietly = TRUE)) {
  library(recipes)
  library(modeldata)
  data(okc_text)

  okc_rec <- recipe(~ ., data = okc_text) %>%
    step_textfeature(essay0)

  okc_obj <- okc_rec %>%
    prep()

  juice(okc_obj) %>%
    slice(1:2)

  juice(okc_obj) %>%
    pull(textfeature_essay0_n_words)

  tidy(okc_rec, number = 1)
  tidy(okc_obj, number = 1)

  # Using custom extraction functions
  nchar_round_10 <- function(x) round(nchar(x) / 10) * 10
```

```

recipe(~ ., data = okc_text) %>%
  step_textfeature(essay0,
                  extract_functions = list(nchar10 = nchar_round_10)) %>%
  prep() %>%
  juice()
}

```

step_texthash	<i>Term frequency of tokens</i>
---------------	---------------------------------

Description

`step_texthash` creates a *specification* of a recipe step that will convert a [tokenlist](#) into multiple variables using the hashing trick.

Usage

```

step_texthash(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  signed = TRUE,
  num_terms = 1024,
  prefix = "hash",
  skip = FALSE,
  id = rand_id("texthash")
)

## S3 method for class 'step_texthash'
tidy(x, ...)

```

Arguments

<code>recipe</code>	A recipe object. The step will be added to the sequence of operations for this recipe.
<code>...</code>	One or more selector functions to choose variables. For <code>step_texthash</code> , this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the <code>tidy</code> method, these are not currently used.
<code>role</code>	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
<code>trained</code>	A logical to indicate if the recipe has been baked.
<code>columns</code>	A list of tibble results that define the encoding. This is <code>NULL</code> until the step is trained by recipes::prep.recipe() .

signed	A logical, indicating whether to use a signed hash-function to reduce collisions when hashing. Defaults to TRUE.
num_terms	An integer, the number of variables to output. Defaults to 1024.
prefix	A character string that will be the prefix to the resulting new variables. See notes below.
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_texthash</code> object.

Details

Feature hashing, or the hashing trick, is a transformation of a text variable into a new set of numerical variables. This is done by applying a hashing function over the tokens and using the hash values as feature indices. This allows for a low memory representation of the text. This implementation is done using the MurmurHash3 method.

The argument `num_terms` controls the number of indices that the hashing function will map to. This is the tuning parameter for this transformation. Since the hashing function can map two different tokens to the same index, will a higher value of `num_terms` result in a lower chance of collision.

The new components will have names that begin with `prefix`, then the name of the variable, followed by the tokens all separated by `-`. The variable names are padded with zeros. For example, if `num_terms < 10`, their names will be `hash1 - hash9`. If `num_terms = 101`, their names will be `hash001 - hash101`.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

References

Kilian Weinberger; Anirban Dasgupta; John Langford; Alex Smola; Josh Attenberg (2009).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to numeric steps: [step_tfidf\(\)](#), [step_tf\(\)](#), [step_word_embeddings\(\)](#)

Examples

```
if (requireNamespace("text2vec", quietly = TRUE)) {
  library(recipes)
  library(modeldata)
  data(okc_text)

  okc_rec <- recipe(~ ., data = okc_text) %>%
```

```

step_tokenize(essay0) %>%
step_tokenfilter(essay0, max_tokens = 10) %>%
step_texthash(essay0)

okc_obj <- okc_rec %>%
  prep()

bake(okc_obj, okc_text)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
}

```

step_text_normalization

*text_normalization*ming of *tokenlist* variables

Description

step_text_normalization creates a *specification* of a recipe step that will perform Unicode Normalization

Usage

```

step_text_normalization(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  normalization_form = "nfc",
  skip = FALSE,
  id = rand_id("text_normalization")
)

## S3 method for class 'step_text_normalization'
tidy(x, ...)

```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose which variables will be transformed. See recipes::selections() for more details. For the tidy method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.

columns	A list of tibble results that define the encoding. This is NULL until the step is trained by <code>recipes::prep.recipe()</code> .
normalization_form	A single character string determining the Unicode Normalization. Must be one of "nfc", "nfd", "nfkd", "nfkc", or "nfkc_casefold". Defaults to "nfc". See <code>stringi::stri_trans_nfc()</code> for more details.
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_text_normalization</code> object.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_texthash\(\)](#) for feature hashing.

Examples

```
if (requireNamespace("stringi", quietly = TRUE)) {
  library(recipes)

  sample_data <- tibble(text = c("sch\u00f6n", "scho\u0308n"))

  okc_rec <- recipe(~ ., data = sample_data) %>%
    step_text_normalization(text)

  okc_obj <- okc_rec %>%
    prep()

  juice(okc_obj, text) %>%
    slice(1:2)

  juice(okc_obj) %>%
    slice(2) %>%
    pull(text)

  tidy(okc_rec, number = 1)
  tidy(okc_obj, number = 1)
}
```

step_tf	<i>Term frequency of tokens</i>
---------	---------------------------------

Description

step_tf creates a *specification* of a recipe step that will convert a [tokenlist](#) into multiple variables containing the token counts.

Usage

```
step_tf(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  weight_scheme = "raw count",
  weight = 0.5,
  vocabulary = NULL,
  res = NULL,
  prefix = "tf",
  skip = FALSE,
  id = rand_id("tf")
)

## S3 method for class 'step_tf'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_tf, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
weight_scheme	A character determining the weighting scheme for the term frequency calculations. Must be one of "binary", "raw count", "term frequency", "log normalization" or "double normalization". Defaults to "raw count".

weight	A numeric weight used if <code>weight_scheme</code> is set to "double normalization". Defaults to 0.5.
vocabulary	A character vector of strings to be considered.
res	The words that will be used to calculate the term frequency will be stored here once this preprocessing step has been trained by <code>prep.recipe()</code> .
prefix	A character string that will be the prefix to the resulting new variables. See notes below
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_tf</code> object.

Details

It is strongly advised to use `step_tokenfilter` before using `step_tf` to limit the number of variables created, otherwise you might run into memory issues. A good strategy is to start with a low token count and go up according to how much RAM you want to use.

Term frequency is a weight of how many times each token appear in each observation. There are different ways to calculate the weight and this step can do it in a couple of ways. Setting the argument `weight_scheme` to "binary" will result in a set of binary variables denoting if a token is present in the observation. "raw count" will count the times a token is present in the observation. "term frequency" will divide the count with the total number of words in the document to limit the effect of the document length as longer documents tends to have the word present more times but not necessarily at a higher percentage. "log normalization" takes the log of 1 plus the count, adding 1 is done to avoid taking log of 0. Finally "double normalization" is the raw frequency divided by the raw frequency of the most occurring term in the document. This is then multiplied by `weight` and `weight` is added to the result. This is again done to prevent a bias towards longer documents.

The new components will have names that begin with `prefix`, then the name of the variable, followed by the tokens all separated by `-`. The new variables will be created alphabetically according to token.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

`step_tokenize()` to turn character into tokenlist.

Other tokenlist to numeric steps: `step_textrhash()`, `step_tfidf()`, `step_word_embeddings()`

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_tf(essay0)

okc_obj <- okc_rec %>%
  prep()

bake(okc_obj, okc_text)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
```

step_tfidf

Term frequency-inverse document frequency of tokens

Description

step_tfidf creates a *specification* of a recipe step that will convert a [tokenlist](#) into multiple variables containing the term frequency-inverse document frequency of tokens.

Usage

```
step_tfidf(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  vocabulary = NULL,
  res = NULL,
  smooth_idf = TRUE,
  norm = "l1",
  sublinear_tf = FALSE,
  prefix = "tfidf",
  skip = FALSE,
  id = rand_id("tfidf")
)

## S3 method for class 'step_tfidf'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_tfidf</code> , this indicates the variables to be encoded into a <code>tokenlist</code> . See <code>recipes::selections()</code> for more details. For the <code>tidy</code> method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by <code>recipes::prep.recipe()</code> .
vocabulary	A character vector of strings to be considered.
res	The words that will be used to calculate the term frequency will be stored here once this preprocessing step has been trained by <code>prep.recipe()</code> .
smooth_idf	TRUE smooth IDF weights by adding one to document frequencies, as if an extra document was seen containing every term in the collection exactly once. This prevents division by zero.
norm	A character, defines the type of normalization to apply to term vectors. "l1" by default, i.e., scale by the number of words in the document. Must be one of c("l1", "l2", "none").
sublinear_tf	A logical, apply sublinear term-frequency scaling, i.e., replace the term frequency with $1 + \log(\text{TF})$. Defaults to FALSE.
prefix	A character string that will be the prefix to the resulting new variables. See notes below.
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_tfidf</code> object.

Details

It is strongly advised to use `step_tokenfilter` before using `step_tfidf` to limit the number of variables created; otherwise you may run into memory issues. A good strategy is to start with a low token count and increase depending on how much RAM you want to use.

Term frequency-inverse document frequency is the product of two statistics: the term frequency (TF) and the inverse document frequency (IDF).

Term frequency measures how many times each token appears in each observation.

Inverse document frequency is a measure of how informative a word is, e.g., how common or rare the word is across all the observations. If a word appears in all the observations it might not give that much insight, but if it only appears in some it might help differentiate between observations.

The IDF is defined as follows: $\text{idf} = \log(1 + (\# \text{ documents in the corpus}) / (\# \text{ documents where the term appears}))$

The new components will have names that begin with `prefix`, then the name of the variable, followed by the tokens all separated by `-`. The new variables will be created alphabetically according to token.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to numeric steps: [step_texthash\(\)](#), [step_tf\(\)](#), [step_word_embeddings\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_tfidf(essay0)

okc_obj <- okc_rec %>%
  prep()

bake(okc_obj, okc_text)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
```

step_tokenfilter

Filter the tokens based on term frequency

Description

`step_tokenfilter` creates a *specification* of a recipe step that will convert a [tokenlist](#) to be filtered based on frequency.

Usage

```
step_tokenfilter(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  max_times = Inf,
  min_times = 0,
  percentage = FALSE,
  max_tokens = 100,
  res = NULL,
  skip = FALSE,
  id = rand_id("tokenfilter")
)

## S3 method for class 'step_tokenfilter'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_tokenfilter</code> , this indicates the variables to be encoded into a <code>tokenlist</code> . See <code>recipes::selections()</code> for more details. For the <code>tidy</code> method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is <code>NULL</code> until the step is trained by <code>recipes::prep.recipe()</code> .
max_times	An integer. Maximal number of times a word can appear before getting removed.
min_times	An integer. Minimum number of times a word can appear before getting removed.
percentage	A logical. Should <code>max_times</code> and <code>min_times</code> be interpreted as a percentage instead of count.
max_tokens	An integer. Will only keep the top <code>max_tokens</code> tokens after filtering done by <code>max_times</code> and <code>min_times</code> . Defaults to 100.
res	The words that will be keep will be stored here once this preprocessing step has been trained by <code>prep.recipe()</code> .
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.

id	A character string that is unique to this step to identify it.
x	A step_tokenfilter object.

Details

This step allow you to limit the tokens you are looking at by filtering on their occurrence in the corpus. You are able to exclude tokens if they appear too many times or too fews times in the data. It can be specified as counts using `max_times` and `min_times` or as percentages by setting `percentage` as `TRUE`. In addition one can filter to only use the top `max_tokens` used tokens. If `max_tokens` is set to `Inf` then all the tokens will be used. This will generally lead to very large datasets when then tokens are words or trigrams. A good strategy is to start with a low token count and go up according to how much RAM you want to use.

It is strongly advised to filter before using [step_tf](#) or [step_tfidf](#) to limit the number of variables created.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_ngram\(\)](#), [step_pos_filter\(\)](#), [step_stem\(\)](#), [step_stopwords\(\)](#), [step_tokenmerge\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_tokenfilter(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
```

step_tokenize	<i>Tokenization of character variables</i>
---------------	--

Description

`step_tokenize()` creates a *specification* of a recipe step that will convert a character predictor into a [tokenlist](#).

Usage

```
step_tokenize(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  options = list(),
  token = "words",
  engine = "tokenizers",
  custom_token = NULL,
  skip = FALSE,
  id = rand_id("tokenize")
)

## S3 method for class 'step_tokenize'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_tokenize()</code> , this indicates the variables to be encoded into a tokenlist . See <code>recipes::selections()</code> for more details. For the <code>tidy</code> method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by <code>recipes::prep.recipe()</code> .
options	A list of options passed to the tokenizer.
token	Unit for tokenizing. See details for options. Defaults to "words".
engine	Package that will be used for tokenization. See details for options. Defaults to "tokenizers".
custom_token	User supplied tokenizer. Use of this argument will overwrite the token and engine arguments. Must take a character vector as input and output a list of character vectors.

skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it
x	A <code>step_tokenize</code> object.

Details

Tokenization is the act of splitting a character string into smaller parts to be further analysed. This step uses the `tokenizers` package which includes heuristics to split the text into paragraphs tokens, word tokens among others. `textrecipes` keeps the tokens in a `tokenlist` and other steps will do their tasks on those `tokenlists` before transforming them back to numeric.

The choice of engine determines the possible choices of token.

If `engine = "tokenizers"`:

- "words" (default)
- "characters"
- "character_shingles"
- "ngrams"
- "skip_ngrams"
- "sentences"
- "lines"
- "paragraphs"
- "regex"
- "tweets"
- "ptb" (Penn Treebank)
- "skip_ngrams"
- "word_stems"

if `engine = "spacyr"`

- "words"

Working with `textrecipes` will almost always start by calling `step_tokenize` followed by modifying and filtering steps. This is not always the case as you sometimes want to do apply pre-tokenization steps, this can be done with `recipes::step_mutate()`.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

`step_untokenize()` to untokenize.

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)

tidy(okc_rec, number = 1)
tidy(okc_obj, number = 1)

okc_obj_chars <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0, token = "characters") %>%
  prep()

juice(okc_obj_chars) %>%
  slice(2) %>%
  pull(essay0)
```

step_tokenmerge

Generate the basic set of text features

Description

step_tokenmerge creates a *specification* of a recipe step that will take multiple [tokenlists](#) and combine them into one [tokenlist](#).

Usage

```
step_tokenmerge(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  prefix = "tokenmerge",
  skip = FALSE,
  id = rand_id("tokenmerge")
)
```



```
## S3 method for class 'step_tokenmerge'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For <code>step_tokenmerge</code> , this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the <code>tidy</code> method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
prefix	A prefix for generated column names, default to "tokenmerge".
skip	A logical. Should the step be skipped when the recipe is baked by recipes::bake.recipe() ? While all operations are baked when recipes::prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it
x	A <code>step_tokenmerge</code> object.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to tokenlist steps: [step_lemma\(\)](#), [step_ngram\(\)](#), [step_pos_filter\(\)](#), [step_stem\(\)](#), [step_stopwords\(\)](#), [step_tokenfilter\(\)](#)

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0, essay1) %>%
  step_tokenmerge(essay0, essay1)

okc_obj <- okc_rec %>%
```

```

  prep()

  juice(okc_obj)

  tidy(okc_rec, number = 1)
  tidy(okc_obj, number = 1)

```

step_untokenize

Untokenization of [tokenlist](#) variables

Description

step_untokenize creates a *specification* of a recipe step that will convert a [tokenlist](#) into a character predictor.

Usage

```

step_untokenize(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  columns = NULL,
  sep = " ",
  skip = FALSE,
  id = rand_id("untokenize")
)

## S3 method for class 'step_untokenize'
tidy(x, ...)

```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_untokenize, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
sep	a character to determine how the tokens should be separated when pasted together. Defaults to " ".

skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_untokenize</code> object.

Details

This steps will turn a [tokenlist](#) back into a character vector. This step is calling `paste` internally to put the tokens back together to a character.

Value

An updated version of recipe with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Examples

```
library(recipes)
library(modeldata)
data(okc_text)

okc_rec <- recipe(~ ., data = okc_text) %>%
  step_tokenize(essay0) %>%
  step_untokenize(essay0)

okc_obj <- okc_rec %>%
  prep()

juice(okc_obj, essay0) %>%
  slice(1:2)

juice(okc_obj) %>%
  slice(2) %>%
  pull(essay0)

tidy(okc_rec, number = 2)
tidy(okc_obj, number = 2)
```

step_word_embeddings *Pretrained word embeddings of tokens*

Description

step_word_embeddings creates a *specification* of a recipe step that will convert a [tokenlist](#) into word-embedding dimensions by aggregating the vectors of each token from a pre-trained embedding.

Usage

```
step_word_embeddings(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  embeddings,
  aggregation = c("sum", "mean", "min", "max"),
  aggregation_default = 0,
  prefix = "w_embed",
  skip = FALSE,
  id = rand_id("word_embeddings")
)

## S3 method for class 'step_word_embeddings'
tidy(x, ...)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose variables. For step_word_embeddings, this indicates the variables to be encoded into a tokenlist . See recipes::selections() for more details. For the tidy method, these are not currently used.
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the recipe has been baked.
columns	A list of tibble results that define the encoding. This is NULL until the step is trained by recipes::prep.recipe() .
embeddings	A tibble of pre-trained word embeddings, such as those returned by the embedding_glove function from the textdata package. The first column should contain tokens, and additional columns should contain embeddings vectors.
aggregation	A character giving the name of the aggregation function to use. Must be one of "sum", "mean", "min", and "max". Defaults to "sum".

aggregation_default	A numeric denoting the default value for case with no words are matched in embedding. Defaults to 0.
prefix	A character string that will be the prefix to the resulting new variables. See notes below.
skip	A logical. Should the step be skipped when the recipe is baked by <code>recipes::bake.recipe()</code> ? While all operations are baked when <code>recipes::prep.recipe()</code> is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using <code>skip = TRUE</code> as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.
x	A <code>step_word_embeddings</code> object.

Details

Word embeddings map words (or other tokens) into a high-dimensional feature space. This function maps pre-trained word embeddings onto the tokens in your data.

The argument `embeddings` provides the pre-trained vectors. Each dimension present in this tibble becomes a new feature column, with each column aggregated across each row of your text using the function supplied in the `aggregation` argument.

The new components will have names that begin with `prefix`, then the name of the aggregation function, then the name of the variable from the embeddings tibble (usually something like "d7"). For example, using the default "word_embeddings" prefix, the "sum" aggregation, and the GloVe embeddings from the `textdata` package (where the column names are `d1`, `d2`, etc), new columns would be `word_embeddings_sum_d1`, `word_embeddings_sum_d2`, etc.

Value

An updated version of `recipe` with the new step added to the sequence of existing steps (if any).

See Also

[step_tokenize\(\)](#) to turn character into tokenlist.

Other tokenlist to numeric steps: [step_texthash\(\)](#), [step_tfidf\(\)](#), [step_tf\(\)](#)

Examples

```
library(recipes)

embeddings <- tibble(
  tokens = c("the", "cat", "ran"),
  d1 = c(1, 0, 0),
  d2 = c(0, 1, 0),
  d3 = c(0, 0, 1)
)

sample_data <- tibble(
  text = c(
```

```
  "The.",
  "The cat.",
  "The cat ran."
),
text_label = c("fragment", "fragment", "sentence")
)

rec <- recipe(text_label ~ ., data = sample_data) %>%
  step_tokenize(text) %>%
  step_word_embeddings(text, embeddings = embeddings)

obj <- rec %>%
  prep()

bake(obj, sample_data)

tidy(rec, number = 2)
tidy(obj, number = 2)
```

tokenlist

Create tokenlist object

Description

A [tokenlist](#) object is a thin wrapper around a list of character vectors, with a few attributes.

Usage

```
tokenlist(tokens = list(), lemma = NULL, pos = NULL)
```

Arguments

tokens	List of character vectors
lemma	List of character vectors, must be same size and shape as x.
pos	List of character vectors, must be same size and shape as x.

Value

a [tokenlist](#) object.

Examples

```
abc <- list(letters, LETTERS)
tokenlist(abc)

unclass(tokenlist(abc))

tibble(text = tokenlist(abc))
```

```
library(tokenizers)
library(modeldata)
data(okc_text)
tokens <- tokenize_words(okc_text$essay0)

tokenlist(tokens)
```

Index

- * **character to character steps**
 - step_text_normalization, 21
- * **character to numeric steps**
 - step_lda, 3
 - step_sequence_onehot, 10
 - step_textfeature, 17
- * **character to tokenlist steps**
 - step_tokenize, 30
- * **tokenlist to character steps**
 - step_untokenize, 34
- * **tokenlist to numeric steps**
 - step_texthash, 19
 - step_tf, 23
 - step_tfidf, 25
 - step_word_embeddings, 36
- * **tokenlist to tokenlist steps**
 - step_lemma, 5
 - step_ngram, 7
 - step_pos_filter, 9
 - step_stem, 12
 - step_stopwords, 14
 - step_tokenfilter, 27
 - step_tokenmerge, 32
- count_functions, 17
- prep.recipe(), 24, 26, 28
- rcpp_ngram, 2
- recipes::bake.recipe(), 4, 6, 8, 9, 11, 13, 15, 18, 20, 22, 24, 26, 28, 31, 33, 35, 37
- recipes::prep.recipe(), 3–9, 11, 13, 15, 17–20, 22–24, 26, 28, 30, 31, 33–37
- recipes::selections(), 3, 5, 7, 9, 11, 13, 15, 17, 19, 21, 23, 26, 28, 30, 33, 34, 36
- recipes::step_mutate(), 31
- step_lda, 3, 12, 18
- step_lemma, 5, 8, 10, 13, 16, 29, 33
- step_ngram, 6, 7, 10, 13, 16, 29, 33
- step_pos_filter, 6, 8, 9, 13, 16, 29, 33
- step_sequence_onehot, 4, 10, 18
- step_stem, 6, 8, 10, 12, 16, 29, 33
- step_stopwords, 6, 8, 10, 13, 14, 29, 33
- step_text_normalization, 21
- step_textfeature, 4, 12, 17
- step_texthash, 19, 24, 27, 37
- step_texthash(), 22
- step_tf, 20, 23, 24, 27, 29, 37
- step_tfidf, 20, 24, 25, 26, 29, 37
- step_tokenfilter, 6, 8, 10, 13, 16, 24, 26, 27, 33
- step_tokenize, 30
- step_tokenize(), 6, 8, 10, 13, 16, 20, 24, 27, 29, 30, 33, 35, 37
- step_tokenmerge, 6, 8, 10, 13, 16, 29, 32
- step_untokenize, 34
- step_untokenize(), 31
- step_word_embeddings, 20, 24, 27, 36
- stringi::stri_trans_nfc(), 22
- tidy.step_lda(step_lda), 3
- tidy.step_lemma(step_lemma), 5
- tidy.step_ngram(step_ngram), 7
- tidy.step_pos_filter(step_pos_filter), 9
- tidy.step_sequence_onehot(step_sequence_onehot), 10
- tidy.step_stem(step_stem), 12
- tidy.step_stopwords(step_stopwords), 14
- tidy.step_text_normalization(step_text_normalization), 21
- tidy.step_textfeature(step_textfeature), 17
- tidy.step_texthash(step_texthash), 19
- tidy.step_tf(step_tf), 23
- tidy.step_tfidf(step_tfidf), 25

tidy.step_tokenfilter
 (step_tokenfilter), 27

tidy.step_tokenize (step_tokenize), 30

tidy.step_tokenmerge (step_tokenmerge),
 32

tidy.step_untokenize (step_untokenize),
 34

tidy.step_word_embeddings
 (step_word_embeddings), 36

tokenlist, 3, 5, 7, 9, 11–15, 17, 19, 21, 23,
 25–28, 30–36, 38, 38