

Package ‘translate’

February 20, 2015

Type Package

Title Bindings for the Google Translate API v2

Description Bindings for the Google Translate API v2

Version 0.1.2

Date 2014-07-10

Author Peter Danenberg <pcd@roxygen.org>

Maintainer Peter Danenberg <pcd@roxygen.org>

License GPL

Imports RCurl, RJSONIO, functional, lisp

NeedsCompilation no

Repository CRAN

Date/Publication 2014-07-16 01:14:43

R topics documented:

translate-package	2
detect.source	2
get.key	3
google.url	3
languages	4
set.key	4
translate	5
Index	6

translate-package *translate*

Description

Bindings for the Google Translate API v2

Examples

```
## Not run:  
set.key('YOUR-API-KEY')  
translate('Hello, world!', 'en', 'de')  
  
## End(Not run)
```

detect.source *Detect the source of a text.*

Description

Detect the source of a text.

Usage

```
detect.source(query, key = get.key())
```

Arguments

query	The text to invoke against
key	The API key

Value

A list of potential source languages

get.key	<i>Pull the API key from getOption('google.key') or the GOOGLE_KEY environment variable.</i>
---------	--

Description

Pull the API key from getOption('google.key') or the GOOGLE_KEY environment variable.

Usage

```
get.key()
```

Value

The API key

google.url	<i>Generate an API URL.</i>
------------	-----------------------------

Description

Generate an API URL.

Usage

```
google.url(method = NULL, query = NULL, source = NULL, target = NULL,  
key = get.key())
```

Arguments

method	One of "translate" (default), "detect", "languages"
query	The text to invoke against
source	The source language, e.g. "en"
target	The target language, e.g. "de"
key	The API key

Value

An API URL

<code>languages</code>	<i>List the valid language mappings; optionally, from a given source or to a given target.</i>
------------------------	--

Description

List the valid language mappings; optionally, from a given source or to a given target.

Usage

```
languages(source = NULL, target = NULL, key = get.key())
```

Arguments

<code>key</code>	The API key
<code>source</code>	The source language, e.g. "en"
<code>target</code>	The target language, e.g. "de"

<code>set.key</code>	<i>Set the API key in options.</i>
----------------------	------------------------------------

Description

Set the API key in options.

Usage

```
set.key(key)
```

Arguments

<code>key</code>	The API key
------------------	-------------

translate*Translate the given text from a source to a target language.*

Description

Translate the given text from a source to a target language.

Usage

```
translate(query, source, target, key = get.key())
```

Arguments

query	The text to invoke against
source	The source language, e.g. "en"
target	The target language, e.g. "de"
key	The API key

Index

`detect.source`, 2

`get.key`, 3

`google.url`, 3

`languages`, 4

`set.key`, 4

`translate`, 5

`translate-package`, 2