

# Package ‘ttwa’

February 20, 2015

**Type** Package

**Title** Travel To Work Area.

**Version** 0.8.5.1

**Date** 2013-08-09

**Author** Francois Semecurbe, Joachim Timoteo

**Maintainer** Francois Semecurbe <francoissemecurbe@gmail.com>

**Description** This package makes Travel To Work Area from a commuting flow data frame.

**License** GPL (>= 2.0)

**LazyLoad** yes

**Depends** data.table

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2013-09-08 15:35:03

## R topics documented:

|                        |   |
|------------------------|---|
| ttwa-package . . . . . | 1 |
| reunion_ttw . . . . .  | 2 |
| ttwa . . . . .         | 3 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>6</b> |
|--------------|----------|

---

|              |                             |
|--------------|-----------------------------|
| ttwa-package | <i>Travel To Work Area.</i> |
|--------------|-----------------------------|

---

## Description

This package makes Travel To Work Area from a commuting flow data frame.

## Details

Package: ttw  
Type: Package  
Version: 0.8.5.1  
Date: 2013-08-12  
License: GPL (>=2.0)

### Author(s)

Francois Semecurbe and Joachim Timoteo. <francoissemecurbe@gmail.com> and <joachim.timoteo@gmail.com>

### References

Christophe Terrier web site is a reference to the method Anabel-Mirabel: [www.christophe-terrier.com](http://www.christophe-terrier.com)

### See Also

[ttwa, reunion\\_ttw](#)

### Examples

```
data(reunion_ttw) #commuting flow in Reunion island
zone_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK", flow="FLOW",
  conti="CONTI",size_center=50000)
zone_emploi$statistic #Zoning quality
# 4 centers : Saint-Denis, Saint-Paul, Saint-Pierre and Saint-Benoit
center_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK",flow="FLOW",
  conti="CONTI",size_center=500000,
  list_center=c("97411","97415","97416","97410"))
center_emploi$statistic
```

---

reunion\_ttw

*Census data on travel to work flow between Reunion Island municipalities.*

---

### Description

A flow data frame travel to work between Reunion island municipalities from census (2010).

### Usage

```
data(reunion_ttw)
```

**Format**

A data frame with 5732 observations on the following 4 variables.

HOME a character vector, INSEE Ids of the municipalities of the resident population

WORK a character vector, INSEE Ids of the municipalities of work

FLOW a numeric vector, working flow between the municipality of residence and the municipality of work

CONTI a numeric vector, indicator function of the contiguity between the municipality of residence and the municipality of work

**Source**

Mobilites professionnelles (deplacements domicile - lieu de travail) - 2010 (Bases flux de mobilite)

Decoupage geographique au 01/01/2012 - Mise a jour : juin 2013

Insee, Recensements de la population

Original data can be retrieved here : <http://www.insee.fr/fr/bases-de-donnees/default.asp?page=recensement/resultats/doc/pre-flux-mobilite-prof.htm>

**See Also**

[ttwa](#)

**Examples**

```
data(reunion_ttw) #commuting flow in Reunion island
zone_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK", flow="FLOW",
  conti="CONTI",size_center=50000)
zone_emploi$statistic #Zoning quality
# 4 centers : Saint-Denis, Saint-Paul, Saint-Pierre and Saint-Benoit
center_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK",flow="FLOW",
  conti="CONTI",size_center=50000,
  list_center=c("97411","97415","97416","97410"))
center_emploi$statistic
```

---

 ttwa

*Zoning Commuting flow*


---

**Description**

This function computes the commuting areas from a flow data. It is especially effective for calculating the travel to work area (TTWA). TTWA are defined to reflect areas where the bulk of the resident population also works within the same area. TTWA defines local labour market area. The ttwa function uses a greedy algorithm. Progressively, areas aggregate themselves with their link when above a threshold. The ttwa is an adaptation of the algorithm used by the INSEE zoning, Anabel.

**Usage**

```
ttwa(df, origin, destination, flow, conti = NULL,
      minimum_link = 0.00001, size_center, list_center = NULL)
```

**Arguments**

|                           |  |
|---------------------------|--|
| <code>df</code>           | data frame that contains the flow information  |
| <code>origin</code>       | name of the variable that contained the identifier of the origin area  |
| <code>destination</code>  | name of the variable that contained the identifier of the destination area   |
| <code>flow</code>         | name of the qualitative variable that contains the flow  |
| <code>conti</code>        | default NULL, name of the boolean variable that contains the contiguity between origin and destination area  |
| <code>minimum_link</code> | minimum link aggregation allows between area   |
| <code>size_center</code>  | size of area who can't be aggregated to an other area. <code>enter_size</code> determines the minimum size of commuting area.                                  |
| <code>list_center</code>  | list of identifiers of non-aggregatable territories to other centers but they can attract other territories and become centers or otherwise isolated clusters. |

**Details**

The ttwa is an adaptation of the algorithm used by the INSEE zoning, Anabel. For each iteration, we search for the strongest link between the two areas which meet the parameters of aggregation (contiguity and center size). Then, it is aggregated to the lines of the data.frame associated with the two areas. Thus, the area's name formed is the name of the destination area of the stream. It repeats the process until we can find areas with a sufficient nexus. The link between area  $i$  to  $j$  is defined as  $\text{flow}_{ij} / \text{total\_outflow}_i$ . The constraint of contiguity provides a related zoning. It may be appropriated to add zeros to the flow variable between contiguous areas without flow to allow the construction of aggregation areas. Quality zoning is measured by the rate of steady flow in commuting area.

**Value**

An object of class "zoning" is a list containing at least the following components:

|                        |   |
|------------------------|---|
| <code>zoning</code>    | data frame contains the initial area and their commuting area of attachment   |
| <code>log</code>       | data frame containing the log of the greedy processus   |
| <code>data</code>      | data frame containing the aggregated flow between commuting area  |
| <code>statistic</code> | data frame containing the statistics area by zone (the total outflow, rate stable at origin, number of primary territories) |

**Author(s)**

The Anabel-Mirabel algorithm has been developed by Christophe Terrier, french statistician. The implementation of the algorithm by Francois Semecurbe and Joachim Timoteo. <francoisseme-curbe@gmail.com> and <joachim.timoteo@gmail.com>

## References

Christophe Terrier web site is a reference to the method Anabel-Mirabel: [www.christophe-terrier.com](http://www.christophe-terrier.com)

## See Also

[reunion\\_ttw](#)

## Examples

```
data(reunion_ttw) #commuting flow in Reunion island
zone_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK", flow="FLOW",
  conti="CONTI",size_center=50000)
zone_emploi$statistic #Zoning quality
# 4 centers : Saint-Denis, Saint-Paul, Saint-Pierre and Saint-Benoit
center_emploi<-ttwa(df=reunion_ttw,origin="HOME",
  destination="WORK",flow="FLOW",
  conti="CONTI",size_center=500000,
  list_center=c("97411","97415","97416","97410"))
center_emploi$statistic
```

# Index

\*Topic **datasets**

reunion\_ttw, 2

\*Topic **package**

ttwa-package, 1

\*Topic **ttwa**

ttwa, 3

reunion\_ttw, 2, 2, 5

ttwa, 2, 3, 3

ttwa-package, 1