

Package ‘yamlthis’

February 4, 2020

Title Write 'YAML' for 'R Markdown', 'bookdown', 'blogdown', and More

Version 0.1.2

Description Write 'YAML' front matter for R Markdown and related documents. `yaml_*`() functions write 'YAML' and `use_*`() functions let you write the resulting 'YAML' to your clipboard or to `.yaml` files related to your project.

License MIT + file LICENSE

URL <https://yamlthis.r-lib.org>, <https://github.com/r-lib/yamlthis>

BugReports <https://github.com/r-lib/yamlthis/issues>

Depends R (>= 3.2)

Imports crayon, fs, glue, magrittr, miniUI, purrr (>= 0.3.2), rlang (>= 0.4.0), rmarkdown, rstudioapi, shiny, shinyBS, stringr, usethis (>= 1.5.0), whoami, withr, yaml

Suggests blogdown, bookdown, covr, knitr, pkgdown, prettydoc, roxygen2 (>= 7.0.0), spelling, testthat, xaringan

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.0.2

NeedsCompilation no

Author Malcolm Barrett [aut, cre] (<<https://orcid.org/0000-0003-0299-5825>>),
Richard Iannone [aut] (<<https://orcid.org/0000-0003-3925-190X>>),
RStudio [cph, fnd]

Maintainer Malcolm Barrett <malcolmbarrett@gmail.com>

Repository CRAN

Date/Publication 2020-02-03 23:00:02 UTC

R topics documented:

| | |
|---|----|
| asis_yaml_output | 3 |
| as_yaml | 3 |
| bib2yaml | 4 |
| blogdown_template | 5 |
| code_chunk | 5 |
| draw_yaml_tree | 6 |
| gitbook_config | 7 |
| has_field | 9 |
| includes2 | 10 |
| is_yaml | 10 |
| last_yaml | 11 |
| pagedown_business_card_template | 11 |
| pandoc_template_types | 14 |
| pkgdown_template | 15 |
| read_json | 15 |
| use_yaml | 17 |
| use_yaml_defaults | 18 |
| use_yaml_file | 19 |
| yaml | 21 |
| yaml_author | 22 |
| yaml_blank | 24 |
| yaml_blogdown_opts | 25 |
| yaml_bookdown_opts | 28 |
| yaml_citations | 30 |
| yaml_clean | 32 |
| yaml_code | 33 |
| yaml_distill_opts | 34 |
| yaml_handlers | 37 |
| yaml_latex_opts | 38 |
| yaml_load | 41 |
| yaml_output | 41 |
| yaml_pagedown_opts | 42 |
| yaml_params | 44 |
| yaml_pkgdown | 48 |
| yaml_reference | 52 |
| yaml_replace | 54 |
| yaml_resource_files | 56 |
| yaml_rsconnect_email | 56 |
| yaml_rtticles_opts | 58 |
| yaml_runtime | 60 |
| yaml_site_opts | 61 |
| yaml_toc | 63 |
| yaml_verbatim | 64 |
| yaml_vignette | 65 |

| | |
|------------------|---|
| asis_yaml_output | <i>Export yml object as a YAML knitr code chunk</i> |
|------------------|---|

Description

asis_yaml_output() exports a yml object as a YAML knitr code chunk instead of as an R object. Doing so adds code highlighting for YAML syntax.

Usage

```
asis_yaml_output(.yaml, fences = TRUE)
```

Arguments

| | |
|--------|---|
| .yaml | a yml object created by yml(), as_yaml(), or returned by a yml_*(()) function |
| fences | Logical. Write fences ("—") before and after YAML? |

See Also

Other yml: [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

| | |
|---------|------------------------------|
| as_yaml | <i>Convert to yml object</i> |
|---------|------------------------------|

Description

as_yaml is a wrapper for [yaml::yaml.load\(\)](#) that stores YAML as a yml object, which prints cleanly to the console and is easy to work with using ymlthis functions.

Usage

```
as_yaml(x)
```

Arguments

| | |
|---|--|
| x | An object, either a character vector of length 1 or list, to convert to yml. |
|---|--|

Value

a yml object

Examples

```
x <- as_yaml("
  author: Hadley Wickham
  date: '2014-09-12'
  title: Tidy Data
  keywords:
  - data cleaning
  - data tidying
  - relational databases
  - R")

x

x %>%
  yaml_subtitle("Hadley's Tidy Data Paper")
```

bib2yaml

Convert bib files to YAML

Description

`bib2yaml()` uses pandoc to convert a `.bib` file to YAML. It also accepts an optional `yaml` object to prepend to the the YAML from the `.bib` file. If you want to cite several R packages, see [knitr::write_bib\(\)](#) to write a bibliography file and convert it with `bib2yaml()`.

Usage

```
bib2yaml(.yaml = NULL, path)
```

Arguments

| | |
|--------------------|---|
| <code>.yaml</code> | a <code>yaml</code> object created by <code>yaml()</code> , <code>as_yaml()</code> , or returned by a <code>yaml_*</code> () function |
| <code>path</code> | a path to the <code>.bib</code> file |

Value

a `yaml` object

See Also

Other `yaml`: [asis_yaml_output\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other citations: [yaml_citations\(\)](#), [yaml_reference\(\)](#)

| | |
|-------------------|---|
| blogdown_template | <i>Create YAML based on blogdown theme archetypes</i> |
|-------------------|---|

Description

blogdown_template() creates YAML based on your blogdown theme archetypes. blogdown is based on Hugo, which supports many custom themes. Each theme uses YAML in a different way. However, many come with archetypes that define the YAML or TOML. To find out which types your theme has, use blogdown_archetypes() to see what's available. Use blogdown_template() to specify the archetype and it will convert the template to YAML that you can use in your post.

Usage

```
blogdown_template(type, path = ".", theme = NULL)
```

```
blogdown_archetypes(path = ".", theme = NULL)
```

Arguments

| | |
|-------|---|
| type | an archetype |
| path | the path to your blogdown site |
| theme | the theme to check for archetypes. By default, blogdown_template() will attempt to read your theme from your config file. |

Value

a yml object

| | |
|------------|---|
| code_chunk | <i>Write code chunks programmatically</i> |
|------------|---|

Description

code_chunk() assembles a knitr code chunk as a character vector. setup_chunk() is a wrapper around code_chunk() to create setup chunks. By default it uses include = FALSE and inserts knitr::opts_chunk\$set(echo = TRUE) into the chunk body. These are helper functions to write R Markdown bodies for [use_rmarkdown\(\)](#).

Usage

```
code_chunk(chunk_code, chunk_name = NULL, chunk_args = NULL)
```

```
setup_chunk(chunk_code = NULL, chunk_args = list(include = FALSE))
```

Arguments

| | |
|------------|--|
| chunk_code | An expression. Surround with {} to capture multiple lines. |
| chunk_name | The name of the chunk |
| chunk_args | A list of chunk options |

Value

a character vector

Examples

```
setup_chunk()

code_chunk({
  yml() %>%
    yml_output(pdf_document())
}, chunk_name = "yml_example")
```

| | |
|---------------|---------------------------------------|
| draw_yml_tree | <i>Draw an tree of YAML hierarchy</i> |
|---------------|---------------------------------------|

Description

draw_yml_tree() draws an ASCII tree of the hierarchy of a given yml object to the console.

Usage

```
draw_yml_tree(.yaml = last_yaml(), indent = "")
```

Arguments

| | |
|--------|--|
| .yaml | a yml object created by yml(), as_yaml(), or returned by a yml_*() function |
| indent | a character vector used to indent the tree |

Value

invisibly, .yaml

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Examples

```
# draw the most recently used `yaml`
draw_yaml_tree()

yaml() %>%
  yaml_output(
    pdf_document(keep_tex = TRUE),
    html_document()
  ) %>%
  draw_yaml_tree()
```

gitbook_config

Configure bookdown::gitbook() output

Description

`gitbook_config()` is a helper function to specify the config argument in `bookdown::gitbook()`, as described in the [bookdown book](#).

Usage

```
gitbook_config(
  toc_collapse = yaml_blank(),
  toc_scroll_highlight = yaml_blank(),
  toc_before = yaml_blank(),
  toc_after = yaml_blank(),
  toolbar_position = yaml_blank(),
  edit = yaml_blank(),
  download = yaml_blank(),
  search = yaml_blank(),
  fontsettings_theme = yaml_blank(),
  fontsettings_family = yaml_blank(),
  fontsettings_size = yaml_blank(),
  sharing_facebook = yaml_blank(),
  sharing_twitter = yaml_blank(),
  sharing_google = yaml_blank(),
  sharing_linkedin = yaml_blank(),
  sharing_weibo = yaml_blank(),
  sharing_instapaper = yaml_blank(),
  sharing_vk = yaml_blank(),
  sharing_all = yaml_blank(),
  ...
)
```

Arguments

| | |
|-----------------------|--|
| toc_collapse | Collapse some items initially when a page is loaded via the collapse option. Its possible values are "subsection" (the default), "section", "none", or NULL. |
| toc_scroll_highlight | Logical. Enable highlighting of TOC items as you scroll the book body? The default is TRUE. |
| toc_before, toc_after | a character vector of HTML to add more items before and after the TOC using the HTML tag . These items will be separated from the TOC using a horizontal divider. |
| toolbar_position | The toolbar position: "fixed" or "static." The default ("fixed") is that the toolbar will be fixed at the top of the page, whereas when set to "static" the toolbar will not scroll with the page. |
| edit | If not empty, an edit button will be added to the toolbar. |
| download | This option takes either a character vector or a list of character vectors with the length of each vector being 2. When it is a character vector, it should be either a vector of filenames or filename extensions. When you only provide the filename extensions, the filename is derived from the book filename of the configuration file <code>_bookdown.yml</code> |
| search | Include a search bar? |
| fontsettings_theme | The theme. "White" (the default), "Sepia", or "Night". |
| fontsettings_family | The font family. "sans" (the default) or "serif". |
| fontsettings_size | The font size. Default is 2. |
| sharing_facebook | Logical. Include Facebook share link? Default is TRUE. |
| sharing_twitter | Logical. Include Twitter share link? Default is TRUE. |
| sharing_google | Logical. Include Google share link? Default is FALSE. |
| sharing_linkedin | Logical. Include LinkedIn share link? Default is FALSE. |
| sharing_weibo | Logical. Include Weibo share link? Default is FALSE. |
| sharing_instapaper | Logical. Include Instapaper share link? Default is FALSE. |
| sharing_vk | Logical. Include VK share link? Default is FALSE. |
| sharing_all | Logical. Include all share links? Default is FALSE. |
| ... | additional named R objects, such as characters or lists, to transform into YAML |

Value

a list to use in the config argument of `bookdown::gitbook()`

See Also

Other bookdown: [yml_bookdown_opts\(\)](#)

has_field

Check if field exists in YAML

Description

`has_field()` retrieves the names of all fields (including nested fields) and checks if `field` is among them.

Usage

```
has_field(.yml, field)
```

Arguments

`.yml` a yml object created by `yml()`, `as_yml()`, or returned by a `yml_*`() function

`field` A character vector, the name of the field(s) to check for

Value

logical

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Examples

```
has_field(yml(), "author")
has_field(yml(), "toc")
```

| | |
|-----------|--------------------------------------|
| includes2 | <i>Include content within output</i> |
|-----------|--------------------------------------|

Description

includes2() is a version of the includes() helper function from rmarkdown that uses yml_blank() instead of NULL as the argument defaults, as ymlthis treats NULLs as literal YAML syntax ("null").

Usage

```
includes2(
  in_header = yml_blank(),
  before_body = yml_blank(),
  after_body = yml_blank()
)
```

Arguments

| | |
|-------------|--|
| in_header | One or more files with content to be included in the header of the document. |
| before_body | One or more files with content to be included before the document body. |
| after_body | One or more files with content to be included after the document body. |

Value

a list

Examples

```
yml() %>%
  yml_output(
    pdf_document(includes = includes2(after_body = "footer.tex"))
  )
```

| | |
|---------|---------------------------------|
| is_yaml | <i>Is object a yaml object?</i> |
|---------|---------------------------------|

Description

Is object a yaml object?

Usage

```
is_yaml(x)
```

Arguments

x An object to test

Value

A logical vector

| | |
|-----------|--|
| last_yaml | <i>Return the most recently printed YAML</i> |
|-----------|--|

Description

yamlthis stores the most recently printed yaml object; you can use last_yaml() to retrieve it to modify, pass to use_*(*) functions, and so on.

Usage

```
last_yaml()
```

Examples

```
yaml() %>%
  yaml_author("Yihui Xie")

last_yaml()
```

| | |
|---------------------------------|--|
| pagedown_business_card_template | |
|---------------------------------|--|

Generate a full YAML template for your pagedown business card

Description

pagedown has a unique output type to make business cards: pagedown::business_card(). pagedown_business_card_template creates a YAML template to use for this output. What's unique about this output type is that almost all of the contents are supplied through YAML. An R Markdown file that only contains YAML related to the business card is enough to produce the output, although you can also customize the output in the body of the document (see the [pagedown vignette](#)). A good workflow to write a business card is to use pagedown_business_card_template() to specify the YAML and pass it to [use_rmarkdown\(\)](#), which you can then to knit into business cards.

Usage

```

pagedown_business_card_template(
  name = yml_blank(),
  person = yml_blank(),
  title = yml_blank(),
  phone = yml_blank(),
  email = yml_blank(),
  url = yml_blank(),
  address = yml_blank(),
  logo = yml_blank(),
  .repeat = yml_blank(),
  paperwidth = yml_blank(),
  paperheight = yml_blank(),
  cardwidth = yml_blank(),
  cardheight = yml_blank(),
  cols = yml_blank(),
  rows = yml_blank(),
  mainfont = yml_blank(),
  googlefonts = yml_blank(),
  ...
)

pagedown_person(...)

```

Arguments

| | |
|-------------|---|
| name | The name |
| person | When you are creating business cards for numerous people with shared information, passing values to the person field can override the default values, which can be any of the values accepted by this function. Use <code>pagedown_person()</code> to do so or manually provide them using <code>list(field = value)</code> . |
| title | The title of the person |
| phone | A phone number |
| email | An email address |
| url | A website URL |
| address | The address |
| logo | A path to a logo file |
| .repeat | The number of cards to repeat. Note that the actual YAML field is <code>repeat</code> . |
| paperwidth | The paper width |
| paperheight | The paper height |
| cardwidth | The width of the card |
| cardheight | The height of the card |
| cols | The number of columns in the card grid |
| rows | The rows of columns in the card grid |

| | |
|-------------|---|
| mainfont | The font |
| googlefonts | A character vector of Google Fonts |
| ... | additional named R objects, such as characters or lists, to transform into YAML |

Value

a yml object

See Also

[use_rmarkdown\(\)](#)

Other pagedown: [yaml_pagedown_opts\(\)](#)

Examples

```
pagedown_business_card_template(  
  name = "Jane Doe",  
  title = "Miss Nobody",  
  phone = "+1 123-456-7890",  
  email = "jane.doe@example.com",  
  url = "www.example.com",  
  address = "2020 South Street,  
  Sunshine, CA 90000",  
  logo = "logo.png",  
  .repeat = 12  
)  
  
pagedown_business_card_template(  
  phone = "+1 123-456-7890",  
  url = "www.example.com",  
  address = "2020 South Street,  
  Sunshine, CA 90000",  
  logo = "logo.png",  
  person = list(  
    pagedown_person(  
      name = "Jane Doe",  
      title = "Miss Nobody",  
      email = "jane.doe@example.com",  
      .repeat = 6  
    ),  
    pagedown_person(  
      name = "John Doe",  
      title = "Mister Nobody",  
      phone = "+1 777-777-7777", # overrides the default phone  
      email = "john.doe@example.com",  
      .repeat = 6  
    )  
  ),  
  paperwidth = "8.5in",  
  paperheight = "11in",  
  cols = 4,  
)
```

```
  rows = 3
)
```

pandoc_template_types *Use pandoc templates and custom highlight themes*

Description

Pandoc has several built in templates and code highlighting themes that can be customized and included in the `template` and `highlight-style` YAML fields, respectively. `pandoc_template_types()` and `pandoc_highlight_styles()` return the available templates and highlight styles in pandoc, respectively. `use_pandoc_template()` creates a new file based on a template from pandoc or R Markdown and `use_pandoc_highlight_style()` creates a new highlight theme file based on an existing pandoc theme.

Usage

```
pandoc_template_types()

pandoc_highlight_styles()

use_pandoc_template(type, path, source = c("rmarkdown", "pandoc"))

use_pandoc_highlight_style(theme, path)
```

Arguments

| | |
|---------------------|---|
| <code>type</code> | The template type |
| <code>path</code> | The path to write the file to |
| <code>source</code> | The template source ("pandoc" or "rmarkdown") |
| <code>theme</code> | The name of the theme |

Value

a character vector

| | |
|------------------|--|
| pkgdown_template | <i>Generate a full YAML template for your pkgdown site</i> |
|------------------|--|

Description

pkgdown includes three helpful `pkgdown::template_*`() functions to generate the navbar, reference, and article YAML for the `_pkgdown.yml` file. `pkgdown_template()` is a wrapper function that runs all three, combines them, and converts them to a `yml` object. You may also pass `pkgdown::template_*`() functions to `as_yml()` to convert the individual sections. `pkgdown_template()` is particularly useful with `use_pkgdown_yml()` to write directly to the `_pkgdown.yml` file.

Usage

```
pkgdown_template(path = ".")
```

Arguments

`path` The path to your package directory

Value

a `yml` object

See Also

[use_pkgdown_yml\(\)](#)

Other pkgdown: [yml_pkgdown\(\)](#)

Examples

```
# requires this to be a package directory
pkgdown_template() %>%
  use_pkgdown_yml()
```

| | |
|-----------|--|
| read_json | <i>Read and write to JSON and TOML</i> |
|-----------|--|

Description

Read JSON and TOML files in as `yml` objects with `read_*`(). Write `yml` objects out as JSON and YAML files with `write_as_*`(). You can also provide `write_as_*`() a path to an existing `.yml` file to translate to JSON or TOML. These functions rely on Hugo and blogdown, so you must have blogdown installed.

Usage

```

read_json(path)

read_toml(path)

write_as_json(
  .yml = NULL,
  path = NULL,
  out = NULL,
  build_ignore = FALSE,
  git_ignore = FALSE,
  quiet = FALSE
)

write_as_toml(
  .yml = NULL,
  path = NULL,
  out = NULL,
  build_ignore = FALSE,
  git_ignore = FALSE,
  quiet = FALSE
)

```

Arguments

| | |
|---------------------------|---|
| <code>path</code> | a path to a JSON or TOML file |
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>out</code> | The path to write out to. If NULL, will write to the path but change the file extension to <code>.toml</code> or <code>.json</code> . |
| <code>build_ignore</code> | Logical. Should the file be added to the <code>.Rbuildignore</code> file? |
| <code>git_ignore</code> | Logical. Should the file be added to the <code>.gitignore</code> file? |
| <code>quiet</code> | Logical. Whether to message about what is happening. |

Value

a yml object (if reading) or the path (if writing)

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

 use_yaml

Copy YAML code to your clipboard or write to a new R Markdown file

Description

use_yaml() takes a yml object and puts the resulting YAML on your clipboard to paste into an R Markdown or YAML file. use_rmarkdown() takes the yml object and writes it to a new R Markdown file. You can add text to include in the body of the file. If it's not specified, use_rmarkdown() will use setup_chunk() by default. You can also set a default for body using options(ymlthis.rmd_body = "{your text}"); see use_rmd_defaults(). Together with specifying default YAML (see use_yaml_defaults()), use_rmarkdown() also serves as an ad-hoc way to make R Markdown templates. You may also supply use_rmarkdown() with an existing R Markdown file from which to read the YAML header; the YAML header from the template is then combined with .yaml, if it's supplied, and written to a new file. use_index_rmd() is a wrapper around use_rmarkdown() that specifically writes to a file called index.Rmd. By default, use_yaml() and use_rmarkdown() use the most recently printed YAML via last_yaml().

Usage

```
use_yaml(.yaml = last_yaml())
```

```
use_rmarkdown(
  .yaml = last_yaml(),
  path,
  template = NULL,
  include_yaml = TRUE,
  include_body = TRUE,
  body = NULL,
  quiet = FALSE,
  open_doc = interactive()
)
```

```
use_index_rmd(
  .yaml = last_yaml(),
  path,
  template = NULL,
  include_yaml = TRUE,
  include_body = TRUE,
  body = NULL,
  quiet = FALSE,
  open_doc = interactive()
)
```

Arguments

| | |
|-------|---|
| .yaml | a yml object created by yml(), as_yaml(), or returned by a yml_*() function |
| path | A file path to write R Markdown file to |

| | |
|--------------|--|
| template | An existing R Markdown file to read YAML from |
| include_yaml | Logical. Include the template YAML? |
| include_body | Logical. Include the template body? |
| body | A character vector to use in the body of the R Markdown file. If no template is set, checks <code>getOption("yamlthis.rmd_body")</code> (see use_rmd_defaults()) and otherwise uses setup_chunk() . |
| quiet | Logical. Whether to message about what is happening. |
| open_doc | Logical. Open the document after it's created? By default, this is TRUE if it is an interactive session and FALSE if not. Also checks that RStudio is available. |

Value

`use_yml()` invisibly returns the input `yml` object

See Also

[code_chunk\(\)](#) [setup_chunk\(\)](#)

Other `yml`: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yml_defaults\(\)](#), [use_yml_file\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

| | |
|-------------------------------|----------------------------|
| <code>use_yml_defaults</code> | <i>Set up default YAML</i> |
|-------------------------------|----------------------------|

Description

`use_yml_defaults()` takes a `yml` object and places code on the clipboard that will save the resulting YAML as the default for `yml()`. The code that is placed on the clipboard is raw YAML passed to `ymlthis.default_yaml` via `options()`. Saving this code to your `.Rprofile` (see [usethis::edit_r_profile\(\)](#)) will allow `yml()` or [get_yml_defaults\(\)](#) to return the saved YAML. `use_rmd_defaults()` does the same for `ymlthis.rmd_body`, which is used in [use_rmarkdown\(\)](#) as the body text of the created R Markdown file.

Usage

```
use_yml_defaults(.yml)
```

```
use_rmd_defaults(x)
```

```
get_yml_defaults()
```

```
get_rmd_defaults()
```

Arguments

.yaml a yaml object created by `yaml()`, `as_yaml()`, or returned by a `yaml_*`() function
 x a character vector to use as the body text in `use_rmarkdown()`.

See Also

`yaml()` `get_yaml_defaults()`

Other yaml: `asis_yaml_output()`, `bib2yaml()`, `draw_yaml_tree()`, `has_field()`, `read_json()`, `use_yaml_file()`, `use_yaml()`, `yaml_author()`, `yaml_blogdown_opts()`, `yaml_bookdown_opts()`, `yaml_citations()`, `yaml_clean()`, `yaml_distill_opts()`, `yaml_latex_opts()`, `yaml_output()`, `yaml_pagedown_opts()`, `yaml_params()`, `yaml_pkgdown()`, `yaml_reference()`, `yaml_replace()`, `yaml_resource_files()`, `yaml_rsconnect_email()`, `yaml_rarticles_opts()`, `yaml_runtime()`, `yaml_site_opts()`, `yaml_toc()`, `yaml_vignette()`

use_yaml_file

Write YAML to file

Description

Write yaml objects to a file. `use_yaml_file()` writes to any given file name. `use_output_yaml()` creates file `_output.yaml`, which can be used by multiple R Markdown documents. All documents located in the same directory as `_output.yaml` will inherit its output options. Options defined within document YAML headers will override those specified in `_output.yaml`. Note that `use_output_yaml()` plucks the output field from yaml; any other YAML top-level fields will be ignored. `use_site_yaml` creates `_site.yaml` for use with R Markdown websites and third-party tools like the `distill` package (see [the R Markdown book for more](#)). `use_navbar_yaml` is a special type of site YAML that only specifies the navbar in `_navbar.yaml` `use_pkgdown_yaml()` and `use_bookdown_yaml()` write YAML files specific to those packages; see the `pkgdown` and `blogdown` documentation for more.

Usage

```
use_yaml_file(
  .yaml = NULL,
  path,
  build_ignore = FALSE,
  git_ignore = FALSE,
  quiet = FALSE
)

use_output_yaml(
  .yaml = NULL,
  path = ".",
  build_ignore = FALSE,
  git_ignore = FALSE,
  quiet = FALSE
)
```

```
use_site_yaml(  
  .yaml = NULL,  
  path = ".",  
  build_ignore = FALSE,  
  git_ignore = FALSE,  
  quiet = FALSE  
)  
  
use_navbar_yaml(  
  .yaml = NULL,  
  path = ".",  
  build_ignore = FALSE,  
  git_ignore = FALSE,  
  quiet = FALSE  
)  
  
use_pkgdown_yaml(  
  .yaml = NULL,  
  path = ".",  
  build_ignore = TRUE,  
  git_ignore = FALSE,  
  quiet = FALSE  
)  
  
use_bookdown_yaml(  
  .yaml = NULL,  
  path = ".",  
  build_ignore = FALSE,  
  git_ignore = FALSE,  
  quiet = FALSE  
)
```

Arguments

| | |
|---------------------------|--|
| <code>.yaml</code> | a yaml object created by <code>yaml()</code> , <code>as_yaml()</code> , or returned by a <code>yaml_*</code> () function |
| <code>path</code> | a file path to write the file to |
| <code>build_ignore</code> | Logical. Should the file be added to the <code>.Rbuildignore</code> file? |
| <code>git_ignore</code> | Logical. Should the file be added to the <code>.gitignore</code> file? |
| <code>quiet</code> | Logical. Whether to message about what is happening. |

Details

By default, the `yaml` package adds a new line to the end of files. Some environments, such as RStudio Projects, allow you to append new lines automatically. Thus, you may end up with 2 new lines at the end of your file. If you'd like to automatically remove the last new line in the file, set `options(yamlthis.remove_blank_line = TRUE)`.

See Also

[yml_bookdown_opts](#) [yml_bookdown_site](#) [yml_pkgdown](#) [yml_pkgdown_articles](#) [yml_pkgdown_docsearch](#)
[yml_pkgdown_figures](#) [yml_pkgdown_news](#) [yml_pkgdown_reference](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#),
[use_yaml_defaults\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#),
[yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#),
[yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#),
[yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#),
[yaml_vignette\(\)](#)

yml

Create a new yml object

Description

`yml()` initializes a yml object. yml objects create valid YAML and print it cleanly to the console. By default, `yml()` looks for your name (using `getOption("usethis.full_name")`, `getOption("devtools.name")`, and `whoami::full_name()`) and uses today's date to use in the author and date fields, respectively. If you've set default YAML in `getOption("ymlthis.default_option")` (see [use_yaml_defaults\(\)](#)), `yml()` will also use include those fields by default. `yml_empty()` is a wrapper that doesn't use any of these default YAML fields. `yml()` and all related `yml_*` functions validate that the results are indeed valid YAML syntax, although not every function is able to check that the input fields are valid for the setting they are used in.

Usage

```
yml(.yaml = NULL, get_yaml = TRUE, author = TRUE, date = TRUE)
```

```
yml_empty()
```

Arguments

| | |
|-----------------------|--|
| <code>.yaml</code> | a character vector, yml object, or YAML-like list. See details. |
| <code>get_yaml</code> | logical. Use YAML stored in <code>getOption("ymlthis.default_option")</code> ? By default, <code>yml()</code> includes if it exists. |
| <code>author</code> | logical. Get default author name? |
| <code>date</code> | logical. Get default date? |

Details

`.yaml` accepts a character vector of YAML, such as "author: Hadley Wickham", an object returned by `ymlthis` functions that start with `yml_*`, or a list object (e.g. `list(author = "Hadley Wickham")`). `.yaml` objects are processed with [as_yaml\(\)](#), a wrapper around `yaml::yaml.load()`. See that function for more details.

Value

a yml object

Examples

```
yml()

yml(date = FALSE)

"author: Hadley Wickham\ndate: 2014-09-12" %>%
  yml() %>%
  yml_title("Tidy Data") %>%
  yml_keywords(
    c("data cleaning", "data tidying", "relational databases", "R")
  )

yml() %>%
  yml_author(
    c("Yihui Xie", "Hadley Wickham"),
    affiliation = rep("RStudio", 2)
  ) %>%
  yml_date("07/04/2019") %>%
  yml_output(
    pdf_document(
      keep_tex = TRUE,
      includes = includes2(after_body = "footer.tex")
    )
  ) %>%
  yml_latex_opts(biblio_style = "apalike")
```

yml_author

Set Top-level R Markdown YAML Fields

Description

These functions add common top-level YAML fields for R Markdown documents, such as `author`, `date`, and `title`. Each takes a yml object and adds fields related to the function, as well as checking for duplicate fields and (where possible) checking for valid entries. `yml_toplevel()` is a catch-all function that will take any named R object and put in the top level of the YAML; it checks for duplicate fields but is unable to validate the input beyond that it is valid YAML syntax. Some R Markdown templates allow for additional variations of the YAML here. For instance, the `distill` package adds `url` and `affiliation_url` to the author field (see [yml_distill_author](#), which wraps [yml_author](#)). Several `yml_*`() functions also contain `...` which allow for these unique fields.

Usage

```
yml_author(.yml, name = NULL, affiliation = NULL, email = NULL, ...)
```

```
yml_date(.yml, date = NULL, format = "")
```

```
yml_title(.yml, title)
```

```
yml_subtitle(.yml, subtitle)
```

```
yml_abstract(.yml, abstract)
```

```
yml_keywords(.yml, keywords)
```

```
yml_subject(.yml, subject)
```

```
yml_description(.yml, description)
```

```
yml_category(.yml, category)
```

```
yml_lang(.yml, lang)
```

```
yml_toplevel(.yml, ...)
```

Arguments

| | |
|--------------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>name</code> | A character vector, name of the author(s) |
| <code>affiliation</code> | The author's affiliation; must match length of <code>name</code> , e.g. if <code>name</code> has length of two, <code>affiliation</code> must as well; use <code>NA</code> if you don't want to include an affiliation for a given author. Note that not all formats support the <code>affiliation</code> field. |
| <code>email</code> | The author email address. Note that not all formats support the <code>email</code> field. |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |
| <code>date</code> | The date; by default this is " <code>\r format(Sys.Date())`</code> ", which will populate the date automatically. |
| <code>format</code> | When the default date is used, the format passed to <code>format.Date()</code> . |
| <code>title</code> | A character vector, the title of the document |
| <code>subtitle</code> | A character vector, the subtitle of the document. Not all R Markdown formats use subtitles, so it may depend on what you use in the output field (see yml_output()). It is available in <code>pdf_document()</code> , <code>html_document()</code> , and <code>word_document()</code> by default. |
| <code>abstract</code> | A character vector, the abstract. Long character vectors are automatically wrapped using valid YAML syntax. This field is not available in all output formats; it is available in <code>pdf_document()</code> and <code>html_document()</code> by default. |
| <code>keywords</code> | A character vector of keywords. This field is not available in all output formats; it is available in <code>pdf_document()</code> , <code>html_document()</code> , <code>word_document()</code> , <code>odt_document()</code> , and <code>powerpoint_presentation()</code> by default. |

| | |
|-------------|---|
| subject | A character vector, the subject of the document. This field is not available in all output formats; it is available in <code>pdf_document()</code> , <code>html_document()</code> , <code>word_document()</code> , <code>odt_document()</code> , and <code>powerpoint_presentation()</code> by default. |
| description | A character vector, a description of the document. This field is not available in all output formats; it is available in <code>word_document()</code> , <code>odt_document()</code> , and <code>powerpoint_presentation()</code> by default. |
| category | A character vector, the category of the document. This field is not available in all output formats; it is available in <code>word_document()</code> and <code>powerpoint_presentation()</code> by default. |
| lang | The document language using IETF language tags such as "en" or "en-US". The Language subtag lookup tool can help find the appropriate tag. |

Value

a yml object

See Also

Other yml: `asis_yaml_output()`, `bib2yaml()`, `draw_yaml_tree()`, `has_field()`, `read_json()`, `use_yaml_defaults()`, `use_yaml_file()`, `use_yaml()`, `yaml_blogdown_opts()`, `yaml_bookdown_opts()`, `yaml_citations()`, `yaml_clean()`, `yaml_distill_opts()`, `yaml_latex_opts()`, `yaml_output()`, `yaml_pagedown_opts()`, `yaml_params()`, `yaml_pkgdown()`, `yaml_reference()`, `yaml_replace()`, `yaml_resource_files()`, `yaml_rsconnect_email()`, `yaml_rarticles_opts()`, `yaml_runtime()`, `yaml_site_opts()`, `yaml_toc()`, `yaml_vignette()`

Examples

```
yml_empty() %>%
  yml_author("Yihui Xie") %>%
  yml_date("02-02-2002") %>%
  yml_title("R Markdown: An Introduction") %>%
  yml_subtitle("Introducing ymlthis") %>%
  yml_abstract("This paper will discuss a very important topic") %>%
  yml_keywords(c("r", "reproducible research")) %>%
  yml_subject("R Markdown") %>%
  yml_description("An R Markdown reader") %>%
  yml_category("r") %>%
  yml_lang("en-US")
```


Description

ymlthis treats NULL, NA, and other common argument defaults as literal (e.g. author = NULL will produce "author: null"). yml_blank() is a helper function to indicate that the field should not be included. yml_blank() is primarily used as a default argument for fields that should not be included by default.

Usage

```
yml_blank()

is_yml_blank(x)
```

Arguments

x a field from a yml object

Value

a yml_blank object

See Also

[yml_discard\(\)](#), [yml_replace\(\)](#)

Examples

```
yml() %>%
  yml_replace(author = yml_blank()) %>%
  yml_discard(~is_yml_blank(.x))
```

yml_blogdown_opts *Set Top-level YAML options for blogdown*

Description

YAML in blogdown comes from a variety of sources. Most YAML will be for your posts, as described in the [blogdown book](#). Common R Markdown fields can be used, but there are two other main sources for YAML fields: Hugo itself and the Hugo theme you are using. Hugo has numerous top-level YAML to control the output (see the [Hugo documentation](#)). yml_blogdown_opts() supports Hugo YAML. Your Hugo theme may also add fields to use. To find YAML specific to your theme, see [blogdown_template\(\)](#). In addition to these sources of YAML, the configuration file for your blog can also be in YAML, but this is not very common; most use a config.toml file, based on TOML (see the [blogdown book](#) for more).

Usage

```

yml_blogdown_opts(
  .yml,
  draft = yml_blank(),
  publishdate = yml_blank(),
  weight = yml_blank(),
  slug = yml_blank(),
  aliases = yml_blank(),
  audio = yml_blank(),
  date = yml_blank(),
  description = yml_blank(),
  expiration_date = yml_blank(),
  headless = yml_blank(),
  images = yml_blank(),
  keywords = yml_blank(),
  layout = yml_blank(),
  lastmod = yml_blank(),
  link_title = yml_blank(),
  resources = yml_blank(),
  series = yml_blank(),
  summary = yml_blank(),
  title = yml_blank(),
  type = yml_blank(),
  url = yml_blank(),
  videos = yml_blank(),
  ...
)

```

Arguments

| | |
|-------------|---|
| .yml | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| draft | Logical. Set post as a draft? Draft posts will not be rendered if the site is built via <code>blogdown::build_site()</code> or <code>blogdown::hugo_build()</code> but will be rendered in the local preview mode. See Section D.3 of the blogdown book . |
| publishdate | A future date to publish the post. Future posts are only rendered in the local preview mode |
| weight | This field can take a numeric value to tell Hugo the order of pages when sorting them, e.g., when you generate a list of all pages under a directory, and two posts have the same date, you may assign different weights to them to get your desired order on the list |
| slug | A character string used as the tail of the post URL. It is particularly useful when you define custom rules for permanent URLs. See Section 2.2.2 of the blogdown book . |
| aliases | A character vector of one or more aliases (e.g., old published paths of renamed content) that will be created in the output directory structure |
| audio | A character vector of paths to audio files related to the page |

| | |
|-----------------|--|
| date | The date assigned to this page. This is usually fetched from the date field in front matter, but this behavior is configurable. |
| description | The description for the content |
| expiration_date | the date at which the content should no longer be published by Hugo. Note that the actual YAML field is expiryDate |
| headless | if TRUE, sets a leaf bundle to be headless . |
| images | A character vector of paths to images related to the page |
| keywords | A character vector of the keywords for the content. |
| layout | The layout Hugo should use while rendering the content. By default, layout matches type and is thus based on the directory. However, it's possible to use additional layouts within a type. See Hugo's Defining a Content Type documentation . |
| lastmod | The date the content was last modified at |
| link_title | used for creating links to content. Note that the actual YAML field is linkTitle |
| resources | A named list. Used for configuring page bundle resources. See Hugo's Page Resources documentation |
| series | A character vector of series this page belongs to |
| summary | A summary of the content in the . Summary Hugo page variable; see the content-summaries section of Hugo's documentation. |
| title | The title for the content |
| type | The type of the content, which is based on the from the directory of the content if not specified |
| url | The full path to the content from the web root |
| videos | A character vector of paths to videos related to the page |
| ... | additional named R objects, such as characters or lists, to transform into YAML |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_blogdown_opts(
    draft = TRUE,
    slug = "blog-post"
  )
```

yml_bookdown_opts *Set Top-level YAML options for bookdown*

Description

bookdown uses YAML in three main places, as described in the [bookdown book](#): `index.Rmd`, `_output.yml`, and `_bookdown.yml`. `index.Rmd` can take most YAML. `_output.yml` is intended for output-related YAML, such as that produced by `yml() %>% yml_output(bookdown::pdf_book())`. `_bookdown.yml` is intended for configuring the build of the book. Pass the results of the `yml_*`() functions to `use_index_rmd()`, `use_bookdown_yaml()`, `use_output_yaml()` to write them to these files. `yml_bookdown_site()` adds the site: "bookdown::bookdown_site" to the YAML metadata.

Usage

```
yml_bookdown_opts(
  .yml,
  book_filename = yml_blank(),
  delete_merged_file = yml_blank(),
  before_chapter_script = yml_blank(),
  after_chapter_script = yml_blank(),
  edit = yml_blank(),
  history = yml_blank(),
  rmd_files = yml_blank(),
  rmd_subdir = yml_blank(),
  output_dir = yml_blank(),
  clean = yml_blank(),
  ...
)

yml_bookdown_site(.yml)
```

Arguments

`.yml` a yml object created by `yml()`, `as_yml()`, or returned by a `yml_*`() function

`book_filename` A character vector, the filename of the main `.Rmd` file, the `.Rmd` file that is created by merging all chapters. By default, it is called "`_main.Rmd`".

`delete_merged_file` Logical. Delete the main `.Rmd` file if it exists?

| | |
|---|--|
| before_chapter_script, after_chapter_script | A character vector of one or more R scripts to be executed before or after each chapter |
| edit | A URL that collaborators can click to edit the .Rmd source document of the current page, usually a link to a GitHub repository. This link should have %s where the actual .Rmd filename for each page will go. |
| history | Similar to edit, a link to the edit/commit history of the current page. |
| rmd_files | A character vector, the order order of .Rmd files for the book. rmd_files can also be a named list where each element of the list is named for the output type, e.g. "html" or "latex". By default, bookdown merges all .Rmd files by the order of filenames. |
| rmd_subdir | whether to search for book source .Rmd files in subdirectories (by default, only the root directory is searched). This may be either a boolean (e.g. TRUE will search for book source .Rmd files in the project directory and all subdirectories) or vector of paths if you want to search for book source .Rmd files in a subset of subdirectories. |
| output_dir | the output directory of the book ("_book" by default) |
| clean | a character vector of files and directories to be cleaned by the bookdown::clean_book() function. |
| ... | additional named R objects, such as characters or lists, to transform into YAML |

Value

a yml object

See Also

[use_index_rmd\(\)](#) [use_bookdown_yml\(\)](#) [use_output_yml\(\)](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other bookdown: [gitbook_config\(\)](#)

Examples

```
yml_empty() %>%
  yml_bookdown_opts(
    book_filename = "my-book.Rmd",
    before_chapter_script = c("script1.R", "script2.R"),
    after_chapter_script = "script3.R",
    edit = "https://github.com/rstudio/bookdown-demo/edit/master/%s",
    output_dir = "book-output",
    clean = c("my-book.bbl", "R-packages.bib")
```

```

)

yml_empty() %>%
  yml_bookdown_opts(
    rmd_files = list(
      html = c("index.Rmd", "abstract.Rmd", "intro.Rmd"),
      latex = c("abstract.Rmd", "intro.Rmd")
    )
  )

x <- yml_empty() %>%
  yml_title("A Minimal Book Example") %>%
  yml_date(yml_code(Sys.Date())) %>%
  yml_author("Yihui Xie") %>%
  yml_bookdown_site() %>%
  yml_latex_opts(
    documentclass = "book",
    bibliography = c("book.bib", "packages.bib"),
    biblio_style = "apalike"
  ) %>%
  yml_citations(
    link_citations = TRUE
  ) %>%
  yml_description("This is a minimal example of using
the bookdown package to write a book.")

x

output_yml <- yml_empty() %>%
  yml_output(
    bookdown::gitbook(
      lib_dir = "assets",
      split_by = "section",
      config = gitbook_config(toolbar_position = "static")
    ),
    bookdown::pdf_book(keep_tex = TRUE),
    bookdown::html_book(css = "toc.css")
  )
output_yml

```

Description

`yml_citations()` sets citation-related YAML fields, such as specifying a bibliography file or style.

For controlling the citation engine in PDF documents, see the `citation_package` argument in `rmarkdown::pdf_document()`.

Usage

```
yml_citations(
  .yml,
  bibliography = yml_blank(),
  biblio_style = yml_blank(),
  biblio_title = yml_blank(),
  csl = yml_blank(),
  citation_abbreviations = yml_blank(),
  link_citations = yml_blank(),
  nocite = yml_blank(),
  suppress_bibliography = yml_blank()
)
```

Arguments

| | |
|-------------------------------------|---|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>bibliography</code> | a path to a bibliography file, such as a <code>.bib</code> file |
| <code>biblio_style</code> | bibliography style, when used with <code>natbib</code> and <code>biblatex</code> . Note that the actual YAML field is <code>biblio-style</code> |
| <code>biblio_title</code> | bibliography title, when used with <code>natbib</code> and <code>biblatex</code> . Note that the actual YAML field is <code>biblio-title</code> |
| <code>csl</code> | a path to a Citation Style Language (CSL) file. CSL files are used to specify the citation style; see the CSL repository for the CSL files of dozens of journals. |
| <code>citation_abbreviations</code> | Path to a CSL abbreviations JSON file. See the pandoc-citeproc documentation . Note that the actual YAML field is <code>citation-abbreviations</code> . |
| <code>link_citations</code> | Logical. Add citations hyperlinks to the corresponding bibliography entries? Note that the actual YAML field is <code>link-citations</code> . |
| <code>nocite</code> | Citation IDs (" <code>@item1</code> ") to include in the bibliography even if they are not cited in the document. Including the wildcard pattern " <code>@*</code> " will include all citations in the bibliography regardless of if they're cited in the document. |
| <code>suppress_bibliography</code> | Logical. Suppress bibliography? |

Value

a yml object

See Also

Other yml: [asis_yml_output\(\)](#), [bib2yml\(\)](#), [draw_yml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yml_defaults\(\)](#), [use_yml_file\(\)](#), [use_yml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#),

[yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Other citations: [bib2yml\(\)](#), [yml_reference\(\)](#)

Examples

```
yml() %>%
  yml_citations(bibliography = "references.bib", csl = "aje.csl")
```

| | |
|------------------------|--|
| <code>yml_clean</code> | <i>Remove intermediate rendering files</i> |
|------------------------|--|

Description

R Markdown may create many documents while rendering the final product, for instance by using knitr to turn the R Markdown file to a Markdown file and then using Pandoc to convert to the final output. The `clean` field tells R Markdown whether or not to remove these files.

Usage

```
yml_clean(.yml, clean)
```

Arguments

| | |
|--------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>clean</code> | Logical. Remove intermediate files that are created while making the R Markdown document? |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yml\(\)](#), [draw_yml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yml_defaults\(\)](#), [use_yml_file\(\)](#), [use_yml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Other R Markdown: [yml_params\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_vignette\(\)](#)

Examples

```
yml() %>%  
  # keep intermediate files  
  yml_clean(FALSE)
```

yml_code

Take code and write it as valid YAML

Description

`yml_code()` takes R code and writes it as valid YAML to be evaluated during knitting. Note that `yml_code()` does not evaluate or validate the R code but only captures it to use in the YAML field. R code needs to be formatted differently when using in the `params` field for parameterized reports; `yml_params_code` will format this correctly for you.

Usage

```
yml_code(x)
```

```
yml_params_code(x)
```

Arguments

x valid R code

Value

a character vector with class `verbatim`

See Also

[yml_verbatim\(\)](#)

Examples

```
yml_empty() %>%  
  yml_date(yml_code(sys.Date()))  
  
yml_empty() %>%  
  yml_params(date = yml_params_code(sys.Date()))
```

Description

distill uses many custom YAML fields to create some of its unique features, such as article metadata and citations. In addition to the arguments in `yml_distill_opts()`, ymlthis supports distill in a number of other ways. `yml_distill_author()` wraps `yml_author()` to include these extra used in distill. For a distill blog, you can specify the listings page a post belongs to, including an optional vector of other posts to list with it; `distill_listing()` is a helper function to pass to the `listing` argument to specify such pages. distill uses the same approach to navbars as R Markdown. `yml_navbar()` and friends will help you write the YAML for that. YAML specifying the site build, like the `output` field and navbars, can also be placed in `_site.yml`; see `yml_site_opts()` for further R Markdown website build options and `use_site_yaml()` for creating that file based on a yml object. distill's YAML options are discussed in greater detail in the [articles on the distill website](#).

Usage

```
yml_distill_opts(  
  .yaml,  
  draft = yml_blank(),  
  slug = yml_blank(),  
  categories = yml_blank(),  
  listing = yml_blank(),  
  collection = yml_blank(),  
  citation_url = yml_blank(),  
  preview = yml_blank(),  
  repository_url = yml_blank(),  
  base_url = yml_blank(),  
  compare_updates_url = yml_blank(),  
  creative_commons = yml_blank(),  
  twitter_site = yml_blank(),  
  twitter_creator = yml_blank(),  
  journal_title = yml_blank(),  
  journal_issn = yml_blank(),  
  journal_publisher = yml_blank(),  
  volume = yml_blank(),  
  issue = yml_blank(),  
  doi = yml_blank(),  
  resources = yml_blank(),  
  ...  
)  
  
yml_distill_author(  
  .yaml,  
  name = yml_blank(),  
  url = yml_blank(),
```

```

    affiliation = yml_blank(),
    affiliation_url = yml_blank()
  )

  distill_listing(listing_name = "posts", slugs = NULL)

  distill_collection(
    collection_name = "post",
    feed_items_max = yml_blank(),
    disqus_name = yml_blank(),
    disqus_hidden = yml_blank(),
    share = yml_blank(),
    citations = yml_blank(),
    subscribe = yml_blank()
  )

  distill_resources(include = yml_blank(), exclude = yml_blank())

```

Arguments

| | |
|----------------------------------|---|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>draft</code> | Logical. Set the post to be a draft? Draft posts won't be published. |
| <code>slug</code> | The abbreviated version of the citation included in the BibTeX entry. If you don't provide a slug then one will be automatically generated. |
| <code>categories</code> | A character vector, the post categories |
| <code>listing</code> | The listing a post is under; either a character vector, the output of <code>distill_listing()</code> , or a named list. |
| <code>collection</code> | Specify the RSS, sharing, and other settings of a listing; use <code>distill_collection()</code> or a named list. |
| <code>citation_url</code> | A URL to the article; automatically generated for blog articles |
| <code>preview</code> | a path or link to the preview image for your article. You can also set this by including <code>preview = TRUE</code> in an R Markdown code chunk in your document. |
| <code>repository_url</code> | A URL where the source code for your article can be found |
| <code>base_url</code> | Base (root) URL for the location where the website will be deployed (used for providing preview images for Open Graph and Twitter Card) |
| <code>compare_updates_url</code> | a URL that will show the differences between the article's current version and the version that was initially published |
| <code>creative_commons</code> | Designate articles that you create as Creative Commons licensed by specifying one of the standard Creative Commons licenses. Common options include "CC BY", "CC BY-SA", "CC BY-ND", and "CC BY-NC". See the distill vignette for more details. |
| <code>twitter_site</code> | The Twitter handle for the site |
| <code>twitter_creator</code> | The Twitter handle for the creator |

| | |
|-------------------|--|
| journal_title | The title of the journal |
| journal_issn | The issn of the journal |
| journal_publisher | The publisher of the journal |
| volume | The volume the article is on |
| issue | The issue the article is on |
| doi | The article Digital Object Identifier (DOI) |
| resources | Files to include or exclude while publishing. Use <code>distill_resources()</code> or a named list to specify. |
| ... | additional named R objects, such as characters or lists, to transform into YAML |
| name | A character vector, name of the author(s) |
| url | the author URL |
| affiliation | The author's affiliation; must match length of name, e.g. if name has length of two, affiliation must as well; use NA if you don't want to include an affiliation for a given author. Note that not all formats support the affiliation field. |
| affiliation_url | the affiliation URL |
| listing_name | A character vector, the name of the listing |
| slugs | A character vector of the posts to include in the listing |
| collection_name | A character vector, the name of the collection |
| feed_items_max | Number of articles to include in the RSS feed (default: 20). Specify FALSE to have no limit on the number of items included in the feed. |
| disqus_name | A shortname for the disqus comments section (<code>base_url</code> field is required in order to use Disqus) |
| disqus_hidden | Logical. Show full text of disqus comments? By default, this is FALSE so as not to obscure the bibliography and other appendices. |
| share | Share buttons to include. Choices: "twitter", "linkedin", "facebook", "google-plus", and "pinterest". (<code>base_url</code> field is required in order to use sharing links) |
| citations | Logical. If your <code>_site.yml</code> file provides a <code>base_url</code> field, an article citation appendix and related metadata will be included automatically within all published posts. Set to FALSE to disable this behavior. |
| subscribe | a path to a HTML file enabling readers to subscribe. See the distill vignette on blog posts for more details. |
| include, exclude | a character vector of files to explicitly include or exclude when publishing a post. Can use wild cards, such as <code>"*.csv"</code> . |

Value

a yml object

See Also

[use_site_yaml\(\)](#) [use_rmarkdown\(\)](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other websites: [yaml_pkgdown\(\)](#), [yaml_site_opts\(\)](#)

Examples

```
post_listing <- distill_listing(
  slugs = c(
    "2016-11-08-sharpe-ratio",
    "2017-11-09-visualizing-asset-returns",
    "2017-09-13-asset-volatility"
  )
)

yaml() %>%
  yaml_title("Gallery of featured posts") %>%
  yaml_distill_opts(listing = post_listing)

yaml_empty() %>%
  yaml_title("Reproducible Finance with R") %>%
  yaml_description("Exploring reproducible finance with the R statistical,
  computing environment.") %>%
  yaml_site_opts(name = "reproducible-finance-with-r") %>%
  yaml_distill_opts(
    base_url = "https://beta.rstudioconnect.com/content/3776/",
    collection = distill_collection(
      feed_items_max = 30,
      Disqus_name = "reproducible-finance-with-r",
      Disqus_hidden = FALSE,
      share = c("twitter", "linkedin")
    )
  )
)
```

Description

`ymlthis` uses the `yaml` package to process and validate YAML; this package also lets you specify how fields and values are printed using a list of handler functions. `yml_handlers()` specifies defaults for the package used in the print statement. See `yaml::yaml.load()` for more on specifying handlers.

Usage

```
yml_handlers()
```

| | |
|----------------|--|
| yml_latex_opts | <i>Set LaTeX YAML options for PDF output</i> |
|----------------|--|

Description

yml_latex_opts() sets top-level YAML fields for LaTeX options used by pandoc (see the [documentation](#), from which these descriptions were derived), as when making a PDF document with pdf_document().

Usage

```
yml_latex_opts(
  .yml,
  block_headings = yml_blank(),
  classoption = yml_blank(),
  documentclass = yml_blank(),
  geometry = yml_blank(),
  indent = yml_blank(),
  linestretch = yml_blank(),
  margin_left = yml_blank(),
  margin_right = yml_blank(),
  margin_top = yml_blank(),
  margin_bottom = yml_blank(),
  pagestyle = yml_blank(),
  papersize = yml_blank(),
  secnumdepth = yml_blank(),
  fontenc = yml_blank(),
  fontfamily = yml_blank(),
  fontfamilyoptions = yml_blank(),
  fontsize = yml_blank(),
  mainfont = yml_blank(),
  sansfont = yml_blank(),
  monofont = yml_blank(),
  mathfont = yml_blank(),
  CJKmainfont = yml_blank(),
  mainfontoptions = yml_blank(),
  sansfontoptions = yml_blank(),
  monofontoptions = yml_blank(),
  mathfontoptions = yml_blank(),
  CJKoptions = yml_blank(),
  microtypeoptions = yml_blank(),
  colorlinks = yml_blank(),
  linkcolor = yml_blank(),
```

```

filecolor = yml_blank(),
citecolor = yml_blank(),
urlcolor = yml_blank(),
toccolor = yml_blank(),
links_as_notes = yml_blank(),
lof = yml_blank(),
lot = yml_blank(),
thanks = yml_blank(),
toc = yml_blank(),
toc_depth = yml_blank(),
biblatexoptions = yml_blank(),
biblio_style = yml_blank(),
biblio_title = yml_blank(),
bibliography = yml_blank(),
natbiboptions = yml_blank()
)

```

Arguments

| | |
|--|---|
| .yml | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| block_headings | make paragraph and subparagraph (fourth- and fifth-level headings, or fifth- and sixth-level with book classes) free-standing rather than run-in; requires further formatting to distinguish from subsection (third- or fourth-level headings). Note that the YAML field is actually called <code>block-headings</code> . |
| classoption | a character vector of options for document class, e.g. "oneside" |
| documentclass | the document class usually "article", "book", or "report" |
| geometry | a character vector of options for the geometry LaTeX package , e.g. "margin=lin" |
| indent | Logical. Use document class settings for indentation? The default LaTeX template otherwise removes indentation and adds space between paragraphs. |
| linestretch | adjusts line spacing using the setspace LaTeX package , e.g. 1.25, 1.5 |
| margin_left, margin_right, margin_top, margin_bottom | sets margins if geometry is not used, otherwise geometry overrides these. Note that the actual YAML fields use - instead of _, e.g. margin-left. |
| pagestyle | control the <code>pagestyle</code> LaTeX command: the default article class supports "plain" (default), "empty" (no running heads or page numbers), and "headings" (section titles in running heads) |
| papersize | paper size, e.g. letter, a4 |
| secnumdepth | numbering depth for sections (with <code>--number-sections</code> pandoc) |
| fontenc | allows font encoding to be specified through fontenc LaTeX package (with <code>pdflatex</code>); default is "T1" (see LaTeX font encodings guide) |
| fontfamily | font package for use with <code>pdflatex</code> : TeX Live includes many options, documented in the LaTeX Font Catalogue . The default is "Latin Modern". |
| fontfamilyoptions | a character vector of options for <code>fontfamily</code> . |

| | |
|--|---|
| fontsize | font size for body text. The standard classes allow "10pt", "11pt", and "12pt". |
| mainfont, sansfont, monofont, mathfont, CJKmainfont | font families for use with xelatex or lualatex: take the name of any system font, using the fontspec LaTeX package . CJKmainfont uses the xecjk LaTeX package . |
| mainfontoptions, sansfontoptions, monofontoptions, mathfontoptions, CJKoptions | a character vector of options to use with mainfont, sansfont, monofont, mathfont, CJKmainfont in xelatex and lualatex. Allow for any choices available through fontspec. |
| microtypeoptions | a character vector of options to pass to the microtype LaTeX package . |
| colorlinks | Logical. Add color to link text? Automatically enabled if any of linkcolor, filecolor, citecolor, urlcolor, or toccolor are set. |
| linkcolor, filecolor, citecolor, urlcolor, toccolor | color for internal links, external links, citation links, linked URLs, and links in table of contents, respectively: uses options allowed by xcolor , including the dvipsnames, svgnames, and x11names lists |
| links_as_notes | Logical. Print links as footnotes? Note that the actual YAML field is links-as-notes |
| lof, lot | Logical. Include list of figures or list of tables? |
| thanks | contents of acknowledgments footnote after document title |
| toc | include table of contents |
| toc_depth | level of section to include in table of contents. Note that the actual YAML field is toc-depth |
| biblatexoptions | list of options for biblatex . |
| biblio_style | bibliography style, when used with natbib and biblatex . Note that the actual YAML field is biblio-style |
| biblio_title | bibliography title, when used with natbib and biblatex . Note that the actual YAML field is biblio-title |
| bibliography | a path to the bibliography file to use for references |
| natbiboptions | a character vector of options for natbib |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_output(pdf_document()) %>%
  yml_latex_opts(
    fontfamily = "Fira Sans Thin",
    fontsize = "11pt",
    links_as_notes = TRUE
  )
```

yml_load*Load YAML from string*

Description

`yml_load()` is a wrapper for `yaml::yaml.load()` that also converts the object to the `yml` class.

Usage

```
yml_load(x)
```

Arguments

`x` an object to pass to `yaml::yaml.load()`

Examples

```
c("title: my title", "author: Malcolm Barrett") %>%
  yml_load()
```

yml_output*Capture, validate, and write output YAML*

Description

`yml_output()` writes valid YAML for the output field of R Markdown YAML. `yml_output()` captures the actual output functions, such as `pdf_document()`, and translates them to YAML. This function accepts multiple output formats (separated by commas) and validates each by evaluating the function internally. The YAML fields in under output come from arguments in their respective R functions. If you wanted to see the available fields in `pdf_document()`, for instance, you would read the documentation for that function using `?pdf_document`.

Usage

```
yml_output(.yml, ...)
```

Arguments

.yml a yml object created by `yml()`, `as_yml()`, or returned by a `yml_*`() function
 ... valid R code calling functions that return objects of class `rmarkdown_output_format`, such as the `*_document()` functions in `rmarkdown`.

Value

a yml object

See Also

Other yml: [asis_yml_output\(\)](#), [bib2yml\(\)](#), [draw_yml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yml_defaults\(\)](#), [use_yml_file\(\)](#), [use_yml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_output(html_document())

yml() %>%
  yml_output(
    pdf_document(keep_tex = TRUE, includes = includes2(after_body = "footer.tex")),
    bookdown::html_document2()
  )
```

`yml_pagedown_opts` *Top-level YAML options for pagedown*

Description

`pagedown` offers several output functions for paginated output, resumes, business cards, theses, and more as described in the [pagedown vignette](#). `pagedown` also accepts a few custom top-level YAML. See [pagedown_business_card_template\(\)](#) for more on setting up the YAML for a business card.

Usage

```
yml_pagedown_opts(
  .yml,
  toc = yml_blank(),
  toc_title = yml_blank(),
  lot = yml_blank(),
```

```

  lot_title = yml_blank(),
  chapter_name = yml_blank(),
  links_to_footnotes = yml_blank(),
  paged_footnotes = yml_blank()
)

```

Arguments

| | |
|--------------------|--|
| .yml | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| toc | Logical. Use a table of contents? |
| toc_title | The title for the table of contents. Note that the actual YAML field is <code>toc-title</code> |
| lot | Logical. Use a list of figures? |
| lot_title | The title for the list of figures. Note that the actual YAML field is <code>lot-title</code> |
| chapter_name | The chapter title prefix |
| links_to_footnotes | Logical. Transform all the URLs to footnotes? Note that the actual YAML field is <code>links-to-footnotes</code> |
| paged_footnotes | Logical. Render notes as footnotes? Note that the actual YAML field is <code>paged-footnotes</code> |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Other pagedown: [pagedown_business_card_template\(\)](#)

Examples

```

yml() %>%
  yml_pagedown_opts(
    toc = TRUE,
    toc_title = "TOC",
    chapter_name = c("CHAPTER\\ ", ". "),
    links_to_footnotes = TRUE
  )

```

Description

R Markdown lets you add dynamic parameters to your report using the `params` YAML field (see the [R Markdown book](#) for examples); parameterized reports are also used in RStudio Connect. The values of these variables can be called inside your R Markdown document using `params$field_name`. **There are several ways to change the values of the parameters:** manually change the YAML, use the `params` argument in `rmarkdown::render()`, or knit with parameters, which launches a Shiny app to select values for each. `yml_params()` accepts any number of named R objects to set as YAML fields. You can also pass arguments to the underlying Shiny functions using YAML. To set a shiny component, use the `shiny_*`() helper functions. `shiny_params()` captures a Shiny output function and transforms it to YAML. However, R Markdown supports only a limited number of components; each of these is included as a function starting with `shiny_*`(), e.g. `shiny_checkbox()`

Usage

```
yml_params(.yml, ...)
```

```
shiny_params(.shiny)
```

```
shiny_checkbox(label, value = FALSE, width = NULL)
```

```
shiny_numeric(label, value, min = NA, max = NA, step = NA, width = NULL)
```

```
shiny_slider(  
  label,  
  min,  
  max,  
  value,  
  step = NULL,  
  round = FALSE,  
  format = NULL,  
  locale = NULL,  
  ticks = TRUE,  
  animate = FALSE,  
  width = NULL,  
  sep = ",",  
  pre = NULL,  
  post = NULL,  
  timeFormat = NULL,  
  timezone = NULL,  
  dragRange = TRUE  
)
```

```
shiny_date(  
  label,  
  value,  
  min = NULL,  
  max = NULL,  
  format = NULL,  
  locale = NULL,  
  timeFormat = NULL,  
  timezone = NULL,  
  dragRange = TRUE  
)
```

```
    label,  
    value = NULL,  
    min = NULL,  
    max = NULL,  
    format = "yyyy-mm-dd",  
    startview = "month",  
    weekstart = 0,  
    language = "en",  
    width = NULL,  
    autoclose = TRUE,  
    datesdisabled = NULL,  
    daysofweekdisabled = NULL  
  )  
  
shiny_text(label, value = "", width = NULL, placeholder = NULL)  
  
shiny_file(  
  label,  
  multiple = FALSE,  
  accept = NULL,  
  width = NULL,  
  buttonLabel = "Browse...",  
  placeholder = "No file selected"  
)  
  
shiny_radio(  
  label,  
  choices = NULL,  
  selected = NULL,  
  inline = FALSE,  
  width = NULL,  
  choiceNames = NULL,  
  choiceValues = NULL  
)  
  
shiny_select(  
  label,  
  choices,  
  selected = NULL,  
  multiple = FALSE,  
  selectize = TRUE,  
  width = NULL,  
  size = NULL  
)  
  
shiny_password(label, value = "", width = NULL, placeholder = NULL)
```

Arguments

| | |
|-------------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |
| <code>.shiny</code> | a Shiny function call to capture and convert to YAML |
| <code>label</code> | Display label for the control, or NULL for no label. |
| <code>value</code> | Initial value (TRUE or FALSE). |
| <code>width</code> | The width of the input, e.g. '400px', or '100%'; see shiny::validateCssUnit() |
| <code>min</code> | Minimum allowed value |
| <code>max</code> | Maximum allowed value |
| <code>step</code> | Interval to use when stepping between min and max |
| <code>round</code> | TRUE to round all values to the nearest integer; FALSE if no rounding is desired; or an integer to round to that number of digits (for example, 1 will round to the nearest 10, and -2 will round to the nearest .01). Any rounding will be applied after snapping to the nearest step. |
| <code>format</code> | Deprecated. |
| <code>locale</code> | Deprecated. |
| <code>ticks</code> | FALSE to hide tick marks, TRUE to show them according to some simple heuristics. |
| <code>animate</code> | TRUE to show simple animation controls with default settings; FALSE not to; or a custom settings list, such as those created using shiny::animationOptions() |
| <code>sep</code> | Separator between thousands places in numbers. |
| <code>pre</code> | A prefix string to put in front of the value. |
| <code>post</code> | A suffix string to put after the value. |
| <code>timeFormat</code> | Only used if the values are Date or POSIXt objects. A time format string, to be passed to the Javascript strftime library. See https://github.com/samsonjs/strftime for more details. The allowed format specifications are very similar, but not identical, to those for R's base::strftime() function. For Dates, the default is "%F" (like "2015-07-01"), and for POSIXt, the default is "%F %T" (like "2015-07-01 15:32:10"). |
| <code>timezone</code> | Only used if the values are POSIXt objects. A string specifying the time zone offset for the displayed times, in the format "+HHMM" or "-HHMM". If NULL (the default), times will be displayed in the browser's time zone. The value "+0000" will result in UTC time. |
| <code>dragRange</code> | This option is used only if it is a range slider (with two values). If TRUE (the default), the range can be dragged. In other words, the min and max can be dragged together. If FALSE, the range cannot be dragged. |
| <code>startview</code> | The date range shown when the input object is first clicked. Can be "month" (the default), "year", or "decade". |
| <code>weekstart</code> | Which day is the start of the week. Should be an integer from 0 (Sunday) to 6 (Saturday). |

| | |
|--------------------|--|
| language | The language used for month and day names. Default is "en". Other valid values include "ar", "az", "bg", "bs", "ca", "cs", "cy", "da", "de", "el", "en-AU", "en-GB", "eo", "es", "et", "eu", "fa", "fi", "fo", "fr-CH", "fr", "gl", "he", "hr", "hu", "hy", "id", "is", "it-CH", "it", "ja", "ka", "kh", "kk", "ko", "kr", "lt", "lv", "me", "mk", "mn", "ms", "nb", "nl-BE", "nl", "no", "pl", "pt-BR", "pt", "ro", "rs-latin", "rs", "ru", "sk", "sl", "sq", "sr-latin", "sr", "sv", "sw", "th", "tr", "uk", "vi", "zh-CN", and "zh-TW". |
| autoclose | Whether or not to close the datepicker immediately when a date is selected. |
| datesdisabled | Which dates should be disabled. Either a Date object, or a string in yyyy-mm-dd format. |
| daysofweekdisabled | Days of the week that should be disabled. Should be a integer vector with values from 0 (Sunday) to 6 (Saturday). |
| placeholder | A character string giving the user a hint as to what can be entered into the control. Internet Explorer 8 and 9 do not support this option. |
| multiple | Whether the user should be allowed to select and upload multiple files at once. Does not work on older browsers, including Internet Explorer 9 and earlier. |
| accept | A character vector of MIME types; gives the browser a hint of what kind of files the server is expecting. |
| buttonLabel | The label used on the button. Can be text or an HTML tag object. |
| choices | List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user). If this argument is provided, then choiceNames and choiceValues must not be provided, and vice-versa. The values should be strings; other types (such as logicals and numbers) will be coerced to strings. |
| selected | The initially selected value (if not specified then defaults to the first value) |
| inline | If TRUE, render the choices inline (i.e. horizontally) |
| choiceNames | List of names and values, respectively, that are displayed to the user in the app and correspond to the each choice (for this reason, choiceNames and choiceValues must have the same length). If either of these arguments is provided, then the other <i>must</i> be provided and choices <i>must not</i> be provided. The advantage of using both of these over a named list for choices is that choiceNames allows any type of UI object to be passed through (tag objects, icons, HTML code, ...), instead of just simple text. See Examples. |
| choiceValues | List of names and values, respectively, that are displayed to the user in the app and correspond to the each choice (for this reason, choiceNames and choiceValues must have the same length). If either of these arguments is provided, then the other <i>must</i> be provided and choices <i>must not</i> be provided. The advantage of using both of these over a named list for choices is that choiceNames allows any type of UI object to be passed through (tag objects, icons, HTML code, ...), instead of just simple text. See Examples. |
| selectize | Whether to use selectize.js or not. |
| size | Number of items to show in the selection box; a larger number will result in a taller box. Not compatible with selectize=TRUE. Normally, when multiple=FALSE, a select input will be a drop-down list, but when size is set, it will be a box instead. |

Value

a yml object

See Also

[yml_params_code\(\)](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Other R Markdown: [yml_clean\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_vignette\(\)](#)

Other shiny: [yml_runtime\(\)](#)

Examples

```
yml() %>%
  yml_params(
    z = "z",
    x = shiny_numeric("Starting value", 23),
    no = shiny_checkbox("No option?"),
    y = shiny_slider("Data range", 0, 1, .5, round = TRUE)
  )
```

yml_pkgdown

Set Top-level YAML options for pkgdown

Description

These functions set YAML for various pkgdown options to be used in `_pkgdown.yml`. The options are described in greater depth in the [pkgdown vignette](#) and in the help pages for `pkgdown::build_site()`, `pkgdown::build_articles()`, `pkgdown::build_reference()`, and `pkgdown::build_tutorials()`. Essentially, they control the build of vignettes and function references. pkgdown also uses the same approach to navbars as R Markdown. [yml_navbar\(\)](#) and friends will help you write the YAML for that. A useful approach to writing pkgdown YAML might be to use `pkgdown_template()` to build a template based on your package directory, modify with `yml_pkgdown_*` and `pkgdown_*` functions or [yml_replace\(\)](#) and [yml_discard\(\)](#), then pass the results to [use_pkgdown_yaml\(\)](#) to write to `_pkgdown.yml`

Usage

```
yml_pkgdown(.yml, as_is = yml_blank(), extension = yml_blank())
```

```
yml_pkgdown_opts(
  .yml,
```



```
  site_title = yml_blank(),
  destination = yml_blank(),
  url = yml_blank(),
  toc_depth = yml_blank()
)

yml_pkgdown_development(
  .yml,
  mode = yml_blank(),
  dev_destination = yml_blank(),
  version_label = yml_blank(),
  version_tooltip = yml_blank()
)

yml_pkgdown_template(
  .yml,
  bootswatch = yml_blank(),
  ganalytics = yml_blank(),
  noindex = yml_blank(),
  package = yml_blank(),
  path = yml_blank(),
  assets = yml_blank(),
  default_assets = yml_blank()
)

yml_pkgdown_reference(.yml, ...)

pkgdown_ref(
  title = yml_blank(),
  desc = yml_blank(),
  contents = yml_blank(),
  exclude = yml_blank(),
  ...
)

yml_pkgdown_news(.yml, one_page = yml_blank())

yml_pkgdown_articles(.yml, ...)

pkgdown_article(
  title = yml_blank(),
  desc = yml_blank(),
  contents = yml_blank(),
  exclude = yml_blank(),
  ...
)

yml_pkgdown_tutorial(.yml, ...)
```

```

pkgdown_tutorial(
  name = yml_blank(),
  title = yml_blank(),
  tutorial_url = yml_blank(),
  source = yml_blank(),
  ...
)

yml_pkgdown_figures(
  .yml,
  dev = yml_blank(),
  dpi = yml_blank(),
  dev.args = yml_blank(),
  fig.ext = yml_blank(),
  fig.width = yml_blank(),
  fig.height = yml_blank(),
  fig.retina = yml_blank(),
  fig.asp = yml_blank(),
  ...
)

yml_pkgdown_docsearch(
  .yml,
  api_key = yml_blank(),
  index_name = yml_blank(),
  doc_url = yml_blank()
)

```

Arguments

| | |
|--------------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>as_is</code> | Logical. Use the <code>output_format</code> and options that you have specified? |
| <code>extension</code> | The output extension, e.g. "pdf". |
| <code>site_title</code> | The title of the website (by default, this is the package name). Note that the actual YAML is <code>title</code> (specified as <code>site_title</code> to avoid duplication with content titles). |
| <code>destination</code> | The path where the site should be rendered ("docs/" by default) |
| <code>url</code> | URL where the site will be published; setting the URL will allow other pkgdown sites to link to your site when needed, generate a <code>sitemap.xml</code> to increase the searchability of your site, and generate a CNAME. |
| <code>toc_depth</code> | The depth of the headers included in the Table of Contents. Note that the actual YAML is <code>depth</code> and is nested under <code>toc</code> . |
| <code>mode</code> | The development mode of the site, one of: "auto", "release", "development", or "unreleased". <code>development</code> controls where the site is built; the color of the |

| | |
|------------------------------|---|
| | package version; the optional tooltip associated with the version; and the indexing of the site by search engines. See <code>?pkgdown::build_site()</code> for more details. |
| <code>dev_destination</code> | The subdirectory used for the development site, which defaults to "dev/". Note that the actual YAML is <code>destination</code> and is nested under <code>development</code> . |
| <code>version_label</code> | Label to display for "development" and "unreleased" mode. One of: "danger" (the default), "default", "info", or "warning". |
| <code>version_tooltip</code> | A custom message to include in the version tooltip |
| <code>bootswatch</code> | A bootswatch theme for the site. See the options at https://rstudio.github.io/shinythemes/ . |
| <code>ganalytics</code> | A Google Analytics tracking id |
| <code>noindex</code> | Logical. Suppress indexing of your pages by web robots? |
| <code>package</code> | an R package with with directories <code>inst/pkgdown/assets</code> and <code>inst/pkgdown/templates</code> to override the default templates and add additional assets; alternatively, you can specify this in <code>path</code> and <code>assets</code> |
| <code>path</code> | A path to templates with which to override the default pkgdown templates |
| <code>assets</code> | A path to additional assets to include |
| <code>default_assets</code> | Logical. Include default assets? |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |
| <code>title</code> | The title of the article, reference, tutorial, or other resource |
| <code>desc</code> | A description of the article or reference |
| <code>contents</code> | The contents, which can also be dplyr-style tidy selectors (e.g. <code>"contains('index')"</code>). |
| <code>exclude</code> | What to exclude of the what's captured by <code>contents</code> |
| <code>one_page</code> | Logical. Create one page per release for <code>NEWS.md</code> ? |
| <code>name</code> | The name of the file |
| <code>tutorial_url</code> | The tutorial URL to embed in an <code>iframe</code> |
| <code>source</code> | A URL to the source code of the tutorial |
| <code>dev</code> | The graphics device (default: <code>"grDevices::png"</code>) |
| <code>dpi</code> | The DPI (default: 96) |
| <code>dev.args</code> | A vector of arguments to pass to <code>dev</code> |
| <code>fig.ext</code> | The figure extension (default: <code>"png"</code>) |
| <code>fig.width</code> | The figure width (default: 7.2916667) |
| <code>fig.height</code> | The figure height (default: <code>NULL</code>) |
| <code>fig.retina</code> | The figure retina value (default: 2) |
| <code>fig.asp</code> | The aspect ratio (default: 1.618) |
| <code>api_key</code> | The API key provided by docsearch (see the pkgdown vignette) |
| <code>index_name</code> | The index name provided by docsearch (see the pkgdown vignette) |
| <code>doc_url</code> | the URL specifying the location of your documentation. Note that the actual YAML field is <code>url</code> but is nested. |

Value

a yml object

See Also

[use_pkgdown_yml\(\)](#) [yml_navbar\(\)](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_resource_files\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Other pkgdown: [pkgdown_template\(\)](#)

Other websites: [yml_distill_opts\(\)](#), [yml_site_opts\(\)](#)

Examples

```
yml_empty() %>%
  yml_pkgdown(
    as_is = TRUE,
    extension = "pdf"
  ) %>%
  yml_pkgdown_reference(
    pkgdown_ref(
      title = "pkgdown functions",
      contents = "contains('function_name')"
    )
  ) %>%
  yml_pkgdown_articles(
    pkgdown_article(
      title = "Introduction to the package"
    )
  )
```

yml_reference

Write references as YAML fields

Description

`yml_reference()` creates YAML fields for references to be used in citation. `reference()` is a simple function to add references to `yml_reference()`. The easiest way to add references to an R Markdown file is to use a bibliography file, such as `.bib`, in the bibliography field (see [yml_citations\(\)](#)). For documents with very few references, however, it might be useful to make the references self-contained in the YAML. `yml_reference()` can also transform to YAML bibentry and citation objects created by [bibentry\(\)](#) and [citation\(\)](#). To cite many R packages and convert the references to YAML, it may be better to use `knitr::write_bib()` to write a bibliography file and convert it with [bib2yaml\(\)](#).

Usage

```
yml_reference(.yml, ..., .bibentry = NULL)
```

```
reference(id = NULL, ...)
```

Arguments

| | |
|------------------------|---|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>...</code> | Fields relevant to the citation (e.g. bibtex fields) |
| <code>.bibentry</code> | An object created by <code>bibentry()</code> or <code>citation()</code> . Note that this requires <code>pandoc-citeproc</code> to be installed. |
| <code>id</code> | a character vector to use as the reference ID |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other citations: [bib2yaml\(\)](#), [yaml_citations\(\)](#)

Examples

```
ref <- reference(
  id = "fenner2012a",
  title = "One-click science marketing",
  author = list(
    family = "Fenner",
    given = "Martin"
  ),
  `container-title` = "Nature Materials",
  volume = 11L,
  URL = "http://dx.doi.org/10.1038/nmat3283",
  DOI = "10.1038/nmat3283",
  issue = 4L,
  publisher = "Nature Publishing Group",
  page = "261-263",
  type = "article-journal",
  issued = list(
    year = 2012,
    month = 3
  )
)
```

```

yml() %>%
  yml_reference(ref)

# from ?bibentry
bref <- c(
  bibentry(
    bibtype = "Manual",
    title = "boot: Bootstrap R (S-PLUS) Functions",
    author = c(
      person("Angelo", "Canty", role = "aut",
        comment = "S original"),
      person(c("Brian", "D."), "Ripley", role = c("aut", "trl", "cre"),
        comment = "R port, author of parallel support",
        email = "ripley@stats.ox.ac.uk")
    ),
    year = "2012",
    note = "R package version 1.3-4",
    url = "https://CRAN.R-project.org/package=boot",
    key = "boot-package"
  ),

  bibentry(
    bibtype = "Book",
    title = "Bootstrap Methods and Their Applications",
    author = as.person("Anthony C. Davison [aut], David V. Hinkley [aut]"),
    year = "1997",
    publisher = "Cambridge University Press",
    address = "Cambridge",
    isbn = "0-521-57391-2",
    url = "http://statwww.epfl.ch/davison/BMA/",
    key = "boot-book"
  )
)

# requires pandoc-citeproc to be installed
yml() %>%
  yml_reference(.bibentry = bref)

yml() %>%
  yml_reference(.bibentry = citation("purrr"))

```

yml_replace

Replace, pluck, or discard top-level YAML fields

Description

`yml_replace()` replaces a named field with another value. As opposed to duplicating top-level fields with other functions, explicitly replacing them with `yml_replace()` will not raise a warning.

`yml_discard()` removes values given either a character vector of names or a purrr-style lambda with a predicate (`~ predicate`); see the examples. `yml_pluck()` and `yml_chuck()` are wrappers around `purrr::pluck()` and `purrr::chuck()` that return yml objects.

Usage

```
yml_replace(.yml, ...)
```

```
yml_discard(.yml, .rid)
```

```
yml_pluck(.yml, ...)
```

```
yml_chuck(.yml, ...)
```

Arguments

| | |
|-------------------|---|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |
| <code>.rid</code> | a character vector of fields to remove or a purrr-style lambda with a predicate (<code>~ predicate</code>) where fields that are TRUE will be discarded |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_clean(TRUE) %>%
  yml_replace(clean = FALSE) %>%
  yml_discard("author")

yml() %>%
  yml_output(
    pdf_document(),
    html_document()
  ) %>%
  yml_discard(~ length(.x) > 1)
```

yml_resource_files *Add external resource files to R Markdown document*

Description

The `resource_files` field specifies a character vectors of paths to external resources to include in the output, e.g. files that are necessary for rendering. These files are handled with `rmarkdown::find_external_resources()`

Usage

```
yml_resource_files(.yml, resource_files)
```

Arguments

`.yml` a yml object created by `yml()`, `as_yml()`, or returned by a `yml_*`() function
`resource_files` A path to a file, directory, or a wildcard pattern (such as "data/*.csv")

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yml_author\(\)](#), [yml_blogdown_opts\(\)](#), [yml_bookdown_opts\(\)](#), [yml_citations\(\)](#), [yml_clean\(\)](#), [yml_distill_opts\(\)](#), [yml_latex_opts\(\)](#), [yml_output\(\)](#), [yml_pagedown_opts\(\)](#), [yml_params\(\)](#), [yml_pkgdown\(\)](#), [yml_reference\(\)](#), [yml_replace\(\)](#), [yml_rsconnect_email\(\)](#), [yml_rarticles_opts\(\)](#), [yml_runtime\(\)](#), [yml_site_opts\(\)](#), [yml_toc\(\)](#), [yml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_resource_files(c("data/mydata.csv", "images/figure.png"))
```

yml_rsconnect_email *Set YAML for Scheduled Emails in RStudio Connect*

Description

RStudio Connect allows you to schedule emails to send using R Markdown. It uses a special type of YAML using the top-level field `rmd_output_metadata` that tells RStudio Connect about the email output. Several `rsc_*` fields exist to specify different components of the email, which can be set in the YAML header or programmatically using `rmarkdown::output_metadata()`. See the [RStudio Connect documentation](#) for more. `yml_output_metadata()` allows you to add any type of content to the `rmd_output_metadata` field.

Usage

```

yml_rsconnect_email(
  .yml,
  rsc_email_subject = yml_blank(),
  rsc_email_body_html = yml_blank(),
  rsc_email_body_text = yml_blank(),
  rsc_email_images = yml_blank(),
  rsc_output_files = yml_blank(),
  rsc_email_attachments = yml_blank(),
  rsc_email_suppress_scheduled = yml_blank(),
  rsc_email_suppress_report_attachment = yml_blank(),
  resource_files = yml_blank(),
  ...
)

yml_output_metadata(.yml, ...)

```

Arguments

`.yml` a yml object created by `yml()`, `as_yml()`, or returned by a `yml_*`() function

`rsc_email_subject` The subject of the email. A report without an `rsc_email_subject` entry uses its published document name.

`rsc_email_body_html`, `rsc_email_body_text` The body of the email, either in plain text or HTML. A report with neither entry uses an automatically generated, plain-text body with a link to the report's URL.

`rsc_email_images` Images to embed in the email. The embedded image must have a Content ID that is used in the body of the HTML and when providing the image to `rsc_email_images`, and the image itself must be base64-encoded, e.g. with the `base64enc` package.

`rsc_output_files` A vector of file names that should be available after the report has rendered. If you list a file that does not exist after rendering your report, Connect will log a message but continue trying to processing the other files listed. If the output files are not generated during the rendering of your report, then you will also need to list them in `resource_files` when you upload your report to Connect.

`rsc_email_attachments` A vector of file names that should be attached to the email.

`rsc_email_suppress_scheduled` Logical. Should the email schedule be suppressed? Default is FALSE.

`rsc_email_suppress_report_attachment` Logical. Should the rendered document be included as an attachment? Default is TRUE.

`resource_files` A file or files to host on RStudio Connect that is *not* generated by your report, e.g. an existing file.

`...` additional named R objects, such as characters or lists, to transform into YAML

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_rsconnect_email(
    rsc_email_subject = "Quarterly report",
    rsc_output_files = "data.csv",
    rsc_email_attachments = c("attachment_1.csv", "attachment_2.csv")
  )
```

| | |
|---------------------------------|---|
| <code>yml_rarticles_opts</code> | <i>Set YAML related to rarticles output formats</i> |
|---------------------------------|---|

Description

The rarticles package include numerous output formats specific to academic journals. All of these can take YAML similar to `pdf_document()`. Additionally, two templates include custom YAML, `rarticles::sage_article()` and `rarticles::sim_article()`. See the help pages for these functions for more details and the sources of the LaTeX templates used for each.

Usage

```
yml_rarticles_opts(
  .yaml,
  title = yml_blank(),
  runninghead = yml_blank(),
  author = yml_blank(),
  authormark = yml_blank(),
  address = yml_blank(),
  corrauth = yml_blank(),
  corres = yml_blank(),
  email = yml_blank(),
  abstract = yml_blank(),
  received = yml_blank(),
  revised = yml_blank(),
  accepted = yml_blank(),
```

```

    keywords = yml_blank(),
    bibliography = yml_blank(),
    longtable = yml_blank(),
    classoption = yml_blank(),
    header_includes = yml_blank(),
    include_after = yml_blank(),
    ...
)

rticles_author(name = yml_blank(), num = yml_blank())

rticles_address(name = yml_blank(), org = yml_blank())

rticles_corr_author(
  name = yml_blank(),
  author = yml_blank(),
  address = yml_blank()
)

```

Arguments

| | |
|-----------------------------|---|
| .yml | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| title | Title of the manuscript |
| runninghead | A character vector, a short author list for the header (<code>sage_article</code>) |
| author | A list of authors, containing name and num fields (<code>sage_article</code> , <code>sim_article</code>). Use <code>rticles_author()</code> or a list to specify. |
| authormark | A character vector, the short author list for the header (<code>sim_article</code>) |
| address | list containing num and org for defining author affiliations (<code>sage_article</code> , <code>sim_article</code>). Use <code>rticles_address()</code> or a list to specify. |
| corrauth | corresponding author name and address (<code>sage_article</code>). Use <code>rticles_corr_author()</code> or a list to specify. |
| corres | author and address for correspondence (<code>sim_article</code>). Use <code>rticles_corr_author()</code> or a list to specify. |
| email | The email of the correspondence author (<code>sage_article</code>) |
| abstract | The abstract, limited to 200 words (<code>sage_article</code>), 250 words (<code>sim_article</code>) |
| received, revised, accepted | The dates of submission, revision, and acceptance of the manuscript (<code>sim_article</code>) |
| keywords | The keywords for the article (<code>sage_article</code>), up to 6 keywords (<code>sim_article</code>) |
| bibliography | BibTeX .bib file name (<code>sage_article</code> , <code>sim_article</code>) |
| longtable | Logical. Include the longtable package? Used by default from pandoc to convert markdown to LaTeX code (<code>sim_article</code>) |
| classoption | a character vector of classoption options for the <code>sagej</code> class (<code>sage_article</code>) |
| header_includes | additional LaTeX code to include in the header, before the <code>\begin{\document}</code> statement (<code>sage_article</code> , <code>sim_article</code>). Note that the actual YAML field is <code>header-includes</code> |

| | |
|---------------|--|
| include_after | additional LaTeX code to include before the <code>\end{\document}</code> statement (<code>sage_article</code> , <code>sim_article</code>). Note that the actual YAML field is <code>include-after</code> . |
| ... | additional named R objects, such as characters or lists, to transform into YAML |
| name | The author's name |
| num | The author's number or address number |
| org | The author's organization |

Value

a yml object

See Also

Other yml: `asis_yaml_output()`, `bib2yaml()`, `draw_yaml_tree()`, `has_field()`, `read_json()`, `use_yaml_defaults()`, `use_yaml_file()`, `use_yaml()`, `yaml_author()`, `yaml_blogdown_opts()`, `yaml_bookdown_opts()`, `yaml_citations()`, `yaml_clean()`, `yaml_distill_opts()`, `yaml_latex_opts()`, `yaml_output()`, `yaml_pagedown_opts()`, `yaml_params()`, `yaml_pkgdown()`, `yaml_reference()`, `yaml_replace()`, `yaml_resource_files()`, `yaml_rsconnect_email()`, `yaml_runtime()`, `yaml_site_opts()`, `yaml_toc()`, `yaml_vignette()`

Examples

```
yml() %>%
  yml_rarticles_opts(received = "09-12-2014")
```

yml_runtime

Activate Shiny in R Markdown

Description

The runtime field lets you use Shiny in your R Markdown document, making it interactive. See the [R Markdown book](#) for examples.

Usage

```
yml_runtime(.yaml, runtime = c("static", "shiny", "shiny_prerendered"))
```

Arguments

| | |
|---------|---|
| .yaml | a yml object created by <code>yml()</code> , <code>as_yaml()</code> , or returned by a <code>yaml_*</code> () function |
| runtime | The runtime target for rendering. <code>static</code> , the default, renders static documents; <code>shiny</code> allows you to include use Shiny in your document. <code>shiny_prerendered</code> is a subset of the <code>shiny</code> runtime that allows pre-rendering of app components (see the R Markdown site for more) |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_site_opts\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other R Markdown: [yaml_clean\(\)](#), [yaml_params\(\)](#), [yaml_site_opts\(\)](#), [yaml_vignette\(\)](#)

Other shiny: [yaml_params\(\)](#)

Examples

```
yml() %>%
  yml_runtime("shiny")
```

yml_site_opts

Add site options for _site.yml and navbars for R Markdown websites

Description

R Markdown has a simple website builder baked in (see the [R Markdown book](#) for a detailed description). An R Markdown website must have at least have an `index.Rmd` file and a `_site.yml` file (which can be empty). Including YAML in `_site.yml` will apply it to all R Markdown files for the website, e.g. setting the output format here will tell R Markdown to use that format across the website. R Markdown websites also support navbars, which you can specify with YAML (see [yaml_navbar\(\)](#), as well as `?rmarkdown::render_site` and `?rmarkdown::html_document`). Pass `navbar_page()` to the left or right field to set up page tabs and use `navbar_separator()` to include a separators. In addition to writing YAML with `yaml_*()` functions, `use_site_yaml()` will take the a yml object and write it to a `_site.yml` file for you.

Usage

```
yml_site_opts(
  .yml,
  name = yml_blank(),
  favicon = yml_blank(),
  output_dir = yml_blank(),
  include = yml_blank(),
  exclude = yml_blank(),
  new_session = yml_blank(),
  ...
)
```

```

)

yml_navbar(
  .yml,
  title = yml_blank(),
  type = yml_blank(),
  left = yml_blank(),
  right = yml_blank(),
  ...
)

navbar_page(
  text = yml_blank(),
  href = yml_blank(),
  icon = yml_blank(),
  menu = yml_blank(),
  ...
)

navbar_separator()

```

Arguments

| | |
|-------------------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>name</code> | The name of the website |
| <code>favicon</code> | Path to a file to use as the favicon |
| <code>output_dir</code> | Directory to copy site content into (" <code>_site</code> " is the default if none is specified) |
| <code>include, exclude</code> | Files to include or exclude from the copied into <code>output_dir</code> . You can use <code>*</code> to indicate a wildcard selection, e.g. " <code>*.csv</code> ". |
| <code>new_session</code> | Logical. Should each website file be rendered in a new R session? |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |
| <code>title</code> | The title of the website |
| <code>type</code> | The color scheme for the navigation bar: either " <code>default</code> " or " <code>inverse</code> ". |
| <code>left, right</code> | the side of the navbar a <code>navbar_page()</code> should go (see example) |
| <code>text</code> | The link text |
| <code>href</code> | The link URL |
| <code>icon</code> | An icon to include |
| <code>menu</code> | drop-down menus specified by including another <code>navbar_page()</code> |

Value

a yml object

See Also

[use_site_yml\(\)](#) [use_navbar_yml\(\)](#) [use_index_rmd\(\)](#)

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_toc\(\)](#), [yaml_vignette\(\)](#)

Other R Markdown: [yaml_clean\(\)](#), [yaml_params\(\)](#), [yaml_runtime\(\)](#), [yaml_vignette\(\)](#)

Other websites: [yaml_distill_opts\(\)](#), [yaml_pkgdown\(\)](#)

Examples

```
yml_empty() %>%
  yml_site_opts(
    name = "my-website",
    output_dir = "_site",
    include = "demo.R",
    exclude = c("docs.txt", "*.csv")
  ) %>%
  yml_navbar(
    title = "My Website",
    left = list(
      navbar_page("Home", href = "index.html"),
      navbar_page(navbar_separator(), href = "about.html")
    )
  ) %>%
  yml_output(html_document(toc = TRUE, highlight = "textmate"))
```

yml_toc

Specify Table of Contents options

Description

It's generally better to specify Table of Contents in the output function you are using so you have a clearer idea of your options (e.g. `html_document(toc = TRUE, toc_float = TRUE)`). However, you can also generally specify at the top level of YAML.

Usage

```
yml_toc(
  .yml,
  toc = yml_blank(),
  toc_depth = yml_blank(),
  toc_title = yml_blank(),
  ...
)
```

Arguments

| | |
|------------------------|--|
| <code>.yml</code> | a yml object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>toc</code> | Logical. Use a Table of Contents? |
| <code>toc_depth</code> | An integer. The depth of headers to use in the TOC. Note that the actual YAML field is <code>toc-depth</code> . |
| <code>toc_title</code> | The title of the TOC. Note that the actual YAML field is <code>toc-title</code> . |
| <code>...</code> | additional named R objects, such as characters or lists, to transform into YAML |

Value

a yml object

See Also

Other yml: [asis_yaml_output\(\)](#), [bib2yaml\(\)](#), [draw_yaml_tree\(\)](#), [has_field\(\)](#), [read_json\(\)](#), [use_yaml_defaults\(\)](#), [use_yaml_file\(\)](#), [use_yaml\(\)](#), [yaml_author\(\)](#), [yaml_blogdown_opts\(\)](#), [yaml_bookdown_opts\(\)](#), [yaml_citations\(\)](#), [yaml_clean\(\)](#), [yaml_distill_opts\(\)](#), [yaml_latex_opts\(\)](#), [yaml_output\(\)](#), [yaml_pagedown_opts\(\)](#), [yaml_params\(\)](#), [yaml_pkgdown\(\)](#), [yaml_reference\(\)](#), [yaml_replace\(\)](#), [yaml_resource_files\(\)](#), [yaml_rsconnect_email\(\)](#), [yaml_rarticles_opts\(\)](#), [yaml_runtime\(\)](#), [yaml_site_opts\(\)](#), [yaml_vignette\(\)](#)

Examples

```
yml() %>%
  yml_toc(toc = TRUE, toc_depth = 1, toc_title = "Article Outline")
```

yml_verbatim

Write YAML field or content verbatim

Description

`yml_verbatim()` is a helper function to write YAML precisely as given to the `yml_*`() function rather than the defaults in `ymlthis` and `yaml`. `ymlthis` uses the `yaml` package to check for valid syntax; `yaml` and `ymlthis` together make decisions about how to write syntax, which can often be done in numerous valid ways. See [`yaml::as.yaml\(\)`](#) for more details.

Usage

```
yml_verbatim(x)
```

Arguments

`x` a character vector

Value

an object of class `verbatimim`

Examples

```
# "yes" and "no" serve as alternatives to `true` and `false`. This writes
# "yes" literally.
yml_verbatim("yes")
```

| | |
|--------------|----------------------------------|
| yml_vignette | <i>Set up a package vignette</i> |
|--------------|----------------------------------|

Description

To use an R Markdown file as a vignette, you need to specify an output format appropriate for inclusion in a package (for example, the lightweight `html_vignette()` output function included in `rmarkdown`) and to specify the `vignette` field, which specifies the title, engine, and encoding type of the vignette. See also [`usethis::use_vignette\(\)`](#) for setting up a package vignette.

Usage

```
yml_vignette(.yml, title, engine = "knitr::rmarkdown", encoding = "UTF-8")
```

Arguments

| | |
|-----------------------|---|
| <code>.yml</code> | a <code>yml</code> object created by <code>yml()</code> , <code>as_yml()</code> , or returned by a <code>yml_*</code> () function |
| <code>title</code> | The title of the vignette |
| <code>engine</code> | The rendering engine for the vignette ("knitr::rmarkdown" by default) |
| <code>encoding</code> | The character encoding for the document ("UTF-8" by default). |

Value

a `yml` object

See Also

Other `yml`: [`asis_yaml_output\(\)`](#), [`bib2yaml\(\)`](#), [`draw_yaml_tree\(\)`](#), [`has_field\(\)`](#), [`read_json\(\)`](#), [`use_yaml_defaults\(\)`](#), [`use_yaml_file\(\)`](#), [`use_yaml\(\)`](#), [`yml_author\(\)`](#), [`yml_blogdown_opts\(\)`](#), [`yml_bookdown_opts\(\)`](#), [`yml_citations\(\)`](#), [`yml_clean\(\)`](#), [`yml_distill_opts\(\)`](#), [`yml_latex_opts\(\)`](#), [`yml_output\(\)`](#), [`yml_pagedown_opts\(\)`](#), [`yml_params\(\)`](#), [`yml_pkgdown\(\)`](#), [`yml_reference\(\)`](#), [`yml_replace\(\)`](#), [`yml_resource_files\(\)`](#), [`yml_rsconnect_email\(\)`](#), [`yml_rarticles_opts\(\)`](#), [`yml_runtime\(\)`](#), [`yml_site_opts\(\)`](#), [`yml_toc\(\)`](#)

Other R Markdown: [`yml_clean\(\)`](#), [`yml_params\(\)`](#), [`yml_runtime\(\)`](#), [`yml_site_opts\(\)`](#)

Examples

```
yml() %>%  
  yml_output(html_vignette()) %>%  
  yml_vignette("An introduction to R Markdown")
```

Index

as_yaml, 3
as_yaml(), 21
asis_yaml_output, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65

base::strftime(), 46
bib2yaml, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65
bib2yaml(), 52
bibentry(), 52
blogdown_archetypes (blogdown_template), 5
blogdown_template, 5
blogdown_template(), 25
bookdown::gitbook(), 7, 8

citation(), 52
code_chunk, 5
code_chunk(), 18

distill_collection (yaml_distill_opts), 34
distill_listing (yaml_distill_opts), 34
distill_resources (yaml_distill_opts), 34
draw_yaml_tree, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65

format.Date(), 23

get_rmd_defaults (use_yaml_defaults), 18
get_yaml_defaults (use_yaml_defaults), 18
get_yaml_defaults(), 18, 19
gitbook_config, 7, 29

has_field, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65

includes2, 10
is_yaml, 10
is_yaml_blank (yaml_blank), 24
knitr::write_bib(), 4, 52

last_yaml, 11
last_yaml(), 17

navbar_page (yaml_site_opts), 61
navbar_separator (yaml_site_opts), 61

pagedown_business_card_template, 11, 43
pagedown_business_card_template(), 42
pagedown_person (pagedown_business_card_template), 11
pandoc_highlight_styles (pandoc_template_types), 14
pandoc_template_types, 14
pkgdown_article (yaml_pkgdown), 48
pkgdown_ref (yaml_pkgdown), 48
pkgdown_template, 15, 52
pkgdown_tutorial (yaml_pkgdown), 48
purrr::chuck(), 55
purrr::pluck(), 55

read_json, 3, 4, 6, 9, 15, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65
read_toml (read_json), 15
reference (yaml_reference), 52
rticles_address (yaml_rticles_opts), 58
rticles_author (yaml_rticles_opts), 58
rticles_corr_author (yaml_rticles_opts), 58

setup_chunk (code_chunk), 5
setup_chunk(), 17, 18
shiny::animationOptions(), 46
shiny::validateCssUnit(), 46

- shiny_checkbox (yml_params), 44
- shiny_date (yml_params), 44
- shiny_file (yml_params), 44
- shiny_numeric (yml_params), 44
- shiny_params (yml_params), 44
- shiny_password (yml_params), 44
- shiny_radio (yml_params), 44
- shiny_select (yml_params), 44
- shiny_slider (yml_params), 44
- shiny_text (yml_params), 44

- use_bookdown_yml (use_yml_file), 19
- use_bookdown_yml(), 29
- use_index_rmd (use_yml), 17
- use_index_rmd(), 29, 63
- use_navbar_yml (use_yml_file), 19
- use_navbar_yml(), 63
- use_output_yml (use_yml_file), 19
- use_output_yml(), 29
- use_pandoc_highlight_style
(pandoc_template_types), 14
- use_pandoc_template
(pandoc_template_types), 14
- use_pkgdown_yml (use_yml_file), 19
- use_pkgdown_yml(), 15, 48, 52
- use_rmarkdown (use_yml), 17
- use_rmarkdown(), 5, 11, 13, 18, 19, 37
- use_rmd_defaults (use_yml_defaults), 18
- use_rmd_defaults(), 17, 18
- use_site_yml (use_yml_file), 19
- use_site_yml(), 34, 37, 63
- use_yml, 3, 4, 6, 9, 16, 17, 19, 21, 24, 27, 29,
31, 32, 37, 40, 42, 43, 48, 52, 53, 55,
56, 58, 60, 61, 63–65
- use_yml_defaults, 3, 4, 6, 9, 16, 18, 18, 21,
24, 27, 29, 31, 32, 37, 40, 42, 43, 48,
52, 53, 55, 56, 58, 60, 61, 63–65
- use_yml_defaults(), 17, 21
- use_yml_file, 3, 4, 6, 9, 16, 18, 19, 19, 24,
27, 29, 31, 32, 37, 40, 42, 43, 48, 52,
53, 55, 56, 58, 60, 61, 63–65
- usethis::edit_r_profile(), 18
- usethis::use_vignette(), 65

- write_as_json (read_json), 15
- write_as_toml (read_json), 15

- yaml::as.yaml(), 64
- yaml::yaml.load(), 3, 21, 37, 41

- yml, 21
- yml(), 18, 19
- yml_abstract (yml_author), 22
- yml_author, 3, 4, 6, 9, 16, 18, 19, 21, 22, 22,
27, 29, 31, 32, 37, 40, 42, 43, 48, 52,
53, 55, 56, 58, 60, 61, 63–65
- yml_author(), 34
- yml_blank, 24
- yml_blogdown_opts, 3, 4, 6, 9, 16, 18, 19, 21,
24, 25, 29, 31, 32, 37, 40, 42, 43, 48,
52, 53, 55, 56, 58, 60, 61, 63–65
- yml_bookdown_opts, 3, 4, 6, 9, 16, 18, 19, 21,
24, 27, 28, 31, 32, 37, 40, 42, 43, 48,
52, 53, 55, 56, 58, 60, 61, 63–65
- yml_bookdown_site (yml_bookdown_opts),
28
- yml_category (yml_author), 22
- yml_chuck (yml_replace), 54
- yml_citations, 3, 4, 6, 9, 16, 18, 19, 21, 24,
27, 29, 30, 32, 37, 40, 42, 43, 48, 52,
53, 55, 56, 58, 60, 61, 63–65
- yml_citations(), 52
- yml_clean, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27,
29, 31, 32, 37, 40, 42, 43, 48, 52, 53,
55, 56, 58, 60, 61, 63–65
- yml_code, 33
- yml_date (yml_author), 22
- yml_description (yml_author), 22
- yml_discard (yml_replace), 54
- yml_discard(), 25, 48
- yml_distill_author, 22
- yml_distill_author (yml_distill_opts),
34
- yml_distill_opts, 3, 4, 6, 9, 16, 18, 19, 21,
24, 27, 29, 31, 32, 34, 40, 42, 43, 48,
52, 53, 55, 56, 58, 60, 61, 63–65
- yml_empty (yml), 21
- yml_handlers, 37
- yml_keywords (yml_author), 22
- yml_lang (yml_author), 22
- yml_latex_opts, 3, 4, 6, 9, 16, 18, 19, 21, 24,
27, 29, 31, 32, 37, 38, 42, 43, 48, 52,
53, 55, 56, 58, 60, 61, 63–65
- yml_load, 41
- yml_navbar (yml_site_opts), 61
- yml_navbar(), 34, 48, 52, 61
- yml_output, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27,
29, 31, 32, 37, 40, 41, 43, 48, 52, 53,

- 55, 56, 58, 60, 61, 63–65
- yml_output(), 23
- yml_output_metadata
 - (yml_rsconnect_email), 56
- yml_pagedown_opts, 3, 4, 6, 9, 13, 16, 18, 19, 21, 24, 27, 29, 31, 32, 37, 40, 42, 42, 48, 52, 53, 55, 56, 58, 60, 61, 63–65
- yml_params, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 44, 52, 53, 55, 56, 58, 60, 61, 63–65
- yml_params_code (yml_code), 33
- yml_params_code(), 48
- yml_pkgdown, 3, 4, 6, 9, 15, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 48, 53, 55, 56, 58, 60, 61, 63–65
- yml_pkgdown_articles (yml_pkgdown), 48
- yml_pkgdown_development (yml_pkgdown), 48
- yml_pkgdown_docsearch (yml_pkgdown), 48
- yml_pkgdown_figures (yml_pkgdown), 48
- yml_pkgdown_news (yml_pkgdown), 48
- yml_pkgdown_opts (yml_pkgdown), 48
- yml_pkgdown_reference (yml_pkgdown), 48
- yml_pkgdown_template (yml_pkgdown), 48
- yml_pkgdown_tutorial (yml_pkgdown), 48
- yml_pluck (yml_replace), 54
- yml_reference, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 52, 55, 56, 58, 60, 61, 63–65
- yml_replace, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 54, 56, 58, 60, 61, 63–65
- yml_replace(), 25, 48
- yml_resource_files, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63–65
- yml_rsconnect_email, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 56, 60, 61, 63–65
- yml_rarticles_opts, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 58, 61, 63–65
- yml_runtime, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 60, 63–65
- yml_site_opts, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 61, 64, 65
- yml_site_opts(), 34
- yml_subject (yml_author), 22
- yml_subtitle (yml_author), 22
- yml_title (yml_author), 22
- yml_toc, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63, 63, 65
- yml_toplevel (yml_author), 22
- yml_verbatim, 64
- yml_verbatim(), 33
- yml_vignette, 3, 4, 6, 9, 16, 18, 19, 21, 24, 27, 29, 32, 37, 40, 42, 43, 48, 52, 53, 55, 56, 58, 60, 61, 63, 64, 65